



Quinfosys Sub-Website Design Blueprint

Scalable page architecture, responsive layout grammar, blueprint-blue section system, and reusable section patterns.

Document 03 · Quinfosys Developer-Facing Design Framework · Version 1.1

1. Framework scope

The design blueprint defines page-level architecture for future Quinfosys sub-sites. The system converts current page structures into reusable templates for products, solutions, services, research, resources, and company verticals.

- Page modules must be reusable without dependency on a single page route.
- Layout ratios must be breakpoint-aware and capped by container width.
- Blueprint sections must remain dark, technical, and restricted to system explanation contexts.
- Content hierarchy must remain consistent across all sub-site categories.

2. Universal page anatomy

Layer	Required pattern	Developer implementation
Application frame	Dark route frame behind all routed pages.	<code>.quinfosys-route-frame { min-height: 100vh; background: #050505; }</code>
Navigation	Fixed 64px header with direct desktop links and mobile overlay below lg.	Header outside page content; z-index 90; body scroll locked during mobile menu.
Hero	Top padding accounts for fixed header; one-column on mobile; two-column or centered on desktop.	pt-24 to pt-32; max-w-7xl; px-5/6/8; min height only when visual composition requires.
Main content	Sections alternate between dark surfaces, light panels, and controlled blueprint modules.	py-16 to py-32; max-w-6xl or max-w-7xl; grid gap 6-8.
CTA band	Single strong final action with rounded container and high contrast.	<code>rounded-[2rem]</code> or <code>rounded-[2.5rem]</code> ; primary pill CTA; supporting copy max-w-2xl.
Footer	Standard website footer with white surface and top border.	Do not alter footer identity across sub-sites.

3. Ratio and placement grammar

Pattern	Desktop ratio	Breakpoint activation	Developer rule
Hero text + visual	5:3 or 8:5	lg and above	Use grid-cols-[1.15fr_0.85fr] or grid-cols-[1fr_0.75fr]. Stack below lg.
Problem + solution	1:1	md and above	Use equal columns when both sides carry similar text weight.
Feature grid	3 columns	lg and above	Use 1 column base, 2 columns md, 3 columns lg. Avoid 4 columns for long copy.
Metric strip	3 or 4 columns	sm and above	Use short labels. Keep values visually heavier than descriptions.
Blueprint diagram + notes	8:5	lg and above	Diagram receives the wider column. Notes remain grouped in compact cards.
CTA content + action	8:5	lg and above	Copy left, action right. Center align on mobile.

4. Responsive page behavior

Viewport range	Layout requirement	Placement rule
320-639px	Single-column. No horizontal overflow. Buttons stack or wrap.	Hero copy first; visual second; cards full width; accordions full width.
640-767px	Optional 2-column grids for short cards.	Use sm:grid-cols-2 only when card copy remains under 28 words.
768-1023px	Two-column grids for features and proof sections.	Use md:grid-cols-2 or md:grid-cols-3 with controlled gaps.
1024-1279px	Desktop nav and ratio layouts activate.	Use lg:grid-cols; page sections max-w-6xl or max-w-7xl.
1280-1535px	Maintain visual width cap.	Use max-w-7xl; avoid expanding text beyond readable line length.
1536px+	Do not scale indefinitely.	Retain capped containers and preserve whitespace.

5. Section template matrix

Section type	Required content	Design rule
Hero	Eyebrow, H1, 24-48 word description, one primary CTA, optional secondary CTA.	Dark or light depending on route. Keep H1 max width controlled.
Feature grid	3-6 capability cards.	Cards use rounded 28-32px radii and thin borders.
Process section	3-5 ordered steps.	Use numbered cards or vertical stack. Avoid dense paragraphs.
Proof section	Metrics, logos, outcomes, or operational claims.	Use compact strips, low-contrast dividers, and short labels.
Blueprint band	System flow, architecture, integrations, data movement, module map.	Use only Blueprint 950-700 backgrounds. Linework uses white opacity only.
CTA band	Final conversion copy and one primary action.	Use rounded 32-40px container and high contrast.

6. Blueprint-blue section system

Blueprint modules use only the approved dark execution palette. Lighter blueprint shades are intentionally removed. White-opacity overlays replace light blue lines and surfaces.

Element	Implementation token	Behavior
Background	Blueprint 950, 900, 800, or 700. Optional gradient #007ACC to #005A99.	Full-width technical section or rounded technical card module.
Foreground text	#FFFFFF primary. #F8F8F8 only on Blueprint 950-800. Body text on #007ACC uses #FFFFFF.	Maintain high contrast. Do not use low-contrast gray on blue.
Blueprint 600	#148DDB only for active lines, small node rings, hover states, and tiny accents.	No body-text background usage. No large panels.
Grid overlay	linear-gradient white lines at 24px or 32px spacing; opacity 0.12-0.22.	Blueprint character without added blue tokens.
Diagram lines	1px solid rgba(255,255,255,0.18-0.38).	No lighter blueprint tokens.
Nodes	#FFFFFF fill; optional rgba(255,255,255,0.22) halo.	Use Blueprint 600 only for active node outline.
CTA	#FFFFFF pill with #005A99 or #050505 text.	Primary action inside blueprint sections.

7. Page template rules

Page type	Required section order	Notes
Product sub-site	Hero → product promise → modules → architecture/blueprint band → proof/process → CTA → footer	Use blueprint sections for integrations, pipelines, architecture, and product mechanics.
Solution sub-site	Hero → problem matrix → solution pillars → outcomes → implementation steps → CTA → footer	Use ratio grids to pair problem context with solution modules.
Service sub-site	Hero → service categories → process → deliverables → contact CTA → footer	Use expandable sections for deliverables and scope.
Research sub-site	Hero → focus areas → labs/projects → methods → resource links → CTA → footer	Use dark technical cards and blueprint bands for frameworks.
Resource sub-site	Hero → resource groups → filters/cards → highlighted download/contact CTA → footer	Use card grids and accordions; keep download CTA visible.
Company sub-site	Hero → mission → leadership/team → partnerships → timeline → contact CTA → footer	Use brighter surfaces sparingly for biographies and imagery.

8. Copy hierarchy for scalable pages

Content level	Length target	Placement
Eyebrow	1-4 words; uppercase; 0.16-0.32em tracking.	Above hero and section headings.
Hero H1	6-12 words.	Single strongest promise or category statement.
Hero description	24-48 words.	Below H1; max-w-2xl; leading 1.7-1.8.
Section H2	4-10 words.	Defines section purpose.
Card title	2-6 words.	Feature, service, module, or capability.
Card copy	12-28 words.	One outcome or function per card.
Tag/chip	1-3 words.	Technology label, category, metric, state, or phase.

9. Implementation acceptance criteria

Criterion	Pass condition
Visual continuity	New page can sit beside current Products, Solutions, Services, Research, Resources, and Company pages without visual discontinuity.
Responsive continuity	No horizontal overflow at 320px; mobile nav, cards, and CTAs stack correctly.
Token consistency	Colors, radii, shadows, font stacks, and grid ratios match defined tokens.
Blueprint usage	#007ACC appears only in technical or engineering visualization contexts.
Accessibility	Keyboard operation, focus states, contrast, and reduced motion pass review.