

Busbar Processor

Function

- Suitable to transmission and distribution in a large work shop, construction and power distribution cabinets and switch cabinets, etc. The use of electrical appliances factory.
- This machine is equipped with : Cutting , Punching & Bending Functionality.
- Optional for switch or wire switch easy to operate

Four-In-One Busbar Processors



GPA-150
GPA-150D

Five-In-One Busbar Processors



GPA-501

Model	GPA-150	GPA-150D	GPA-501
Functions	Cutting / Punching Bending / Electric Pump	Cutting / Punching Bending / Electric Pump	Cutting / Punching / Embossing Bending / Electric Pump
Input voltage/Control voltage	50HZ, 220V	50HZ, 220V	50HZ, 220V
Rating oil pressure	700kgf/cm2	700kgf/cm2	700kgf/cm2
Cutting force	15 ton	15 ton	15 ton
Cutting capacity	150mm x 12mm	150mm x 12mm	150mm x 12mm
Punching force	31 ton	31 ton	35 ton
The distance between center bore and row edge	95mm	95mm	110mm
Punching capability-copper bus bar/aluminum bus bar	₵6*₵20.5 :10mm	₵6*₵20.5 :10mm	₵6*₵20.5 :12mm
Standard punching mold	₵ 7, ₵ 9, ₵ 10.5, ₵ 13.8, ₵ 17.5, ₵ 20.5mm	₵ 7, ₵ 9, ₵ 10.5, ₵ 13.8, ₵ 17.5, ₵ 20.5mm	₵ 7, ₵ 9, ₵ 10.5, ₵ 13.8, ₵ 17.5, ₵ 20.5mm
Bend board strenght	20 ton	16 ton	25 ton
Horizontal bending capability	150 x 12mm	150 x 12mm	150 x 12mm
Weight	170kg	165kg	275kg
Dimension of moveable workbench	650mm(L) x 600mm(W) x 1100mm(H)	750mm(L) x 750mm(W) x 1000mm(H)	850mm(L) x 750mm(W) x 1100mm(H)

Four-In-One Busbar Processors

Four-In-One Busbar Processors



GPA-200



GPA-401

Model	GPA-200	GPA-401
Functions	Cutting / Punching Bending / Electric Pump	Cutting / Punching Bending / Electric Pump
Input voltage/Control voltage	50HZ, 220V	50HZ, 220V
Rating oil pressure	700kgf/cm2	700kgf/cm2
Cutting force	30 ton	15 ton
Cutting capacity	200mm x 12mm	150mm x 12mm
Punching force	35 ton	35 ton
The distance between center bore and row edge	110mm	110mm
Punching capability-copper bus bar/aluminum bus bar	Ø6*Ø20.5 :12mm	Ø6*Ø20.5 :12mm
Standard punching mold	Ø 7, Ø 9, Ø 10.5, Ø 13.8, Ø 17.5, Ø 20.5mm	Ø 7, Ø 9, Ø 10.5, Ø 13.8, Ø 17.5, Ø 20.5mm
Bend board strenght	20 ton	25 ton
Horizontal bending capability	200 x 12mm	150 x 12mm
Weight	195kg	220kg
Dimension of moveable workbench	800mm(L) x 750mm(W) x 1100mm(H)	850mm(L) x 750mm(W) x 1100mm(H)