

Hydraulic Crimping Tools

Function

- The compression pliers are designed for hydraulic crimping on power cable and wire. The crimped conductor performed in high conductivity and everlasting .
- Open cut design for easy operation.

  Dies are quickly put on tube by double speed unit. The compression force lift and automatically change to low speed. The operation saves time and energy.
- The head could be rotated 180° , it suit all kind of working space.
- Build in with safety valve. Pressure release automatically while pressure reaching the maximum value .
- Fiber glass insulated handles to prevent accidentally shock .

HYDRAULIC CRIMPING TOOLS


GPJ-120A


GPJ-120B


GPJ-300C


GPJ-300D


GPJ-240A


GPJ-240C


GPJ-430


GPJ-510

Function

- Outer design with beauty.
- High speed: Hydraulic mould reaches hydration pipe fast.
- Slow speed: Guarantee quality with easy operation.
- There is a safe protective equipment of "Kacha" vica when it reaches to high or low.

Model	GPJ-120A	GPJ-120B	GPJ-240A	GPJ-240C
Max.pressure(T)	12	12	13	13
Max.stroke(mm)	14	14	18	18
Crimping range(mm)	10-120	10-240	10-240	10-240
Size of standard dies(mm2)	10,16,25,35,50, 70,95,120	10,16,25,35,50, 70,95,120	16,25,35,50,70,95, 120,150,185,240	16,25,35,50,70,95, 120,150,185,240
Crimp pattern	Hexagon	Hexagon	Hexagon	Hexagon
G.W.(kg)	4.5	4.5	6.2	6.2
Volume(cm)	(1/5)45 x 45 x 22	(1/4)53 x 39 x 23	(1/4)53 x 39 x 23	(1/4)53 x 39 x 23

Model	GPJ-300C	GPJ-300D	GPJ-430	GPJ-510
Max.pressure(T)	14	12	16	16
Max.stroke(mm)	20	16	38	38
Crimping range(mm)	16-300	Cu300,Al240	50-400	50-400
Size of standard dies(mm2)	16,25,35,50,70,95, 120,150,185,240,300	50,70,95,120, 150,185,240,300	50,70,95,120,150, 185,240,300,400	50,70,95,120,150, 185,240,300,400
Crimp pattern	Hexagon	Hexagon	Hexagon	Hexagon
G.W.(kg)	8.5	9	11.5	11.5
Volume(cm)	62 x 15 x 10	55 x 25 x 14	77 x 24 x 13	77 x 24 x 13

SEPARABLE HYDRAULIC CRIMPING TOOLS



Function

- Suitable to use in indoor & outdoor power transmission and distribution projects.
- Designed for high voltage cable conduits(10KV-500KV),wire holders,ferrules and terminals.
- Welcome to order special specification tools.



GPF-1000F

GPF-510F



GPF-630F



GPF-500F



GPF-400F

Model	GPF-1000F	GPF-630F	GPF-500F	GPF-400F	GPF-510F
Max.pressure(T)	45	25	16	16	16
Max.stroke(mm)	30	22	38	30	38
Crimping range(mm)	240-1000	150-630	50-500	50-400	16-400
Size of standard dies (mm2)	400,500,630 800,1000	240,300,400 500,630	50,70,95,120,150, 185,240,300,400,500	50,70,95,120,150, 185,240,300,400,	50,70,95,120,150, 185,240,300,400,
Crimp pattern	Hexagon	Hexagon	Hexagon	Hexagon	Hexagon
G.W.(kg)	24	13.5	13.5	4.5	7.2
Volume(cm)	20 x 20 x 39	20 x 17 x 32	20 x 17 x 32	21 x 11 x10	35 x 19 x 9