HAND PUMP



GPE - 700A



GPE -700-2



GPE - 700B



GPE - 180



GPE - 700S

Model	Rated output (Kg/PSI)	Output oil perminute		Oil capacity (CC)	Weight(kg)	Volume(cm)	Remarks
		Low-pressure	High-pressure				
GPE-700A	700-10000	13	2.3	2700	14	82 x 18 x 18	Manual type
GPE-700B	700-10000	13	2.2	700	13	78 x 18 x 27	Manual type
GPE-700S	700-10000	13	2.3	3000	16	73 x 24 x 27	Manual type
GPE-700-2	700-10000	13	2.3	3000	13	73 x 24 x 27	Manual type
GPE-180	600-8000	13		280	5	48 x 26 x 13	Manual type

Electric / Hand Pump

Function

- High and low speed two stage design is for quick oil output. Turbine oil absorption could ensure reaching Max Effective oil volume.
- Over pressure safety valve unit could avoid over pressure damages at 700kg/cm2 automatically release.
- Oil pipe fitted with quick coupling could be ordered for any length.
- Oil pipe coupling fitted with PT3/8" thread.
- Supplied with oil hose and quick couplers. **[Hand Pump Only]**
- Oil must renewed every half year. **[Hand Pump Only]**



ELECTRIC PUMP



GPD-700 -A



GPD-700 -B



GPD-700 - C

Model	Output power	Power-Driven	Frequency	Rotate Speed	flow	Voltage	Electricity Current	Oil Capacity
GPD - 700 -A	70Mpa	750W	50HZ	1400R/min	3.5L/min	220V	5.1A	8L
GPD - 700 -B	70Mpa	750W	50HZ	1400R/min	3.5L/min	220V	5.1A	8L
GPD - 700 -C	70Mpa	750W	50HZ	1400R/min	3.5L/min	220V	5.1A	8L
GPD - 700 A-10L	70Mpa	2.2KW	50HZ	1420R/min	1.5L/min	380V	5.1A	10L



GPD-700A-10L



GPD-750

Model	Output Power	flow	Power Driven	Voltage	Frequency	Oil Capacity	Volume
GPD 750	H70Mpa	H 0.6 L/min	750W	220V	50HZ	7L	30 X 24 X 40mm
	L7Mpa	L 4 L/min					