

Sari-sari MS

☰ Category	
Σ Learning Progress	👉 Let's start

Laravel Backend

Problems Encountered:

▼ Completely stop WSL from calling Windows executables.

```
sudo nano /etc/wsl.conf
```

Put this EXACT config:

```
[interop]
enabled=false
appendWindowsPath=false
```

- Press **CTRL + O** → (write/save)
- Press **Enter**
- Press **CTRL + X** → (exit)

Then:

```
wsl --shutdown
```

Confirm:

```
which cmd.exe
```

should not show shit

▼ Install optional dependencies (vite kulang problem)

(Cannot find native binding (@rolldown/binding-linux-x64-gnu))

```
rm -rf node_modules package-lock.json
npm cache clean --force
```

```
npm install --include=optional
```

▼ Docker cant get node image in dockerfile

```
docker pull node:20 (manual shit)
```

▼ Laravel needs php:8.3-fpm

▼ Tempnam() error (persmission shit) (this)

```
docker compose exec app sh
```

```
chown -R www-data:www-data /var/www/storage /var/www/bootstrap/cache
```

```
chmod -R 775 /var/www/storage /var/www/bootstrap/cache
```

```
exit
```

▼ Node needs to run always (only does run after npm run dev)

```
node:
  build:
    context: .
    dockerfile: docker/node/dockerfile
  container_name: laravel-node
  volumes:
    - ./var/www
    - /var/www/node_modules
  ports:
    - "5173:5173"
  networks:
    - sari_sari_ms
  command: sh -c "npm install && npm run dev"
  tty: true
```

▼ IDK YET (vite not running or cant be reached)

vite.config.js

```
import { defineConfig } from 'vite';
import laravel from 'laravel-vite-plugin';
import react from '@vitejs/plugin-react'

export default defineConfig({
  plugins: [
    laravel({
      input: 'resources/js/main.tsx',
      refresh: true,
    }),
    react(),
  ],
  server: {
    host: '0.0.0.0', // <--- bind to all network interfaces
    port: 5173,      // make sure this matches your docker-compose port
    strictPort: true, // fail if 5173 is taken
    watch: {
      ignored: ['**/storage/framework/views/**'],
    },
  },
});
```

```
    },  
  });  
}
```

package.json

```
{  
  "$schema": "https://www.schemastore.org/package.json",  
  "private": true,  
  "type": "module",  
  "scripts": {  
    "build": "vite build",  
    "dev": "vite --host 0.0.0.0"  
  },  
  "devDependencies": {  
    "@tailwindcss/vite": "^4.0.0",  
    "@types/react": "^19.2.14",  
    "@types/react-dom": "^19.2.3",  
    "@vitejs/plugin-react": "^6.0.1",  
    "axios": "^1.11.0",  
    "concurrently": "^9.0.1",  
    "laravel-vite-plugin": "^3.0.0",  
    "tailwindcss": "^4.0.0",  
    "typescript": "^5.9.3",  
    "vite": "^8.0.0"  
  },  
  "dependencies": {  
    "react": "^19.2.4",  
    "react-dom": "^19.2.4"  
  }  
}
```

▼ **IDK YET (<http://localhost:8000/> gets data in the wrong port "0.0.0.0.5173")**

```
APP_NAME=Laravel  
APP_ENV=local  
APP_KEY=base64:o0XZ2HNLNEH1hz0EtVhzQ9jTBudElR6RII0ysZ8SUpo=  
APP_DEBUG=true  
APP_URL=http://localhost  
  
APP_LOCALE=en  
APP_FALLBACK_LOCALE=en  
APP_FAKER_LOCALE=en_US  
  
APP_MAINTENANCE_DRIVER=file  
# APP_MAINTENANCE_STORE=database  
  
# PHP_CLI_SERVER_WORKERS=4  
  
BCRYPT_ROUNDS=12  
  
LOG_CHANNEL=stack  
LOG_STACK=single  
LOG_DEPRECATIONS_CHANNEL=null  
LOG_LEVEL=debug  
  
DB_CONNECTION=mysql
```

```
DB_HOST=mysql
DB_PORT=3306
DB_DATABASE=sari_sari_ms
DB_USERNAME=user
DB_PASSWORD=user

SESSION_DRIVER=database
SESSION_LIFETIME=120
SESSION_ENCRYPT=false
SESSION_PATH=/
SESSION_DOMAIN=null

BROADCAST_CONNECTION=log
FILESYSTEM_DISK=local
QUEUE_CONNECTION=database

CACHE_STORE=database
# CACHE_PREFIX=

MEMCACHED_HOST=127.0.0.1

REDIS_CLIENT=phpredis
REDIS_HOST=127.0.0.1
REDIS_PASSWORD=null
REDIS_PORT=6379

MAIL_MAILER=log
MAIL_SCHEME=null
MAIL_HOST=127.0.0.1
MAIL_PORT=2525
MAIL_USERNAME=null
MAIL_PASSWORD=null
MAIL_FROM_ADDRESS="hello@example.com"
MAIL_FROM_NAME="${APP_NAME}"

AWS_ACCESS_KEY_ID=
AWS_SECRET_ACCESS_KEY=
AWS_DEFAULT_REGION=us-east-1
AWS_BUCKET=
AWS_USE_PATH_STYLE_ENDPOINT=false

VITE_APP_NAME="${APP_NAME}"
VITE_DEV_SERVER_URL=http://node:5173
```

vite config.js

```
import { defineConfig } from 'vite';
import laravel from 'laravel-vite-plugin';
import react from '@vitejs/plugin-react'

export default defineConfig({
  plugins: [
    laravel({
      input: 'resources/js/main.tsx',
      refresh: true,
    }),
    react(),
  ],
  server: {
    host: '0.0.0.0', // <--- bind to all network interfaces
```

```

    port: 5173,      // make sure this matches your docker-compose port
    strictPort: true, // fail if 5173 is taken
    hmr: {
      host: 'localhost', // your machine host for HMR
      protocol: 'ws',
    }, // For HOT RELOAD
    watch: {
      ignored: ['**/storage/framework/views/**'],
    },
  },
});

```

▼ Installation (Laravel, react + tsx)

composer create-project laravel/laravel [app]

inside app:

npm install (1st dependancies)

React and typescript

npm install react react-dom

npm install -D typescript @types/react @types/react-dom

npm install -D @vitejs/plugin-react

vite.config.js

```

import { defineConfig } from 'vite'
import laravel from 'laravel-vite-plugin'
import react from '@vitejs/plugin-react'
import tailwindcss from '@tailwindcss/vite'

export default defineConfig({
  plugins: [
    laravel({
      input: 'resources/js/main.tsx', // 🖱️ changed
      refresh: true,
    }),
    react(), // 🖱️ added
    tailwindcss(),
  ],
  server: {
    watch: {
      ignored: ['**/storage/framework/views/**'],
    },
  },
})

```

js/main.tsx

```
import React from 'react'
import ReactDOM from 'react-dom/client'
import '../css/app.css' // 👉 import Tailwind here

function App() {
  return <h1 className="text-3xl font-bold">React + TS + Laravel 🚀</h1>
}

ReactDOM.createRoot(document.getElementById('app')).render(
  <React.StrictMode>
    <App />
  </React.StrictMode>
)
```

resources/views/app.blade.php

```
<!DOCTYPE html>
<html>
<head>
  @vite('resources/js/main.tsx')
</head>
<body>
  <div id="app"></div>
</body>
</html>
```

npm run dev (frontend)

php artisan serve (backend)

▼ Containerization

laravel

- docker
- nginx
- default.conf
- docker.compose.yaml
- dockerfile

made:

docker.compose.yaml

2 docker file:

changes in package.json (IDK YET (vite not running or cant be reached))

changes in env (IDK YET (<http://localhost:8000/> gets data in the wrong port "0.0.0.0.5173"))

changes in vite.config.js (IDK YET (<http://localhost:8000/> gets data in the wrong port "0.0.0.0.5173"))

if new machine:

put .env file (yawa i check ang file kay env ra walay dot)

docker compose up --build (inside laravel)

docker compose exec app sh


```
composer install (vendor missing (gitignore))
```

```
chown -R www-data:www-data /var/www/storage /var/www/bootstrap/cache
```

```
chmod -R 775 /var/www/storage /var/www/bootstrap/cache
```

```
php artisan migrate
```

Tempnam() error (persmission shit)

Dugang:

```
composer require laravel/sanctum (KINIT)
```