





Template Files

Author: Nho Luong

Skill: DevOps Engineer Lead





Let's Add a Template!

Adding all the information into the recipe did make it hard to read.

Objective:

- ❑ Create a template with chef generate Define the
- ❑ contents of the ERB template Change the file
- ❑ resource to the template resource Update the
- ❑ cookbook's version number Apply the updated
- ❑ recipe and verify the results

GL: What Can chef generate Do?



```
$ chef generate --help
```

```
Usage: chef generate GENERATOR [options]
```

Available generators:

app	Generate an application repo	Generate a single
cookbook	cookbook	Generate a new recipe
recipe	attributes file	Generate a file template
attribute	cookbook file	Generate a lightweight
template file	resource/provider	Generate a Chef policy
lwrp repo	repository	

```
policyfile Generate a Policyfile for use with the install/push commands  
(experimental)
```

LOCAL

GL: What Can chef generate template

Do?



```
$ chef generate template --help
```

Usage: chef generate template [path/to/cookbook] NAME [options]

-C, --copyright COPYRIGHT
defaults to 'The Authors'

Name of the copyright holder -

-m, --email EMAIL
to ...

Email address of the author - defaults

-a, --generator-arg KEY=VALUE
VALUE in the

Use to set arbitrary attribute KEY to

-l, --license LICENSE
- defaults to

all_rights, apache2, mit, gplv2, gplv3

-s, --source SOURCE_FILE
-g GENERATOR_COOKBOOK_PATH,
code_generator

Copy content from SOURCE_FILE

Use GENERATOR_COOKBOOK_PATH for the

--generator-cookbook

LOCAL

Generating a motd Template



```
> chef generate template cookbooks/workstation motd
```

```
Recipe: code_generator::template
```

```
* directory[cookbooks/workstation/templates/default] action  
create
```

```
  - create new directory  
cookbooks/workstation/templates/default
```

```
* template[cookbooks/workstation/templates/motd.erb] action  
create
```

```
  - create new file cookbooks/workstation/templates/motd.erb  
  - update content in file
```

```
cookbooks/workstation/templates/motd.erb from none to e3b0c4  
(diff output suppressed by config)
```

Examining the templates Directory




```
> tree cookbooks/workstation/templates
```

```
cookbooks/workstation/templates/
```

```
├── default
```

```
└── motd.erb
```

```
1 directory, 1 file
```




Cleaner Recipes

Adding the node attributes to the default page did make it harder to read the recipe.

Objective:

- ✓ Create a template with chef generate Define the contents of the ERB
- ✓ template Change the file resource to the template resource in the 'apache'
- ✓ cookbook



ERB

An Embedded Ruby (ERB) template allows Ruby code to be embedded inside a text file within specially formatted tags. Ruby code can be embedded using expressions and statements.

<https://docs.chef.io/templates.html#variables>


Text Within an ERB Template

```
<% if (50 + 50) == 100 %> 50 + 50 = <%= 50 + 50 %> <% else %> At  
some point all of MATH I learned in school changed. <% end %>
```

Each ERB tag has a beginning tag and a matched ending tag.

Text Within an ERB Template

```
<% if (50 + 50) == 100 %> 50 + 50 = <%= 50 + 50 %> <% else %> At  
some point all of MATH I learned in school changed. <% end %>
```




The diagram illustrates the structure of an ERB template. It shows a code snippet enclosed in a dashed box. The code contains an if-else statement. Blue arrows point from the opening tags to their corresponding closing tags: from `<% if` to `<% end %>` and from `<%=` to `<% %>`. Yellow arrows point from the closing tags back to the opening tags: from `<% end %>` to `<% if` and from `<% %>` to `<%=`.

Each ERB tag has a beginning tag and a matched ending tag.

Text Within an ERB Template

```
<% if (50 + 50) == 100 %> 50 + 50 = <%= 50 + 50 %> <% else %> At  
some point all of MATH I learned in school changed. <% end %>
```



Each ERB tag has a beginning tag and a matched ending tag.

Text Within an ERB Template


```
<% if (50 + 50) == 100 %> 50 + 50 = <%= 50 + 50 %> <% else %> At  
some point all of MATH I learned in school changed. <% end %>
```

Executes the ruby code within the brackets and do not display the result.

Text Within an ERB Template

```
<% if (50 + 50) == 100 %> 50 + 50 = <%= 50 + 50 %> <% else %> At  
some point all of MATH I learned in school changed. <% end %>
```

Executes the ruby code within the brackets and display the results.



CONCEPT

The Angry Squid

<0%=>

7-13

Copying the Existing Content into the Template



~/cookbooks/workstation/templates/motd.erb

Property of ...

```
IPADDRESS: #{node['ipaddress']}  
HOSTNAME : #{node['hostname']}  
MEMORY   : #{node['memory']['total']}  
CPU       : #{node['cpu']['0']['mhz']}
```

Changing String Interpolation to ERB Tags



~/cookbooks/workstation/templates/motd.erb


Property of ...

IPADDRESS: <%= node['ipaddress'] %>

HOSTNAME : <%= node['hostname'] %>

MEMORY : <%= node['memory']['total'] %>

CPU : <%= node['cpu']['0']['mhz'] %>



Cleaner Recipes

The template is created and defined. It now needs to be used within the recipe.

Objective:

- ✓ Create a template with chef generate Define the
- ✓ contents of the ERB template Change the file
- ✓ resource to the template resource Update the
- ✓ cookbook's version number Apply the updated
- ✓ recipe and verify the results



Thank You