



BootStrap Node

Author: Nho Luong

Skill: DevOps Engineer Lead






Hosted Chef

Adding nodes to your Chef Server


Objective:

- ✓ Create a Hosted Chef Account Upload your
- ✓ cookbooks to the Hosted Chef Server Bootstrap a
- ✓ node and update its runlist

CONCEPT



The Node



Change to the chef-repo



```
$ cd ~/chef-repo
```

LOCAL

Run 'knife node -help'



```
$ knife node --help
```

```
** NODE COMMANDS ** knife node bulk delete REGEX (options)
knife node create NODE (options) knife node delete NODE
(options) knife node edit NODE (options) knife node environment
set NODE ENVIRONMENT knife node from file FILE (options) knife
node list (options) knife node run_list add [NODE] [ENTRY[,ENTRY]]
(options) knife node run_list remove [NODE] [ENTRY[,ENTRY]]
(options) knife node run_list set NODE ENTRIES (options) knife
node show NODE (options)
```

LOCAL


Run 'knife node list'



```
$ knife node list
```

LOCAL

CONCEPT



Bootstrapping a Node

The node may not have Chef installed. It may also not have details of where the Chef Server is located or the credentials to securely talk to that Server. To add those credentials we can bootstrap that node to install all those components.

<https://learn.chef.io/skills/beyond-essentials-1>

LOCAL

Run 'knife bootstrap -help'



```
$ knife bootstrap --help
```

```
knife bootstrap FQDN (options)
```

```
--bootstrap-curl-options OPTIONS
```

Add options to curl when install chef-client

```
--bootstrap-install-command
```

```
COMMANDS
```

Custom command to install chef-client

```
--bootstrap-no-proxy
```

```
[NO_PROXY_URL|NO_PROXY_IP] Do not proxy locations for the node being bootstrapped; this option is used internally by Opscode
```

```
--bootstrap-proxy PROXY_URL The proxy server for the node being bootstrapped
```

```
-t TEMPLATE, Bootstrap Chef using a built-in or custom template. Set to the full path of an erb template or use one of the built-in templates.
```

LOCAL

Bootstrap Your Node - options



```
$ knife bootstrap FQDN -x USER -P PWD --sudo -N node_name
```

Creating new client for node1 Creating new node for node1
Feuctlyi nQgu taoli fieecd2 -D5o4m-1a7i5n- 46-24.compute-1.amazonaws.com
ec2-54-175-4N6a-m24e.compute-1.amazonaws.com Starting first Chef Client run...

user name

password

sudo flag

node name

ec2-54-175-46-24.compute-1.amazonaws.com Starting Chef Client, version 12.3.0

ec2-54-175-46-24.compute-1.amazonaws.com resolving cookbooks for run list: []

ec2-54-175-46-24.compute-1.amazonaws.com Synchronizing Cookbooks:

ec2-54-175-46-24.compute-1.amazonaws.com Compiling Cookbooks...

ec2-54-175-46-24.compute-1.amazonaws.com [2016-09-16T16:51:21+00:00] WARN: Node node1

has an empty run list. ec2-54-175-46-24.compute-1.amazonaws.com Converging 0 resources ec2-54-175-46-24.compute-1.amazonaws.com ec2-54-175-46-24.compute-1.amazonaws.com Running handlers:

LOCAL

Verify the port and identity file for web1



```
$ vagrant ssh-config web1
```

```
Host
```

```
web1 HostName 127.0.0.1 User vagrant Port 2200 UserKnownHostsFile /dev/null
```

```
StrictHostKeyChecking no PasswordAuthentication no IdentityFile /Users/USER/chef-  
repo/.vagrant/machines/web1/virtualbox/private_key IdentitiesOnly yes LogLevel FATAL
```

LOCAL

Bootstrap Your Node



```
$ knife bootstrap localhost --ssh-port WEB1_PORT --ssh-user vagrant --sudo --identity-file PATH_TO_KEY -N web1
```

```
Creating new client for web1 Creating new node for web1 Connecting to localhost localhost -----> Installing Chef Omnibus (-v 12) localhost downloading https://omnitruck-direct.chef.io/chef/install.sh
```

```
localhost to file /tmp/install.sh.12058/install.sh
```

```
localhost trying wget... localhost el 7 x86_64 localhost Getting information for chef stable 12 for el... localhost downloading https://omnitruck-direct.chef.io/stable/chef/metadata?v=12&p=el&pv=7&m=x86_64
```

```
localhost to file /tmp/install.sh.12063/metadata.txt  
localhost trying wget...
```

LOCAL

Run 'knife node list' Again



```
$ knife node list
```

```
web  
1
```

LOCAL

View More Information About Your Node



```
$ knife node show web1
```

```
Node Name:  web
Environment: default
FQDN: IP:    web1
Run List:   10.0.2.15
Roles:
Recipes:
Platform:
Tags:       centos 7.2.1511
```

Notice that the IPAddress is not what we defined in the Vagrantfile. It's the internal IP instead.

LOCAL

Add a Recipe to web1's Run List



```
$ knife node run_list add web1 "recipe[workstation],recipe[apache]"
```

Web1

```
: run_list: recipe[workstation]  
  run_list: recipe[apache]
```

LOCAL

View More Information About Your Node



```
$ knife node show web1
```

```
Node Name:  web
Environment: default
FQDN: IP:   web1 10.0.2.15 recipe[workstation],
Run List:   recipe[apache]
Roles:
Recipes:
Platform:
Tags:       centos 7.2.1511
```

Your Run List for web1 should contain the workstation and apache cookbooks

LOCAL

Login to web1



```
$ vagrant ssh web1
```

```
Last login: Sat Dec 31 02:59:27 2016 from 10.0.2.2
```

```
[vagrant@web1 ~]$
```

LOCAL

Run chef-client to converge web1



```
[vagrant@web1 ~]$ sudo chef-client
```

```
Starting Chef Client, version 12.17.44 resolving cookbooks for run  
list: ["workstation", "apache"] Synchronizing Cookbooks: - apache  
(0.2.1) - workstation (0.2.1) Installing Cookbook Gems: Compiling  
Cookbooks... Converging 8 resources....
```

LOCAL

Verify the state of your web application



```
[vagrant@web1 ~]$ curl localhost
```

```
<html>
<body>
  <h1>Hello, world!</h1>
  <h2>ipaddress: 192.168.10.43</h2>
  <h2>hostname: web1</h2>
</body>
</html>
```

LOCAL

Return to your Workstation



```
[vagrant@web1 ~]$ exit
```

```
logout Connection to 127.0.0.1  
closed.
```

LOCAL

View More Information About Your Node




```
$ knife node show web1
```

```
Node Name:  web
Environment: default
FQDN:      web1
IP:        192.168.10.43
Run List:   recipe[workstation], recipe[apache]
Roles:
Recipes:    workstation, workstation::default, apache, apache::default,
workstation::vagrant, workstation::setup, apache::server
Platform:   centos 7.2.1511
Tags:
```

The IPAddress should now match what we defined in the Vagrantfile.

LOCAL



Hosted Chef

More easily manage multiple nodes

Objective:

- ✓ Create a Hosted Chef Account Upload your
- ✓ cookbooks to the Hosted Chef Server Add web1 as
- ✓ a managed node

DISCUSSION



Discussion

What is the benefit of storing cookbooks in a central repository? What is the primary tool for communicating with the Chef Server? How did you add a node to your organization?



Thank You