

Kubernetes Ochestration












Introduction

Kubernetes (K8s) is an open-source system for automating deployment, scaling, and management of containerized applications




Author: Nho Luong

Kubernetes-Advantages

- Kubernetes can scale without increasing your ops team
- •Whether testing locally or running a global enterprise, Kubernetes flexibility grows with you to deliver your applications consistently and easily no matter how complex your need is.
- Kubernetes is open source giving you the freedom to take advantage of on-premises, hybrid, or public cloud infrastructure, letting you effortlessly move workloads to where it matters to you.

Kubernetes Architecture



•

Kube-API Server

The API server is a component of the Kubernetescontrol planethat exposes the Kubernetes API. The API server is the front end for the Kubernetes control plane. The main implementation of a Kubernetes API server iskube-apiserver. kube-apiserveris designed to scale erver horizontally—that is, it scales by deploying more instances. You can run several instances of kube-apiserverand balance traffic between those instances.

etcd

kube-scheduler

Consistent and highly-available key value store used as Kubernetes' backing store for all cluster data. If your Kubernetes cluster uses etcdas its backing store, make sure you have aback upplan for those data.

Control plane component that watches for newly createdPodswith no assignednode, and selects a

node for them to run on. Factors taken into account for scheduling decisions

include: individual and collective resource requirements, hardware/software/policy constraints,

affinity and anti-affinity specifications, data locality, inter-workload interference, and deadlines.

kube-controller-manager

Control Plane component that runscontrollerprocesses. Logically, each controller a separate process, but to reduce complexity, they are all compiled into a single binary and run in a single process. These controllers include: Node controller: Responsible for noticing and responding when nodes go down. Replication controller: Responsible for maintaining the correct number of pods for every replication controller object in the system. Endpoints controller: Populates the Endpoints object (that is, joins Services & Pods). Service Account & Token controllers: Create default accounts and API access tokens for new namespaces

Author: Nho Luong

Cloud-Controller Manager

A Kubernetescontrol plane component that embeds cloud-specific control logic. The cloud controller manager lets you link your cluster into your cloud provider's API, and separates out the components that interact with that cloud platform from components that just interact with your cluster. The following controllers can have cloud provider dependencies: Node controller: For checking the cloud provider to determine if a node has been deleted in the cloud after it stops responding Route controller: For setting up routes in the underlying cloud infrastructure Service controller: For creating, updating and deleting cloud provider load balancers

Author: Nho Luong

Node Components

(2) (2) (3) (3) (4) (3) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4	
kubelet	An agent that runs on eachnodein the cluster. It makes sure that containers are running in aPod. The kubelettakes a set of PodSpecsthat are provided through various mechanisms and ensures that the containers described in those PodSpecsare running and healthy. The kubeletdoesn't manage containers which were not created by Kubernetes.
kube-proxy	kube-proxy is a network proxy that runs on eachnodein your cluster, implementing part of the KubernetesServiceconcept. kube-proxymaintains network rules on nodes. These network rules allow network communication to your Pods from network sessions inside or outside of your cluster.
Container RunTime	The container runtime is the software that is responsible for running containers.

Addons

Addonsuse Kubernetes resources (DaemonSet, Deployment, etc) to implement cluster features.
 Because these are providing cluster-level features, namespacedresources for addonsbelong within the kube-system namespace

Addons	
DNS	Cluster DNS is a DNS server, in addition to the other DNS server(s) in your environment, which serves DNS records for Kubernetes services. Containers started by Kubernetes automatically include this DNS server in their DNS searches.
WebUI	Dashboardis a general purpose, web-based UI for Kubernetes clusters. It allows users to manage and troubleshoot applications running in the cluster, as well as the cluster itself. Container Resource Monitoringrecords generic time-series metrics about containers in a central database, and provides a UI for browsing that da
Container Resource Monitoring	



Author: Nho Luong