

810 Invoice

Functional Group=IN

This Draft Standard for Trial Use contains the format and establishes the data contents of the Invoice Transaction Set (810) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to the billing for goods and services provided.

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	ST	Transaction Set Header	M	1			Must use
0200	BIG	Beginning Segment for Invoice	M	1			Must use
0500	REF	Reference Identification	O	12			Used
LOOP ID - N1					200		
0700	N1	Name	O	1			Used
0800	N2	Additional Name Information	O	2			Used
0900	N3	Address Information	O	2			Used
1000	N4	Geographic Location	O	1			Used
1300	ITD	Terms of Sale/Deferred Terms of Sale	O	>1			Used
1400	DTM	Date/Time Reference	O	10			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - IT1					200000		
0100	IT1	Baseline Item Data (Invoice)	O	1			Used
0500	CTP	Pricing Information	O	25			Used
LOOP ID - PID					1000		
0600	PID	Product/Item Description	O	1			Used
1000	PO4	Item Physical Details	O	1			Used
1200	REF	Reference Identification	O	>1			Used
LOOP ID - SAC					>1		
1800	SAC	Service, Promotion, Allowance, or Charge Information	O	1			Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	TDS	Total Monetary Value Summary	M	1			Must use

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - SAC					>1		
0400	SAC	Service, Promotion, Allowance, or Charge Information	O	1			Used
0700	CTT	Transaction Totals	O	1		N3/0700	Used
0800	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

Notes:

3/0700 Number of line items (CTT01) is the accumulation of the number of IT1 segments. If used CTT02 is the hash total of the quantities invoiced (IT102) for each IT1 segment.

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use
		Description: Code identifying the type of information in the Authorization Information All valid standard codes are used.				
ISA02	I02	Authorization Information	M	AN	10/10	Must use
		Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)				
ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
		Description: Code identifying the type of information in the Security Information All valid standard codes are used.				
ISA04	I04	Security Information	M	AN	10/10	Must use
		Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)				
ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
		Description: Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified All valid standard codes are used.				
ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use
		Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element				
ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
		Description: Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified All valid standard codes are used.				
ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use
		Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them				
ISA09	I08	Interchange Date	M	DT	6/6	Must use
		Description: Date of the interchange				
ISA10	I09	Interchange Time	M	TM	4/4	Must use

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		Description: Time of the interchange				
ISA11	I65	Repetition Separator	M		1/1	Must use
		Description: Type is not applicable; the repetition separator is a delimiter and not a data element; this field provides the delimiter used to separate repeated occurrences of a simple data element or a composite data structure; this value must be different than the data element separator, component element separator, and the segment terminator				
ISA12	I11	Interchange Control Version Number	M	ID	5/5	Must use
		Description: Code specifying the version number of the interchange control segments				
		All valid standard codes are used.				
ISA13	I12	Interchange Control Number	M	N0	9/9	Must use
		Description: A control number assigned by the interchange sender				
ISA14	I13	Acknowledgment Requested	M	ID	1/1	Must use
		Description: Code indicating sender's request for an interchange acknowledgment				
		All valid standard codes are used.				
ISA15	I14	Usage Indicator	M	ID	1/1	Must use
		Description: Code indicating whether data enclosed by this interchange envelope is test, production or information				
		All valid standard codes are used.				
ISA16	I15	Component Element Separator	M		1/1	Must use
		Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator				

GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use
		Description: Code identifying a group of application related transaction sets				
		<u>Code</u> <u>Name</u>				
		IN Invoice Information (810)				
GS02	142	Application Sender's Code	M	AN	2/15	Must use
		Description: Code identifying party sending transmission; codes agreed to by trading partners				
GS03	124	Application Receiver's Code	M	AN	2/15	Must use
		Description: Code identifying party receiving transmission; codes agreed to by trading partners				
GS04	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				
GS05	337	Time	M	TM	4/8	Must use
		Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)				
GS06	28	Group Control Number	M	N0	1/9	Must use
		Description: Assigned number originated and maintained by the sender				
GS07	455	Responsible Agency Code	M	ID	1/2	Must use
		Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480				
		All valid standard codes are used.				
GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use
		Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed				
		<u>Code</u> <u>Name</u>				
		004020VICS				

Semantics:

1. GS04 is the group date.
2. GS05 is the group time.
3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

Comments:

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

ST Transaction Set Header

Pos: 0100	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 3

User Option (Usage): Must use

To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use
		Description: Code uniquely identifying a Transaction Set				
		<u>Code</u> <u>Name</u>				
		810 Invoice				
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				
ST03	1705	Implementation Convention Reference	O	AN	1/35	Used
		Description: Reference assigned to identify Implementation Convention				

Semantics:

1. The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
2. The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation convention to match the transaction set definition.

BIG Beginning Segment for Invoice

Pos: 0200	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 7

User Option (Usage): Must use

To indicate the beginning of an invoice transaction set and transmit identifying numbers and dates

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BIG01	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				
BIG02	76	Invoice Number	M	AN	1/22	Must use
		Description: Identifying number assigned by issuer				
BIG03	373	Date	O	DT	8/8	Used
		Description: Date expressed as CCYYMMDD				
BIG04	324	Purchase Order Number	O	AN	1/22	Used
		Description: Identifying number for Purchase Order assigned by the orderer/purchaser				
BIG05	328	Release Number	O	AN	1/30	Used
		Description: Number identifying a release against a Purchase Order previously placed by the parties involved in the transaction				
BIG06	327	Change Order Sequence Number	O	AN	1/8	Used
		Description: Number assigned by the orderer identifying a specific change or revision to a previously transmitted transaction set				
BIG07	640	Transaction Type Code	O	ID	2/2	Used
		Description: Code specifying the type of transaction				
		Code	Name			
		BB	Billback			
		BH	Bill and Hold Goods			
		CA	Cash			
		CI	Consolidated Invoice			
		FI	First Cost Invoice			
		ME	Memorandum			
		PB	Partial Bill			

Semantics:

1. BIG01 is the invoice issue date.
2. BIG03 is the date assigned by the purchaser to purchase order.
3. BIG10 indicates the consolidated invoice number. When BIG07 contains code CI, BIG10 is not used.

Comments:

1. BIG07 is used only to further define the type of invoice when needed.

REF Reference Identification

Pos: 0500	Max: 12
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use
Description: Code qualifying the Reference Identification						
Code Name						
IA Internal Vendor Number						
REF02	127	Reference Identification	X	AN	1/30	Used
Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier						

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop N1

Pos: 0700	Repeat: 200
Optional	
Loop: N1	Elements: N/A

User Option (Usage): Used

To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0700	N1	Name	O	1		Used
0800	N2	Additional Name Information	O	2		Used
0900	N3	Address Information	O	2		Used
1000	N4	Geographic Location	O	1		Used

N1 Name

Pos: 0700	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use
		Description: Code identifying an organizational entity, a physical location, property or an individual				
		<u>Code</u> <u>Name</u>				
		BT Bill-to-Party				
		RI Remit To				
		ST Ship To				
N102	93	Name	X	AN	1/60	Used
		Description: Free-form name				
N103	66	Identification Code Qualifier	X	ID	1/2	Used
		Description: Code designating the system/method of code structure used for Identification Code (67)				
		<u>Code</u> <u>Name</u>				
		92 Assigned by Buyer or Buyer's Agent				
N104	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N2 Additional Name Information

Pos: 0800	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify additional names

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N201	93	Name	M	AN	1/60	Must use
		Description: Free-form name				
N202	93	Name	O	AN	1/60	Used
		Description: Free-form name				

N3 Address Information

Pos: 0900	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4 Geographic Location

Pos: 1000	Max: 1
Heading - Optional	
Loop: N1	Elements: 3

User Option (Usage): Used

To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Used
		Description: Free-form text for city name				
N402	156	State or Province Code	X	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Used
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				

Syntax Rules:

1. E0207 - Only one of N402 or N407 may be present.
2. C0605 - If N406 is present, then N405 is required.
3. C0704 - If N407 is present, then N404 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

ITD Terms of Sale/Deferred Terms of Sale

Pos: 1300	Max: >1
Heading - Optional	
Loop: N/A	Elements: 7

User Option (Usage): Used

To specify terms of sale

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ITD01	336	Terms Type Code	O	ID	2/2	Not used
		Description: Code identifying type of payment terms All valid standard codes are used.				
ITD02	333	Terms Basis Date Code	O	ID	1/2	Not used
		Description: Code identifying the beginning of the terms period All valid standard codes are used.				
ITD03	338	Terms Discount Percent	O	R	1/6	Used
		Description: Terms discount percentage, expressed as a percent, available to the purchaser if an invoice is paid on or before the Terms Discount Due Date				
ITD04	370	Terms Discount Due Date	X	DT	8/8	Used
		Description: Date payment is due if discount is to be earned expressed in format CCYYMMDD				
ITD05	351	Terms Discount Days Due	X	N0	1/3	Used
		Description: Number of days in the terms discount period by which payment is due if terms discount is earned				
ITD06	446	Terms Net Due Date	O	DT	8/8	Used
		Description: Date when total invoice amount becomes due expressed in format CCYYMMDD				
ITD12	352	Description	O	AN	1/80	Used
		Description: A free-form description to clarify the related data elements and their content				

Syntax Rules:

1. L03040513 - If ITD03 is present, then at least one of ITD04, ITD05 or ITD13 is required.
2. L08040513 - If ITD08 is present, then at least one of ITD04, ITD05 or ITD13 is required.
3. L091011 - If ITD09 is present, then at least one of ITD10 or ITD11 is required.

Semantics:

1. ITD15 is the percentage applied to a base amount used to determine a late payment charge.

Comments:

1. If the code in ITD01 is "04", then ITD07 or ITD09 is required and either ITD10 or ITD11 is required; if the code in ITD01 is "05", then ITD06 or ITD07 is required.

DTM Date/Time Reference

Pos: 1400	Max: 10
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use				
Description: Code specifying type of date or time, or both date and time										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>011</td><td>Shipped</td></tr></table>							<u>Code</u>	<u>Name</u>	011	Shipped
<u>Code</u>	<u>Name</u>									
011	Shipped									
DTM02	373	Date	X	DT	8/8	Used				
Description: Date expressed as CCYYMMDD										

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

Loop IT1

Pos: 0100	Repeat: 200000
Optional	
Loop: IT1	Elements: N/A

User Option (Usage): Used

To specify the basic and most frequently used line item data for the invoice and related transactions

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	IT1	Baseline Item Data (Invoice)	O	1		Used
0500	CTP	Pricing Information	O	25		Used
0600		Loop PID	O		1000	Used
1000	PO4	Item Physical Details	O	1		Used
1200	REF	Reference Identification	O	>1		Used
1800		Loop SAC	O		>1	Used

IT1 Baseline Item Data (Invoice)

Pos: 0100	Max: 1
Detail - Optional	
Loop: IT1	Elements: 6

User Option (Usage): Used

To specify the basic and most frequently used line item data for the invoice and related transactions

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IT102	358	Quantity Invoiced	X	R	1/10	Used
		Description: Number of units invoiced (supplier units)				
IT103	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				
		All valid standard codes are used.				
IT104	212	Unit Price	X	R	1/17	Used
		Description: Price per unit of product, service, commodity, etc.				
IT105	639	Basis of Unit Price Code	O	ID	2/2	Used
		Description: Code identifying the type of unit price for an item				
		All valid standard codes are used.				
IT106	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		<u>Code</u>		<u>Name</u>		
		UP		U.P.C. Consumer Package Code (1-5-5-1)		
IT107	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				

Syntax Rules:

1. P020304 - If either IT102, IT103 or IT104 are present, then the others are required.
2. P0607 - If either IT106 or IT107 is present, then the other is required.
3. P0809 - If either IT108 or IT109 is present, then the other is required.
4. P1011 - If either IT110 or IT111 is present, then the other is required.
5. P1213 - If either IT112 or IT113 is present, then the other is required.
6. P1415 - If either IT114 or IT115 is present, then the other is required.
7. P1617 - If either IT116 or IT117 is present, then the other is required.
8. P1819 - If either IT118 or IT119 is present, then the other is required.
9. P2021 - If either IT120 or IT121 is present, then the other is required.
10. P2223 - If either IT122 or IT123 is present, then the other is required.
11. P2425 - If either IT124 or IT125 is present, then the other is required.

Semantics:

1. IT101 is the line item identification.

Comments:

1. Element 235/234 combinations should be interpreted to include products and/or services. See the Data Dictionary for a complete list of IDs.
2. IT106 through IT125 provide for ten different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

CTP Pricing Information

Pos: 0500	Max: 25
Detail - Optional	
Loop: IT1	Elements: 3

User Option (Usage): Used

To specify pricing information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTP01	687	Class of Trade Code	O	ID	2/2	Used
		Description: Code indicating class of trade All valid standard codes are used.				
CTP02	236	Price Identifier Code	X	ID	3/3	Used
		Description: Code identifying pricing specification <u>Code</u> <u>Name</u> MSR Manufacturer's Suggested Retail				
CTP03	212	Unit Price	X	R	1/17	Used
		Description: Price per unit of product, service, commodity, etc.				

Syntax Rules:

1. P0405 - If either CTP04 or CTP05 is present, then the other is required.
2. C0607 - If CTP06 is present, then CTP07 is required.
3. C0902 - If CTP09 is present, then CTP02 is required.
4. C1002 - If CTP10 is present, then CTP02 is required.
5. C1103 - If CTP11 is present, then CTP03 is required.

Semantics:

1. CTP07 is a multiplier factor to arrive at a final discounted price. A multiplier of .90 would be the factor if a 10% discount is given.
2. CTP08 is the rebate amount.

Comments:

1. See Figures Appendix for an example detailing the use of CTP03 and CTP04.
2. See Figures Appendix for an example detailing the use of CTP03, CTP04 and CTP07.

Loop PID

Pos: 0600	Repeat: 1000
Optional	
Loop: PID	Elements: N/A

User Option (Usage): Used

To describe a product or process in coded or free-form format

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0600	PID	Product/Item Description	O	1		Used

PID Product/Item Description

Pos: 0600	Max: 1
Detail - Optional	
Loop: PID	Elements: 2

User Option (Usage): Used

To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
PID01	349	Item Description Type	M	ID	1/1	Must use				
Description: Code indicating the format of a description										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>F</td><td>Free-form</td></tr></table>							<u>Code</u>	<u>Name</u>	F	Free-form
<u>Code</u>	<u>Name</u>									
F	Free-form									
PID05	352	Description	X	AN	1/80	Used				
Description: A free-form description to clarify the related data elements and their content										

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

PO4 Item Physical Details

Pos: 1000	Max: 1
Detail - Optional	
Loop: IT1	Elements: 1

User Option (Usage): Used

To specify the physical qualities, packaging, weights, and dimensions relating to the item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO401	356	Pack	O	N0	1/6	Used

Description: The number of inner containers, or number of eaches if there are no inner containers, per outer container

Syntax Rules:

1. P0203 - If either PO402 or PO403 is present, then the other is required.
2. C0506 - If PO405 is present, then PO406 is required.
3. P0607 - If either PO406 or PO407 is present, then the other is required.
4. P0809 - If either PO408 or PO409 is present, then the other is required.
5. C1013 - If PO410 is present, then PO413 is required.
6. C1113 - If PO411 is present, then PO413 is required.
7. C1213 - If PO412 is present, then PO413 is required.
8. L13101112 - If PO413 is present, then at least one of PO410, PO411 or PO412 is required.
9. C1716 - If PO417 is present, then PO416 is required.
10. C1804 - If PO418 is present, then PO404 is required.

Semantics:

1. PO415 is used to indicate the relative layer of this package or range of packages within the layers of packaging. Relative Position 1 (value R1) is the innermost package.
2. PO416 is the package identifier or the beginning package identifier in a range of identifiers.
3. PO417 is the ending package identifier in a range of identifiers.
4. PO418 is the number of packages in this layer.

Comments:

1. PO403 - The "Unit or Basis for Measure Code" in this segment position is for purposes of defining the pack (PO401) /size (PO402) measure which indicates the quantity in the inner pack unit. For example: If the carton contains 24 12-Ounce packages, it would be described as follows: Data element 356 = "24"; Data element 357 = "12"; Data element 355 = "OZ".
2. PO413 defines the unit of measure for PO410, PO411, and PO412.

REF Reference Identification

Pos: 1200	Max: >1
Detail - Optional	
Loop: IT1	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use
Description: Code qualifying the Reference Identification						
Code Name						
DP Department Number						
PK Packing List Number						
REF02	127	Reference Identification	X	AN	1/30	Used
Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier						

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop SAC

Pos: 1800

Repeat: >1

Optional

Loop: SAC Elements: N/A

User Option (Usage): Used

To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
1800	SAC	Service, Promotion, Allowance, or Charge Information	O	1		Used

SAC Service, Promotion, Allowance, or Charge Information

Pos: 1800	Max: 1
Detail - Optional	
Loop: SAC	Elements: 4

User Option (Usage): Used

To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SAC01	248	Allowance or Charge Indicator	M	ID	1/1	Must use
		Description: Code which indicates an allowance or charge for the service specified All valid standard codes are used.				
SAC02	1300	Service, Promotion, Allowance, or Charge Code	X	ID	4/4	Used
		Description: Code identifying the service, promotion, allowance, or charge All valid standard codes are used.				
SAC05	610	Amount	O	N2	1/15	Used
		Description: Monetary amount				
SAC12	331	Allowance or Charge Method of Handling Code	O	ID	2/2	Used
		Description: Code indicating method of handling for an allowance or charge All valid standard codes are used.				

Syntax Rules:

1. R0203 - At least one of SAC02 or SAC03 is required.
2. P0304 - If either SAC03 or SAC04 is present, then the other is required.
3. P0607 - If either SAC06 or SAC07 is present, then the other is required.
4. P0910 - If either SAC09 or SAC10 is present, then the other is required.
5. C1110 - If SAC11 is present, then SAC10 is required.
6. L130204 - If SAC13 is present, then at least one of SAC02 or SAC04 is required.
7. C1413 - If SAC14 is present, then SAC13 is required.
8. C1615 - If SAC16 is present, then SAC15 is required.

Semantics:

1. If SAC01 is "A" or "C", then at least one of SAC05, SAC07, or SAC08 is required.
2. SAC05 is the total amount for the service, promotion, allowance, or charge.
3. If SAC05 is present with SAC07 or SAC08, then SAC05 takes precedence.
4. SAC08 is the allowance or charge rate per unit.
5. SAC10 and SAC11 is the quantity basis when the allowance or charge quantity is different from the purchase order or invoice quantity.
6. SAC10 and SAC11 used together indicate a quantity range, which could be a dollar amount, that is applicable

to service, promotion, allowance, or charge.

7. SAC13 is used in conjunction with SAC02 or SAC04 to provide a specific reference number as identified by the code used.
8. SAC14 is used in conjunction with SAC13 to identify an option when there is more than one option of the promotion.
9. SAC16 is used to identify the language being used in SAC15.

Comments:

1. SAC04 may be used to uniquely identify the service, promotion, allowance, or charge. In addition, it may be used in conjunction with SAC03 to further define SAC02.
2. In some business applications, it is necessary to advise the trading partner of the actual dollar amount that a particular allowance, charge, or promotion was based on to reduce ambiguity. This amount is commonly referred to as "Dollar Basis Amount". It is represented in the SAC segment in SAC10 using the qualifier "DO" - Dollars in SAC09.

TDS Total Monetary Value Summary

Pos: 0100	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

To specify the total invoice discounts and amounts

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TDS01	610	Amount Description: Monetary amount	M	N2	1/15	Must use
TDS02	610	Amount Description: Monetary amount	O	N2	1/15	Used
TDS03	610	Amount Description: Monetary amount	O	N2	1/15	Used
TDS04	610	Amount Description: Monetary amount	O	N2	1/15	Used

Semantics:

1. TDS01 is the total amount of invoice (including charges, less allowances) before terms discount (if discount is applicable).
2. TDS02 indicates the amount upon which the terms discount amount is calculated.
3. TDS03 is the amount of invoice due if paid by terms discount due date (total invoice or installment amount less cash discount).
4. TDS04 indicates the total amount of terms discount.

Comments:

1. TDS02 is required if the dollar value subject to discount is not equal to the dollar value of TDS01.

Loop SAC

Pos: 0400	Repeat: >1
Optional	
Loop: SAC	Elements: N/A

User Option (Usage): Used

To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0400	SAC	Service, Promotion, Allowance, or Charge Information	O	1		Used

SAC Service, Promotion, Allowance, or Charge Information

Pos: 0400	Max: 1
Summary - Optional	
Loop: SAC	Elements: 4

User Option (Usage): Used

To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SAC01	248	Allowance or Charge Indicator	M	ID	1/1	Must use
Description: Code which indicates an allowance or charge for the service specified All valid standard codes are used.						
SAC02	1300	Service, Promotion, Allowance, or Charge Code	X	ID	4/4	Used
Description: Code identifying the service, promotion, allowance, or charge All valid standard codes are used.						
SAC05	610	Amount	O	N2	1/15	Used
Description: Monetary amount						
SAC12	331	Allowance or Charge Method of Handling Code	O	ID	2/2	Used
Description: Code indicating method of handling for an allowance or charge All valid standard codes are used.						

Syntax Rules:

1. R0203 - At least one of SAC02 or SAC03 is required.
2. P0304 - If either SAC03 or SAC04 is present, then the other is required.
3. P0607 - If either SAC06 or SAC07 is present, then the other is required.
4. P0910 - If either SAC09 or SAC10 is present, then the other is required.
5. C1110 - If SAC11 is present, then SAC10 is required.
6. L130204 - If SAC13 is present, then at least one of SAC02 or SAC04 is required.
7. C1413 - If SAC14 is present, then SAC13 is required.
8. C1615 - If SAC16 is present, then SAC15 is required.

Semantics:

1. If SAC01 is "A" or "C", then at least one of SAC05, SAC07, or SAC08 is required.
2. SAC05 is the total amount for the service, promotion, allowance, or charge.
3. If SAC05 is present with SAC07 or SAC08, then SAC05 takes precedence.
4. SAC08 is the allowance or charge rate per unit.
5. SAC10 and SAC11 is the quantity basis when the allowance or charge quantity is different from the purchase order or invoice quantity.
6. SAC10 and SAC11 used together indicate a quantity range, which could be a dollar amount, that is applicable

to service, promotion, allowance, or charge.

7. SAC13 is used in conjunction with SAC02 or SAC04 to provide a specific reference number as identified by the code used.
8. SAC14 is used in conjunction with SAC13 to identify an option when there is more than one option of the promotion.
9. SAC16 is used to identify the language being used in SAC15.

Comments:

1. SAC04 may be used to uniquely identify the service, promotion, allowance, or charge. In addition, it may be used in conjunction with SAC03 to further define SAC02.
2. In some business applications, it is necessary to advise the trading partner of the actual dollar amount that a particular allowance, charge, or promotion was based on to reduce ambiguity. This amount is commonly referred to as "Dollar Basis Amount". It is represented in the SAC segment in SAC10 using the qualifier "DO" - Dollars in SAC09.

CTT Transaction Totals

Pos: 0700	Max: 1
Summary - Optional	
Loop: N/A	Elements: 7

User Option (Usage): Used

To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use
		Description: Total number of line items in the transaction set				
CTT02	347	Hash Total	O	R	1/10	Used
		Description: Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element. Example: -.0018 First occurrence of value being hashed. .18 Second occurrence of value being hashed. 1.8 Third occurrence of value being hashed. 18.01 Fourth occurrence of value being hashed. -----1855 Hash Total				
CTT03	81	Weight	X	R	1/10	Used
		Description: Numeric value of weight				
CTT04	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.				
CTT05	183	Volume	X	R	1/8	Used
		Description: Value of volumetric measure				
CTT06	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.				
CTT07	352	Description	O	AN	1/80	Used
		Description: A free-form description to clarify the related data elements and their content				

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 0800	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
Description: Total number of segments included in a transaction set including ST and SE segments						
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

Comments:

1. SE is the last segment of each transaction set.

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element						
GE02	28	Group Control Number	M	N0	1/9	Must use
Description: Assigned number originated and maintained by the sender						

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
Description: A count of the number of functional groups included in an interchange						
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
Description: A control number assigned by the interchange sender						

Table of Contents

810 Invoice	1
ISA Interchange Control Header	3
GS Functional Group Header	5
ST Transaction Set Header	7
BIG Beginning Segment for Invoice	8
REF Reference Identification	9
N1 Loop N1	10
N1 Name	11
N2 Additional Name Information	12
N3 Address Information	13
N4 Geographic Location	14
ITD Terms of Sale/Deferred Terms of Sale	15
DTM Date/Time Reference	16
IT1 Loop IT1	17
IT1 Baseline Item Data (Invoice)	18
CTP Pricing Information	20
PID Loop PID	21
PID Product/Item Description	22
PO4 Item Physical Details	23
REF Reference Identification	24
SAC Loop SAC	25
SAC Service, Promotion, Allowance, or Charge Information	26
TDS Total Monetary Value Summary	28
SAC Loop SAC	29
SAC Service, Promotion, Allowance, or Charge Information	30
CTT Transaction Totals	32
SE Transaction Set Trailer	33
GE Functional Group Trailer	34
IEA Interchange Control Trailer	35