


★ Security Score



Security Score 59/100


🛡️ Risk Rating



Grade



📊 Severity Distribution (%)



🏠 Privacy Risk



User/Device Trackers

📄 Findings



High
1



Medium
13




Info




Secure

4

 Hotspot
0

3

| | |
|--|--------------------------|
| <div>high</div> Domain config is insecurely configured to permit clear text traffic to these domains in scope | NETWORK |
| <div>medium</div> Base config is configured to trust system certificates | NETWORK |
| <div>medium</div> Service (androidx.glance.appwidget.GlanceRemoteViewsService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_REMOTEVIEWS [android:exported=true] | MANIFEST |
| <div>medium</div> Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true] | MANIFEST |
| <div>medium</div> Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true] | MANIFEST |
| <div>medium</div> Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true] | MANIFEST |
| <div>medium</div> Files may contain hardcoded sensitive information like usernames, passwords, keys etc. | CODE |
| <div>medium</div> IP Address disclosure | CODE |
| <div>medium</div> App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database. | CODE |
| <div>medium</div> The App uses an insecure Random Number Generator. | CODE |
| <div>medium</div> App can read/write to External Storage. Any App can read data written to External Storage. | CODE |
| <div>medium</div> MD5 is a weak hash known to have hash collisions. | CODE |
| <div>medium</div> SHA-1 is a weak hash known to have hash collisions. | CODE |
| <div>medium</div> This app may contain hardcoded secrets | SECRETS |
| <div>info</div> This App uses SQL Cipher. SQLCipher provides 256-bit AES encryption to sqlite database files. | CODE |
| <div>info</div> The App logs information. Sensitive information should never be logged. | CODE |
| <div>info</div> App can write to App Directory. Sensitive Information should be encrypted. | CODE |
| <div>info</div> This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it. | CODE |
| <div>secure</div> Base config is configured to disallow clear text traffic to all domains | NETWORK |
| <div>secure</div> This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel. | CODE |
| <div>secure</div> This application has no privacy trackers | TRACKERS |

MobSF Application Security Scorecard generated for  (Pager Rat 0.9.1) 