

# **Tools for secondary analyses for individualized effects**

Tuesday afternoon session

# (Personalized) Sequential decision making

- Mobile health: Personalized app notifications to promote healthy behavior
- Online education: Personalized teaching strategies for better learning
- Online advertising: Personalized ads / placements to increase revenue

Physical activity



Wearable/trackers



# Personalized decision making in medicine

- Precision medicine with RCTs
  - Subgroup analysis – typically very limiting
  - ITE, counterfactual, conditional average treatment effect – Helps with better decisions **in hindsight**, but becomes useful step for hypothesis generation for the future
  - Precision medicine is a doctor's goal – <https://nam.edu/wp-content/uploads/2019/08/Caring-for-the-Individual-Patient-prepub.pdf>

# Primary analyses

- Trials are designed to help answer primary questions of interest, aka, primary analyses
  - **On average:** Does the mobile app with the RL algorithm help people become more active?
  - **Subgroup analysis:** Same question can be asked for pre-specified subgroups of population
- These analyses are done by the scientists involved in the trials
- These analyses are pre-specified and in best cases, pre-registered at [clinicaltrials.gov](https://clinicaltrials.gov) or openscience


# Examples in mHealth trials

- **HeartSteps V1**: Delivering (vs. not delivering) a contextually-tailored activity suggestion increases average step count in the 30 min following a decision point
- **SARA**: Offering (vs. not offering) an inspirational quote increases the likelihood to fully complete current day's survey and/or active tasks
- **ORALYTICS**: Delivering an engagement prompt increases proximal oral self-care behaviors (OSCB) in the subsequent brushing window as compared to not delivering an engagement prompt
- Typically these analyses are marginal in nature, often across both ***users and time***, about treatment effect on average

# Secondary analyses

- Given the data from the trials, what else can we learn from it? What new theories can be conjectured from it?
- For example:
  - What group of people benefit the most from the app?
  - How does the benefit vary over time?
- Can we assess these conjectures on the same data?
- Essentially, exploratory data analyses with the goal to provide insights

# Secondary analyses



**Similar to Induction in logical reasoning**

# Examples for HeartSteps

- Secondary:
  - Which states are more useful for personalizing the intervention?
  - Is there heterogeneity in how the people respond? Which group of people respond the best to the app?





# Are the two related?

- The questions of interest are generally formulated as hypothesis
  - And the goal of primary analyses is to illustrate whether the data from the trial accepts or refutes the hypothesis with quantitative support (often in terms of statistical significance)
  - But where do these questions come from?

# Are the two related?




- The questions of interest are generally formulated as hypothesis
  - And the goal of primary analyses is to illustrate whether the data from the trial accepts or refutes the hypothesis with quantitative support (often in terms of statistical significance)
  - But where do these questions come from?
  - Typically the output of secondary analyses from some other data

## Primary analyses





## Secondary analyses

## Primary analyses






## Secondary analyses



## Primary analyses





## Secondary analyses








**Testable questions**



**Observation**




**Induction**


**some explanations**




## Testable questions



## Testing




## Evaluation




## Observation



## Analysis



## Hypothesis



**Deduction**


**Induction**

**some explanations**

## Testable questions


## Testing

## Evaluation




## Induction

some explanations




# Empirical research cycle / Scientific method

[De Groot 1961]



# Data science life cycle [Yu & Kumbier 2021]



**Next:**


# **Two approaches for secondary analyses with adaptively collected data**

Today + Tomorrow morning: Using factor models

Tomorrow second session: Using simulators

# Building AI agents for personalized treatments

How to [assign personalized digital treatments](#) to help you?




Mobile health study:  
**Personalized HeartSteps** [Liao+ '20]

- ▶ **Goal:** Promote physical activity via mobile app
- ▶ **Population:** 91 hypertension patients, 90 days
- ▶ **Treatment:** Mobile notifications upto 5 times/day assigned by a bandit algorithm
- ▶ **Outcome:** 30-min step count after decision time

# Building AI agents for personalized treatments

How to assign personalized digital treatments to help you?



Mobile health study: **Personalized HeartSteps** [Liao+ '20]

- ▶ **Goal:** Promote physical activity via mobile app
- ▶ **Population:** 91 hypertension patients, 90 days
- ▶ **Treatment:** Mobile notifications upto 5 times/day assigned by a bandit algorithm
- ▶ **Outcome:** 30-min step count after decision time



image credits  
[va.gov](https://va.gov)  
[apple.com](https://apple.com)



Apple Research app

**The future of health research is you.**



# Motivating questions for our secondary analyses

- Was sending the notification effective for different users? (E.g., was there a treatment effect for a given user?)
- Was the RL algorithm effective in personalizing the timing of these notifications? (E.g., did the RL algorithm learn these effects and send notifications accordingly?)

# The two approaches

- Today: When we **do not** have access to the RL algorithm
  - Proceed by modeling and some estimation procedure, provide theoretical guarantees under strong assumptions
- Tomorrow: When we **have** access to the RL algorithm
  - Proceed by modeling and simulations using the RL algorithm, provide empirical evidence under weak assumptions

# An ambitious question

- For a given user  $i$  at a given time  $t$ , should we have sent the notification?
  - **Mathematizing this question is non-trivial. Why?**

# An ambitious question

- For a given user  $i$  at a given time  $t$ , should we have sent the notification?
  - **Mathematizing this question is non-trivial. Why?**
  - When we have delayed effects, to answer this question, we have to ask what we did before time  $t$  and what we are going to do after time  $t$ ?

# An ambitious question: Simplified setting

- For a given user  $i$  at a given time  $t$ , should we have sent the notification?
  - Let's simplify the problem: Suppose we are in a bandit-like setting and have no delayed effects. Suppose we don't even have states. **Can we easily answer the question without any assumptions?**

# An ambitious question: Simplified setting

- For a given user  $i$  at a given time  $t$ , should we have sent the notification?
  - Let's simplify the problem: Suppose we are in a bandit-like setting and have no delayed effects. Suppose we don't even have states. **Can we easily answer the question without any assumptions?**
  - **No.** Because answering this question requires us to estimate counterfactual quantities.

# An ambitious question: Simplified setting

- For a given user  $i$  at a given time  $t$ , should we have sent the notification?
  - Let's simplify the problem: Suppose we are in a bandit-like setting and have no delayed effects. Suppose we don't even have states. **Can we easily answer the question without any assumptions?**
  - **No.** Because answering this question requires us to estimate counterfactual quantities.
  - **What if the potential outcomes  $R_t(1), R_t(0)$  are iid at each time?**

# An ambitious question: Simplified setting

- For a given user  $i$  at a given time  $t$ , should we have sent the notification?
  - Let's simplify the problem: Suppose we are in a bandit-like setting and have no delayed effects. Suppose we don't even have states. **Can we easily answer the question without any assumptions?**
  - **No.** Because answering this question requires us to estimate counterfactual quantities.
  - **What if the potential outcomes  $R_t(1), R_t(0)$  are iid at each time? Still no.** We need to have some notion of repeated measurements for the “quantity of interest”.



# A factor model for potential outcomes with “no delayed effects”

- The potential outcomes of  $N$  units (aka users) across  $T$  decision times are sampled as follows:

# A factor model for potential outcomes with “no delayed effects”

- The potential outcomes of  $N$  units (aka users) across  $T$  decision times are sampled as follows:
  - For each unit  $i \in [N]$ , sample its “unit factor” for each treatment  $u_i^{(1)}, u_i^{(0)}$ , which remains fixed across time – these denote user traits, like gender, personality

# A factor model for potential outcomes with “no delayed effects”

- The potential outcomes of  $N$  units (aka users) across  $T$  decision times are sampled as follows:
  - For each unit  $i \in [N]$ , sample its “unit factor” for each treatment  $u_i^{(1)}, u_i^{(0)}$ , which remains fixed across time – these denote user traits, like gender, personality
  - For each decision time  $t \in [T]$ , sample the corresponding “time factor”  $v_t^{(1)}, v_t^{(0)}$ , that is shared across units – these denote time traits, like societal and weather changes

# A factor model for potential outcomes with “no delayed effects”


- The potential outcomes of  $N$  units (aka users) across  $T$  decision times are sampled as follows:
  - For each unit  $i \in [N]$ , sample its “unit factor” for each treatment  $u_i^{(1)}, u_i^{(0)}$ , which remains fixed across time – these denote user traits, like gender, personality
  - For each decision time  $t \in [T]$ , sample the corresponding “time factor”  $v_t^{(1)}, v_t^{(0)}$ , that is shared across units – these denote time traits, like societal and weather changes
  - The potential outcomes for unit  $i$  at time  $t$  satisfy
$$\mathbb{E}[R_{i,t}(a) | u_i^{(a)}, v_t^{(a)}] = \langle u_i^{(a)}, v_t^{(a)} \rangle \triangleq \theta_{i,t}^{(a)}$$
and  $R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$

# A factor model for potential outcomes with “no delayed effects”

- The potential outcomes of  $N$  units (aka users) across  $T$  decision times are sampled as follows:
  - For each unit  $i \in [N]$ , sample its “unit factor” for each treatment  $u_i^{(1)}, u_i^{(0)}$ , which remains fixed across time – these denote user traits, like gender, personality
  - For each decision time  $t \in [T]$ , sample the corresponding “time factor”  $v_t^{(1)}, v_t^{(0)}$ , that is shared across units – these denote time traits, like societal and weather changes
  - The potential outcomes for unit  $i$  at time  $t$  satisfy
$$\mathbb{E}[R_{i,t}(a) | u_i^{(a)}, v_t^{(a)}] = \langle u_i^{(a)}, v_t^{(a)} \rangle \triangleq \theta_{i,t}^{(a)}$$
and  $R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$

Where is the no  
delayed effects  
assumption kicking in?

# A factor model for potential outcomes



We allow  $A_{i,t}$  to be assigned by a bandit algorithm that may be **pooling** data across users

# Is the ambitious question now tractable?

- $\mathbb{E}[R_{i,t}(a) \mid u_i^{(a)}, v_t^{(a)}] = \langle u_i^{(a)}, v_t^{(a)} \rangle \triangleq \theta_{i,t}^{(a)}$

$$\text{and } R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$$

- **Can we now hope to learn  $\theta_{i,t}^{(1)}$  – the conditional mean parameter for a unit with factor  $u_i^{(1)}$  at decision time with factor  $v_t^{(1)}$ ?**
- If yes, we can then also estimate  $\theta_{i,t}^{(1)} - \theta_{i,t}^{(0)}$ : the “treatment effect” for unit  $i$  at time  $t$ .


# Another look at the factor model

$$R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$$

$$\theta_{i,t}^{(a)} \triangleq \langle u_i^{(a)}, v_t^{(a)} \rangle$$

user factor  
(e.g., personal  
traits)

time factor  
(e.g., societal, weather  
changes)





# Another look at the factor model


$$R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$$

$$\theta_{i,t}^{(a)} \triangleq \langle u_i^{(a)}, v_t^{(a)} \rangle$$

user factor  
(e.g., personal  
traits)

time factor  
(e.g., societal, weather  
changes)

Factor model also a form of  
dimensionality reduction for  
number of unknowns



# Another look at the factor model

$$R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$$


$$\theta_{i,t}^{(a)} \triangleq \langle u_i^{(a)}, v_t^{(a)} \rangle$$

user factor  
(e.g., personal  
traits)

time factor  
(e.g., societal, weather  
changes)

$N$  user  
factors

$T$  time factors




Questions:

- What are the limitations of this model?
- What are the advantages of this model?
- Is estimating  $\theta_{i,t}^{(1)} - \theta_{i,t}^{(0)}$  equivalent to estimating margins in a "factorized pooled bandits"?

# Next: User nearest neighbors estimator for treatment $a$

$$R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$$



# User nearest neighbors estimator for treatment $a$

$$R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$$


1. Compute distance between user pairs

$i, j$  under treatment  $a$  **using all data**

$$\rho_{i,j}^{(a)} = \frac{\sum_{t'=1}^T (R_{i,t'} - R_{j,t'})^2 \cdot \mathbf{1}(A_{i,t'} = A_{j,t'} = a)}{\sum_{t'=1}^T \mathbf{1}(A_{i,t'} = A_{j,t'} = a)}$$

$$+ \frac{\hat{\sigma}_\rho}{\sqrt{\sum_{t'=1}^T \mathbf{1}(A_{i,t'} = A_{j,t'} = a)}}$$

$\hat{\sigma}_\rho^2 = \text{Variance estimate for } (\varepsilon_{i,t'} - \varepsilon_{j,t'})^2$



# User nearest neighbors estimator for treatment $a$

$$R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$$

1. Compute distance between user pairs


$i, j$  under treatment  $a$  **using all data**

$$\rho_{i,j}^{(a)} = \frac{\sum_{t'=1}^T (R_{i,t'} - R_{j,t'})^2 \cdot \mathbf{1}(A_{i,t'} = A_{j,t'} = a)}{\sum_{t'=1}^T \mathbf{1}(A_{i,t'} = A_{j,t'} = a)}$$

$$+ \frac{\hat{\sigma}_\rho}{\sqrt{\sum_{t'=1}^T \mathbf{1}(A_{i,t'} = A_{j,t'} = a)}}$$

$\hat{\sigma}_\rho^2 = \text{Variance estimate for } (\varepsilon_{i,t'} - \varepsilon_{j,t'})^2$

Why do we have a second term? Is there another way to operationalize it?



# User nearest neighbors estimator for treatment $a$

$$R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$$

1. Compute distance between user pairs


$i, j$  under treatment  $a$  **using all data**

$$\rho_{i,j}^{(a)} = \frac{\sum_{t'=1}^T (R_{i,t'} - R_{j,t'})^2 \cdot \mathbf{1}(A_{i,t'} = A_{j,t'} = a)}{\sum_{t'=1}^T \mathbf{1}(A_{i,t'} = A_{j,t'} = a)}$$

$$+ \frac{\hat{\sigma}_\rho}{\sqrt{\sum_{t'=1}^T \mathbf{1}(A_{i,t'} = A_{j,t'} = a)}}$$


2. Average over **user neighbors** treated with  $a$  at time  $t$

$$\hat{\theta}_{i,t,\text{user-NN}}^{(a)} = \frac{\sum_{j=1}^N R_{j,t} \mathbf{1}(\rho_{i,j}^{(a)} \leq \eta, A_{j,t} = a)}{\sum_{j=1}^N \mathbf{1}(\rho_{i,j}^{(a)} \leq \eta, A_{j,t} = a)}$$



# Bias-variance tradeoff for the nearest neighbors with $\eta$


**MSE for estimates  
on observed entries**



Discuss: Why do we expect this U-shaped curve?

# Bias-variance tradeoff for the nearest neighbors with $\eta$


**MSE for estimates  
on observed entries**





# Can you think of another variant of nearest neighbors?

$$R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$$



# Time nearest-neighbor estimators

$$R_{i,t} = R_{i,t}(A_{i,t}) \triangleq \theta_{i,t}^{(A_{i,t})} + \varepsilon_{i,t}^{(A_{i,t})}$$

1. Compute distance between time pairs


$t, t'$  under treatment  $a$  **using all data**

$$\rho_{t,t'}^{(a)} = \frac{\sum_{j=1}^N (R_{j,t} - R_{j,t'})^2 \cdot \mathbf{1}(A_{j,t} = A_{j,t'} = a)}{\sum_{j=1}^N \mathbf{1}(A_{j,t} = A_{j,t'} = a)}$$

$$+ \frac{\hat{\sigma}_\rho}{\sqrt{\sum_{j=1}^N \mathbf{1}(A_{j,t} = A_{j,t'} = a)}}$$

2. Average over **user neighbors** treated with  $a$  at time  $t$

$$\hat{\theta}_{i,t,\text{user-NN}}^{(a)} = \frac{\sum_{j=1}^N R_{j,t} \mathbf{1}(\rho_{i,j}^{(a)} \leq \eta, A_{j,t} = a)}{\sum_{j=1}^N \mathbf{1}(\rho_{i,j}^{(a)} \leq \eta, A_{j,t} = a)}$$



# Discussion questions

- Which of the two estimators, time NN or user NN, might you prefer? When would these estimators be not appropriate?
  - Do you think these estimators are interpretable?
  - Is there an easy way to diagnose for which  $(i, t)$  pairs, the NN estimates, are likely to be reliable? **Hint:** Think about a unique user on a unique day.
- Given all these counterfactual estimates, what kind of quantities could you investigate?
- How would you generalize the factor model to include
  - delayed effects?
  - state information?

# Tomorrow first lecture: Deep dive into the NN analysis

- When would these estimators do well?
- An even better variant of nearest neighbors