



EDI INBOUND TRANSLATION RULES

Contents

Table Structure.....	1
Valid Comparisons	2
Special Output Types	2
Insert Example	3
Simple Example:	4
Moderate Example:	5

Table Structure

Trns_trns_tbl (Table that will be affected by the rule)

Trns_trns_fld (Field we want to update with rule)

Trns_end_dte (When the rule will no longer be in affect)

Trns_seq (Seq of which the rule will be checked)

Trns_strt_dte (When the rule will be active)

Trns_source_comp (What fields you want to compare)

trns_operation (What operator you want to execute)

trns_value (What value you want to compare it against)

trns_output_value (result if true that gets put into the field defined in trns_trns_fld)

trns_output_type (used for Expresssion and Exclude operations)

Audit Fields

Valid Comparisons

=	Equals
<>	Not Equal
IN	If the value is in an array of values
NOT IN	Not in an array of values
IS NULL	If the value is null/blank/undefined
IS NOT NULL	If the value is not null/blank/undefined

Special Output Types

1. Expression

- a. Makes the value be evaluated instead of it being a constant value

2. ADD_ROW

- a. Adds an extra row copying from a different row and changing a value within it
 - i. Currently only for Adding A Mill to our JSON document for Invex.

3. EXCLUDE

- a. Used to exclude rows from being inserted into our Invex Tables

Insert Example

← Back

Edit Translation Table Rule

Table Name

856_SNF_Names

name_qual_id

Start Date

10/12/2025

End Date*

10/12/2075

Sequence in which rule will be checked

1

Character

Output Value

1

Rule Comparisons

Comp	Operator	Value	Action
name_id	IN	005159199,0039134 23,832061845,61880 5733	Remove

Add Rule

Insert Rule

Field that needs translation

Output type

Output if true value

Comparisons

Simple Example:

This example shows 1:1 mapping.

A row from the Names comes in and we use the different values from that row for our comparison.

Source Table: 856_SNF_Names

Translated Field: name_qual

Output if true value: S

{=,=,NOT_IN}

Trns_source_comp	trns_operation	trns_value
Name_qual	=	ST
Name_id	=	067716142
Name_qual_id	NOT_IN	1,2,3,4

Moderate Example:

For this example, we will use references to other rows in our table that determine our rule.

Source Table: 856_SNF_Names

Translated Field: name_qual

Output if true value: S

Trns_source_comp	trns_operation	trns_value
Name_qual	=	ST
SNF_Names[name_qual=MF].name_qual	=	MF
SNF_Names.name_qual	=	SF

The first line is a simple comparison from our row being passed in.

The second line searches our SNF_Names to find where the name_qual = MF and return that record that in turn the .name_qual returns the name_qual value.

Without the .name_qual the return would be an array rather than a single object we want to compare.

The third line searches our SNF_Names for any record that has name_qual = to SF.