


JavaScript Basics

Syntax, Data Type and Variables, Operators,
Conditional Statements, Loops, Debugging



SoftUni Team
Technical Trainers



SoftUni



Software University

<https://softuni.bg>

You Have Questions?


sli.do

#QA-Auto-BackEnd

Table of Contents

1. JavaScript Overview
2. JavaScript Syntax
3. Data Types and Variables
4. Operators
5. Conditional Statements
6. Loops
7. Debugging Techniques





JavaScript Overview

Definition, Execution, IDE Setup

What is JavaScript?


- JavaScript (**JS**) is a **high-level** programming language
 - One of the **core technologies** of the World Wide Web
 - Enables **interactive** web pages and applications
 - Can be **executed** on the **server** and on the **client**
- Features
 - C-like **syntax** (curly-brackets, identifiers, operator)
 - **Multi-paradigm** (imperative, functional, OOP)
 - Dynamic **typing**



- JavaScript is a **dynamic programming language**
 - Operations otherwise done at **compile-time** can be done at **run-time**
- It is **possible** to change the **type** of a variable or add new properties or methods to an object **while** the program is **running**
- In **static programming languages**, such changes are normally **not possible**


Web Browser Dev Console

- Developer Console: **[F12]**



The screenshot shows the Chrome DevTools Console with the 'Console' tab selected. The interface includes a toolbar with a close button, a filter icon, a dropdown menu set to 'top', and a 'Preserve log' checkbox. The console log contains the following entries:

```
> function add(a, b) {  
    return a + b;  
}  
< undefined  
> add(5, 3)  
< 8  
> |
```




The screenshot shows the Firefox DevTools Console with the 'Console' tab selected. The interface includes a toolbar with a close button, a filter icon, and a 'Filter Output' dropdown. The console log contains the following entries:

```
>> function add(a, b) { return a + b; }  
< undefined  
>> add(5, 3)  
< 8  
>>
```

Node.js

- What is **Node.js**?
 - **Server-side** JavaScript runtime
 - Chrome V8 JavaScript engine
 - NPM **package manager**
 - Install node packages



```
>node
> let a = 5;
undefined
> console.log(a);
5
undefined
>
```




JavaScript Syntax

Functions, Operators, Input and Output

JavaScript Syntax

- Defining and initializing variables



Declare a variable
with **let**

```
let a = 5;  
let b = 10;
```

Variable name

Variable value

- Conditional statement

Body of the
conditional statement

```
if (b > a) {  
  console.log(b);  
}
```

Functions and Input Parameters

- In order to solve different problems, we are going to use **functions** and the **input** will come as **parameters**
- A function is similar to a **procedure**, which executes when called

declaration

parameters

```
function solve (num1, num2) {  
    // some logic  
}
```

```
solve(2, 3);
```

calling the function

- We use the `console.log()` method to print to console

```
function solve (name, grade) {  
  console.log('The name is: ' + name + ', grade: ' + grade);  
}
```

```
solve('Peter', 3.555);  
// The name is: Peter, grade: 3.555
```

- Text can be composed easier using interpolated strings
 - Works only with the ``` brackets

```
console.log(`The name is: ${name}, grade: ${grade}`);
```

- To format a number, use the **toFixed()** method
 - Converts a number to **string**
 - Rounds the string to a specified number of decimals
 - Default value is 0 (no decimals)

Number of digits after the decimal sign

```
grade.toFixed(2);  
// The name is: Peter, grade: 3.56
```

- If the number of decimals is higher than in the number, zeros are added



Data Types and Variables


Definitions and Examples

JavaScript Data Types

- Seven **primitive types**
 - Boolean
 - null
 - undefined
 - Number
 - String
 - Symbol
 - BigInt
- and **Objects** (including Functions and Arrays)



Data Types Examples



```
let number = 10;           // Number
let person = {name: 'George', age: 25}; // Object
let array = [1, 2, 3];     // Array
let isTrue = true;        // Boolean
let name = 'George';      // String
let empty = null;         // null
let unknown = undefined;  // undefined
```


- **var**

- Use **function scope**
- Can be accessed anywhere in the function, including outside the initial block

```
{  
  var x = 2;  
}  
console.log(x);  
// 2
```

- **let** and **const**

- Use **block scope**
- Can **NOT** be accessed from outside the **{ }** block where initially declared

```
{  
  let x = 2;  
}  
console.log(x);  
// Error
```



■ **let**

- Can be reassigned after initial assignment
- Variable's value can change
- **let** is used when reassignment is necessary

■ **const**

- Cannot be reassigned after initial assignment, remains constant
- Variable's value remains fixed
- **const** is used when variable will not be reassigned



Undefined

- A variable without a value has the value **undefined**
 - The **typeof** is also **undefined**

```
let car;  
// Value is undefined, type is undefined
```

- A variable can be emptied, by setting the value to **undefined**
 - The type will also be **undefined**

```
let car = undefined;  
// Value is undefined, type is undefined
```




Null

- **Null** is "nothing"
- It is supposed to be something that doesn't exist
- The **typeof** null is an **object**



```
let person = {  
  firstName: "John",  
  lastName: "Doe",  
  age: 50  
};  
person = null;  
console.log(person);           // null  
console.log(typeof(person));  // object
```



Operators

Overview of Different Types of Operators

- **Arithmetic operators**

- Take numerical values (either literals or variables) as their operands
- Return a single numerical value
 - Addition (+)
 - Subtraction (-)
 - Multiplication (*)
 - Division (/)
 - Remainder (%)
 - Exponentiation (**)

```
let a = 15;  
let b = 5;  
let c;  
c = a + b; // 20  
c = a - b; // 10  
c = a * b; // 75  
c = a / b; // 3  
c = a % b; // 0  
c = a ** b; // 155 = 759375
```

- Used in logical statements to determine equality or difference between various variables or values

Operator	Notation in JS
Equal value	<code>==</code>
Equal value and type	<code>===</code>
Not equal value	<code>!=</code>
Not equal value/type	<code>!==</code>
Greater than	<code>></code>
Greater than or Equal	<code>>=</code>
Less than	<code><</code>
Less than or Equal	<code><=</code>

Comparison Operators – Examples

```
console.log(1 == '1'); // true
console.log(1 === '1'); // false
console.log(3 != '3'); // false
console.log(3 !== '3'); // true
console.log(5 < 5.5); // true
console.log(5 <= 4); // false
console.log(2 > 1.5); // true
console.log(2 >= 2); // true
console.log((5 > 7) ? 4 : 10); // 10
```



Ternary operator

- The **typeof** operator returns a string indicating the type of an operand

```
const val = 5;  
console.log(typeof val);    // number
```

```
const str = 'hello';  
console.log(typeof str);    // string
```

```
const obj = {name: 'Maria', age:18};  
console.log(typeof obj);    // object
```



Conditional Statements

Implementing Control-Flow Logic

What is a Conditional Statement?

- The **if-else** statement
 - Do action depending on a specified condition

```
let a = 5;  
if (a >= 5) {  
  console.log(a);  
}
```

If the condition **is met**,
the code will execute

- You can chain conditions

```
else {  
  console.log('no');  
}
```

Continue on the **next condition**, if the first is **not met**



Chained Conditional Statements

- The **if-else if-else...** construct is a series of checks

```
let a = 5;  
if (a > 10)  
    console.log("Bigger than 10");  
else if (a < 10)  
    console.log("Less than 10");  
else  
    console.log("Equal to 10");
```

Only "**Less than 10**"
will be printed

- If one condition is true, it does not proceed to verify the next conditions

- **Logical operators** give us the ability to write multiple conditions in one **if** statement
- They return a boolean result (**true** or **false**)

Operator	Description	Example
!	NOT	!false → true
&&	AND	true && false → false
	OR	true false → true

The Switch-Case Statement

- Works as a series of **if-else if-else if...**

```
switch (...) {  
  case ...: ...  
    // code  
    break;  
  case ...: ...  
    // code  
    break;  
  default:  
    // code  
    break;  
}
```

List of conditions
(values) for the
inspection

The condition in
the **switch case** is
a value

Code to be executed if
there is no match with any
case



Loops

Code Block Repetition

Loops in JavaScript

- Loops execute a block of code a number of times
- JavaScript supports 5 kinds of loops
 - **for**
 - **for-in**
 - **for-of**
 - **while**
 - **do-while**



- The **for** loop

- Loops through a block of code a specified number of times

```
for (let i = 0; i < 5; i++) {  
  console.log(i);  
}
```

- The **for-of** loop

- Iterates through all **elements** in an iterable object
- Cannot access the current index

```
for (let el of collection) {  
  // Process the value here  
}
```

- The **while** loop
 - Executes a block of code as long as the specified condition is true

```
while (condition) {  
    // code to be executed  
}
```

- The **do-while** loop
 - Executes a block of code once, then checks the condition

```
do {  
    // code to be executed  
}  
while (condition);
```



Debugging Techniques

Strict Mode, IDE Debugging Tools

Strict Mode

- **Strict mode** limits certain "sloppy" language features
 - Silent errors will **throw exception** instead

```
'use strict';           // File-level  
mistypeVariable = 17;    // ReferenceError
```


```
function strict() {  
    'use strict';        // Function-level  
    mistypeVariable = 17;  
}
```

- Enabled by default in **modules**



Debugging in Visual Studio Code

- Visual Studio Code has a built-in **debugger**
- It provides
 - **Breakpoints**
 - Ability to **trace** the code execution
 - Ability to **inspect** variables at runtime




Using the Debugger in Visual Studio Code

- Start without Debugger: **[Ctrl+F5]**
- Start with Debugger: **[F5]**
- Toggle a breakpoint: **[F9]**
- Trace step by step: **[F10]**
- Force step into: **[F11]**

- JS == a **high-level** programming language
- Node.js == **server-side JS runtime**
- There are **objects** and **7 primitive** data types
- 3 variable types – **let, const, var**
- Conditional statement – **if-else, switch-case**
- Loops – **for, for-in, for-of, while, do-while**
- Different **debugging techniques**



Questions?



SoftUni Diamond Partners



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is **copyrighted content**
- Unauthorized copy, reproduction or use is illegal
- © SoftUni – <https://about.softuni.bg/>
- © Software University – <https://softuni.bg>



- Software University – High-Quality Education, Profession and Job for Software Developers

- softuni.bg, about.softuni.bg

- Software University Foundation

- softuni.foundation

- Software University @ Facebook

- facebook.com/SoftwareUniversity

- Software University Forums

- forum.softuni.bg

