

CZ4041 - MACHINE LEARNING

PETER

SCHOOL OF COMPUTER ENGINEERING 2016/17

Contents

\mathbf{C}	ontents	j
Li	ist of Tables	ii
Li	ist of Figures	iii
1	Introduction	1
	1.1 Team Members	1
	1.2 Problem Statement	1
	1.2.1 Challenge	1
2	Preprocessing	2
3	Experiments	4
	3.1 LSTM	4
	3.2 Neural Network	5
4	Results	6
5	Conclusion	7

List of Tables

List of Figures

1. Introduction

Lorem ipsum dolor sit amet.

1.1 Team Members

Lorem ipsum dolor sit amet.

1.2 Problem Statement

Lorem ipsum dolor sit amet.

1.2.1 Challenge

2. Preprocessing

The problem contains three files, train.csv, test.csv, and store.csv. The file train.csv contains historical data including sales for 1115 stores everyday from 1 Jan 2013 to 31 July 2015. While store.csv contains supplemental information about each store. Then, test.csv contains historical data excluding sales and number of customers everyday from 1 Aug 2015 to 17 Sept 2015.

Each row in *train.csv* contains store ID, day of week, date, number of customers, sales, whether the store is open, whether the store is doing a promo, state holiday, and whether that day is a school holiday. Columns in *test.csv* is almost identical to those of *train.csv*, except that sales and number of customers are unknown in *test.csv*. Each row in *test.csv* contains a submission ID for the purpose of evaluation on prediction result. On the other hand, each row in *store.csv* contains the details of a store, such as store type, assortment type, whether the store has competition, since when the competition exists, competition distance, whether the store is doing *promo2*, and *promo2* period.

Initially, our preprocessing method merges train.csv and store.csv by store ID. The columns DayOfWeek and StateHoliday in train.csv are transformed into one-hot vector respectively. The columns StoreType and Assortment in store.csv are transformed into one-hot vector respectively as well. The columns CompetitionOpenSinceMonth and CompetitionOpenSinceYear are substituted into a single column HasCompetition which depends on its respective Date column. The same thing also applies to the columns Promo2SinceWeek, Promo2SinceYear, and PromoInterval, they are substituted into a single column IsDoingPromo2 which depends in its respective Date column. CompetitionDistance is set to the maximum value in the training set if a store does not have a competition in any given date. All store data are retained even when a store is closed on a particular date.

After train.csv and store.csv has been merged, we proceed to merge test.csv and

store.csv by store ID as well. The preprocessing method in this step is identical in the previous paragraph. The difference is that sales and the number of customers are unknown in the test dataset.

3. Experiments

Lorem ipsum dolor sit amet.

3.1 LSTM

LSTM (abbreviation for Long-short Term Memory) is a variant of recurrent neural network. LSTM seeks to solve vanishing gradient and exploding gradient problem in vanilla recurrent neural network. These problems happen when a training sequence is too long. LSTM introduces gating concept in recurrent neural network. An LSTM contains three gates, an input gate, an output gate, and a forget gate. A forget gate determines when to reset the content of the cell memory. An input and output gate control the flows of input and output of the LSTM respectively.




Figure 3.1: An LSTM unit

We use LSTM unit provided by Caffe¹ framework. It requires CUDA 8 and

¹Caffe is developed by Berkeley Vision and Learning Center (BVLC)

cuDNN v5.1 from Nvidia, which enable Caffe framework to utilize Nvidia GPU to train a neural network. We used Nvidia GTX 850m to train our LSTM network. GTX 850m is pretty decent to train a medium-sized network.

3.2 Neural Network

4. Results

5. Conclusion