TRITON LED
MAX-Emergency

MAX-E Series- Reliable, Long-Lasting.

For easy installation, durability and sustainability!

Our quest for sustainable and efficient lighting solutions, modern design principles combined with technological advancements have led to significant benefits)

Optimized Design for Efficiency: Fewer fixtures needed, which reduces investment costs and simplifies the overall lighting scheme.

Easy Installation, Swift and Simple Setup: Engineered for rapid installation, reducing working hours and costs (Remove if there's no space;, "for both new installations and retrofits". Modular plug-and-play components significantly cut down the complexity.

Reusability and Recycling - Low Environmental Footprint: Designed with sustainability in mind. Advanced technology ensures a longer lifespan. All components are easily disassembled, allowing for parts to be reused, or recycled. Our design philosophy minimizes waste and supports a circular economy.

Features:

- Flicker Free Light Distribution
- Extensive functionality
- Highly efficient lifetime solution
- Easy installation and maintenance
- Controllable and programmable Driver
- Precise and high quality output
- Robust, compact design integrated into the architectural structure.

Applications:

- Storage Lighting
- Sports Hall Lighting
- Industrial Lighting
- Commercial Lighting

Technical Data

Colors	3000K-4000K-5000K-6500K
Lumen:	80Ra:178–195 (Energy label A or B)
Mode:	Daylight/Non-Daylight
CRI:	Ra80
Optics Angle:	30°, 60°, 90°, 110° (PMMA)
Driver:	Dali2 (B2L), OnOff
Power Consuption:	4W (Emergency)/ 29W Daylight
Current Variations:	500mA
Average Lifetime:	100.000h/@25°C - L90/B10 72.000h/@40°C - L80/B10 56.000h/@75°C - L80/B20
Temperature:	-15°C to 50°C
Size Increments:	500mm (500 - 3000mm.)
IP Grade:	Quick Connector: IP20 W1,W2,W3, EN.
Material:	6061 Anodized Aluminium
Color Options:	Silver, White, Black
Accessories	Bracket: Standard 15mm Option: 30mm, 150mm, 240mm
Certifications:	CE (EMC, LVD, RoHS), EUR1.

Wireless protocols: MultiSensors:

B2L ready · DIMMABLE · FLICKER FREE

DRIVER protocols:

DALI 2 · AP (on/off)

5 YEAR WARRANTY

TRITONLED
www.triton-solutions.co