Decision	Our choice	Reason
Area depth Dg	4, the paper's value	Best trees in the final generation held 48 to 1 610 nodes, and the explore rule below makes sure the best tree reaches below the area, so exploit always has levels to vary.
Ending an explore phase	After Sg generations, but only once the best tree is deeper than Dg	Exploit can only change levels below the area. A best tree no deeper than the area would be copied into the whole population with nothing left to vary.
Entering exploit	One seeding generation: only the best tree is kept as an elite and every offspring is bred from it, with operators already restricted below Dg	Every tree then contains the area by construction, without grafting the area onto other individuals.
What "structure" means	Node symbols only; constants are content. EnemyInRange 0.2 and EnemyInRange 0.6 match	Otherwise a nudged constant would count as a new structure and the filter would be trivially passed.
Terminals in the similarity count	Counted	Our trees often have terminals within the top four levels.
Threshold Tg	6, not capped	With Dg = 4, areas hold many more than six nodes, so the threshold can always be reached.
Exploit stagnation	Any increase in the best combat score resets the Wg counter	The evaluation cache makes repeated scores identical, so "no change" is meaningful. Most training opponents are deterministic; see Section M.8 for the exception.
When no offspring passes the filter	After five failed attempts the last candidate is admitted anyway	Keeps the population size fixed. The filter is therefore soft: under heavy rejection, a few non-conforming trees can enter.
Best of run	The best tree of any generation	Retiring an area can drop the previous best from the population.
Run-level stopping	Separate from Wg: stop after 100 generations without a 0.005 gain in combat score	Ends runs that have stalled across several areas. Used once, in batch 2, seed 3.
Resuming a run	Phase and area memory are not saved in checkpoints	Kept the checkpoint format simple. A resumed run starts a fresh explore phase with an empty memory (this happened once; Section M.5.3).