

Laboratory 05A

CS-102

Spring 2022

Laboratory 5A

- Write a program with a loop that lets the user enter a series of integers until the user enters the number -99.
- When that occurs, the program should print out:
 - The number of integers that you entered.
 - The sum of all the integers that you entered.
 - The average of all the integers that you entered.
- Your program should also test to be sure that the number of integers that you typed in is > 0 .
 - Otherwise, when you compute the average, you will be dividing by zero.
- Your name should appear in the first line of your output.

Laboratory 5A

- Below is some sample output.

```
Jane Doe's Statistics Program
Enter a number: 82
Enter a number: 74
Enter a number: 16
Enter a number: 95
Enter a number: 47
Enter a number: 73
Enter a number: -99

The number of numbers entered is: 6
The sum of the numbers is: 387
The average value is: 64.5
```

Laboratory 5A

- Call your program: *YourName-Lab05A-1.cpp*
- If you are doing this Lab synchronously, demonstrate your solution to the instructor to receive proper credit.
- If you are doing this Lab asynchronously, submit your program to Canvas.
- Following are some programs in the text that might prove helpful.

Program 5-13

```
1  // This program calculates the total number of points a
2  // soccer team has earned over a series of games. The user
3  // enters a series of point values, then -1 when finished.
4  #include <iostream>
5  using namespace std;
6
7  int main()
8  {
9      int game = 1,    // Game counter
10         points,      // To hold a number of points
11         total = 0;   // Accumulator
12
13     cout << "Enter the number of points your team has earned\n";
14     cout << "so far in the season, then enter -1 when finished.\n\n";
15     cout << "Enter the points for game " << game << ": ";
16     cin >> points;
17
18     while (points != -1)
19     {
20         total += points;
21         game++;
22         cout << "Enter the points for game " << game << ": ";
23         cin >> points;
24     }
25     cout << "\nThe total points are " << total << endl;
26     return 0;
27 }
```

A
Sentinel
in
Program
5-13

Continued...

A Sentinel in Program 5-13

Program Output with Example Input Shown in Bold

```
Enter the number of points your team has earned  
so far in the season, then enter -1 when finished.
```

```
Enter the points for game 1: 7 [Enter]  
Enter the points for game 2: 9 [Enter]  
Enter the points for game 3: 4 [Enter]  
Enter the points for game 4: 6 [Enter]  
Enter the points for game 5: 8 [Enter]  
Enter the points for game 6: -1 [Enter]
```

```
The total points are 34
```

Laboratory 5A – Part 2

- Now we're going to repeat part A, but instead of using a numeric Sentinel value, we're going to use an alpha character to end the loop.
- When that occurs, the program should print out:
 - The number of integers that you entered.
 - The sum of all the integers that you entered.
 - The average of all the integers that you entered.
- Your program should also test to be sure that the number of integers that you typed in is > 0 .
 - Otherwise, when you compute the average, you will be dividing by zero.
- If you examine the sample program, Sum.cpp, you will see how this works, using **cin >> input** in the while loop condition.
- Call your program: *YourName-Lab05A-2.cpp*

Laboratory 5A – Part 2

- If you are doing this Lab synchronously, demonstrate your solution to the instructor to receive proper credit.
- If you are doing this Lab asynchronously, submit your program to Canvas.


```
// Sum.cpp
#include <iostream>
using namespace std;
int main()
{
    cout << "Enter all the numbers you wish to Total, strike Q to quit." << endl;
    double total = 0;
    double input;
    while (cin >> input)
    {
        total = total + input;
    }
    cout << "The Total = " << total << endl;
    cin.clear();          // The following four statements will clear out the
    cin.ignore();          // false output from the while loop,
    cin.get();             // and get rid of the hanging key stroke, thus
    cin.get();             // enabling the output to be held on the screen.
    return 0;
}
```

Using the cin <<
Boolean result
to end a loop of
numeric data
entry.

Laboratory 5A – Part 3

- In this Lab we are going to look at a C++ command which violates the rules of Structured Programming when used in loops, yet is tempting to use in certain situations.
- As the **continue** command is not necessary, we're going to show you where it might appear and how you can avoid its use altogether.
 - In Structured Programming, a loop is allowed to have one entrance and one exit.
 - The **continue** commands allows the loop to have more than one exit point.
 - This makes the loop more difficult to follow as well as debug.
- Program 5-26 shows the use of the **continue** command.
- Go ahead and enter this program and get it working. Test it so that you are clear about how it works.

Program 5-26: The Continue Statement - Example

```
// This program calculates the charges for DVD rentals.
```

```
// Every third DVD is free.
```

```
#include <iostream>
```

```
#include <iomanip>
```

```
using namespace std;
```

```
int main()
```

```
{
```

```
    int dvdCount = 1; // DVD counter
```

```
    int numDVDs;      // Number of DVDs rented
```

```
    double total = 0.0; // Accumulator
```

```
    char current;     // Current release, Y or N
```


```
    // Get the number of DVDs.
```

```
    cout << "How many DVDs are being rented? ";
```

```
    cin >> numDVDs;
```

Program 5-26 Concluded

```
// Determine the charges.
do
{
    if ((dvdCount % 3) == 0)
    {
        cout << "DVD #" << dvdCount << " is free!\n";
        continue; // Immediately start the next iteration
    }
    cout << "Is DVD #" << dvdCount;
    cout << " a current release? (Y/N) ";
    cin >> current;
    if (current == 'Y' || current == 'y')
        total += 3.50;
    else
        total += 2.50;
} while (dvdCount++ < numDVDs);
// Display the total.
cout << fixed << showpoint << setprecision(2);
cout << "The total is $" << total << endl;
return 0;
}
```



```
"C:\CodeBlocksWorkArea\Chapter 05\Pr5-2... - [X]
How many DVDs are being rented? 6
Is DVD #1 a current release? (Y/N) y
Is DVD #2 a current release? (Y/N) n
DVD #3 is free!
Is DVD #4 a current release? (Y/N) n
Is DVD #5 a current release? (Y/N) y
DVD #6 is free!
The total is $12.00
```

Laboratory 5A – Part 3

- Program 5-26 shows the use of the **continue** statement in a C++ program.
- Your job is to rewrite the program so that the **continue** statement is no longer needed.
- Tip: You will need to change your outer **if ()** statement into an **if () else** statement.
- After you have worked out the new loop, rewrite the relevant lines and after you have it working, demonstrate your modified program to the Instructor.

Laboratory 5A, Part 3 Summary

- The take-away from this Lab is that in writing loops, the use of the **continue** command is unnecessary.
- With the **continue** command, there was no change in the number of lines for the loop when you wrote the loop avoiding its use.
- The result in avoiding this command is a loop with one exit, not two possible exits, hence a result that is easier to read as well as debug.
- Call your program: *YourName-Lab05A-3.cpp*
- If you are doing this Lab synchronously, demonstrate your solution to the instructor to receive proper credit.
- If you are doing this Lab asynchronously, submit your program to Canvas.

Lab 05 – Part 4

- **Problem 4:** Write a program that can be used as a math tutor for elementary school students.
- Display a menu to choose addition, subtraction, multiplication, or division.
- Generate two random numbers in the range of 1 to 12.
- For the subtraction problem, make sure the answer is positive (the larger number comes first).
- For the division problem, we only want integer answers. So multiply the two numbers to create the first number. For example, if the numbers generated were 4 and 5, instead of making the problem as: $4 / 5$ (which has a decimal answer), multiply the numbers and use that as the first number, so the problem would be $20 / 5$ (which has an integer answer).
- The program should loop as long as the user wants to continue. Use an input of 'q' or 'Q' to quit.

Welcome to the Math Tutor!

Select an operation (+ - / *) or press q to quit: +

9 + 10 = **19**

That's right

Select an operation (+ - / *) or press q to quit: -

12 - 8 = **2**

The answer is 4

Select an operation (+ - / *) or press q to quit: /

24 / 6 = **4**

That's right

Select an operation (+ - / *) or press q to quit: *

9 * 3 = **27**

That's right

Select an operation (+ - / *) or press q to quit: **q**

Test Case 1 for Part 4

Note Student Answers
are in **bold**

Laboratory 5A Part 4

- Call your program: *YourName*-Lab05A-4.cpp
- If you are doing this Lab synchronously, demonstrate your solution to the instructor to receive proper credit.
- If you are doing this Lab asynchronously, submit your program to Canvas.