GOSIM

GOSIM Paris 2026

GOSIM Paris 2026

May 5-6, 2026 Station F, Paris

GOSIM

GOSIM Paris 2026

The Adoption of Python Array API in scikit-learn

by Olivier Grisel and Stefanie Senger

:probabl.



CONTENTS

GOSIM Paris 2026

Part 01 Adopting the Array API Standard in scikit-learn

Part 02 Implementation and Challenges

Part 03 单击此处修改标题

Part 04 单击此处修改标题

GOSIM

GOSIM Paris 2026

01

Adopting the Array API Standard in scikit-learn

Why Array API matters for scikit-learn

- scikit-learn grew around **NumPy-style arrays on the CPU**

- many workflows now use **GPUs** and **other array libraries**

- support is **experimental** and has grown since **1.3** (June 2023): more estimators and functions over time

Why Array API matters for scikit-learn

- scikit-learn is an array consuming library:

  → inputs are arrays

  → outputs are arrays

- goal:

  let serious work **stay on the hardware and library** the data already lives in

- users can bring **CuPy** or **PyTorch** data today; **JAX** is being prepared

The Array API Standard

Consortium for Python Data API Standards maintains the **Array API** standard (specification published at data-apis.org)

- **array-api-tests**: shared conformance test suite
- **array-api-strict**: strict, minimal implementation used heavily in scikit-learn CI
- **array-api-compat**: bridges NumPy, PyTorch, and CuPy where their APIs differ fromArray API standard; vendored in scikit-learn since 1.7
- **array-api-extra**: helpers for operations the core standard does not define; vendored in scikit-learn since 1.7

Using Array API compatible inputs in scikit-learn

Array API in scikit-learn is **opt-in**:

- `SCIPY_ARRAY_API=1` environment variable to enable it in **SciPy**
- scikit-learn global configuration (`set_config`) or the `config_context` context manager: `array_api_dispatch=True`

- scikit-learn user docs: "**Array API support (experimental)**"

scikit learn

12.2.2. Example usage

The example code snippet below demonstrates how to use CuPy to run `LinearDiscriminantAnalysis` on a GPU:

```
>>> from sklearn.datasets import make_classification
>>> from sklearn import config_context
>>> from sklearn.discriminant_analysis import LinearDiscriminantAnalysis
>>> import cupy

>>> X_np, y_np = make_classification(random_state=0)
>>> X_cu = cupy.asarray(X_np)
>>> y_cu = cupy.asarray(y_np)
>>> X_cu.device
<CUDA Device 0>

>>> with config_context(array_api_dispatch=True):
...     lda = LinearDiscriminantAnalysis()
...     X_trans = lda.fit_transform(X_cu, y_cu)
>>> X_trans.device
<CUDA Device 0>
```

GOSIM

GOSIM Paris 2026

02

Implementation and Challenges

Implementation in scikit-learn and Challenges

Code | Issues 1.5k | Pull requests 528 | Agents | Discussions | Actions | Projects | Wiki | Security

Path for Adopting the Array API spec #22352

Closed

thomasjpfan opened on Feb 1, 2022 · edited by thomasjpfan Edits Member

I have been experimenting with adopting the Array API spec into scikit-learn. The Array API is one way for scikit-learn to run on other hardware such as GPUs.

I have some POCs on my fork for LinearDiscriminantAnalysis and GaussianMixture. Overall, there is runtime performance benefit when running on CuPy compared to NumPy, as shown in notesbooks for LDA (14x improvement) and GMM (7x improvement).

Official acceptance of the Array API in numpy is tracked as NEP 47.

Proposed User API

Here is the proposed API for dispatching. We require the array to adopt the Array API standard and we have a configuration option to turn on Array API dispatching:

Implementation in scikit-learn and Challenges

Computations stay on the same **namespace** and **device** as the input arrays:

```
from sklearn.utils._array_api import get_namespace, device

xp, is_array_api = get_namespace(X)   # same library as `X`
device = device(X)                    # same device as `X`
```

Inside estimators:

1. keep operations on namespace `xp`
2. create new arrays on namespace `xp` and `device`

Implementation in scikit-learn and Challenges

Bridge gap of **Array API standard** deliberately defining a subset of NumPy's surface by internal helper functions:

```
def _nanmin(X, axis=None, xp=None):
    # TODO: refactor once nan-aware reductions are standardized:
    # https://github.com/data-apis/array-api/issues/621
    xp, _, device_ = get_namespace_and_device(X, xp=xp)
    if _is_numpy_namespace(xp):
        return xp.asarray(numpy.nanmin(X, axis=axis))

    else:
        mask = xp.isnan(X)
        X = xp.min(
            xp.where(mask, xp.asarray(+xp.inf, dtype=X.dtype, device=device_), X),
            axis=axis,
        )
        # Replace Infs from all NaN slices with NaN again
        mask = xp.all(mask, axis=axis)
        if xp.any(mask):
            X = xp.where(mask, xp.asarray(xp.nan, dtype=X.dtype, device=device_), X)
        return X
```

Implementation in scikit-learn and Challenges

Common in productionised ML: **input arrays that differ or change by step** (due to different origins or requirements)

- train models on **GPU** then run inference and deploy on **CPU**
- new data at each pipeline stage may use **different array library or device**
- **string arrays** (`labels`) in classification (NumPy only)
-
-

Implementation in scikit-learn and Challenges

Common in productionised ML: **input arrays that differ or change by step**

1. explicitly **support flexible models** by adding a helper (`convert_estimator`) that moves fitted estimator attributes to the namespace and device of the array passed as `X` to `predict`

2. in a single call, explicitly **support mixed array input**
   - → `y` follows `X`
   - → `y_true`, `sample_weight` and `labels` follow `y_pred` / `y_score`

Implementation in scikit-learn and Challenges

Computation intense tasks on **compiled code** (Cython, C, C++) optimised for CPU is an ongoing challenge. Estimators can:

a) use the compiled path by copying data to CPU, then **map results back** to the input namespace and device

b) use the compiled path only for NumPy inputs; otherwise follow an Array API Python path

Implementation in scikit-learn and Challenges

- trade-offs between runtime **speed** and **memory** footprint
- maintainers often need to compare and **profile multiple options**
- benchmarking on realistic workloads versus **edge cases**
- clearly **define rules** for (silent) conversions to prevent surprises for users

Implementation in scikit-learn and Challenges

- plans of moving out of experimental mode
- stable Array API behaviour in scikit-learn requires **predictable behaviour** in upstream implementations of Array API, especially in **SciPy**

Code | Issues 1.5k | Pull requests 526 | Agents | Discussions | Actions | Projects | Wiki | Security and quality | Insights

RFC a plan to move array API support out of experimental #33444

Open

ogrisel opened on Mar 3 · edited by ogrisel Edits Member

Now that we have added array API support to several important models and tools (including classifiers, regressors, transformers, meta estimators, pipelines, evaluation and model selection tools...), it might be important to discuss what are our plans and conditions to remove the "experimental" marker for that set of features.

To me, moving out of experimental means the following things in particular:

GOSIM

GOSIM Paris 2026

Thanks!

:probabl.