

Pengantar


Ghandy, M.Sc.
IBDA4311 – Computer Vision

© Copyright 2024 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Computer Vision



Computer Vision



Capaian Pembelajaran

- Silabus
- Instalasi
- Visi



Logistik

- Jam kuliah : Selasa (09.00 – 12.00 WIB, 3x50 menit)
- Tempat : Lab Komputer 1 (Fisik)
- Harap menggunakan laptop ketika menghadiri kelas
- *Office hours* : by appointment
- E-mail : ghandy.salim@calvin.ac.id
- Komunikasi : Canvas (silabus, materi kuliah, tugas, *announcement*) maupun e-mail

Pustaka

Wajib

- [1] R. Szeliski, *Computer vision: algorithms and applications*. 2nd ed, London ; New York: Springer, 2022. <https://szeliski.org/Book/>

Rekomendasi

- [2] Stephen-Palmer, *Vision Science: Photons to Phenomenology*. MIT Press, 1999.
- [3] I. Goodfellow, Y. Bengio, and A. Courville, *Deep learning*, Cambridge, Massachusetts: The MIT Press, 2016. deeplearningbook.org/

Silabus



© Copyright 2024 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Tips untuk berhasil dalam MK ini


- Konsisten mengerjakan tugas dan projek sebaik mungkin.
- Bertanya dan partisipasi secara aktif di dalam kelas, sehingga dosen juga mendapat *feedback* jika terlalu cepat atau ada yang kurang jelas.
- Tidak tertinggal pelajaran: jika tidak paham di awal, segera menghubungi dosen atau bertanya kepada mahasiswa lainnya.
- Gunakan *office hours* dosen untuk lebih memahami materi dan tugas.
- Mata kuliah ini banyak memakai pemrograman dengan Python dengan *libraries* seperti numpy, scikit-learn, pandas, keras, pytorch, tensorflow. Bacalah dokumentasi dari *libraries* untuk lebih terbiasa menggunakannya. Anda juga dapat menggunakan ChatGPT untuk memahami kode-kode pemrograman yang diberikan

Setelah Anda menyelesaikan perkuliahan ini, Anda akan:

- Memahami dasar matematis, fisika, filosofis, dan teoretis yang digunakan di dalam *computer vision*
- Mampu membuat model *computer vision* untuk menyelesaikan berbagai macam permasalahan



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



Anaconda

- Anaconda adalah sistem manajemen paket python
- Melalui Anaconda, maka versi dari paket python yang ada akan dikelola oleh package management system conda.



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Instalasi Anaconda

Gunakan tutorial di bawah ini untuk instalasi Anaconda:

1. https://www.youtube.com/watch?v=itVBw_rNYI&t=315s&ab_channel=GeekyScript

Gunakan tutorial di bawah ini untuk membuat "new environment" pada Anaconda ([Gunakan Python 3.9.17 untuk mata kuliah ini!](#)):


1. https://www.youtube.com/watch?v=sV0ca-6lIM8&ab_channel=LigentTutorials
2. https://www.youtube.com/watch?v=A8dlq-AUDpc&ab_channel=TheEducationMachine



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



Paket Python



Instalasi *library* berikut ini pada *environment* baru anda:

- | | |
|-----------------|-----------------|
| 1. numpy | 7. tensorflow |
| 2. scipy | 8. keras |
| 3. matplotlib | 9. pytorch |
| 4. seaborn | 10. jupyterLab |
| 5. pandas | 11. statsmodels |
| 6. scikit-learn | 12. gensim |
| | 13. nltk |

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Visi



Apa itu visi?

- "A picture is worth a thousand words"



- Visi menentukan aksi

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

GPU cloud

- CIT (hanya untuk riset)
- GCP, AWS (mahal)
- Azure (free \$200)
- Google colabs (gratis dengan limit)
- Gradient (gratis dengan limit): <https://gradient.run/free-gpu>
- Deepnote (gratis dengan limit): <https://deepnote.com/>


Perbandingan CPU dan GPU:

<https://colab.research.google.com/notebooks/gpu.ipynb>




© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Human Sensory



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Emotion Detection Based on Images



Persepsi Visual

- Pemodelan lingkungan




Figure 1.1.5

Ambiguous figures. Figure A can be seen either as a white vase against a black background or as a pair of black faces against a white background. Figure B can be seen as a cube viewed from above or below. Figure C can be seen as a duck (facing left) or a rabbit (facing right).

Persepsi Visual

- Pemodelan lingkungan




Figure 1.1.6

Visual completion behind partly occluding objects. Figure A is perceived as consisting of a square, a circle, and a rectangle even though the only visible regions are those shown separated in Figure B.

Persepsi Visual

- Konstruksi Makna



Figure 1.1.9

Many kinds of dogs. Visual perception goes beyond the physical description of objects to classify them into known categories. Despite the substantial physical differences in their appearance, all these animals are readily perceived as belonging to the category of dogs.



Limitasi visi

- Lukisan impressionist berusaha memvisualkan aspek yang melampaui batasan visual




© Copyright 2000 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or reused without prior approval.



23

Limitasi visi

- Lukisan impressionist berusaha memvisualkan aspek yang melampaui batasan visual



© Copyright 2000 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or reused without prior approval.



24

Ilusi Optik




Figure 1.1.14 Some common optical illusions and what they might tell us about the visual system: (a) The classic Müller-Lyer illusion, where the lengths of the two horizontal lines appear different, probably due to the imagined perspective effects. (b) The "white" square B in the shade and "black" square A in the light are actually the same size and intensity. The reason for the illusion is that our brain's attempt to discount illumination when interpreting colors. Image courtesy of Ted Adelson, <http://percil.mit.edu/jaikay/checkershadow>. (c) A variation of the Hermann grid illusion, courtesy of Hany Farid. As you move your eyes over the figure, gray spots appear at the intersections. (d) Count the red X's in the left half of the figure. Now count them in the right half. Is it significantly harder? The explanation has to do with a pop-out effect (Treisman 1985), which tells us about the operations of parallel perception and integration pathways in the brain.




Informasi Optikal

- Persepsi visual tergantung pada 3 hal:

- Cahaya
- Objek yang memantulkan cahaya
- Sistem visual pengamat

© Copyright 2000 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or reused without prior approval.

Spektrum Cahaya



© Copyright 2000 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or reused without prior approval.

25


Istirahat 15 Menit

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.




Color

- Color as physiological and psychological properties
 - Hue




- Luminance/ Lightness/
 - A. Mean \leftrightarrow Hue




- B. Area \leftrightarrow Lightness



- C. Variance \leftrightarrow Saturation




© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



https://www.pexels.com/search/color/black/

Color Space

- Color space dibentuk dari kombinasi hue dan saturation



28

Color Space


Apa itu Color Space?

Warna adalah bagian integral dari sistem visi komputer. Color Space adalah kombinasi warna secara terorganisir dan terutama digunakan saat kita mereproduksi warna dalam media yang berbeda. Misalnya, Anda memiliki layar laptop dan monitor besar 52". Tentunya, akan ada perbedaan total piksel dan kombinasi warna. Ruang warna yang berbeda membantu membuatnya kompatibel dengan resolusi layar untuk memberikan pengalaman kombinasi warna yang lebih baik.

Diagram kromatisitas di samping ini mewakili Color Space. Ini menunjukkan segmen gelombang untuk nilai sumbu x dan y yang berbeda dengan berbagai panjang gelombang. Ruang membuat semua kemungkinan kombinasi warna terlihat oleh sistem penglihatan manusia. Ada banyak ruang warna seperti RGB, sRGB, dll. Kombinasi warna di bawah setiap ruang warna (ditandai dengan segitiga) menyimpan warna yang ditentukan.



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



CC-BY-SA by chromatix_dragon Under Wikipedia Commons free license




32

Color Space

- Color addition vs subtraction

Cara mudah untuk mengingat perbedaan pencampuran warna aditif dan subtraktif adalah **pencampuran warna aditif** terjadi ketika kita **mencampur lampu** dengan warna berbeda sedangkan **pencampuran warna subtraktif** terjadi ketika kita **mencampur cat** atau bahan berwarna lainnya.



Color Addition




Color Subtraction

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

33




https://www.pexels.com/search/color/light/



Trichromatic Theory

- Young-Helmholtz: Teori trikromatik penglihatan warna adalah teori yang menyatakan ada **tiga receptor warna yang berbeda di retina**. Sel kerucut di retina inilah yang memberi penglihatan warna. Teori ini mengatakan sel kerucut sensitif terhadap tiga warna berbeda: **hijau, biru, dan merah**



Relative Activity Level (% of total)

Short wavelength receptors

Medium wavelength receptors




Figure 3.2.8

Patterns of activation in trichromatic theory. Different color perceptions were proposed to result from different balances of activity in the three receptor systems, as illustrated here for six basic colors.



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

36

Trichromatic Theory



Opponent Process Theory

- Ewald Hering
- Warna komplementer: 2 warna bersebrangan, jika digabung akan saling cancel (hue)






Figure 3.2.10

Hering's opponent process theory of color vision. Hering suggested that three types of receptors could respond in two opposite directions (+ versus -) from a neutral point (0) to signal red versus green, blue versus yellow, and black versus white.

CALVIN
INSTITUTE OF TECHNOLOGY



Opponent Process Theory



Aplikasi warna komplementer



CALVIN
INSTITUTE OF TECHNOLOGY

Dual Process Theory

- Hurvich & Jameson




Figure 3.2.13

Neural response curves for the three types of cones. Short- (S), medium- (M), and long- (L) wavelength cones provide overlapping but differential responses to light of different wavelengths, as predicted by trichromatic theory. These curves are defined by the absorption spectra of the three pigments found in normal cones. (After Schnapf, Kraft, & Baylor, 1987.)

CALVIN
INSTITUTE OF TECHNOLOGY




Figure 3.2.14

Buta warna

- Protanopia are unable to perceive any 'red' light
- Deutanopia are unable to perceive 'green' light
- Tritanopia are unable to perceive 'blue' light.




Figure 3.2.15




Plate 3.5

A test for color blindness. People with normal color vision see the number 3 in A and 42 in B, whereas protanopes see no number in A and 2 in B, and deuteranopes see no number in A and 4 in B. (Courtesy of Graham-Field Surgical Company.)

Lintasan cahaya

- Cahaya menempuh lintasan terpendek (geodesik)






Illustration of the principle of least time. We construct on the other side of MM' an artificial point B' , which is the same distance below the plane MM' as the point B is above the plane. Then we draw the line EB' .

http://www.feynmanlectures.caltech.edu_1_26.html

Iluminasi



A. Point-Source Illumination



B. Spatially Extended Illumination

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2000 Calvin Institute of Technology.
The information contained herein may not be used, copied, published, quoted, and/or revised without prior approval.

Interaksi dengan permukaan objek




Figure 3.2.20
Interactions between light and surfaces. A photon can be transmitted through a surface, absorbed by it, or reflected off it.



Figure 3.2.21
Refraction of light. When light is transmitted through an object, it can be bent (refracted), leading to erroneous perceptions, such as the misaligned appearance of the spoon handle in this glass of water.

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2000 Calvin Institute of Technology.
The information contained herein may not be used, copied, published, quoted, and/or revised without prior approval.

Mata





Figure 1.3.4
A cross section of the human eye. Light enters the eye through the cornea, aqueous humor, lens, and vitreous humor before striking the light-sensitive receptors of the retina, where light is converted into electrochemical signals that are carried to the brain via the optic nerve.



CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

46

Sistem syaraf




Figure 1.3.6
A typical neuron. A neuron is a cell that consists of a cell body that integrates graded electrical signals from its dendrites and transmits the result via discrete action potentials. These spikes travel along an axon, which is encased in a myelinated sheath, to terminals, where neurotransmitters are released at synapses to stimulate the dendrites of other neurons.


CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



Figure 1.3.7

Sistem visual manusia



CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.




Figure 1.3.9

The human visual system. Visual processing begins in the eyes and is relayed to the brain by the optic nerve. The primary visual pathway goes from the lateral geniculate nucleus to the optic radiations. From there, visual information travels to other parts of the brain. A secondary pathway goes from the optic nerve to the superior colliculus and then to other brain centers. (From Rosenzweig & Leinen, 1982.)

48

Classical Theory of Vision




Figure 2.1.1
A timeline of visual theorists. The life spans of some of the most important psychological theorists of vision are represented over the past two centuries. Wundt and Titchener were structuralists; Wertheimer, Köhler, and Koffka were Gestalts; Brunswick and Gibson were ecologists; and Helmholtz, Rock, Gregory, and Hochberg were constructivists.

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

50

German Idealism


- Immanuel Kant: Phenomena, Noumena
- Gestaltism/holism: Wertheimer
 - The whole is different from the sum of its parts



Figure 2.1.5
Emergent properties of a configuration. The arrangement of several dots in a line gives rise to emergent properties, such as length, orientation, and curvature, that are different from the properties of the dots that compose it.

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



Phenomenology

- Edmund Husserl: Natural Experience
- Ecological Optics: James Gibson
 - "Ask not what's inside your head, but what your head's inside of"
 - foreshadow modern work in computational vision
- Constructivism: Helmholtz
 - global percepts are constructed from local information




Figure 2.1.7

Two possible interpretations of a simple image. Image A can be interpreted either as a circle behind a square (interpretation B) or as a three-quarter circle next to a square (interpretation C). The fact that the visual system strongly prefers interpretation B to C can be explained by the principles of likelihood and/or Prägnanz.

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Reformational Philosophy

- Realita diciptakan dalam keragaman aspek → setiap aspek ciptaan bukan Pencipta
- Pre-theoretical vs theoretical thought:
 - Pre-theoretical thinking takes in reality as a whole
 - Theoretical thinking analyses reality from one aspect.
- Example:
 - a gardener may look at a plant in its unity as a plant; whereas a biologist may analyse the plant in terms of its biotic aspect.
 - When we see a sunset, we admire it as a sunset rather than in terms of the movement of the earth on its axis and its movement around the sun.

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Summary

- Silabus
- Instalasi
- Visi: fondasi dan filsafat

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Tuhan Memberkati

Pemrosesan Gambar

Ghandy, M.Sc.
IBDA4311 – Computer Vision

© Copyright 2020 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Capaian Pembelajaran

- Pengantar Paket Python
 - 1. Numpy
 - 2. PyTorch
 - 3. Matplotlib
 - 4. OpenCV

- Pemrosesan Gambar
 - Membaca gambar
 - Channel dan format
 - Operasi dasar
 - Menulis Gambar
 - Video
 - Thresholding
 - Blurring



© Copyright 2020 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Pengantar Paket Python

Python

- Python adalah Bahasa pemrogrammang yang sifatnya high-level
- Python code hampir seperti pseudocode (bisa mengesekpresikan ide dengan bebas)
- [Python yang akan digunakan adalah python 3.9](#)



Packages: Python 3.9.17

© Copyright 2020 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

NumPy

- NumPy adalah paket untuk melakukan perhitungan numerik (vs Scipy lebih untuk matematika sains)
- Array berbentuk objek
- Sangat berguna untuk problem linear algebra



NumPy

Array and Matrices

- Array di numpy (np.array) merupakan kumpulan daftar elemen
- Setiap array harus memiliki tipe yang sama
- Beberapa datatype:
 - Float (float16, float32, float64)
 - Int (int8, int16, int32, int64)
 - UInt
 - Bool
 - Complex
- Matrices adalah array yang memiliki 2 jenis dimensi
- Jika memiliki lebih dari 2 jenis dimensi disebut Tensor

© Copyright 2020 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



© Copyright 2020 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



© Copyright 2020 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

6

Operasi Matriks


- Keunggulan numpy terletak pada operasi matriks
- Operasi matematika dasar (+, -, *, %) dianggap sebagai operasi elemen
- Operasi matriks yang umum dapat menggunakan:
 - Matrik multiplication: np.matmul
 - Transpose: property objek numpy.T
 - Inverse: np.linalg.inv
 - Penjumlahan sepanjang axis: np.sum
 - Menumpuk 2 array: np.stack
 - Menyambung 2 array: np.concatenate

PyTorch

- PyTorch adalah paket untuk deeplearning dan optimisasi operasi tensor
- Mengapa numpy dan opencv tidak cukup?
 - Karena PyTorch dapat menggunakan GPU untuk operasi tensor
 - Karena PyTorch dapat melakukan turunan parsial otomatis
- Ada beberapa deep learning frameworks yang populer:
 - TensorFlow (google) → compatible dengan KERAS (banyak digunakan di industri)
 - PyTorch (facebook) → lebih mudah untuk mengakat-akit tensornya (banyak digunakan untuk riset)



PyTorch vs TensorFlow



© Copyright 2020 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



© Copyright 2020 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



© Copyright 2020 Calvin Institute of Technology
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

9

Matplotlib



- Matplotlib adalah paket untuk menghasilkan grafik dengan fleksibel
- Terdapat beberapa toolkit tambahan yang bisa dibangun diatas matplotlib:
 - Basemap dan cartopy: untuk proyeksi dan mapping
 - Bokeh: untuk plot interaktif pada browser
 - Seaborn: untuk high level interface visualization



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

OpenCV



- OpenCV (open source computer vision library) adalah paket untuk aplikasi computer vision
- Memiliki berbagai macam interfaces (c++, python, java, matlab)
- Mendukung berbagai macam OS (windows, linux, mac, android)
- Dirancang untuk aplikasi real-time



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

10

Pemrosesan Gambar



Membaca gambar

- Membaca terhadap file path tertentu dapat menggunakan cv2.imread
- Gambar pada opencv akan direpresentasikan dalam bentuk numpy array



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Channel dan format

- Shape dari gambar tersebut berbentuk (tinggi, lebar, warna BGR)
- Ini dikarenakan opencv memperlakukan gambar seperti rows (tinggi) dan column (lebar) pada numpy
- Konvensi ini mungkin akan berbeda dengan kesepakatan paket tensor lain!!!
- Warna apapun dikonstruksi sebagai kombinasi 3 warna dasar (subjective color) dengan urutan: blue, green, red



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

11

Menampilkan gambar

- Untuk menampilkan gambar dapat menggunakan cv2.imshow (tidak berlaku untuk jupyter)
- Untuk jupyter gunakan plt.imshow



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

15

Operasi dasar

- Untuk mengubah gambar berwarna menjadi abu-abu gunakan cvtColor
- Grayscale tidak mempunyai dimensi warna, namun setiap pixel memiliki luminosity diantara 0 dan 255
- Untuk mengubah ukuran gambar gunakan resize (tapi kali ini menggunakan konvensi lebar lalu tinggi)



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Menulis Gambar


- Gambar dapat ditulis kedalam sebuah file atau variable dengan imwrite



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Video

- Video sebenarnya hanyalah sebuah urutan-urutan gambar
- Untuk membaca video dari webcams, IP cameras, atau file, kita dapat menggunakan VideoCapture
- Untuk menuliskannya dalam file, kita dapat menggunakan VideoWriter



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.


18

Thresholding

- Binary thresholding memaksa gambar menjadi 2 nilai.
- Binary thresholding dapat digunakan untuk memperoleh mask.




© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



Thresholding

- Thresholding juga dapat digunakan untuk keperluan segmentasi



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.


Gaussian Blur

- Fungsi gaussian dapat dipakai untuk merata-rata suatu posisi dengan nilai terdekatnya
- Ini akan menghasilkan efek blur pada gambar



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Summary



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Garis Batas

- Sistem visual manusia berdasarkan garis batas
- Kita dapat mengidentifikasi sebuah objek dengan hanya menggunakan garis batas



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Capaian Pembelajaran

- Deteksi Batas
- Deteksi Garis

Edge Detection
line detection




© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Tujuan Deteksi Batas

- Tensor
1. Memetakan gambar (kumpulan pixel 2D) menjadi himpunan kurva, segmen garis, atau kontur
 2. Representasi lebih padat dari sekedar gambar yang lengkap


Garis dapat ditentuk dari dua titik yang dihubungkan.
Sinar merupakan garis yang tidak berujung.
Sedangkan segmen merupakan garis yang panjangnya dapat kita ukur.




© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Aplikasi Modern

- 1. Lane Detection (self driving car)
- 2. Sistem Navigasi Helikopter



Apa saja yang menyebabkan batas



Gradien Gambar

- Gradien dari sebuah gambar: $\nabla f = \begin{bmatrix} \frac{\partial f}{\partial x}, \frac{\partial f}{\partial y} \end{bmatrix}$
 - Gradien mengarah pada perubahan intensitas yang paling besar
- $\nabla f = \begin{bmatrix} \frac{\partial f}{\partial x}, 0 \end{bmatrix}$ $\nabla f = \begin{bmatrix} 0, \frac{\partial f}{\partial y} \end{bmatrix}$
- Arah dari gradien (arah normal dari batas) di deskripsikan oleh: $\theta = \tan^{-1} \left(\frac{\frac{\partial f}{\partial x}}{\frac{\partial f}{\partial y}} \right)$
- Kekuatan batas diberikan oleh nilai dari gradien $|\nabla f| = \sqrt{\left(\frac{\partial f}{\partial x}\right)^2 + \left(\frac{\partial f}{\partial y}\right)^2}$




© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Turunan dan Konvolusi

- Untuk fungsi 2D, $f(x, y)$, turunan parsial adalah:

$$\frac{\partial f(x, y)}{\partial x} = \lim_{\epsilon \rightarrow 0} \frac{f(x + \epsilon, y) - f(x, y)}{\epsilon}$$
- Untuk data diskrit, kita dapat menggunakan finite difference:


$$\frac{\partial f(x, y)}{\partial x} = \frac{f(x+1, y) - f(x, y)}{\Delta x}$$
- Untuk mengimplementasikannya sebagai konvolusi, filter apa yang sesuai?



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Soal Latihan


- Kerjakanlah soal di dalam file SobelFilter.xlsx untuk lebih memahami mengenai konvolusi dan cara kerja filter sobel.



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.


Turunan dan Batas

- Sebuah batas adalah tempat terjadinya perubahan drastis pada intensitas gambar



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Filter finite difference



$$\text{Prewitt: } M_x = \begin{bmatrix} -1 & 0 & 1 \\ -1 & 0 & 1 \\ -1 & 0 & 1 \end{bmatrix}; \quad M_y = \begin{bmatrix} 1 & 1 & 1 \\ 0 & 0 & 0 \\ -1 & -1 & -1 \end{bmatrix}$$

$$\text{Sobel: } M_x = \begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix}; \quad M_y = \begin{bmatrix} 1 & 2 & 1 \\ 0 & 0 & 0 \\ -1 & -2 & -1 \end{bmatrix}$$


$$\text{Roberts: } M_x = \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}; \quad M_y = \begin{bmatrix} 1 & 0 \\ 0 & -1 \end{bmatrix}$$



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Jawaban Latihan

- 1 orang mahasiswa/i mempresentasikan hasilnya



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

$$\text{Sobel: } M_x = \begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix}$$

$$M_y = \begin{bmatrix} 1 & 2 & 1 \\ 0 & 0 & 0 \\ -1 & -2 & -1 \end{bmatrix}$$

Uji Pemahaman

- Batas apakah yang ditangkap filter-filter sebelumnya?

Prewitt: $M_x = \begin{bmatrix} -1 & 0 & 1 \\ -1 & 0 & 1 \\ -1 & 0 & 1 \end{bmatrix}$; $M_y = \begin{bmatrix} 1 & 1 & 1 \\ 0 & 0 & 0 \\ -1 & -1 & -1 \end{bmatrix}$


Sobel: $M_x = \begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix}$; $M_y = \begin{bmatrix} 1 & 2 & 1 \\ 0 & 0 & 0 \\ -1 & -2 & -1 \end{bmatrix}$

Roberts: $M_x = \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}$; $M_y = \begin{bmatrix} 1 & 0 \\ 0 & -1 \end{bmatrix}$

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Noise


- Misalkan kita mengambil satu baris dari gambar, lalu plot intensitas sebagai fungsi dari posisi:




- Finite difference berespon terlalu kuat terhadap noise (image noise berbentuk pixel yang sangat berbeda dengan pixel tetangganya)
- Apa yang harus dilakukan?

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Smoothing



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



https://www.youtube.com/watch?v=mlWkWamyQzsd&channel=curingmath

Animation of Convolution of Two Time Signals


https://www.youtube.com/watch?v=CJNSGMVZDok&channel=YangCao

Turunan dari konvolusi

- Sifat turunan dari konvolusi:

$$(f * g)' = f * \frac{\partial}{\partial x} g$$


$$\begin{aligned} (f * g)' &= \frac{d}{dt} \int_{-\infty}^{\infty} f(\tau)g(t-\tau) d\tau \\ &= \int_{-\infty}^{\infty} f(\tau) \frac{\partial}{\partial t} g(t-\tau) d\tau \\ &= \int_{-\infty}^{\infty} f(\tau)g'(t-\tau) d\tau = f * g'. \end{aligned}$$



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Turunan dari filter gaussian

- Apakah filter ini dapat dipisahkan?



- Ya, kita dapat memisahkannya menjadi 2 buah filter yang urutannya tidak penting
- Median filter adalah contoh sebuah filter yang tidak dapat dipisahkan

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Median Filter

8	9	10	11	12
12	8	9	10	11
13	12	8	9	10
14	12	12	8	9
15	14	13	12	8

https://www.youtube.com/watch?v=jeat1H68sM8&channel=CODEKODAK

Median Filter

- Median filter adalah contoh dari filter yang tidak dapat dipisahkan karena ia menggunakan informasi spasial dari data inputnya untuk menghasilkan outputnya.
- Filter yang tidak dapat dipisahkan adalah jenis filter yang tidak dapat diwakilkan oleh fungsi matematis tunggal. Sebaliknya, jenis filter ini memerlukan pemrosesan data yang bergantung pada konteks lokal di sekitarnya.

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

15

16


17

20

21


Smoothing tradeoffs

- Turunan yang dihaluskan menghilangkan noise, tapi blur batas
- Batas dapat ditemukan dalam skala yang berbeda



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.


Filter deteksi batas



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Laplacian of Gaussian (LoG)

- Manakah batas menurut mekanisme ini?



1	1	1
1	-8	1
1	1	1

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



Difference of Gaussians

MATLAB

<https://www.youtube.com/watch?v=2spdw4QmBb>, channel Knowledge Amplifier

Difference of Gaussians (DoG)

- DoG dapat mengaproksimasi LoG secara cukup baik
 - LoG (dashed blue) vs DoG (black)




Deteksi Batas dan Garis

IBDA4311 – Computer Vision

Piramida Gaussian dan DoG

- DoG biasanya digunakan untuk piramida gaussian untuk deteksi fitur yang bersifat scale-invariant



Apakah deteksi batas yang baik?

- Deteksi:
 - Meminimalkan false positives (deteksi yang salah)
 - Meminimalkan false negatives (gagal mendeteksi batas sebenarnya)
 - Memaksimalkan deteksi yang benar
- Lokalisasi:
 - Batas yang terdeteksi harus sedekat mungkin dengan batas yang benar
- Respon tunggal:
 - Menghasilkan satu respons untuk setiap posisi batas yang benar
 - Menghubungkan deteksi ke garis



Apa sajakah parameter dalam deteksi batas?

- Skala
- Threshold

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.


© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

4

Pemilihan skala

- Kita menghaluskan image dengan kernel gaussian untuk mengurangi noise
- Skala Gaussian menentukan seberapa halus




CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Efek dari skala terhadap turunan

- Hasil berbeda tergantung skala Gaussian
- Skala besar: deteksi batas berskala besar
- Skala kecil: deteksi batas yang lebih tipis



$\sigma = 1 \text{ pixel}$

$\sigma = 3 \text{ pixels}$

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

5

Bagaimana memilih skala?

- Tergantung dari apa yang kita cari
- Skala terlalu kecil: tidak bisa melihat hal besar
- Skala terlalu besar: tidak dapat membedakan hal-hal tipis

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

6

Threshold

- Pilih sebuah nilai threshold
- Tentukan gradien apapun diantara 0 sampai nilai tersebut (off)
- Tentukan gradien apapun diantara nilai tersebut sampai 1 (on)

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Canny edge detector

- Deteksi batas yang paling umum digunakan di computer vision
- Deteksi step-edges yang dirusak oleh gaussian noise

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

5

Canny edge detector


- Filter gambar dengan turunan gaussian
- Menemukan orientasi dan besar dari gradien
- Non-maximum suppression: (lokalisasi)
 - Dimulai dari rik dengan lebar multi-pixel sampai lebar 1 pixel
- Linking and thresholding:
 - Tentukan 2 thresholds: low dan high
 - Gunakan threshold yang lebih tinggi untuk membuat garis batas lalu lanjutkan dengan threshold yang lebih rendah
- Cv2.Canny()

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

6

Canny edge detector




CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Non-Maximum Suppression (NMS)


Non-Maximum Suppression (NMS)



CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

12




13

Hysteresis Thresholding

Non-max suppression outputs a more accurate representation of real edges in an image. But you can see that some edges are more bright than others. The brighter ones can be considered as strong edges but the lighter ones can actually be edges or they can be because of noise. To solve the problem of which edges are really edges and which are not? Canny uses the Hysteresis thresholding. In this, we set two thresholds 'High' and 'Low'.

- Any edges with intensity greater than 'High' are the sure edges.
- Any edges with intensity less than 'Low' are sure to be non-edges.
- The edges between 'High' and 'Low' thresholds are classified as edges only if they are connected to a sure edge otherwise discarded.

Let's take an example to understand



Here, A and B are sure-edges as they are above 'High' threshold. Similarly, D is a sure non-edge. Both C and E are weak edges but since C is connected to B which is a sure edge. C is also considered as a strong edge. Using the same logic E is discarded. This way we will get only the strong edges in the image.

This is based on the assumption that the edges are long lines.

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

14

Deteksi Garis




Line Fitting

Metode-metode yang dapat digunakan:

1. Hough Transform
2. RANSAC *→ deep learning*
3. SCNN


Hough Transform

- Transformasi image space (x,y) menuju Hough space (m,b)
- Sebuah garis pada gambar adalah sebuah titik pada hough space
- Hough: untuk himpunan poin (x,y) temukan semua (m,b) dimana $y = mx + b$




Hough Transform

- Sebuah titik (x_0, y_0) pada gambar adalah solusi dari $b = -x_0m + y_0$ (Titik → Garis)




- Sebuah garis yang berisi titik (x_0, y_0) dan (x_1, y_1) adalah pertemuan garis $b = -x_0m + y_0$ dan garis $b = -x_1m + y_1$




Menemukan garis dengan transformasi Hough

- Setiap titik batas voting untuk himpunan parameter mungkin pada Hough space
- Hitung votes pada sebuah himpunan diskrit
- Parameter dengan voting banyak mengindikasikan garis pada image space




Representasi polar dari garis

- Persamaan garis $y = mx + b$ dapat bermasalah, misalnya:
 1. Dapat bernilai tak hingga
 2. Tidak dapat didefinisikan untuk garis vertikal
- Solusi: gunakan representasi polar




Uji Pemahaman

- Apakah representasi polar dari garis $y = x$




Contoh Transformasi Hough

- Untuk suatu titik (x_0, y_0) $r(\theta) = x_0 \cos \theta + y_0 \sin \theta$
- Untuk 3 titik sepanjang garis ($d \equiv r$)



Contoh pada gambar

- Image space vs parameter space




Sifat Transformasi Hough

- Noise dan clutter votes tidak konsisten sehingga tidak akan terakumulasi
- Dapat mengatur occlusion selama model menerima cukup banyak votes
- Efisien



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.


Noise pada Transformasi Hough



26

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.



Kelebihan dan Kekurangan Transformasi Hough

Kelebihan

- Dapat menerima occlusions
- Robust terhadap noise
- Dapat mendeteksi beberapa garis sekaligus dalam sekali proses gambar

Kekurangan

- Kompleksitas meningkat eksponensial sesuai jumlah parameter

garis > 2 p

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

CALVIN
INSTITUTE OF TECHNOLOGY

28

Ransac

- RAN**dom **S**ample **C**onsensus [Fischler & Bolles 1981]
- Cari "Inliers" dan hanya gunakan ini
- Jika kita fit sebuah model pada "outliers" kita tidak akan memperoleh fit yang sesuai

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Algoritma Ransac

- Loop:
 - Pilih secara acak kumpulan titik
 - Fit sebuah model terhadap pilihan tersebut
 - Temukan inliers dari model yang sudah dihitung
 - Jika jumlah inliers sudah cukup besar, hitung ulang model dengan hanya menggunakan inliers
 - Hitung jumlah inliers dari model yang sudah diperbaharui
- Yang dipilih: model dengan jumlah inliers terbanyak


31

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Contoh Algoritma RANSAC

- Data input: kumpulan titik
- Step 1: pilih 2 titik
- Step 2: fit garis pada titik-titik tersebut
- Step 3: temukan inliers
- Step 4: ulangi step 1-3 sampai konvergen



32

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

33

Kelebihan dan Kekurangan

Kelebihan

- Metode umum yang bekerja cukup baik untuk berbagai jenis masalah model fitting
- Mudah diimplementasikan

Kekurangan

- Situasi dimana persentase outliers banyak sehingga butuh banyak iterasi dan tingkat kegagalan meningkat

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

36

Kriteria Stop

Opsi 1: Ketika model sudah cukup baik

- Menurut jumlah inliers
- Menurut fitting error

Opsi 2: menurut peluang

- Misalkan K adalah jumlah iterasi
- Misalkan n adalah jumlah titik yang diperlukan untuk menghitung model
- Misalkan f adalah fraksi inliers dari sebuah model
- Maka peluang sebuah sampel benar adalah: f_n^K
- Peluang bahwa semua sampel K gagal adalah: $(1 - f_n)^K$
- Pilih nilai K cukup tinggi untuk menjaga tingkat kegagalan rendah

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Implementasi

- OpenCV menggunakan Homografi: `cv2.findHomography(src_pts, dst_pts, cv2.RANSAC)`
- Scikit-image menggunakan: `skimage.measure.ransac()`
- Scikit-learn menggunakan: `sklearn.linear_model.RANSACRegressor()`

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

35

CALVIN
INSTITUTE OF TECHNOLOGY

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.


36

SCNN

- Spatial Convolutional Neural Network
- CNN Klasik tidak memiliki pengertian spasial: tidak dapat menangkap relasi spasial (rotasi dan translasi)
- Relasi spasial memiliki banyak kegunaan:
 - Lampu lalu lintas umumnya memiliki relasi spasial seperti berdiri vertikal dan diletakkan di kiri atau kanan jalan
 - Identifikasi lajur


© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Arsitektur SCNN



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

Contoh SCNN



© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.


Summary

Edge detection

- Filter
- Turunan, konvolusi, Gaussian blur, LoG, DoG
- Canny Detection

Line detection


- Hough transform
- RANSAC
- SCNN



IBDA4311 Computer Vision

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

X-Rays Wavelength




Sumber: Encyclopedia Britannica, Inc.

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

September 26, 2023

Confidential. Not to be copied / distributed

Construction Of Stationary X-Ray Anode Tube



Sumber: "Handbook of Biomedical Instrumentation", Third Edition, Author: Dr. R. S. Khndpur, Publisher McGraw Hill Education, ISBN: 9789339205430.

© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

September 26, 2023

Confidential. Not to be copied / distributed

X-Ray


© Copyright 2020 Calvin Institute of Technology.
The information contained herein shall not be used, copied, published, quoted, and/or released without prior approval.

37

38


39

Basis Of Diagnostic Radiology




Gambar: Basic set up for a diagnostic radiology image formation process. Sumber: "Handbook of Biomedical Instrumentation", Third Edition.

X-Ray Images




Computed Tomography (CT)

I. Scanning System: Scanning Arrangements



Gambar: Scanning arrangements of the early CT machines. Sumber: "Handbook of Biomedical Instrumentation", Third Edition.

II. Processing System: Gantry Geometry




Sumber: Friedrich Uebel

Video: Inside Of CT Scanner At Full Speed




Sumber: <https://www.youtube.com/watch?v=qjgjxQdLbJw>

I. Scanning System: Scanning Arrangements



Gambar: The spiral CT scan principle in volumetric scanning. Sumber: "Handbook of Biomedical Instrumentation", Third Edition.


II. Processing System: Processing Unit



► Fig. 20.16 Principle of iterative reconstruction method


Gambar: Principle of iterative reconstruction method. Sumber: "Handbook of Biomedical Instrumentation", Third Edition.

CT Images



Magnetic Resonance Imaging (MRI)

History Of MRI




Gambar: The 1st 0.15 Tesla MRI Prototype from Philips was put into operation in 1979. Sumber: Friedrich Uebelte



Gambar: 4th Generation and High-Power 3 Tesla MRI scanner Signa Magnetom from Siemens.

Video: How MRI Machine Works



Sumber: https://www.youtube.com/watch?v=j4kHmTPslab, channel: SiemensHealthineers

September 26, 2023

Confidential. Not to be copied / distributed

17



September 26, 2023

Confidential. Not to be copied / distributed




Sumber: https://www.youtube.com/watch?v=j4kHmTPslab, channel: SiemensHealthineers

September 26, 2023

Confidential. Not to be copied / distributed

17

MRI Images



September 26, 2023

Confidential. Not to be copied / distributed

Ultrasonic Imaging Systems



18



September 26, 2023

Confidential. Not to be copied / distributed

20

Ultrasound Procedures



September 26, 2023

Confidential. Not to be copied / distributed

20

Ultrasound Images



September 26, 2023

Confidential. Not to be copied / distributed

Impedansi Karakteristik

Impedansi karakteristik atau impedansi akustik spesifik suatu medium didefinisikan sebagai produk kerapatan medium dengan kecepatan suara dalam medium yang sama.


$$z = \rho V$$

where ρ = specific acoustic impedance
 V = velocity of sound in the medium.

Impedansi karakteristik menentukan derajat pemantulan dan pembiasan pada antarafasa antara dua media. Persentase energi gelombang datang yang dipantulkan digambarkan oleh rumus berikut ini:

$$\left[\frac{z_1 - z_2}{z_1 + z_2} \right]^2 \times 100\%$$

where z_1 = acoustic impedance of medium 1
 z_2 = acoustic impedance of medium 2




Gambar: Pemantulan dan pembiasan ultrasuara pada antarafasa antara dua media yang memiliki impedansi akustik yang berbeda.

Anatomy of USG

Probe dengan prinsip konverter yang berbeda:

- **Phased Array:** Kontrol fokus dan arah dilakukan sepenuhnya oleh elektronik. Semua elemen dinyalakan bersama-sama sekaligus
- **Linear Array:** Grup-grup dari elemen dinyalakan secara bergantian
- **Konvex Array:** Grup-grup dari elemen dinyalakan secara bergantian seperti Linear Array, tetapi pancaran berbentuk kipas
- **Mechanical Sector:** Elemen tunggal berporos motor



Sumber: Friedrich Uebelte

September 26, 2023

23



September 26, 2023

Confidential. Not to be copied / distributed

21




Medical Image Processing



ImageJ -> Install


- Image processing software with emphasis on medical and scientific applications
- Set of basic functions available
- Written in Java, offers Programming interface for own methods (**Plugins**)
- Open source: <http://rsbweb.nih.gov/ij/>
- Download 64-bit Java for Windows: <https://www.java.com/en/download/>



Courtesy Prof. Dr.-Ing. Thomas Schreiber
September 26, 2023


Confidential. Not to be copied / distributed 27

Image Workflow




2 Examples

➤ Image Processing: Edge Detection



➤ Computer Graphics: 3D Visualization of MRI



Voxel-Man, University Hospital Hamburg-Eppendorf

Courtesy Prof. Dr.-Ing. Thomas Schreiber
September 26, 2023

Confidential. Not to be copied / distributed 26

MeVisLab -> Install


- Professional software for medical image processing and visualization.
- Programming interface for own methods (**modules**) in C++.
- Graphical programming of module networks
- Free license: <http://www.mevislab.de/download>
- <https://ij.lumify.org/>



Courtesy Prof. Dr.-Ing. Thomas Schreiber
September 26, 2023

Confidential. Not to be copied / distributed 28

MeVisLab




Fraunhofer MEVIS

Courtesy Prof. Dr.-Ing. Thomas Schreiber
September 26, 2023

Confidential. Not to be copied / distributed 29

MeVisLab



Fraunhofer MEVIS


Source: <https://archimede.scs.fraunhofer.de/>



September 26, 2023

Confidential. Not to be copied / distributed 30


MeVisLab



September 26, 2023


Confidential. Not to be copied / distributed 31

MeVisLab



September 26, 2023

Confidential. Not to be copied / distributed 32




<https://www.medvislab.de/mevislab/images>

September 26, 2023


Confidential. Not to be copied / distributed

What is an image?

- Grid or array of pixels (picture elements)
 - each pixel carries intensity or color information



- 2D (diskrete) function $f(x,y)$
 - function value: intensity or color information



Binary and gray value images

- 1 Bit: black and white = binary images



- 8 Bit: 256 gray values (0-255)
- 12 Bit: 4096 gray values used in CT: Hounsfield units -1024...3071



- 16 Bit: 65536 gray values

Courtesy Prof. Dr.-Ing. Thomas Schreiner

September 26, 2023

Confidential. Not to be copied / distributed

35

Histograms

- Histograms show frequencies of intensities ("How many pixels are in the image with a certain intensity?")
- The information of a histogram can basically be represented in a list:

Intensity	Number of pixels
0	25898
1	7834
2	35
...	...


Courtesy Prof. Dr.-Ing. Thomas Schreiner

September 26, 2023

Confidential. Not to be copied / distributed

Examples

- Usually, histograms are displayed as bar-diagrams



Courtesy Prof. Dr.-Ing. Thomas Schreiner

Histogram based operations

- Selection of an intensity interval to be mapped onto the maximum and minimum intensities, which can be displayed, usually $\text{max}=0$, $\text{min}=255$.

Setting

- maximum and minimum
- brightness and contrast
- level and window ("medical dictio")




Courtesy Prof. Dr.-Ing. Thomas Schreiner

September 26, 2023


Confidential. Not to be copied / distributed

37

Example



Computer Tomography



Courtesy Prof. Dr.-Ing. Thomas Schreiner

Confidential. Not to be copied / distributed
40

RGB-Color-Model

- Colors are defined by addition of the three basic colors red, green and blue
- grey/white = red+green+blue in equal percentages
- colors = $p_1 \cdot \text{red} + p_2 \cdot \text{green} + p_3 \cdot \text{blue}$



Courtesy Prof. Dr.-Ing. Thomas Schreiner

September 26, 2023


Confidential. Not to be copied / distributed

41


Lookup-Tables (LUT)

- Lookup-tables assign a new intensity or color to each original intensity


Example 1:



Examples



Examples



Threshold

- Gray value images $I(x,y)$ can be converted to binary images $B(x,y)$ by setting a lower threshold t_1 and an upper threshold t_2 ($t_1 \leq t_2$):

$$B(x,y) = \begin{cases} 1, & \text{if } t_1 \leq I(x,y) \leq t_2 \\ 0, & \text{otherwise} \end{cases}$$

Courtesy Prof. Dr.-Ing. Thomas Schlemmer
September 26, 2023
Confidential. Not to be copied / distributed

45

Latihan

Kerjakanlah Latihan Minggu 5_1



Courtesy Prof. Dr.-Ing. Thomas Schlemmer
September 26, 2023
Confidential. Not to be copied / distributed

46

Medical Image Processing: Segmentation Problem

The Segmentation Problem

- Questions on an image of the abdomen:
 - Does pixel (40,320) belong to the liver?
 - Which is the area/volume of the liver?
 - Which is the center of mass of the liver?
 - Which is the distance of the liver from the spine?
 - How many different anatomical structures can be seen on the image?

We need a layer of additional information.

Courtesy Prof. Dr.-Ing. Thomas Schlemmer

September 26, 2023
Confidential. Not to be copied / distributed

48

The Segmentation Problem

- Basis: Assigning labels (numbers) to groups of connected pixels.

HAW Binary image
HAW Labels shown as grey values
HAW Labels shown with LUT

- Possible statements after segmentation:
 - There are three letters.
 - The letter with label 1 (red) is H.
 - The letter with label 2 (green) is A.
 - The letter with label 3 (blue) is W.
 - ...



September 26, 2023
Confidential. Not to be copied / distributed

Region Labelling

- Methods for region labeling use a binary input-image and create a grey-value output-image, where groups of connected pixels (=regions) have the same intensity (=label).

- Example:

Input (binary)	Output (intensities=labels)


Courtesy Prof. Dr.-Ing. Thomas Schlemmer

September 26, 2023
Confidential. Not to be copied / distributed

50

Example

- Example: Segmentation of the eyes



Courtesy Prof. Dr.-Ing. Thomas Schimannek

September 26, 2023


Confidential. Not to be copied / distributed

51

Connectivity

- There are 2 important types of connectivity:

- Only connectivity via an edge is considered. Then an inner pixel has 4 neighbors.
 - Also connectivity via a corner is considered. Then an inner pixel has 8 neighbors.
- Boundary pixels have less neighbors.
 - Other types of connectivity may also consider neighbors with a distance larger than 1.




- Using the 4-neighborhood is quicker and results in more separated regions, which is usually preferable in segmentation problems.

Courtesy Prof. Dr.-Ing. Thomas Schimannek

Method 1: Flood Filling

- Find the next set pixel without a label
- Label this pixel and all connected pixels with the same label
- Recursive programming or administration of a stack



Courtesy Prof. Dr.-Ing. Thomas Schimannek

September 26, 2023


Confidential. Not to be copied / distributed

53

Steps

- Set the current label-value to 1 and start at pixel (0,0)
- Find the first (or next) set and unlabeled pixel and assign the current label-value to this pixel
- Check all neighbors:

- a: Just one neighbor is set, unlabeled and not stored on stack
Move to this neighbor, assign the current label and continue at 2.




Courtesy Prof. Dr.-Ing. Thomas Schimannek

Confidential. Not to be copied / distributed

54

Steps

- b: $N \geq 2$ neighbors are set, unlabeled and not stored on stack
Put $N-2$ neighbors on stack
Move to 1 neighbor, assign the current label and continue at 2.
- c: No set neighbors and unlabeled neighbors, but stack filled
Take pixel from stack
Move to this pixel, assign the current label and continue at 2
- d: No set and unlabeled neighbors, and stack empty
Increase the current label-value and continue at 1




Courtesy Prof. Dr.-Ing. Thomas Schimannek

September 26, 2023 Confidential. Not to be copied / distributed

Method 2: Sequential Filling

- Move through the whole image in a sequential order
- Assign the lowest label of the neighborhood to each pixel or assign a new label, if all neighbors are unlabeled.
- administration of a connection table
- 2 passes through the image



Courtesy Prof. Dr.-Ing. Thomas Schimannek

September 26, 2023

Confidential. Not to be copied / distributed

56

Binary Morphological Operations

- Basic operations: dilation and erosion
- Composed operations: opening and closing
- The operations are controlled by a structuring element, which can be regarded as a (small) binary image
 - typical structuring elements:

0 0 0 0 0	0 0 0 0 0	0 0 1 0 0
0 0 1 0 0	0 1 1 1 0	0 1 1 1 0
0 1 1 1 0	0 1 1 1 0	1 1 1 1 1
0 0 1 0 0	0 1 1 1 0	0 1 1 1 0
0 0 0 0 0	0 0 0 0 0	0 0 1 0 0

Courtesy Prof. Dr.-Ing. Thomas Schimannek

September 26, 2023

Confidential. Not to be copied / distributed

57

Dilation


- The structuring element is positioned at every 1-pixel of the (binary) image.
- Every 0-pixel of the image, which is hit by a 1 of the structuring element is set to 1.
- Dilation widens structures.

Example: Dilation by 3x3 box

letters letters

Courtesy Prof. Dr.-Ing. Thomas Schimannek

Dilation Example



Courtesy Prof. Dr.-Ing. Thomas Schimannek

September 26, 2023

Confidential. Not to be copied / distributed

59

Erosion


- The structuring element is positioned at every 1-pixel of the (binary) image.
- If a 1 of the structuring element hits a 0 of the image, the image is set to 0 at the center of the structuring element.
- "Dilation of the background"
- Erosion narrows structures.

Example: Erosion by 3x3 box

letters letters

Courtesy Prof. Dr.-Ing. Thomas Schlemmer

Erosion Example



Opening

- Opening = 1. Erosion, 2. Dilation
- Erosion and Dilation are "opposite" operations, but they are not inverse.
- Only those pixels are left in the image, which are covered by a 1 of the structuring element, while it is completely located on 1-pixels of the image.
- The structuring element stamps its shape onto the original structures.

Courtesy Prof. Dr.-Ing. Thomas Schlemmer

Opening

Example: Opening by 3x3 box

letters letters

Example: Opening of a square object by a circular structuring element



Courtesy Prof. Dr.-Ing. Thomas Schlemmer

Closing

- Closing = 1. Dilation, 2. Erosion
- Opening of the background
- Filling of holes, which are smaller or equal to the structuring element.

Example: Closing by 3x3 box

letters letters

Courtesy Prof. Dr.-Ing. Thomas Schlemmer

Applications

- Finding boundaries
 - Erosion
 - Subtract erosion-output from input
- Separating objects from each other (Segmentation)
- Removal of small objects (opening)
- Filling of small holes (closing)
- (Finding objects of a certain shape)

Courtesy Prof. Dr.-Ing. Thomas Schlemmer

Morphological Operations in Formulas

Let I be the image, S the structuring element, and $I_{(i,j)}$ the image shifted i pixels in x -direction and j pixels in y -direction.
(The origin of the coordinate-system is usually located in the top left corner)

Then the dilation can be defined as

$$I \oplus S = \bigcup_{(i,j) \in S} I_{(-i,-j)} \quad (\text{Union of all shifted images})$$

and erosion as

$$I \ominus S = \bigcap_{(i,j) \in S} I_{(-i,-j)} \quad (\text{Intersection of all shifted images})$$

Courtesy Prof. Dr.-Ing. Thomas Schlemmer

Grey-Value Morphological Operations

The image I and the structuring element S both are containing grey-values now.

Then the dilation is defined as

$$(I \oplus S)(x,y) = \max_{(i,j) \in S} \{I(x+i, y+j) + S(i,j)\}$$

and erosion as

$$(I \ominus S)(x,y) = \min_{(i,j) \in S} \{I(x+i, y+j) - S(i,j)\}$$

Courtesy Prof. Dr.-Ing. Thomas Schlemmer

Example

Image (surrounded by zeros)	Structuring Element	Structuring element positioned at (1,1) for dilation	Dilation
7 6 3 5 5 6 2 3 5 9 3 2 3 5 7 7	2 1 0 0 3 1 5 9 7 2 0 0 4	9 7 3 5 5 9 3 3 5 9 7 2 3 5 7 7	9 9 7 8 13 9 8 6 10 12 11 5 6 10 11 10
			Erosion
			2 -2 -1 2 2 -1 -2 0 1 2 0 -1 0 2 2 1
			9 9 7 8 13 9 8 6 10 12 11 5 6 10 11 10

Courtesy Prof. Dr.-Ing. Thomas Schlemmer

Special Case: Maximum-Filter

- The maximum filter is the grey-value *dilation* with a structuring element filled by zeros.
- Each pixel is replaced by the maximum intensity of its neighborhood, which is defined by the structuring element.



Courtesy Prof. Dr.-Ing. Thomas Schlemmer

September 26, 2023

Confidential. Not to be copied / distributed

69

Special Case: Minimum-Filter

- The minimum filter is the grey-value *erosion* with a structuring element filled by zeros.
- Each pixel is replaced by the minimum intensity of its neighborhood, which is defined by the structuring element.



Courtesy Prof. Dr.-Ing. Thomas Schlemmer


September 26, 2023

Confidential. Not to be copied / distributed

70

Latihan

Kerjakanlah Latihan Minggu 5_2 dan kumpulkanlah jawaban anda dalam Canvas



Courtesy Prof. Dr.-Ing. Thomas Schlemmer
September 26, 2023

Confidential. Not to be copied / distributed

72

Terima Kasih
Tuhan Memberkati