
BurnoutExys

Release 1.0.0

Stefano Bia, Younes Laihi, Alfonso Íñiguez, Mohammed Ali

May 13, 2026

CONTENTS:

1	Application Packages	1
1.1	data package	1
1.2	evaluation package	6
1.3	inference package	7
1.4	main module	15
1.5	ui package	15
1.6	visualization package	22
2	Application Test Suites	23
2.1	test_ast module	23
2.2	test_controller module	23
2.3	test_data module	24
2.4	test_engines module	25
2.5	test_evaluation module	25
2.6	test_parsers module	25
3	Indices and Search	27
	Python Module Index	29
	Index	31

APPLICATION PACKAGES

1.1 data package

1.1.1 Data Management Package

This package provides a centralized container and robust parsers for loading, validating, and managing all domain-specific data sets, mapping configurations, fuzzy linguistic variables, and logic rules required by the application.

Author

System Authors

Version

1.0.0

class `data.Data`

Bases: `object`

Container for managing application data, including input sets, rules, variables, and inference results.

Variables

- **`_data`** (`pd.DataFrame` / `None`) – Internal Pandas DataFrame holding processed inputs.
- **`_mappings`** (`dict[str, str]` / `None`) – Column mappings from the raw CSV.
- **`_rules`** (`tuple[Rule, ...]` / `None`) – Tuple of loaded fuzzy logic rules.
- **`_vars`** (`dict[str, Variable]` / `None`) – Dictionary of loaded linguistic variables mapped by name.
- **`_outvar`** (`Variable` / `None`) – The final output linguistic variable for inference.
- **`_results`** (`dict[str, pd.DataFrame]`) – Dictionary caching generated results DataFrames by engine ID.

property `data`: `DataFrame`

Get processed input data.

Returns

DataFrame containing processed data.

load_csv(`path: str`) → `bool`

Ingest data from a CSV file.

Warning

If pandas fails to parse the CSV or the file is empty, this method will catch the exception internally and reset the `_data` attribute to `None` to prevent corrupted states.

Parameters

path (*str*) – Path to the CSV file.

Returns

True if successful, False otherwise.

Return type

bool

Raises

ValueError – Caught internally if the CSV data is empty.

load_map(*path: str*) → bool

Load column mappings from a .map file.

Parameters

path (*str*) – Path to the mapping file.

Returns

True if successful, False otherwise.

Return type

bool

Raises

ValueError – Caught internally if the mapping file resolves to empty.

load_rules(*path: str*) → bool

Load fuzzy rules from a .rules file.

Parameters

path (*str*) – Path to the rules file.

Returns

True if successful, False otherwise.

Return type

bool

Raises

ValueError – Caught internally if rules payload resolves to empty.

load_vars(*path: str*) → bool

Load fuzzy variables from a .vars file.

Parameters

path (*str*) – Path to the vars file.

Returns

True if successful, False otherwise.

Return type

bool

Raises

ValueError – Caught internally if variable payload resolves to empty.

property outvar: *Variable* | None

Get the output variable.

Returns

Output variable, if any, or None.

property results: dict[*str*, DataFrame]

Get results data.

Returns

Dictionary containing results DataFrames indexed by id.

property rules: `tuple[Rule, ...]`

Get the loaded fuzzy rules.

Returns

Tuple of Rule objects.

store(*results: DataFrame*, *engine: type[object]*) → None

Store inference results in the container.

Parameters

- **results** (*pd.DataFrame*) – DataFrame containing the inference results.
- **engine** (*type[object]*) – Engine instance used to compute the results.

property variables: `dict[str, Variable]`

Get the loaded fuzzy variables.

Returns

Dict of Variable objects mapped by their names.

1.1.2 Submodules

1.1.3 data.data module

Data Container

This module provides the central Data container class. It acts as the in-memory repository for the entire application state, storing parsed rules, linguistic variables, mappings, and the raw and processed pandas DataFrames.

class `data.data.Data`

Bases: `object`

Container for managing application data, including input sets, rules, variables, and inference results.

Variables

- **_data** (*pd.DataFrame | None*) – Internal Pandas DataFrame holding processed inputs.
- **_mappings** (*dict[str, str] | None*) – Column mappings from the raw CSV.
- **_rules** (*tuple[Rule, ...] | None*) – Tuple of loaded fuzzy logic rules.
- **_vars** (*dict[str, Variable] | None*) – Dictionary of loaded linguistic variables mapped by name.
- **_outvar** (*Variable | None*) – The final output linguistic variable for inference.
- **_results** (*dict[str, pd.DataFrame]*) – Dictionary caching generated results DataFrames by engine ID.

property data: `DataFrame`

Get processed input data.

Returns

DataFrame containing processed data.

load_csv(*path: str*) → bool

Ingest data from a CSV file.

Warning

If pandas fails to parse the CSV or the file is empty, this method will catch the exception internally and reset the `_data` attribute to `None` to prevent corrupted states.

Parameters

path (*str*) – Path to the CSV file.

Returns

True if successful, False otherwise.

Return type

bool

Raises

ValueError – Caught internally if the CSV data is empty.

load_map(*path: str*) → bool

Load column mappings from a .map file.

Parameters

path (*str*) – Path to the mapping file.

Returns

True if successful, False otherwise.

Return type

bool

Raises

ValueError – Caught internally if the mapping file resolves to empty.

load_rules(*path: str*) → bool

Load fuzzy rules from a .rules file.

Parameters

path (*str*) – Path to the rules file.

Returns

True if successful, False otherwise.

Return type

bool

Raises

ValueError – Caught internally if rules payload resolves to empty.

load_vars(*path: str*) → bool

Load fuzzy variables from a .vars file.

Parameters

path (*str*) – Path to the vars file.

Returns

True if successful, False otherwise.

Return type

bool

Raises

ValueError – Caught internally if variable payload resolves to empty.

property outvar: *Variable* | None

Get the output variable.

Returns

Output variable, if any, or None.

property results: `dict[str, DataFrame]`

Get results data.

Returns

Dictionary containing results DataFrames indexed by id.

property rules: `tuple[Rule, ...]`

Get the loaded fuzzy rules.

Returns

Tuple of Rule objects.

store(*results: DataFrame*, *engine: type[object]*) → None

Store inference results in the container.

Parameters

- **results** (*pd.DataFrame*) – DataFrame containing the inference results.
- **engine** (*type[object]*) – Engine instance used to compute the results.

property variables: `dict[str, Variable]`

Get the loaded fuzzy variables.

Returns

Dict of Variable objects mapped by their names.

1.1.4 data.parsers module

Domain Parsers

This module provides concrete parser implementations for transforming raw text file payloads (.rules, .vars) into structured, operable domain objects such as LinguisticVariables and Abstract Syntax Trees for fuzzy logic rules.

data.parsers.PRECISION: int = 1000

Integer defining the resolution (number of discrete steps) used when generating numpy arrays for fuzzy universes.

class data.parsers.Parser

Bases: ABC

Abstract base class for parsers.

abstractmethod parse(*text: str*) → object

Parse text and return corresponding object.

Parameters

text – Text to parse.

Returns

Parsed object.

class data.parsers.RuleParser

Bases: *Parser*

Parser for fuzzy rules definitions.

Format: IF Var1 OR Var2 AND (Var3 OR NOT Var4) THEN OutputVar IS OutputSet

Variables

- **_pos** (*int*) – Current index position in the token list during parsing.
- **_tokens** (*list[str]*) – List of extracted string tokens from the rule antecedent.

Example

```
>>> parser = RuleParser()
>>> rule = parser.parse("IF exhaustion IS high AND cynicism IS high,
↳ THEN burnout IS high")
```

parse(text: str) → list[Rule]

Parse rule definitions from text.

Parameters

text – Text containing rule definitions.

Returns

List of parsed Rule objects.

property pos: int

Get current position.

Returns

Current position index.

property tokens: list[str]

Get current tokens.

Returns

List of tokens.

class data.parsers.VariableParser

Bases: *Parser*

Parser for linguistic variables definitions.

Format: VariableName<DomainStart, DomainEnd>: (FirstSet<func, val1, ..., valn>; ...; NSet<func, val2, ..., valn>)

parse(text: str) → list[Variable]

Parse variable definitions from text.

Parameters

text – Text containing variable definitions.

Returns

List of parsed Variable objects.

1.2 evaluation package

Evaluation package for calculating metrics.

class evaluation.Evaluator(x_results: DataFrame | Series, y_results: DataFrame | Series)

Bases: object

Compare engine results.

property mae: float

Calculate Mean Absolute Error.

Returns

MAE score.

property mse: float

Calculate Mean Squared Error.

Returns

MSE score.

1.2.1 Submodules

1.2.2 evaluation.metrics module

Evaluation metrics module.

class `evaluation.metrics.Evaluator`(*x_results: DataFrame | Series, y_results: DataFrame | Series*)

Bases: `object`

Compare engine results.

property `mae: float`

Calculate Mean Absolute Error.

Returns

MAE score.

property `mse: float`

Calculate Mean Squared Error.

Returns

MSE score.

1.3 inference package

1.3.1 Inference Subsystem

This package contains the core intelligence of the application. It provides the base infrastructure and specialized engines capable of executing evaluations, whether through deterministic rules (MBI) or advanced logical operators over fuzzy sets.

Author

System Authors

Version

1.0.0

1.3.2 Subpackages

`inference.engines` package

Inference Engines

This package houses concrete implementations of inference strategies that derive burnout and risk scores from processed data. It utilizes the Strategy Pattern, a design approach that allows the system to seamlessly swap out different evaluation algorithms (like deterministic MBI logic versus fuzzy logic) at runtime without altering the internal code that leverages them.

Author

System Authors

Version

1.0.0

class `inference.engines.BaseEngine`

Bases: `ABC`

Abstract base class for inference engines.

Variables

- **`_meta`** (`Data`) – Reference to the application's Data container for evaluating rules.
- **`_results`** (`pd.DataFrame`) – Cached pandas DataFrame containing the computed inference results.

- **_colnames** (*tuple*[*str*, ...]) – Tuple of variable names forming the columns of the results table.

evaluate(*data*: [Data](#), *progress_fn*: *Callable*[[*int*, *int*], *None*] | *None* = *None*) → *None*

Evaluate input data and store results.

Parameters

- **data** ([Data](#)) – Input Data containing raw/processed data.
- **progress_fn** (*Callable*[[*int*, *int*], *None*] | *None*) – Optional callback for reporting progress (current, total).

abstract property results: DataFrame

class `inference.engines.FuzzyEngine`

Bases: [BaseEngine](#)

Inference engine based on fuzzy logic.

Variables

- **_input_variables** (*dict*[*str*, [Variable](#)]) – Dictionary of linguistic variables used as inputs.
- **_output_variable** ([Variable](#)) – The linguistic variable representing the output.
- **_rules** (*tuple*[[Rule](#), ...] | *list*[[Rule](#)]) – Tuple or list of fuzzy rules guiding the inference process.

property results: DataFrame

Get the inference results.

Returns

DataFrame containing Fuzzy engine results.

class `inference.engines.MBIEngine`

Bases: [BaseEngine](#)

Inference engine based on Maslach Burnout Inventory deterministic rules.

Variables

groups (*dict*[*str*, *tuple*[*str*, ...]]) – Dictionary mapping MBI dimension groups to their corresponding data columns.

groups: *dict*[*str*, *tuple*[*str*, ...]] = {'despersonalization': (), 'exhaustion': (), 'fullfilment': ()}

Dictionary mapping MBI dimension groups to their corresponding data columns.

property results: DataFrame

Get the inference results.

Returns

DataFrame containing MBI results.

Submodules

`inference.engines.base_engine` module

Base Inference Engine

This module provides the foundational architecture for all inference engines in the application. It employs the Template Method design pattern to dictate the generic, step-by-step algorithm for processing data row by row during evaluation. Child classes inherit this base and override specific hooks (initialization, single-row evaluation, and result storage) to inject their own distinct logic.

class inference.engines.base_engine.BaseEngine

Bases: ABC

Abstract base class for inference engines.

Variables

- **_meta** (*Data*) – Reference to the application’s Data container for evaluating rules.
- **_results** (*pd.DataFrame*) – Cached pandas DataFrame containing the computed inference results.
- **_colnames** (*tuple[str, ...]*) – Tuple of variable names forming the columns of the results table.

evaluate(*data: Data, progress_fn: Callable[[int, int], None] | None = None*) → None

Evaluate input data and store results.

Parameters

- **data** (*Data*) – Input Data containing raw/processed data.
- **progress_fn** (*Callable[[int, int], None] | None*) – Optional callback for reporting progress (current, total).

abstract property results: DataFrame**inference.engines.fuzzy_engine module****Fuzzy Logic Engine**

This module implements the core FuzzyEngine, inheriting the BaseEngine Template Method. It evaluates complex fuzzy logic rule sets against input data, computing aggregate membership activation strengths and returning defuzzified centroid scores.

class inference.engines.fuzzy_engine.FuzzyEngineBases: *BaseEngine*

Inference engine based on fuzzy logic.

Variables

- **_input_variables** (*dict[str, Variable]*) – Dictionary of linguistic variables used as inputs.
- **_output_variable** (*Variable*) – The linguistic variable representing the output.
- **_rules** (*tuple[Rule, ...] | list[Rule]*) – Tuple or list of fuzzy rules guiding the inference process.

property results: DataFrame

Get the inference results.

Returns

DataFrame containing Fuzzy engine results.

inference.engines.mbi_engine module**Deterministic MBI Engine**

This module implements the MBIEngine, inheriting the BaseEngine Template Method. It evaluates raw data using standard deterministic Maslach Burnout Inventory thresholds to output simple boolean risk classifications and averaged scores.

class `inference.engines.mbi_engine.MBIEngine`

Bases: `BaseEngine`

Inference engine based on Maslach Burnout Inventory deterministic rules.

Variables

groups (`dict[str, tuple[str, ...]]`) – Dictionary mapping MBI dimension groups to their corresponding data columns.

groups: `dict[str, tuple[str, ...]] = {'despersonalization': (), 'exhaustion': (), 'fullfilment': ()}`

Dictionary mapping MBI dimension groups to their corresponding data columns.

property results: `DataFrame`

Get the inference results.

Returns

`DataFrame` containing MBI results.

`inference.fuzzy` package

Fuzzy Logic Subsystem

This package constructs a domain-specific language (DSL) and Abstract Syntax Tree (AST) for defining and evaluating fuzzy logic constraints, operators, rules, and linguistic variables across mathematical universes.

Author

System Authors

Version

1.0.0

type `inference.fuzzy.BinaryOp = Callable[[ndarray, ndarray], ndarray]`

class `inference.fuzzy.BranchNode(left: Node, right: Node | None = None)`

Bases: `Node`, `ABC`

Branch node representing a logical operation between nodes.

Variables

- **_left** (`Node`) – Left child node.
- **_right** (`Node | None`) – Optional right child node.

class `inference.fuzzy.LeafNode(variable: str, term: str)`

Bases: `Node`

A leaf node representing a single fuzzy variable evaluation.

Variables

- **_variable** (`str`) – Name of the variable in the context.
- **_term** (`str`) – Name of the membership function to evaluate.

evaluate (`context: dict[str, dict[str, ndarray]]`) → `ndarray`

Evaluate the leaf node by fetching membership from context.

Parameters

context (`dict[str, dict[str, np.ndarray]]`) – Dictionary containing evaluated memberships.

Returns

Membership value.

Return type

`np.ndarray`

Raises

KeyError – If the variable or term is not found in the context.

class `inference.fuzzy.Node`

Bases: `ABC`

Abstract base class for all nodes in the evaluation tree.

abstractmethod `evaluate(context: dict[str, dict[str, ndarray]]) → ndarray`

Evaluate the node given a context.

Parameters

context (`dict[str, dict[str, np.ndarray]]`) – Dictionary containing fuzzified data for evaluation.

Returns

Evaluation results.

Return type

`np.ndarray`

class `inference.fuzzy.Rule(antecedent: Node, consequent: LeafNode)`

Bases: `object`

Represent a fuzzy IF-THEN rule.

property `antecedent: Node`

Get the antecedent term.

Returns

Antecedent term Node.

property `consequent: LeafNode`

Get the consequent term.

Returns

Consequent term Node.

evaluate(`context: dict[str, dict[str, ndarray]]`) → `ndarray`

Evaluate rule.

Parameters

context – Fuzzified input data.

Returns

Activation strength of the rule.

type `inference.fuzzy.UnaryOp = Callable[[ndarray], ndarray]`

class `inference.fuzzy.Variable(name: str, universe: ndarray)`

Bases: `object`

Represent a linguistic fuzzy variable with membership functions.

add_term(`term: str, membership_fn: ndarray`) → `None`

Add a linguistic term and its membership function.

Parameters

- **term** – Name of the term (e.g., 'low', 'high').
- **membership_fn** – Array of membership values corresponding to the universe.

fuzzify(`values: float | ndarray`) → `dict[str, ndarray]`

Calculate membership degrees for input value.

Parameters

value – Input value or values to fuzzify.

Returns

Dictionary of term names to membership arrays.

property name: `str`

Get variable name.

property terms: `dict[str, ndarray]`

Get variable terms.

property universe: `ndarray`

Get variable universe.

Submodules**inference.fuzzy.ast module**

AST for fuzzy rule evaluation.

class `inference.fuzzy.ast.AndNode`(*left*: `Node`, *right*: `Node` | `None` = `None`)

Bases: `BranchNode`

Represent a fuzzy AND operation.

evaluate(*context*: `dict[str, dict[str, ndarray]]`) → `ndarray`

Evaluate the fuzzy AND using `np.fmin`.

Parameters

context (`dict[str, dict[str, np.ndarray]]`) – Dictionary containing data/context for evaluation.

Returns

Minimum membership value.

Return type

`np.ndarray`

Raises

AssertionError – If the right child node is missing.

type `inference.fuzzy.ast.BinaryOp` = `Callable[[ndarray, ndarray], ndarray]`

Type alias for a binary operation over numpy arrays.

class `inference.fuzzy.ast.BranchNode`(*left*: `Node`, *right*: `Node` | `None` = `None`)

Bases: `Node`, `ABC`

Branch node representing a logical operation between nodes.

Variables

- **_left** (`Node`) – Left child node.
- **_right** (`Node` | `None`) – Optional right child node.

class `inference.fuzzy.ast.LeafNode`(*variable*: `str`, *term*: `str`)

Bases: `Node`

A leaf node representing a single fuzzy variable evaluation.

Variables

- **_variable** (`str`) – Name of the variable in the context.
- **_term** (`str`) – Name of the membership function to evaluate.

evaluate(*context: dict[str, dict[str, ndarray]]*) → ndarray

Evaluate the leaf node by fetching membership from context.

Parameters

context (*dict[str, dict[str, np.ndarray]]*) – Dictionary containing evaluated memberships.

Returns

Membership value.

Return type

np.ndarray

Raises

KeyError – If the variable or term is not found in the context.

class inference.fuzzy.ast.**Node**

Bases: ABC

Abstract base class for all nodes in the evaluation tree.

abstractmethod evaluate(*context: dict[str, dict[str, ndarray]]*) → ndarray

Evaluate the node given a context.

Parameters

context (*dict[str, dict[str, np.ndarray]]*) – Dictionary containing fuzzified data for evaluation.

Returns

Evaluation results.

Return type

np.ndarray

class inference.fuzzy.ast.**NotNode**(*child: Node*)

Bases: [BranchNode](#)

Represent a fuzzy NOT operation.

evaluate(*context: dict[str, dict[str, ndarray]]*) → ndarray

Evaluate fuzzy NOT using 1.0 - val.

Parameters

context (*dict[str, dict[str, np.ndarray]]*) – Dictionary containing data/context for evaluation.

Returns

Inverted membership value.

Return type

np.ndarray

inference.fuzzy.ast.OPERATORS: *dict[str, UnaryOp | BinaryOp]* = {'AND': <ufunc 'fmin'>, 'NOT': <function <lambda>>, 'OR': <ufunc 'fmax'>}

Dictionary mapping string identifiers to their corresponding logical numpy operations.

class inference.fuzzy.ast.**OrNode**(*left: Node, right: Node | None = None*)

Bases: [BranchNode](#)

Represent a fuzzy OR operation.

evaluate(*context: dict[str, dict[str, ndarray]]*) → ndarray

Evaluate the fuzzy OR using np.fmax.

Parameters

context (*dict[str, dict[str, np.ndarray]]*) – Dictionary containing data/context for evaluation.

Returns

Maximum membership value.

Return type

np.ndarray

Raises

AssertionError – If the right child node is missing.

type inference.fuzzy.ast.UnaryOp = Callable[[ndarray], ndarray]

Type alias for a unary operation over numpy arrays.

inference.fuzzy.rules module**Fuzzy Logic Rules**

This module defines the Rule and ThenNode objects, which tie together an antecedent (an AST of conditions) and a consequent (the resulting output term) to compute final activation strengths using numpy array operations.

inference.fuzzy.rules.OPERATORS: dict[str, BinaryOp] = {'THEN': <ufunc 'fmin'>}

Dictionary mapping consequent string operators to their underlying numpy aggregation functions.

class inference.fuzzy.rules.Rule(antecedent: Node, consequent: LeafNode)

Bases: object

Represent a fuzzy IF-THEN rule.

property antecedent: Node

Get the antecedent term.

Returns

Antecedent term Node.

property consequent: LeafNode

Get the consequent term.

Returns

Consequent term Node.

evaluate(context: dict[str, dict[str, ndarray]]) → ndarray

Evaluate rule.

Parameters

context – Fuzzified input data.

Returns

Activation strength of the rule.

class inference.fuzzy.rules.ThenNode(left: Node, right: Node | None = None)

Bases: BranchNode

Represent a fuzzy THEN operation.

evaluate(context: dict[str, dict[str, ndarray]]) → ndarray

Evaluate the fuzzy THEN using np.fmax.

Parameters

context – Dictionary containing data/context for evaluation.

Returns

Minimum membership value.

inference.fuzzy.variables module

Fuzzy Linguistic Variables

This module encapsulates the representation of fuzzy linguistic variables, including their mathematically defined universe of discourse and associated membership functions (e.g., 'low', 'high') used during fuzzification.

class `inference.fuzzy.variables.Variable(name: str, universe: ndarray)`

Bases: object

Represent a linguistic fuzzy variable with membership functions.

add_term(term: str, membership_fn: ndarray) → None

Add a linguistic term and its membership function.

Parameters

- **term** – Name of the term (e.g., 'low', 'high').
- **membership_fn** – Array of membership values corresponding to the universe.

fuzzify(values: float | ndarray) → dict[str, ndarray]

Calculate membership degrees for input value.

Parameters

value – Input value or values to fuzzify.

Returns

Dictionary of term names to membership arrays.

property name: str

Get variable name.

property terms: dict[str, ndarray]

Get variable terms.

property universe: ndarray

Get variable universe.

1.4 main module

1.4.1 Application Entry Point

This module serves as the primary entry point for the Fuzzy Expert System. It encapsulates the bootstrap logic required to instantiate the interactive terminal Menu and delegates execution control to the UI package.

main.main() → None

Bootstrap and start the interactive terminal application.

This function instantiates the root Menu component and hands over the main execution thread to its event loop, returning the final status code upon exit.

1.5 ui package

1.5.1 User Interface Package

This package encapsulates the interactive terminal views, the main application controller, and utilities for rich console rendering and interactive file browsing.

Author

System Authors

Version

1.0.0

class ui.Menu

Bases: object

Interactive menu for the application.

Variables

- **options** (*dict[str, str]*) – Dictionary mapping display names of menu options to their corresponding Controller methods.
- **status_items** (*dict[str, tuple[str, str]]*) – Dictionary mapping state keys to a tuple of display title and default value for the status bar.
- **_console** (*Console*) – Active Rich console instance.
- **_status** (*Display*) – Dedicated Display instance for rendering the static status bar.
- **_rules** (*Display*) – Dedicated Display instance for rendering loaded rules summary.
- **_vars** (*Display*) – Dedicated Display instance for rendering loaded variables summary.
- **_output** (*Display*) – Dedicated Display instance for ad-hoc command responses and warnings.
- **_controller** (*Controller*) – Central application Controller managing state logic.

cls() → None

Clear the console screen.

property data: *Data*

Get the underlying data container.

Returns

Data container instance.

echo(*string: str | ConsoleRenderable = ""*) → None

Print to the console.

Parameters

string – String to print.

```
options: dict[str, str] = {'Execute Inference': 'execute_inference', 'Generate Visualizations': 'generate_visualizations', 'Load Data': 'load_data', 'Load Mappings': 'load_mappings', 'Load Rules': 'load_rules', 'Load Variables': 'load_variables', 'Switch Engine': 'switch_engine'}
```

Dictionary mapping display names of menu options to their corresponding Controller methods.

read(*prompt: str = ""*) → str

Read input from the console.

Parameters

prompt – Input prompt.

Returns

User input.

run() → int

Execute interactive main menu loop.

Returns

Exit status code.

property state: *dict[str, str | type[BaseEngine] | None]*

Get the current application state.

Returns

State dictionary.

```
status_items: dict[str, tuple[str, str]] = {'data': ('Data', 'No'), 'engine':
('Engine', 'None'), 'mappings': ('Mappings', 'No'), 'rules': ('Rules', 'No'),
'variables': ('Variables', 'No')}
```

Dictionary mapping state keys to a tuple of display title and default value for the status bar.

1.5.2 Submodules

1.5.3 ui.browser module

File Browser Component

This module provides the `FileBrowser` class, which utilizes the *questionary* library to render an interactive, terminal-based file navigation interface. It allows users to traverse the local filesystem and select specific files filtered by extension.

```
class ui.browser.FileBrowser(path: str, extensions: tuple[str, ...])
```

Bases: object

Provide interactive file browser using *questionary*.

Variables

- **icons** (*dict[str, str]*) – Dictionary mapping item types to their corresponding terminal icon strings.
- **_extensions** (*tuple[str, ...]*) – Tuple of allowed file extensions.
- **_items** (*list[str] | None*) – Cached list of all directory items.
- **_folders** (*list[str] | None*) – Cached list of folder names.
- **_files** (*list[str] | None*) – Cached list of file names filtered by allowed extensions.
- **_choices** (*list[str] | None*) – Cached list of *questionary* Choice strings.
- **_cd** (*str*) – Absolute path to the currently active directory.

property cd: str

Get current directory path.

Returns

Current directory path string.

property choices: list[str]

Get menu choices for *questionary*.

Returns

List of choice strings.

property extensions: tuple[str, ...]

Get allowed file extensions.

Returns

Tuple of extension strings.

property files: list[str]

Get filtered files in current directory.

Returns

List of file names.

property folders: list[str]

Get folders in current directory.

Returns

List of folder names.

icons: `dict[str, str] = {'exit': '»', 'file': '[FILE]', 'folder': '[DIR]}'`

Dictionary mapping item types to their corresponding terminal icon strings.

into(*directory: str*) → None

Navigate into child directory.

Parameters

directory – Target directory name.

property items: `list[str]`

Get all items in current directory.

Returns

List of item names.

run() → `str` | None

Execute interactive file browser loop.

Note

This method takes control of the terminal until the user makes a valid selection or chooses to cancel the prompt.

Returns

Selected file path or None if cancelled.

Return type

`str` | None

up() → None

Navigate to parent directory.

1.5.4 ui.chooser module

Interactive checkbox chooser module.

class `ui.chooser.Chooser`(*min_n: int, max_n: int, choices: tuple[dict[str, Any], ...], console: Console*)

Bases: `object`

Interactive checkbox chooser for selecting items from a list.

run() → `list[str]` | None

Execute the interactive chooser.

Returns

List of selected values, or None if no valid selection was made.

1.5.5 ui.controller module

Application Controller

This module defines the central `Controller` responsible for orchestrating the application's primary workflow. It acts as the mediator between the interactive terminal views (`Menu`, `Browser`, `Display`) and the backend logic (`Data`, `Inference Engines`), ensuring state consistency and managing the execution lifecycle.

class `ui.controller.Controller`(*display: Display*)

Bases: `object`

Controller orchestrating the application flow.

Variables

- **engines** (`tuple[type[BaseEngine], ...]`) – Tuple of available BaseEngine subclasses that can be dynamically swapped.
- **_data** (`Data`) – The central Data container tracking all parsed values.
- **_display** (`Display`) – System-wide display controller for rendering outputs.
- **_progressbar** (`ProgressBar`) – System-wide progress bar utility for long-running inferences.
- **_engine** (`int`) – Index representing the currently active evaluation engine.
- **_browsers** (`dict[str, FileBrowser]`) – Dictionary mapping domain file types to their FileBrowser prompts.
- **_state** (`dict[str, str | type[BaseEngine] | None]`) – Application state dictionary accessible across the UI layer.

property data: `Data`

Get the data container.

Returns

Data container instance.

```
engines: tuple[type[BaseEngine], ...] = (<class
'inference.engines.mbi_engine.MBIEngine'>, <class
'inference.engines.fuzzy_engine.FuzzyEngine'>)
```

Tuple of available BaseEngine subclasses that can be dynamically swapped.

execute_inference() → None

Execute inference on loaded data.

generate_visualizations() → None

load_data() → bool

Load data into the container.

Returns

True if successful, False otherwise.

load_mappings() → bool

Load mapping into the container.

Returns

True if successful, False otherwise.

load_rules() → bool

Load fuzzy rules from a .rules file.

Returns

True if successful, False otherwise.

load_variables() → bool

Load fuzzy variables from a .vars file.

Returns

True if successful, False otherwise.

property state: `dict[str, str | type[BaseEngine] | None]`

Get current application state.

Returns

State dictionary.

switch_engine() → None

Switch between available inference engines.

1.5.6 ui.display module

Console display utility module.

class `ui.display.Display(title: str, console: Console)`

Bases: `object`

Console display manager for rendering messages, warnings, and panels.

Variables

- **styles** (`dict[str, dict[str, str]]`) – Global dictionary mapping semantic types to rich styling parameters.
- **_console** (`Console`) – Active Rich console for rendering text.
- **_title** (`str | None`) – Optional title string for rendered panels.
- **_type** (`str`) – Semantic type defining the current rendering style (e.g., 'error', 'success').
- **_message** (`str | None`) – Content body to be displayed upon invocation.

echo(`string: str | ConsoleRenderable = ""`) → `None`

Print a raw string to the console.

Parameters

string – String to print.

set(`message: str, type: str | None = None`) → `None`

Set a formatted message to be displayed later.

Only the last set message will be displayed and messages will be displayed only once.

Parameters

- **message** – Content of the message.
- **type** – Optional type for styling the message.

show() → `None`

Render the configured message, if any, inside a styled panel, then reset state.

property style: `dict[str, str]`

Get the current style configuration.

Returns

Dictionary containing color specifications.

```
styles: dict[str, dict[str, str]] = {'error': {'border': 'bold red', 'text': 'red', 'title': 'bold red'}, 'normal': {'border': 'bold blue', 'text': 'blue', 'title': 'bold blue'}, 'success': {'border': 'bold green', 'text': 'green', 'title': 'bold green'}, 'warning': {'border': 'bold orange', 'text': 'orange', 'title': 'bold orange'}}
```

property type: `str`

Get the active message type (e.g., error, normal).

Returns

String representing the message type.

1.5.7 ui.menu module

Interactive terminal menu.

class ui.menu.Menu

Bases: object

Interactive menu for the application.

Variables

- **options** (*dict[str, str]*) – Dictionary mapping display names of menu options to their corresponding Controller methods.
- **status_items** (*dict[str, tuple[str, str]]*) – Dictionary mapping state keys to a tuple of display title and default value for the status bar.
- **_console** (*Console*) – Active Rich console instance.
- **_status** (*Display*) – Dedicated Display instance for rendering the static status bar.
- **_rules** (*Display*) – Dedicated Display instance for rendering loaded rules summary.
- **_vars** (*Display*) – Dedicated Display instance for rendering loaded variables summary.
- **_output** (*Display*) – Dedicated Display instance for ad-hoc command responses and warnings.
- **_controller** (*Controller*) – Central application Controller managing state logic.

cls() → None

Clear the console screen.

property data: *Data*

Get the underlying data container.

Returns

Data container instance.

echo (*string: str | ConsoleRenderable = ""*) → None

Print to the console.

Parameters**string** – String to print.

```
options: dict[str, str] = {'Execute Inference': 'execute_inference', 'Generate
Visualizations': 'generate_visualizations', 'Load Data': 'load_data', 'Load
Mappings': 'load_mappings', 'Load Rules': 'load_rules', 'Load Variables':
'load_variables', 'Switch Engine': 'switch_engine'}
```

Dictionary mapping display names of menu options to their corresponding Controller methods.

read (*prompt: str = ""*) → str

Read input from the console.

Parameters**prompt** – Input prompt.**Returns**

User input.

run() → int

Execute interactive main menu loop.

Returns

Exit status code.

property state: *dict[str, str | type[BaseEngine] | None]*

Get the current application state.

Returns

State dictionary.

```
status_items: dict[str, tuple[str, str]] = {'data': ('Data', 'No'), 'engine':  
('Engine', 'None'), 'mappings': ('Mappings', 'No'), 'rules': ('Rules', 'No'),  
'variables': ('Variables', 'No')}
```

Dictionary mapping state keys to a tuple of display title and default value for the status bar.

1.5.8 ui.progress module

Progress Bar Utility

This module provides a context manager for rendering an interactive progress bar in the terminal. It leverages the rich library to display real-time progress updates, spinners, and task completion metrics during long-running operations.

```
class ui.progress.ProgressBar
```

Bases: object

Context manager for a Rich progress bar.

1.6 visualization package

1.6.1 Visualization Package

This package provides utilities for generating and rendering 2D and 3D plots of membership functions, rule surfaces, and evaluation metrics using matplotlib and seaborn.

1.6.2 Submodules

1.6.3 visualization.plotters module

Visualization utilities.

```
class visualization.plotters.Plotter
```

Bases: object

Utility class for generating visualizations.

```
static plot_membership_functions(universe: ndarray, terms: dict[str, ndarray], title: str,  
                                filename: str) → None
```

Plot membership functions of a linguistic variable and save to a file.

Parameters

- **universe** – Universe of discourse.
- **terms** – Dictionary of terms to their membership arrays.
- **title** – Title of the plot.
- **filename** – Output file path.

```
static plot_surface(x: ndarray, y: ndarray, z: ndarray, title: str, filename: str) → None
```

Plot 3D surface graph.

Parameters

- **x** – 2D array of X coordinates.
- **y** – 2D array of Y coordinates.
- **z** – 2D array of Z coordinates (evaluated scores).
- **title** – Title of the plot.
- **filename** – Output file path.

APPLICATION TEST SUITES

2.1 test_ast module

Tests for the fuzzy AST and operators.

`test_ast.test_ast_complex_structure()` → None

Test AST operations in a complex tree structure.

`test_ast.test_ast_evaluation_array()` → None

Test AST operations with vector values.

`test_ast.test_ast_evaluation_scalar()` → None

Test AST operations with scalar values.

2.2 test_controller module

Tests for the UI controller module.

class `test_controller.DummyEngine`

Bases: *BaseEngine*

Dummy engine for testing.

property results: `DataFrame`

`test_controller.test_controller_execute_inference(tmp_path: Path, mocker: MockerFixture)` → None

Test inference execution delegation.

Simulate data loading, switch to a dummy engine, and invoke inference execution. Ensure that the Controller correctly captures and stores the evaluation results.

`test_controller.test_controller_generate_visualizations(mocker: MockerFixture)` → None

Test visualization pipeline execution.

Verify that the Controller's `generate_visualizations` method executes cleanly without crashing, even when data is empty or results are absent.

`test_controller.test_controller_initialization()` → None

Test Controller instantiation.

Verify that the Controller correctly sets up its internal state dictionary, data container, and engine bindings upon initialization with a Display.

`test_controller.test_controller_load_data(tmp_path: Path, mocker: MockerFixture)` → None

Test CSV data loading through the controller.

Mock the interactive `FileBrowser` to simulate a user selecting a CSV file, and verify that the Controller successfully delegates the ingestion to the Data container.

`test_controller.test_controller_load_mappings(tmp_path: Path, mocker: MockerFixture) → None`

Test .map data loading through the controller.

Mock the interactive FileBrowser to simulate a user selecting a .map file, and verify that the Controller successfully delegates the ingestion to the Data container.

`test_controller.test_controller_load_rules(tmp_path: Path, mocker: MockerFixture) → None`

Test .rules data loading through the controller.

Mock the interactive FileBrowser to simulate a user selecting a .rules file, and verify that the Controller successfully delegates the ingestion to the Data container.

`test_controller.test_controller_load_variables(tmp_path: Path, mocker: MockerFixture) → None`

Test .vars data loading through the controller.

Mock the interactive FileBrowser to simulate a user selecting a .vars file, and verify that the Controller successfully delegates the ingestion to the Data container.

`test_controller.test_controller_switch_engine() → None`

Test engine switching logic in the controller.

Iterate through multiple engine switches and verify that the controller cycles through the available engine types defined in its class attribute.

2.3 test_data module

Tests for the data module.

class `test_data.DummyEngine`

Bases: *BaseEngine*

Dummy engine for testing purposes.

property results: `DataFrame`

`test_data.test_ingest_from_csv(tmp_path: Path) → None`

Test successful CSV file ingestion.

Verify that the Data container correctly reads a CSV file and stores its content in the internal DataFrame state.

`test_data.test_ingest_from_csv_failure() → None`

Test graceful failure during CSV ingestion.

Ensure that attempting to load a non-existent CSV file returns a failure status and leaves the data container empty.

`test_data.test_map(tmp_path: Path) → None`

Test mapping file loading and column renaming.

Verify that a .map file correctly triggers the renaming of columns in the ingested DataFrame within the Data container.

`test_data.test_map_failure() → None`

Test graceful failure during mapping file loading.

Ensure that a missing .map file is handled correctly by returning a failure status.

`test_data.test_rules(tmp_path: Path) → None`

Test successful loading of fuzzy rules from a file.

Verify that the RuleParser is correctly invoked to populate the internal rules tuple from a provided payload.

`test_data.test_rules_failure()` → None

Test graceful failure during rule file loading.

Ensure that missing rule files result in an empty rules tuple and a failure return status.

`test_data.test_save_results()` → None

Test inference results storage.

Verify that evaluated results from an inference engine are correctly cached within the Data container's results dictionary.

`test_data.test_vars(tmp_path: Path)` → None

Test successful loading of fuzzy variables from a file.

Verify that the VariableParser correctly populates the internal variables dictionary from a provided payload.

`test_data.test_vars_failure()` → None

Test graceful failure during variable file loading.

Ensure that missing variable files result in an empty variables dictionary and a failure return status.

2.4 test_engines module

Tests for inference engines.

`test_engines.test_fuzzy_engine()` → None

Test complete Fuzzy logic evaluation lifecycle.

Inject synthetic fuzzy sets (Variables), membership functions, and logical Rules into the engine. Verify that the FuzzyEngine reliably translates inputs to degrees of truth, triggers correct consequents, defuzzifies the output via centroid method, and appends the RESULTS column appropriately.

`test_engines.test_mbi_engine()` → None

Test Maslach Burnout Inventory deterministic evaluation.

Feed raw exhaustion and cynicism data into the MBIEngine, and assert that it correctly calculates the average MBI score and sets the high-risk boolean flag strictly based on its static thresholds.

2.5 test_evaluation module

Tests for evaluation module.

`test_evaluation.test_calculate_discrepancy()` → None

Test MAE and MSE calculations.

Verify that the Evaluator correctly computes the Mean Absolute Error (MAE) and Mean Squared Error (MSE) between two sets of inference results.

`test_evaluation.test_calculate_discrepancy_empty()` → None

Test error metric calculation with missing data.

Ensure that the Evaluator handles empty input series gracefully by returning zeroed metrics instead of crashing.

2.6 test_parsers module

Tests for the parser module.

`test_parsers.test_rule_parser()` → None

Test Rule DSL syntax resolution.

Provide complex logical conditions and verify the parser generates the correct abstract syntax tree consisting of OrNodes, AndNodes, NotNodes, and LeafNodes bound to the correct Rule consequent object.

`test_parsers.test_rule_parser_errors()` → None

Test graceful degradation of Rule parsing.

Feed syntactically invalid strings into the Rule parser and ensure it swallows the errors gracefully, skipping malformed rules without crashing the system.

`test_parsers.test_variable_parser()` → None

Test Variable DSL syntax resolution.

Supply a raw multiline string of custom DSL Variable syntax and verify that the parser constructs valid `LinguisticVariables` with correctly scoped numpy universes and correctly bound scikit-fuzzy membership functions.

INDICES AND SEARCH

- genindex
- modindex
- search

PYTHON MODULE INDEX

d

data, 1
data.data, 3
data.parsers, 5

e

evaluation, 6
evaluation.metrics, 7

i

inference, 7
inference.engines, 7
inference.engines.base_engine, 8
inference.engines.fuzzy_engine, 9
inference.engines.mbi_engine, 9
inference.fuzzy, 10
inference.fuzzy.ast, 12
inference.fuzzy.rules, 14
inference.fuzzy.variables, 15

m

main, 15

t

test_ast, 23
test_controller, 23
test_data, 24
test_engines, 25
test_evaluation, 25
test_parsers, 25

U

ui, 15
ui.browser, 17
ui.chooser, 18
ui.controller, 18
ui.display, 20
ui.menu, 20
ui.progress, 22

V

visualization, 22
visualization.plotters, 22

A

`add_term()` (*inference.fuzzy.Variable* method), 11
`add_term()` (*inference.fuzzy.variables.Variable* method), 15
`AndNode` (*class in inference.fuzzy.ast*), 12
`antecedent` (*inference.fuzzy.Rule* property), 11
`antecedent` (*inference.fuzzy.rules.Rule* property), 14

B

`BaseEngine` (*class in inference.engines*), 7
`BaseEngine` (*class in inference.engines.base_engine*), 8
`BinaryOp` (*in module inference.fuzzy*), 10
`BinaryOp` (*in module inference.fuzzy.ast*), 12
`BranchNode` (*class in inference.fuzzy*), 10
`BranchNode` (*class in inference.fuzzy.ast*), 12

C

`cd` (*ui.browser.FileBrowser* property), 17
`choices` (*ui.browser.FileBrowser* property), 17
`Chooser` (*class in ui.chooser*), 18
`cls()` (*ui.Menu* method), 16
`cls()` (*ui.menu.Menu* method), 21
`consequent` (*inference.fuzzy.Rule* property), 11
`consequent` (*inference.fuzzy.rules.Rule* property), 14
`Controller` (*class in ui.controller*), 18

D

`data`
 module, 1
`Data` (*class in data*), 1
`Data` (*class in data.data*), 3
`data` (*data.Data* property), 1
`data` (*data.data.Data* property), 3
`data` (*ui.controller.Controller* property), 19
`data` (*ui.Menu* property), 16
`data` (*ui.menu.Menu* property), 21
`data.data`
 module, 3
`data.parsers`
 module, 5
`Display` (*class in ui.display*), 20
`DummyEngine` (*class in test_controller*), 23
`DummyEngine` (*class in test_data*), 24

E

`echo()` (*ui.display.Display* method), 20
`echo()` (*ui.Menu* method), 16
`echo()` (*ui.menu.Menu* method), 21
`engines` (*ui.controller.Controller* attribute), 19
`evaluate()` (*inference.engines.base_engine.BaseEngine* method), 9
`evaluate()` (*inference.engines.BaseEngine* method), 8
`evaluate()` (*inference.fuzzy.ast.AndNode* method), 12
`evaluate()` (*inference.fuzzy.ast.LeafNode* method), 12
`evaluate()` (*inference.fuzzy.ast.Node* method), 13
`evaluate()` (*inference.fuzzy.ast.NotNode* method), 13
`evaluate()` (*inference.fuzzy.ast.OrNode* method), 13
`evaluate()` (*inference.fuzzy.LeafNode* method), 10
`evaluate()` (*inference.fuzzy.Node* method), 11
`evaluate()` (*inference.fuzzy.Rule* method), 11
`evaluate()` (*inference.fuzzy.rules.Rule* method), 14
`evaluate()` (*inference.fuzzy.rules.ThenNode* method), 14
`evaluation`
 module, 6
`evaluation.metrics`
 module, 7
`Evaluator` (*class in evaluation*), 6
`Evaluator` (*class in evaluation.metrics*), 7
`execute_inference()` (*ui.controller.Controller* method), 19
`extensions` (*ui.browser.FileBrowser* property), 17

F

`FileBrowser` (*class in ui.browser*), 17
`files` (*ui.browser.FileBrowser* property), 17
`folders` (*ui.browser.FileBrowser* property), 17
`fuzzify()` (*inference.fuzzy.Variable* method), 11
`fuzzify()` (*inference.fuzzy.variables.Variable* method), 15
`FuzzyEngine` (*class in inference.engines*), 8
`FuzzyEngine` (*class in inference.engines.fuzzy_engine*), 9

G

`generate_visualizations()`
 (*ui.controller.Controller* method), 19
`groups` (*inference.engines.mbi_engine.MBIEngine* attribute), 10

groups (*inference.engines.MBIEngine* attribute), 8

I

icons (*ui.browser.FileBrowser* attribute), 17

inference

 module, 7

inference.engines

 module, 7

inference.engines.base_engine

 module, 8

inference.engines.fuzzy_engine

 module, 9

inference.engines.mbi_engine

 module, 9

inference.fuzzy

 module, 10

inference.fuzzy.ast

 module, 12

inference.fuzzy.rules

 module, 14

inference.fuzzy.variables

 module, 15

into() (*ui.browser.FileBrowser* method), 18

items (*ui.browser.FileBrowser* property), 18

L

LeafNode (*class in inference.fuzzy*), 10

LeafNode (*class in inference.fuzzy.ast*), 12

load_csv() (*data.Data* method), 1

load_csv() (*data.data.Data* method), 3

load_data() (*ui.controller.Controller* method), 19

load_map() (*data.Data* method), 2

load_map() (*data.data.Data* method), 4

load_mappings() (*ui.controller.Controller* method), 19

load_rules() (*data.Data* method), 2

load_rules() (*data.data.Data* method), 4

load_rules() (*ui.controller.Controller* method), 19

load_variables() (*ui.controller.Controller* method), 19

load_vars() (*data.Data* method), 2

load_vars() (*data.data.Data* method), 4

M

mae (*evaluation.Evaluator* property), 6

mae (*evaluation.metrics.Evaluator* property), 7

main

 module, 15

main() (*in module main*), 15

MBIEngine (*class in inference.engines*), 8

MBIEngine (*class in inference.engines.mbi_engine*), 9

Menu (*class in ui*), 15

Menu (*class in ui.menu*), 20

module

 data, 1

 data.data, 3

 data.parsers, 5

 evaluation, 6

evaluation.metrics, 7

inference, 7

inference.engines, 7

inference.engines.base_engine, 8

inference.engines.fuzzy_engine, 9

inference.engines.mbi_engine, 9

inference.fuzzy, 10

inference.fuzzy.ast, 12

inference.fuzzy.rules, 14

inference.fuzzy.variables, 15

main, 15

test_ast, 23

test_controller, 23

test_data, 24

test_engines, 25

test_evaluation, 25

test_parsers, 25

ui, 15

ui.browser, 17

ui.chooser, 18

ui.controller, 18

ui.display, 20

ui.menu, 20

ui.progress, 22

visualization, 22

visualization.plotters, 22

mse (*evaluation.Evaluator* property), 6

mse (*evaluation.metrics.Evaluator* property), 7

N

name (*inference.fuzzy.Variable* property), 12

name (*inference.fuzzy.variables.Variable* property), 15

Node (*class in inference.fuzzy*), 11

Node (*class in inference.fuzzy.ast*), 13

NotNode (*class in inference.fuzzy.ast*), 13

O

OPERATORS (*in module inference.fuzzy.ast*), 13

OPERATORS (*in module inference.fuzzy.rules*), 14

options (*ui.Menu* attribute), 16

options (*ui.menu.Menu* attribute), 21

OrNode (*class in inference.fuzzy.ast*), 13

outvar (*data.Data* property), 2

outvar (*data.data.Data* property), 4

P

parse() (*data.parsers.Parser* method), 5

parse() (*data.parsers.RuleParser* method), 6

parse() (*data.parsers.VariableParser* method), 6

Parser (*class in data.parsers*), 5

plot_membership_functions() (*visualization.plotters.Plotter* static method), 22

plot_surface() (*visualization.plotters.Plotter* static method), 22

Plotter (*class in visualization.plotters*), 22

pos (*data.parsers.RuleParser* property), 6

PRECISION (*in module data.parsers*), 5

ProgressBar (*class in ui.progress*), 22

R

[read\(\)](#) (*ui.Menu method*), 16
[read\(\)](#) (*ui.menu.Menu method*), 21
[results](#) (*data.Data property*), 2
[results](#) (*data.data.Data property*), 5
[results](#) (*inference.engines.base_engine.BaseEngine property*), 9
[results](#) (*inference.engines.BaseEngine property*), 8
[results](#) (*inference.engines.fuzzy_engine.FuzzyEngine property*), 9
[results](#) (*inference.engines.FuzzyEngine property*), 8
[results](#) (*inference.engines.mbi_engine.MBIEngine property*), 10
[results](#) (*inference.engines.MBIEngine property*), 8
[results](#) (*test_controller.DummyEngine property*), 23
[results](#) (*test_data.DummyEngine property*), 24
[Rule](#) (*class in inference.fuzzy*), 11
[Rule](#) (*class in inference.fuzzy.rules*), 14
[RuleParser](#) (*class in data.parsers*), 5
[rules](#) (*data.Data property*), 3
[rules](#) (*data.data.Data property*), 5
[run\(\)](#) (*ui.browser.FileBrowser method*), 18
[run\(\)](#) (*ui.chooser.Chooser method*), 18
[run\(\)](#) (*ui.Menu method*), 16
[run\(\)](#) (*ui.menu.Menu method*), 21

S

[set\(\)](#) (*ui.display.Display method*), 20
[show\(\)](#) (*ui.display.Display method*), 20
[state](#) (*ui.controller.Controller property*), 19
[state](#) (*ui.Menu property*), 16
[state](#) (*ui.menu.Menu property*), 21
[status_items](#) (*ui.Menu attribute*), 16
[status_items](#) (*ui.menu.Menu attribute*), 21
[store\(\)](#) (*data.Data method*), 3
[store\(\)](#) (*data.data.Data method*), 5
[style](#) (*ui.display.Display property*), 20
[styles](#) (*ui.display.Display attribute*), 20
[switch_engine\(\)](#) (*ui.controller.Controller method*), 19

T

[terms](#) (*inference.fuzzy.Variable property*), 12
[terms](#) (*inference.fuzzy.variables.Variable property*), 15
[test_ast](#)
 module, 23
[test_ast_complex_structure\(\)](#) (*in module test_ast*), 23
[test_ast_evaluation_array\(\)](#) (*in module test_ast*), 23
[test_ast_evaluation_scalar\(\)](#) (*in module test_ast*), 23
[test_calculate_discrepancy\(\)](#) (*in module test_evaluation*), 25
[test_calculate_discrepancy_empty\(\)](#) (*in module test_evaluation*), 25
[test_controller](#)
 module, 23

[test_controller_execute_inference\(\)](#) (*in module test_controller*), 23
[test_controller_generate_visualizations\(\)](#) (*in module test_controller*), 23
[test_controller_initialization\(\)](#) (*in module test_controller*), 23
[test_controller_load_data\(\)](#) (*in module test_controller*), 23
[test_controller_load_mappings\(\)](#) (*in module test_controller*), 23
[test_controller_load_rules\(\)](#) (*in module test_controller*), 24
[test_controller_load_variables\(\)](#) (*in module test_controller*), 24
[test_controller_switch_engine\(\)](#) (*in module test_controller*), 24
[test_data](#)
 module, 24
[test_engines](#)
 module, 25
[test_evaluation](#)
 module, 25
[test_fuzzy_engine\(\)](#) (*in module test_engines*), 25
[test_ingest_from_csv\(\)](#) (*in module test_data*), 24
[test_ingest_from_csv_failure\(\)](#) (*in module test_data*), 24
[test_map\(\)](#) (*in module test_data*), 24
[test_map_failure\(\)](#) (*in module test_data*), 24
[test_mbi_engine\(\)](#) (*in module test_engines*), 25
[test_parsers](#)
 module, 25
[test_rule_parser\(\)](#) (*in module test_parsers*), 25
[test_rule_parser_errors\(\)](#) (*in module test_parsers*), 26
[test_rules\(\)](#) (*in module test_data*), 24
[test_rules_failure\(\)](#) (*in module test_data*), 24
[test_save_results\(\)](#) (*in module test_data*), 25
[test_variable_parser\(\)](#) (*in module test_parsers*), 26
[test_vars\(\)](#) (*in module test_data*), 25
[test_vars_failure\(\)](#) (*in module test_data*), 25
[ThenNode](#) (*class in inference.fuzzy.rules*), 14
[tokens](#) (*data.parsers.RuleParser property*), 6
[type](#) (*ui.display.Display property*), 20

U

[ui](#)
 module, 15
[ui.browser](#)
 module, 17
[ui.chooser](#)
 module, 18
[ui.controller](#)
 module, 18
[ui.display](#)
 module, 20
[ui.menu](#)
 module, 20

`ui.progress`
 module, [22](#)
`UnaryOp` (in module `inference.fuzzy`), [11](#)
`UnaryOp` (in module `inference.fuzzy.ast`), [14](#)
`universe` (`inference.fuzzy.Variable` property), [12](#)
`universe` (`inference.fuzzy.variables.Variable` property), [15](#)
`up()` (`ui.browser.FileBrowser` method), [18](#)

V

`Variable` (class in `inference.fuzzy`), [11](#)
`Variable` (class in `inference.fuzzy.variables`), [15](#)
`VariableParser` (class in `data.parsers`), [6](#)
`variables` (`data.Data` property), [3](#)
`variables` (`data.data.Data` property), [5](#)
`visualization`
 module, [22](#)
`visualization.plotters`
 module, [22](#)