Transient Protection

Charge Amplifiers ft = 1/(2pi RC) = 18Hz

Duplicate R7 nd R8 value for G=5

Try 1uF cap at R38,R39,R37 and R36

Insensitive channel

Differential Amplifier G=8.2 was 2.5

Decommutator G=1 or -1 with switch closed

Inverting Filter low pass 12Hz 12dB oct

Buffer G=1.4

Sensitive channel

Differential Amplifier G=25

Decommutator G=1 or -1 with switch closed

Inverting Filter low pass 12Hz 12dB oct

Buffer G=1.4

Zero Relay

Motor and relay regulator

82 Hz two pulses per rotation about 2500 rpm

Close switch with logic HIGH

Motor ON/OFF

NAND

ANALOG SWITCH

Q = A NAND B

Truth Table

Input A	Input B	Output Q
0	0	1
0	1	1
1	0	1
1	1	0

31 Hz or 1850 RPM @ 3.5V

Real value for R2+TR1 is 243 ohm

Calculated value for R2+TR1 is 186 ohm

K=40

Rm = 10 ohm Im = 35mA Vm= 3.5V @ 1850RPM

TITLE: Field Mill Analog B/D	REV: 1.0
Company: Your Company	Sheet: 1/1
Date: 2022-10-05	Drawn By: Stefano_Trentini