



Código

```
#include <LiquidCrystal.h>
```

```
#define PIN_BUTTON 2
```

```
#define PIN_AUTOPLAY 1
```

```
#define PIN_READWRITE 10
```

```
#define PIN_CONTRAST 12
```

```
#define SPRITE_RUN1 1
```

```
#define SPRITE_RUN2 2
```

```
#define SPRITE_JUMP 3
```

```
#define SPRITE_JUMP_UPPER ' ' // Use the ' ' character for the head
```

```
#define SPRITE_JUMP_LOWER 4
```

```
#define SPRITE_TERRAIN_EMPTY ' ' // User the ' ' character
```

```
#define SPRITE_TERRAIN_SOLID 5
```

```
#define SPRITE_TERRAIN_SOLID_RIGHT 6
```

```
#define SPRITE_TERRAIN_SOLID_LEFT 7
```

```

#define HERO_HORIZONTAL_POSITION 1 // Horizontal position of hero on screen

#define TERRAIN_WIDTH 16
#define TERRAIN_EMPTY 0
#define TERRAIN_LOWER_BLOCK 1
#define TERRAIN_UPPER_BLOCK 2

#define HERO_POSITION_OFF 0 // Hero is invisible
#define HERO_POSITION_RUN_LOWER_1 1 // Hero is running on lower row (pose 1)
#define HERO_POSITION_RUN_LOWER_2 2 // (pose 2)

#define HERO_POSITION_JUMP_1 3 // Starting a jump
#define HERO_POSITION_JUMP_2 4 // Half-way up
#define HERO_POSITION_JUMP_3 5 // Jump is on upper row
#define HERO_POSITION_JUMP_4 6 // Jump is on upper row
#define HERO_POSITION_JUMP_5 7 // Jump is on upper row
#define HERO_POSITION_JUMP_6 8 // Jump is on upper row
#define HERO_POSITION_JUMP_7 9 // Half-way down
#define HERO_POSITION_JUMP_8 10 // About to land

#define HERO_POSITION_RUN_UPPER_1 11 // Hero is running on upper row (pose 1)
#define HERO_POSITION_RUN_UPPER_2 12 // (pose 2)

LiquidCrystal lcd(11, 9, 6, 5, 4, 3);
static char terrainUpper[TERRAIN_WIDTH + 1];
static char terrainLower[TERRAIN_WIDTH + 1];
static bool buttonPushed = false;

void initializeGraphics(){
    static byte graphics[] = {
        // Run position 1
        B01100,
        B01100,
        B00000,
        B01110,
        B11100,
        B01100,
        B11010,
        B10011,
        // Run position 2
        B01100,
        B01100,
        B00000,
        B01100,
        B01100,
        B01100,
        B01100,
        B01110,
        // Jump
        B01100,
        B01100,
        B00000,
        B11110,
        B01101,
    }
}

```

```

B11111,
B10000,
B00000,
// Jump lower
B11110,
B01101,
B11111,
B10000,
B00000,
B00000,
B00000,
B00000,
// Ground
B11111,
B11111,
B11111,
B11111,
B11111,
B11111,
B11111,
B11111,
// Ground right
B00011,
B00011,
B00011,
B00011,
B00011,
B00011,
B00011,
B00011,
// Ground left
B11000,
B11000,
B11000,
B11000,
B11000,
B11000,
B11000,
B11000,
};
int i;
// Skip using character 0, this allows lcd.print() to be used to
// quickly draw multiple characters
for (i = 0; i < 7; ++i) {
    lcd.createChar(i + 1, &graphics[i * 8]);
}
for (i = 0; i < TERRAIN_WIDTH; ++i) {
    terrainUpper[i] = SPRITE_TERRAIN_EMPTY;
    terrainLower[i] = SPRITE_TERRAIN_EMPTY;
}
}

// Slide the terrain to the left in half-character increments
//

```

```

void advanceTerrain(char* terrain, byte newTerrain){
    for (int i = 0; i < TERRAIN_WIDTH; ++i) {
        char current = terrain[i];
        char next = (i == TERRAIN_WIDTH-1) ? newTerrain : terrain[i+1];
        switch (current){
            case SPRITE_TERRAIN_EMPTY:
                terrain[i] = (next == SPRITE_TERRAIN_SOLID) ? SPRITE_TERRAIN_SOLID_RIGHT : SPRITE_TERRAIN_EMPTY;
                break;
            case SPRITE_TERRAIN_SOLID:
                terrain[i] = (next == SPRITE_TERRAIN_EMPTY) ? SPRITE_TERRAIN_SOLID_LEFT : SPRITE_TERRAIN_SOLID;
                break;
            case SPRITE_TERRAIN_SOLID_RIGHT:
                terrain[i] = SPRITE_TERRAIN_SOLID;
                break;
            case SPRITE_TERRAIN_SOLID_LEFT:
                terrain[i] = SPRITE_TERRAIN_EMPTY;
                break;
        }
    }
}

```

```

bool drawHero(byte position, char* terrainUpper, char* terrainLower, unsigned int score) {
    bool collide = false;
    char upperSave = terrainUpper[HERO_HORIZONTAL_POSITION];
    char lowerSave = terrainLower[HERO_HORIZONTAL_POSITION];
    byte upper, lower;
    switch (position) {
        case HERO_POSITION_OFF:
            upper = lower = SPRITE_TERRAIN_EMPTY;
            break;
        case HERO_POSITION_RUN_LOWER_1:
            upper = SPRITE_TERRAIN_EMPTY;
            lower = SPRITE_RUN1;
            break;
        case HERO_POSITION_RUN_LOWER_2:
            upper = SPRITE_TERRAIN_EMPTY;
            lower = SPRITE_RUN2;
            break;
        case HERO_POSITION_JUMP_1:
        case HERO_POSITION_JUMP_8:
            upper = SPRITE_TERRAIN_EMPTY;
            lower = SPRITE_JUMP;
            break;
        case HERO_POSITION_JUMP_2:
        case HERO_POSITION_JUMP_7:
            upper = SPRITE_JUMP_UPPER;
            lower = SPRITE_JUMP_LOWER;
            break;
        case HERO_POSITION_JUMP_3:
        case HERO_POSITION_JUMP_4:
        case HERO_POSITION_JUMP_5:
        case HERO_POSITION_JUMP_6:
            upper = SPRITE_JUMP;
            lower = SPRITE_TERRAIN_EMPTY;

```

```

    break;
case HERO_POSITION_RUN_UPPER_1:
    upper = SPRITE_RUN1;
    lower = SPRITE_TERRAIN_EMPTY;
    break;
case HERO_POSITION_RUN_UPPER_2:
    upper = SPRITE_RUN2;
    lower = SPRITE_TERRAIN_EMPTY;
    break;
}
if (upper != ' ') {
    terrainUpper[HERO_HORIZONTAL_POSITION] = upper;
    collide = (upperSave == SPRITE_TERRAIN_EMPTY) ? false : true;
}
if (lower != ' ') {
    terrainLower[HERO_HORIZONTAL_POSITION] = lower;
    collide |= (lowerSave == SPRITE_TERRAIN_EMPTY) ? false : true;
}

byte digits = (score > 9999) ? 5 : (score > 999) ? 4 : (score > 99) ? 3 : (score > 9) ? 2 : 1;

// Draw the scene
terrainUpper[TERRAIN_WIDTH] = '\0';
terrainLower[TERRAIN_WIDTH] = '\0';
char temp = terrainUpper[16-digits];
terrainUpper[16-digits] = '\0';
lcd.setCursor(0,0);
lcd.print(terrainUpper);
terrainUpper[16-digits] = temp;
lcd.setCursor(0,1);
lcd.print(terrainLower);

lcd.setCursor(16 - digits,0);
lcd.print(score);

terrainUpper[HERO_HORIZONTAL_POSITION] = upperSave;
terrainLower[HERO_HORIZONTAL_POSITION] = lowerSave;
return collide;
}

// Handle the button push as an interrupt
void buttonPush() {
    buttonPushed = true;
}

void setup(){
    pinMode(PIN_READWRITE, OUTPUT);
    digitalWrite(PIN_READWRITE, LOW);
    pinMode(PIN_CONTRAST, OUTPUT);
    digitalWrite(PIN_CONTRAST, LOW);
    pinMode(PIN_BUTTON, INPUT);
    digitalWrite(PIN_BUTTON, HIGH);
    pinMode(PIN_AUTOPLAY, OUTPUT);
    digitalWrite(PIN_AUTOPLAY, HIGH);

```

```

// Digital pin 2 maps to interrupt 0
attachInterrupt(0/*PIN_BUTTON*/, buttonPush, FALLING);

initializeGraphics();

lcd.begin(16, 2);
}

void loop(){
    static byte heroPos = HERO_POSITION_RUN_LOWER_1;
    static byte newTerrainType = TERRAIN_EMPTY;
    static byte newTerrainDuration = 1;
    static bool playing = false;
    static bool blink = false;
    static unsigned int distance = 0;

    if (!playing) {
        drawHero((blink) ? HERO_POSITION_OFF : heroPos, terrainUpper, terrainLower, distance >> 3);
        if (blink) {
            lcd.setCursor(0,0);
            lcd.print("Press Start");
        }
        delay(250);
        blink = !blink;
        if (buttonPushed) {
            initializeGraphics();
            heroPos = HERO_POSITION_RUN_LOWER_1;
            playing = true;
            buttonPushed = false;
            distance = 0;
        }
        return;
    }

    // Shift the terrain to the left
    advanceTerrain(terrainLower, newTerrainType == TERRAIN_LOWER_BLOCK ? SPRITE_TERRAIN_SOLID :
    SPRITE_TERRAIN_EMPTY);
    advanceTerrain(terrainUpper, newTerrainType == TERRAIN_UPPER_BLOCK ? SPRITE_TERRAIN_SOLID :
    SPRITE_TERRAIN_EMPTY);

    // Make new terrain to enter on the right
    if (--newTerrainDuration == 0) {
        if (newTerrainType == TERRAIN_EMPTY) {
            newTerrainType = (random(3) == 0) ? TERRAIN_UPPER_BLOCK : TERRAIN_LOWER_BLOCK;
            newTerrainDuration = 2 + random(10);
        } else {
            newTerrainType = TERRAIN_EMPTY;
            newTerrainDuration = 10 + random(10);
        }
    }

    if (buttonPushed) {
        if (heroPos <= HERO_POSITION_RUN_LOWER_2) heroPos = HERO_POSITION_JUMP_1;
    }
}

```

```

    buttonPushed = false;
}

if (drawHero(heroPos, terrainUpper, terrainLower, distance >> 3)) {
    playing = false; // The hero collided with something. Too bad.
} else {
    if (heroPos == HERO_POSITION_RUN_LOWER_2 || heroPos == HERO_POSITION_JUMP_8) {
        heroPos = HERO_POSITION_RUN_LOWER_1;
    } else if ((heroPos >= HERO_POSITION_JUMP_3 && heroPos <= HERO_POSITION_JUMP_5) &&
terrainLower[HERO_HORIZONTAL_POSITION] != SPRITE_TERRAIN_EMPTY) {
        heroPos = HERO_POSITION_RUN_UPPER_1;
    } else if (heroPos >= HERO_POSITION_RUN_UPPER_1 && terrainLower[HERO_HORIZONTAL_POSITION] ==
SPRITE_TERRAIN_EMPTY) {
        heroPos = HERO_POSITION_JUMP_5;
    } else if (heroPos == HERO_POSITION_RUN_UPPER_2) {
        heroPos = HERO_POSITION_RUN_UPPER_1;
    } else {
        ++heroPos;
    }
    ++distance;

    digitalWrite(PIN_AUTOPLAY, terrainLower[HERO_HORIZONTAL_POSITION + 2] == SPRITE_TERRAIN_EMPTY ? HIGH : LOW);
}
delay(50);
}

```