

Getting a crash log from your Tab5

This lets us see *why* the panadapter is rebooting. It takes about 2 minutes and doesn't need any developer tools installed.

What you need

- The Tab5, connected to a Windows PC via USB-C (the same port/cable you used to flash it)
- The file `capture_serial_log.ps1` — download it from the same place you got this guide (the release page, under "Assets")

Steps

1. **Save** `capture_serial_log.ps1` to your Desktop (or any folder).
2. **Right-click** the file → **Run with PowerShell**.

If you see a blue "Windows protected your PC" popup, click **More info** → **Run anyway**.

If PowerShell instead says scripts are disabled, open PowerShell, go to the folder where you saved the file, and run:

```
powershell -ExecutionPolicy Bypass -File capture_serial_log.ps1
```

3. The script lists COM ports and asks which one to use. If only one is listed, it picks it automatically. Otherwise pick the one that mentions "USB Serial" or "JTAG".
4. **Power-cycle the Tab5** — unplug and replug the USB-C cable (or hold the power button to turn it off, then on again). Watch it boot, show the panadapter screen, then reset.
5. Let it cycle through **2–3 reboots** (about 30–60 seconds), then press **Ctrl+C** in the PowerShell window to stop.
6. A file named `qmx_log_<date>_<time>.txt` appears in the same folder. **Send that file back** — that's all we need.

Notes

- The window will keep scrolling with text — that's normal, it's the device's debug output.
- If nothing appears at all, double-check the USB-C cable supports data (some cables are power-only) and try a different USB port.