

Generalization

Machine Learning II

Lecture 6







THE GEORGE
WASHINGTON
UNIVERSITY

WASHINGTON, DC





$$g(p) = 1 + \sin\left(\frac{i\pi}{4}p\right)$$

1-3-1 Network





Choice of Network Architecture

$$g(p) = 1 + \sin\left(\frac{6\pi}{4}p\right)$$





$$g(p) = 1 + \sin(\pi p)$$



$$\{\mathbf{p}_1, \mathbf{t}_1\}, \{\mathbf{p}_2, \mathbf{t}_2\}, \dots, \{\mathbf{p}_Q, \mathbf{t}_Q\}$$

$$g(p) = 1 + \sin\left(\frac{\pi}{4}p\right)$$


$$p = -2, -1.6, -1.2, \dots, 1.6, 2$$





- A cat that once sat on a hot stove will never again sit on a hot stove or on a cold one either.

Mark Twain

- The network input-output mapping is accurate for the training data and for test data never seen before.
- The network interpolates well.
- Poor generalization is caused by using a network that is too complex (too many neurons/parameters). To have the best performance we need to find the least complex network that can represent the data (Ockham's Razor).
- Find the simplest model that explains the data.



Extrapolation in 3-D



Measuring Generalization

- Part of the available data is set aside during the training process.
- After training, the network error on the test set is used as a measure of generalization ability.
- The test set must never be used in any way to train the network, or even to select one network from a group of candidate networks.
- The test set must be representative of all situations for which the network will be used.

Methods for Improving Generalization

- Pruning (removing neurons) until the performance is degraded.
- Growing (adding neurons) until the performance is adequate.
- Validation Methods
- Regularization

- Break up data into training, validation, and test sets.
- Use only the training set to compute gradients and determine weight updates.
- Compute the performance on the validation set at each iteration of training.
- Stop training when the performance on the validation set goes up for a specified number of iterations.
- Use the weights which achieved the lowest error on the validation set.

Early Stopping Example

