Stenopos · Cheatsheet

Memory-safe, taint-aware systems language — brace syntax, LLVM backend.

v1.0.0-beta.12 · **quick reference**
stenopos.github.io

01 CLI COMMANDS

`stenopos build <f>`	Compile `.sten` to a native binary
`stenopos run <f>`	Compile and run in one step
`stenopos check <f>`	Type-check only, no binary
`stenopos fmt <f>`	Format source (`--check` to verify)
`stenopos lint <f>`	Report style / correctness lints
`stenopos doc <f>`	Markdown API reference (`-o` to file)
`stenopos test <f>`	Run the file's `@test` functions
`stenopos new <n>`	Scaffold a new project
`stenopos emit-ir <f>`	Print Stenopos IR (debug)
`stenopos emit-llvm <f>`	Emit LLVM IR (`.ll`)
`stenopos clean`	Remove build artifacts
`stenopos version`	Print version
`stenopos help`	Print help

02 CLI OPTIONS

`-o <out>`	Output binary path
`--release`	Build with optimizations
`--verbose`	Print timing information
`--version`	Print version
`--help`	Print help

```
stenopos run hello.sten
stenopos build -o myapp --release main.sten
```

03 TYPES

`int32 int64`	Signed integers (fixed width)
`uint32 uint64`	Unsigned integers
`float32 float64`	IEEE 754 floats
`bool`	`true` / `false`
`str`	UTF-8 string (owned)
`T[N]`	Fixed-size array
`T[]`	Slice (borrowed view)
`List[T]`	Growable list
`HashMap[str,V]`	String-keyed hash map
`T?`	Nullable
`ptr[T]`	Raw pointer (`unsafe`)

```
int32 x = 42
float64 pi = 3.14159
str name = "Stenopos"
bool active = true
int32 flags = zeroed()  // zero-init
auto n = 42             // inferred
const int32 MAX = 100
```

Mutable by default — use `const` for immutability. No `let` / `mut`.

04 FUNCTIONS

```
func add(int32 a, int32 b) -> int32 {
    return a + b
}

// -> void is required
func greet(str name) -> void {
    println("Hello, {name}!")
}

// generics use [T], not <T>
func identity[T](T val) -> T {
    return val
}
```

Interpolation: `"total = {a + b}"`. Booleans interpolate as `true` / `false`.

05 OPERATORS

Arithmetic	`+ - * / %`
Comparison	`== != < <= > >=`
Logical	`&& || !`
Bitwise	`& | ^ ~ << >>`
Assign	`= += -= *= /= %=`
	`&= |= ^= <<= >>=`
Nullable	`?.  ??  !!`

Logical is `&&` `||` `!` only — no `and` / `or` / `not`. `?.` safe call · `??` default · `!!` assert non-null.

`+ - *` are **overflow-checked** (abort on overflow) — opt into modular math with `wrapping_add/sub/mul`.

06 CONTROL FLOW

```
if (x > 0) {
    // ...
} else if (x == 0) {
} else {
}

for (i in 0..10) { }   // inclusive
for (i in 0..<10) { }  // exclusive
for (item in list) { }
for (i, item in list) { }

while (cond) { }

match (color) {
    case Color.Red: handle_red()
    case Color.Blue: handle_blue()
    case _: handle_other()
}
```

One `for` loop — no `foreach`. Parens + braces required. Newline ends a statement (no semicolons).

07 COLLECTIONS

```
// List[T]
List[int32] xs = list_new()
xs.push(10)
int32 v = xs.get(0)    // checked
int32 f = xs.first()
int32 l = xs.last()
int32 t = xs.pop()      // rm+ret last
xs.sort()               // ascending
xs.reverse()
bool h = xs.contains(10)
int64 at = xs.index_of(10) // or -1
bool e = xs.is_empty()
int64 n = xs.len()
xs.clear()              // keep cap

// HashMap[str, V]
HashMap[str,int32] ages = map_new()
ages.insert("ada", 36)
int32 a = ages.get("ada")
bool k = ages.contains("ada")
```

Indexing is bounds-checked and aborts on out-of-range — no negative indexing; use `first()` / `last()`.

08 STRUCTS · CLASSES · ENUMS

```
// private by default; pub/protected
struct Point {
    float64 x
    float64 y
    pub func norm() -> float64 {
        return this.x*this.x + this.y*this.y
    }
}

// inheritance; `parent`, not `base`
class Dog : Animal {
    override func speak() -> void {
        parent.speak()
        println("Woof!")
    }
}

// backing type required
enum Color : int32 {
    Red = 0
    Green = 1
    Blue = 2
}
Point p = Point { x: 1.0, y: 2.0 }
```

`clone()` is a deep copy — modifying a clone never touches the original.

09 ERROR HANDLING

```
try {
    File f = open("data.txt")
} catch (IOError e) {
    log(e.message)
} finally {
    cleanup()
}

defer close(resource)  // scope cleanup
throw("something failed")
```

`try/catch/finally` only — there is no `?` operator.

10 CASTING & CONVERSIONS

```
float64 f = cast[float64](x)   // safe
int32 n = f.to_int32()         // method
const_cast[T](v)               // drop const
unsafe_cast[T](v)              // reinterpret
int64 sz = sizeof(Point)
```

11 NULLABLE TYPES

```
str? maybe = null
if (maybe != null) {
    println(maybe.len())  // narrowed
}
int32 len = maybe?.len() ?? 0
```

The compiler narrows `T?` to `T` after a `!= null` check.

12 CONCURRENCY

`spawn` `chan` `atomic` `mutex` `rwlock` `spinlock` `semaphore`

```
spawn worker()   // green thread (Hemerodrome)
chan[int32] ch = chan()
atomic[int64] c = atomic(0)
c.fetch_add(1)

mutex[int32] m = mutex(0)
with (m.guard()) {    // scoped lock
    // ... auto-unlocks
}
```

13 MEMORY — NOVA

Automatic, leak-free memory, **no GC**. Every value has an owner; heap buffers free at scope exit.

`Declared` `Owned` `Moved` `Borrowed` `Locked` `Freed`

```
unsafe {
    ptr[int32] p = &x
    int32 val = *p
}
```

The six states above appear in diagnostics.

14 ANNOTATIONS

`@ignore_discard`	Callers may drop the return value (results are must-use by default)
`@no_return`	Function never returns
`@packed @aligned(N)`	Struct layout control
`@inline @cold @hot`	Optimization hints
`@section("n")`	Place symbol in a linker section
`@deprecated("m")`	Emit a deprecation warning
`@sensitive`	Encrypt value in the binary
`@tainted @sink`	Taint tracking (+ `@sanitizer`)
`@test`	Mark a test function
`@repr("C")`	C-compatible layout

15 IMPORTS

```
import std.io.File
import std.collections.{HashMap, HashSet}
```

Use `import`, not `use`.