

Workbench Notes:

f(s) = 53.8 Hz

Q(ts) = 0.352

V(as) = 3.12 liters (0.11 cubic feet)

SPL = 82.8 dB SPL 1W/1m

Nominal Diam. = 0 mm (0 in.)

4-layer VC, extended pole piece, Aluminum former, 4mm Xmax, vented pole piece

Memory 1 Notes:

f(s) = 53.8 Hz

Q(ts) = 0.352

V(as) = 3.12 liters (0.11 cubic feet)

SPL = 82.8 dB SPL 1W/1m

Nominal Diam. = 0 mm (0 in.)

R(e) = 3.2 OhmsQ(es) = 0.397

Piston Diam. = 80 mm (3.15 in.)

SPL = 86.8 dB SPL 2.83 Vrms

C(ms) = 0.879 mm/N

R(e) = 3.2 Ohms

Q(es) = 0.397

Piston Diam. = 80 mm (3.15 in.)

SPL = 86.8 dB SPL 2.83 Vrms

C(ms) = 0.879 mm/N

4-layer VC, extended pole piece, Aluminum former, 4mm Xmax, vented pole piece

L(e) = 0.973 mH at 1kHz

Q(ms) = 3.14

BL = 5.21

n(0) = 0.117 %

 $\dot{M}(ms) = 9.95 \text{ grams}$

L(e) = 0.973 mH at 1 kHz

Q(ms) = 3.14BL = 5.21

n(0) = 0.117 %

 $\dot{M}(ms) = 9.95 \text{ grams}$

My Company

My Address My City State Zip

My Phone

Measurements by: My Name Title: My Title