

Step by Step: Stream Black Panda Data into SavvyCAN using a Linux Operating System

By Stephen Ranieri

Prerequisites:

- Python Downloaded
- Linux System
- SavvyCan

Step 1: Open Terminal on Linux Operating System

Run the following commands in the terminal in order to create and activate vcan0:

```
sudo modprobe vcan  
sudo ip link add dev vcan0 type vcan  
sudo ip link set up vcan0
```

To test to make sure it works you can run the following command:

```
ip link show vcan0
```

If it works correctly you should something similar to the following response:

```
Vcan0: <NOARP, UP, LOWER_UP> mtu ...
```

Step 2: Connect to the Black Panda and Forward Data

Plug in black panda to ADAS system via usb and car harness

Use the python file panda_to_vcan.py in order to start forwarding data to the vcan0 link

To do this open terminal and execute the following command inside the directory that the file is located in:

```
python panda_to_vcan.py
```

Step 3: Open SavvyCan and Connect to vcan0

Launch SavvyCan

Within SavvyCan:

Click connection > Open connection window > Add New Device Connection > QT SerialBus Devices (SocketCAN, PeakCan, etc)

Then underneath SerialBus Device Type drop down select **socket can**, in port select vcan0

Notes:

- Savvy CAN will not log unless panda_to_vcan.py is running
- Savvy CAN will only log data from the specific bus you are connected to
- Car Harness can only natively connect to the ADAS system
 - Future use case would be to connect to other ECUs
 - i.e Body Control Module (BCM)