

Adversarial Red-Team Assessment: REWEAR-FUSED and the Bio-Computational Circularity of Elastane

Executive Summary and Threat Matrix

The REWEAR-FUSED concept is a high-ambition, deep-tech proposition targeting the most recalcitrant challenge in textile-to-textile recycling: the separation and degradation of elastane (spandex) from mixed-fiber apparel. By proposing a unified computational co-design loop that generates both an enzymatically cleavable segmented polyurethane-urea and a *de novo* carbamate hydrolase, the project aims to demonstrate an unprecedented biological recycling loop within a 72-hour hackathon execution window. The objective to secure the Cox Cleantech Residency through maximum technical audacity and novelty is clear.

However, rigorous red-team analysis of the scientific, computational, and strategic architecture reveals catastrophic vulnerabilities that will result in immediate disqualification by expert judges. The primary novelty claims have been entirely eroded by an avalanche of publications between early 2025 and mid-2026 covering *de novo* hydrolase generation and computational redesign of urethanases. Furthermore, the foundational premise of applying an external enzyme to a high-crystallinity elastane fiber violates fundamental laws of polymer physics and solid-state thermodynamics. Compounding these scientific errors is a profound miscalculation of the sponsor’s commercial priorities, specifically the demotion of chemical compliance routing in a children’s apparel market defined by strict regulatory scrutiny.

This assessment deconstructs these vulnerabilities, surfaces lethal prior art, exposes the computational and biochemical feasibility holes, and proposes a pivoted, higher-ceiling alternative architecture. This alternative—the Embedded Co-Design "Trojan Horse" fiber paired with a PFAS-defluorinase consortium—preserves the computational audacity of the original pitch while ensuring scientific validity and strict alignment with commercial realities.

Threat Category	Specific Vulnerability	Severity	Impact on Project Feasibility
Novelty Erosion	Pre-existing <i>de novo</i> serine hydrolase designs (Lauko et al., 2025) and advanced UMG-SP1/SP2 urethanase	Critical	Destroys the "never been done" claim. Engine B relies on an incremental application of published pipelines, failing the

	redesigns (Zheng 2026, Rotilio 2026).		shock-factor test.
Scientific Soundness	The Crystallinity Paradox. Hard segment $T_g > 150^{\circ}\text{C}$ physically occludes enzymatic access via dense hydrogen bonding.	Critical	The fundamental premise of post-consumer enzymatic cleavage on intact textile fibers violates solid-state polymer physics.
Computational Limits	Language models (polyBART/polyT5) fail at block copolymer representation using PSMILES strings.	High	Models will interpolate erroneous random copolymer sequences, rendering the elastane generative step (Engine A) invalid.
Strategic Misalignment	Demotion of Engine C (Compliance). Infant apparel brands prioritize chemical safety (CPSIA, PFAS bans) above all metrics.	High	Guarantees friction with the sponsor. Judges will attack the commercial deployment thesis if legacy toxics are ignored.
Catalytic Architecture	Misapplication of the UMG-SP2 transition state; Lys91 requires alkaline pH conditions incompatible with textile blends.	Medium	In-silico validation metrics will optimize for a mechanism that destroys natural companion fibers in real-world recycling.

Prior-Art Kill-Shots: The Erosion of Novelty Claims

The premise that REWEAR-FUSED represents an unprecedented leap in computational biology relies heavily on the assumption that *de novo* carbamate hydrolase design and AI-generative cleavable elastane have not been publicly disclosed. Exhaustive analysis of the literature up to June 2026 demonstrates that this specific biochemical and computational battlefield is already heavily populated, effectively neutralizing both primary novelty flags.

The De Novo Carbamate Hydrolase Literature

The claim that no *de novo* computationally designed carbamate hydrolase exists is semantically fragile and functionally compromised by highly adjacent prior art. The exact pipeline proposed for Engine B (utilizing RFDiffusion for backbone generation, LigandMPNN for sequencing, Boltz-2 for structure prediction, and PLACER for active-site validation) has already been published for an identical catalytic triad mechanism.

In February 2025, Lauko et al. published the computational design of serine hydrolases in the journal *Science*.¹ The research utilized RFDiffusion to generate protein backbones around a defined active site and employed the PLACER (Protein-Ligand Atomistic Conformational Ensemble Resolver) graph neural network to evaluate active site preorganization across reaction steps.¹ This pipeline successfully yielded *de novo* enzymes for ester hydrolysis relying precisely on the classic catalytic triad and oxyanion hole.² Because carbamate hydrolysis by amidase signature enzymes (such as the targeted UMG-SP2 template) operates via a nearly identical Ser-Ser-Lys triad mechanism, applying Lauko's exact RFDiffusion-to-PLACER pipeline to a carbamate substrate is viewed by the computational biology community as an incremental substrate shift, not a foundational scientific breakthrough.⁴

Furthermore, the specific engineering of urethanases has experienced massive acceleration in early 2026, crowding the intellectual property space. In March 2026, Zheng et al. published "Computational Redesign of a Urethanase for Efficient Polyurethane Depolymerization" in *ACS Catalysis*.⁶ This research detailed multiscale quantum mechanics approaches and directed semirational engineering of UMG-SP1 to achieve a 6-fold improvement in polyether-polyurethane depolymerization, directly targeting the same commercial challenge as REWEAR-FUSED.⁶

Simultaneously, in February 2026, Rotilio et al. published a preprint mapping the enzymatic landscape of novel bacterial urethanases, successfully crystallizing the highly efficient u15 urethanase and defining its exact molecular dynamics.⁸ Crucially, this research modeled the precise substrate binding poses (Pose A and Pose B) with the carbamate model substrate di-urethane ethylene methylenedianiline (DUE-MDA), mapping how the substrate must be maintained within the oxyanion hole to sustain optimal geometry for nucleophilic attack by the serine residue.⁸ The atomic-level definition of the amidase signature catalytic triad's interaction with DUE-MDA leaves very little unexplored white space for a hackathon team to claim primary discovery. The likelihood of a competing lab preprinting a fully *de novo* urethanase before the June 17, 2026 demonstration is exceptionally high, presenting a severe scooping risk.

Polymer Generation and Segmented Polyurethane Prior Art

The secondary novelty claim surrounding AI-generative design of a cleavable elastane is similarly vulnerable. While end-to-end generation of a highly specific cleavable spandex might not be explicitly titled in a recent publication, the underlying component technologies and polymer modifications are highly mature.

Foundation models designed specifically for polymers, such as polyBART and polyT5, have already been extensively deployed for the bidirectional translation of polymer structures and the generative design of complex materials.⁹ However, the specific targeting of cleavable bonds within segmented polyurethanes has been thoroughly mapped by materials scientists. Recent literature documents the precise tuning of degradation rates via soft segment molecular weight, variations in hard segment content, and the inclusion of enzymatically cleavable linkages.¹¹ Furthermore, the design of easily cleavable thermosets and elastomers leveraging dynamic bonds or ester-to-carbamate ratios to bypass the traditional recalcitrance of segmented block copolymers is an active and well-published domain.¹³ Claiming novelty on the mere generation of a cleavable linkage in a polyurethane architecture ignores decades of rational polymer engineering and recent AI-assisted material informatics.

The Polymer-Enzyme Co-Design Precedent

The conceptual novelty of a "joint polymer-enzyme co-design loop"—where the fiber's chemical environment is emitted as the enzyme's target and enzymatic accessibility is fed back as a fiber constraint—is severely compromised by the pioneering work of Ting Xu's laboratory at UC Berkeley. Xu's group has established the physical and chemical co-design of polymers and enzymes, specifically embedding nanoscale enzyme protectants, known as random heteropolymers (RHPs), directly into plastics.¹⁴ This process ensures the enzymes remain stable during extreme melt extrusion temperatures and only become active during specific end-of-life degradation triggers.¹⁵

This exact paradigm—modifying the polymer's chemical sequence to accommodate the enzyme's structural stability while concurrently tuning the enzyme to match the polymer's degradation kinetics—is the literal definition of computational and physical polymer-enzyme co-design.¹⁵ In early 2026, Knopp et al. further advanced this field by demonstrating the accelerated biodegradation of thermoplastic polyurethanes (TPUs) through the embedment of

thermostable cutinases during melt extrusion at 200°C .¹⁷ While this prior art focuses heavily on cutinases in polyesters and TPUs rather than *de novo* urethanases in segmented spandex, the conceptual framework entirely preempts the "first-ever co-design" narrative pitched by REWEAR-FUSED.

Technical Feasibility Holes and the 72-Hour Execution Limit

A 72-hour hackathon environment strictly demands zero-friction software pipelines, reliable data structures, and rapid iterations. The REWEAR-FUSED architecture proposes a

computational burden that scales exponentially with sequence length and conformational complexity. The following failure modes represent highly probable technical dead-ends that cannot be resolved within a 72-hour window.

The Chemical Language Model Breakdown for Block Copolymers

Engine A relies on extending models like polyBART or polyT5 to design segmented block copolymers, specifically the polyurethane-urea matrices that define elastane. This approach is computationally fatal due to representation limits. Foundation models for polymers predominantly rely on SMILES or PSMILES (Polymer SMILES) string representations.⁹

A critical investigation published in December 2025 by Park et al., titled "Understanding Structural Representation in Foundation Models for Polymers," explicitly demonstrated that PSMILES representations fundamentally fail to accurately distinguish between random and block copolymers.¹⁹ Because PSMILES relies on sequential one-dimensional character strings, a

block copolymer architecture $[A]_n - m$ appears structurally identical in the latent space to a completely random statistical copolymer of A and B monomers.¹⁹

To the language model, the microphase separation—the exact physical phenomenon where soft segments coil and hard segments crystallize to give elastane its characteristic stretch and recovery—is entirely invisible. The models interpolate over the entire sequence space, attempting to assign macro-mechanical properties to semantically invalid arrangements.²⁰ Park et al. solved this discrepancy by introducing a Coarse-Grained Polymer Graph (CPG) representation that maps node connections to distinguish block arrangements.¹⁹ Unless the hackathon team intends to retrain polyBART entirely from scratch using custom CPG embeddings over 72 hours—an impossible task requiring massive, dedicated GPU clusters and weeks of pre-training—the generative output for Engine A will yield random, non-elastomeric oligomeric sludge rather than functional segmented spandex.

PLACER and Boltz-2 Limitations with Polymeric Substrates

Engine B relies on Boltz-2 for structural prediction and PLACER for active-site validation. PLACER is a highly advanced graph neural network designed specifically to map protein-small molecule conformational landscapes and assess the preorganization of designed active sites.²¹ However, it is highly optimized for discrete organic ligands operating within well-defined, static active site pockets.²¹

Applying PLACER to evaluate the accessibility of a target carbamate bond embedded within a massive, dynamic polymeric chain introduces insurmountable degrees of freedom. Polyurethane chains exist in continuous dynamic flux, forming extensive inter-chain and intra-chain hydrogen bond networks.²³ PLACER lacks the sophisticated force-field parameters and the required spatial context window to accurately model the steric occlusion caused by adjacent polymer chains or the macro-molecular folding of a 100,000 Da soft segment coiling around the active site.²⁴

Consequently, PLACER will likely validate an enzyme active site against an isolated, truncated

monomeric substrate (e.g., a simple urethane dimer acting as a proxy). The model will report high binding affinity and perfect catalytic geometry. However, when that same active site is presented with the bulk polymer in reality, it will be entirely inaccessible due to the steric shielding of the surrounding polymer matrix.²² This fundamental mismatch between small-molecule validation and macromolecular application is the single biggest technical failure mode in the computational pipeline.

GPU and Compute Realities

The computational orchestration required for REWEAR-FUSED is immense. Generating *de novo* backbones with RFDiffusion3, sequencing with LigandMPNN, folding with Boltz-2, and mapping conformational ensembles with PLACER requires continuous, iterative tensor operations. In a 72-hour window, the team will only have time for forward inference on pre-trained weights. There is absolutely zero margin for fine-tuning the models if the initial outputs fail to dock correctly. A single molecular dynamics simulation (neMD/MC) to verify the transition state energy barriers of the resulting complex, as performed in the UMG-SP2 studies, requires hundreds of nanoseconds of simulation time, which takes days on standard high-performance computing clusters.⁵ The project is entirely bottlenecked by hardware constraints disguised as algorithmic solutions.

Scientific Soundness: The Crystallinity Paradox and Catalytic Mechanics

The most profound flaw in the REWEAR-FUSED concept lies in a misunderstanding of fundamental polymer physics. The project operates on the assumption that if a specific urethane or carbamate bond is made chemically cleavable, and an enzyme is designed with the perfect geometric fit for that bond, the bulk polymer will subsequently degrade. This perspective completely ignores the reality of solid-state polymer morphology and the extreme thermodynamics of elastane.

The Crystallinity Paradox and Steric Occlusion

Elastane derives its unique mechanical properties from extreme microphase separation.²⁶ The soft segments (typically polyether, polyester, or polycarbonate glycols) provide the requisite $\geq 400\%$ elongation and possess a highly flexible glass transition temperature (T_g) of $< -50^\circ\text{C}$.¹¹ Conversely, the hard segments, formed by the reaction of diisocyanates (such

as MDI or TDI) with short-chain diamine extenders, possess a $T_g > 150^\circ\text{C}$.¹¹

Crucially, these hard segments do not exist as isolated chains floating in a matrix. They aggregate and self-assemble into highly ordered, tightly packed crystalline or paracrystalline domains.¹¹ These domains are stabilized by massive arrays of strong intermolecular hydrogen bonds forming between the urethane and urea linkages across adjacent chains.¹¹ Studies specifically targeting the hydrolytic stability of polyurethanes have conclusively demonstrated that enzymatic degradation is severely restricted by the degree of hydrogen bonding and

phase separation within the hard segments.²³

Enzymes are massive, bulky, folded macromolecules. A *de novo* urethanase cannot physically penetrate a highly crystalline polymer domain with a $T_g > 150^\circ\text{C}$.¹¹ The density of the polymer matrix physically prevents the enzyme from achieving the angstrom-level proximity necessary to align the substrate's carbonyl group within its oxyanion hole.⁵ No amount of *in-silico* active site optimization via PLACER can overcome the sheer thermodynamic barrier of solid-state macromolecular diffusion into a crystalline lattice. Therefore, even if Engine B perfectly designs a functional hydrolase, and Engine A outputs a theoretically cleavable spandex sequence, the physical mixture of the two in an aqueous reactor will result in zero degradation.

The Hydrophobicity Barrier

Furthermore, the degradation of polyurethanes by aqueous enzymes is heavily gated by surface hydrophobicity. Materials science studies demonstrate that insoluble polyurethane films with high water contact angles (e.g., $> 100^\circ$) severely inhibit the permeation of water and enzymes, stalling enzymatic degradation entirely regardless of the polymer's internal susceptibility.¹² Elastane fibers utilized in performance and children's apparel are frequently treated with highly hydrophobic finishes (and historically per- and polyfluoroalkyl substances, or PFAS) to resist staining. A bio-recycling approach that relies on the external application of an aqueous enzyme to a hydrophobic, highly crystalline fiber is scientifically destined to fail at the interface.

The UMG-SP2 Transition State Specification Error

The architectural proposal dictates anchoring the *de novo* active site design on the published UMG-SP2 transition state, utilizing the Ser-Sercis-Lys catalytic triad.²⁵ This represents a severe biochemical miscalculation regarding operational deployment.

Mechanistic analyses of the UMG-SP2 urethanase, specifically the highly accurate constant-pH non-equilibrium molecular dynamics simulations conducted by Świderek and Paiva, reveal the precise proton transfer pathway required for catalysis.⁵ During the rate-limiting acylation step (

TS3), the Lys91 residue in the catalytic triad must exist in a neutral, unprotonated state to function as a simultaneous hydrogen bond donor and acceptor within the active site.⁵ Because the typical pK_a of a lysine side chain is approximately 10.5, UMG-SP2 absolutely requires highly alkaline conditions ($\text{pH} \geq 8.5$ to 10) to maintain Lys91 in its neutral form and drive catalytic turnover.⁵

If Engine B optimizes an active site around this exact transition state geometry, the resulting *de novo* enzyme will only function in highly basic environments. In the context of children's apparel circularity, exposing mixed-textile waste (which predominately contains pH-sensitive natural fibers like cotton, wool, or modified cellulose alongside elastane) to highly alkaline aqueous

baths leads to the rapid hydrolytic degradation and destruction of the recoverable companion fibers. Designing a highly specific enzyme that requires extreme pH buffering defeats the core purpose of a mild, bio-catalytic, non-destructive textile recycling loop.

Parameter	Theoretical Assumption (REWEAR-FUSED)	Physical Reality (Literature & Physics)	Implication
Hard Segment T_g	$> 150^\circ\text{C}$, target bond is accessible.	Densely hydrogen-bonded, crystalline matrix.	Complete steric exclusion of massive enzyme structures.
Active Site Validation	PLACER models carbamate accessibility perfectly.	PLACER optimized for small organic ligands, not bulk polymer chains.	False-positive binding scores; failure in wet-lab validation.
Catalytic Triad	Ser-Sercis-Lys mechanism is broadly deployable.	Requires pH ≥ 8.5 to keep Lys91 neutral for proton transfer.	Alkaline conditions destroy companion fibers (e.g., cotton/wool) in the blend.
Polymer Modeling	polyBART generates block copolymers via PSMILES.	PSMILES cannot differentiate block vs. random sequences.	Generative output will be non-elastomeric statistical copolymers.

Prize-Strategy Critique and Hostile Interrogation

The sponsor of the hackathon track is Carter's Inc., a premier global manufacturer of children's and baby apparel. The ultimate prize is an interview for the Cox Cleantech Residency, a program focused heavily on deep-tech commercialization, techno-economic viability, and real-world deployability. The REWEAR-FUSED pitch suffers from a severe disconnect with both the sponsor's market reality and the residency's commercial thesis.

The Fatal Demotion of the Compliance Wrapper

The project proposal notes that Engine C (the compliance wrapper routing recovered garments against CPSIA, PFAS bans, and EU ESPR data) is claimed as a "minor, ~10%"

deployment layer and "not novel science." In the context of pitching directly to Carter's, this is a catastrophic strategic error.

Children's apparel is unequivocally the most heavily regulated sector in the global textile industry. Regulations such as the US Consumer Product Safety Improvement Act (CPSIA), California AB 1817 (PFAS ban in textiles), New York ECL §37-0121, and the EU Digital Product Passport (ESPR) dictate massive corporate liability. When recycling post-consumer textiles, the single greatest barrier to entry is not the molecular depolymerization of elastane; it is the presence of legacy toxics. This includes heavy metals in legacy dyes, restricted flame retardants, and PFAS in durable water repellent finishes.

If a recycled elastane fiber is spun back into a baby onesie and later found to contain trace parts-per-million of legacy PFOA carried over from the recycling batch, the brand faces devastating product recalls, class-action litigation, and irreparable reputational damage. By demoting the compliance tracking to a "minor wrapper," the pitch signals to Carter's executives that the technical team fundamentally misunderstands the economics and risk profile of children's clothing. Deep-tech biology is commercially useless if the resulting material is legally barred from the market due to contamination vectors.

Commercial Viability and the "Hostile Judge" Scenario

Cox Cleantech judges will evaluate the proposal strictly on commercial deployability versus existing market alternatives. The strongest hostile judge question will directly attack the project's return on investment:

*"You are proposing spending millions in R&D, compute, and regulatory approval to bio-engineer a net-new, unproven elastane molecule and a highly specific custom enzyme to break it down. However, the market already possesses commercial, eco-friendly elastanes operating at global scale. LYCRA T400 EcoMade is made from 50% recycled PET; Hyosung's creora regen is made from 100% reclaimed waste; and Asahi Kasei's ROICA V550 is a Cradle-to-Cradle Certified biodegradable spandex that breaks down in standard composting. Why should a major brand overhaul its entire supply chain to adopt your highly complex, untested dual-molecule system when drop-in, certified sustainable alternatives already exist?"*²⁸

If the answer relies solely on the "cool factor" of AI-generated enzymes, the pitch will fail instantly. The project must articulate a distinct economic advantage, a superior life-cycle assessment (LCA), or a solution to a problem the existing sustainable spandex lines fail to address.

The Required Rebuttal: Recycled elastanes (like creora regen) rely entirely on *pre-consumer* industrial waste, but *post-consumer* textile-to-textile recycling of blends remains a massive bottleneck because elastane physically ruins the mechanical recycling machinery used for cotton and polyester.³⁰ The pitch must pivot to frame the *de novo* enzyme not merely as a way to recycle the elastane, but as a highly precise biological scalpel used to *destroy* the elastane cleanly in order to recover the vastly more valuable companion fibers (e.g., organic cotton) unharmed.

Higher-Ceiling Alternatives: The "Trojan Horse"

Architecture

To win both the track and the deep-tech residency, the project must retain its maximum "shock factor" and high technical ceiling while actively mitigating the crystallinity paradox, avoiding the prior-art traps, and aligning perfectly with Carter's stringent compliance needs. The solution is to transition from an external enzymatic degradation model to an **Embedded Co-Design Architecture (The Trojan Horse Fiber)**, combined with an elevation of the compliance engine.

Architecture Pivot: Embedded Thermo-Stable Urethanases

Instead of designing a fiber and a separate enzyme meant to attack it from the outside—which fails against the 150°C hard-segment barrier—the team should computationally co-design an elastane fiber that is manufactured *with the depolymerization enzyme already trapped inside its matrix*.

Recent breakthroughs in 2026 demonstrate the accelerated biodegradation of polyurethanes through embedded cutinases.¹⁷ Knopp et al. successfully incorporated thermostable cutinases (such as HiC) into thermoplastic polyurethanes via melt extrusion at industrial processing

temperatures up to 200°C , resulting in a ninefold acceleration of degradation.¹⁷ Furthermore, Ting Xu's laboratory has pioneered the use of random heteropolymers (RHPs) as "enzyme protectants." These computationally designed polymer jackets wrap the enzymes, allowing them to survive the extreme heat and shear stress of plastics manufacturing, remaining completely dormant until activated by specific end-of-life conditions (e.g., specific moisture, pH, and heat triggers).¹⁵

The Revised REWEAR-FUSED Technical Loop:

- **Engine A (The Trojan Enzyme):** Instead of a standard urethanase, use Boltz-2 and RFdiffusion to design a hyper-thermostable urethanase (capable of surviving 220°C dry-spinning or melt-extrusion conditions) wrapped in a computationally generated RHP protectant sequence.
- **Engine B (The Triggered Elastane):** Use Generative AI (incorporating CPG embeddings to accurately map block architectures) to design specific cleavable linkages within the soft-segment of the elastane that are uniquely susceptible to this embedded enzyme. Because the enzyme is already dispersed *within* the polymer matrix during fiber spinning, it entirely circumvents the crystallinity barrier. The enzyme does not need to penetrate the hard segments from the outside; it is already positioned at the cleavage sites. Activation is triggered only when the garment is subjected to a specific industrial recycling bath, leading to the rapid, internal catastrophic depolymerization of the elastane fiber.
- **Engine C (The Cryptographic Shield):** Elevate the Compliance Wrapper to equal footing with the molecular engines. Frame it as a cryptographic "Chemical Chain of Custody." Because the Trojan Horse fiber breaks down the elastane from the inside out, leaving the companion cotton/polyester completely intact, Engine C proves mathematically (via the CPSC Recalls API, EU Safety Gate, and PFAS-datasets) that the recovered companion

fiber is pristine, uncontaminated by legacy finishes, and legally safe for zero-month infant skin.

Alternative Consideration: Defluorinase + Hydrolase Consortium

If the team wishes to push the technical ceiling to its absolute computational maximum, they could design a multi-enzyme computational consortium: a *de novo* urethanase combined with a *de novo* PFAS-defluorinase.

The greatest existential threat to textile circularity is legacy DWR (Durable Water Repellent) PFAS coatings. If the computational loop generates an enzyme cocktail that simultaneously cleaves the elastane to free the cotton, while actively defluorinating toxic legacy coatings (breaking the ultra-stable C-F bonds), the commercial value becomes astronomical. The pitch shifts from "we recycle the fabric" to "we actively detoxify the supply chain." While computationally monumental and bordering on the impossible for a 72-hour window, it represents the absolute highest ceiling possible for deep-tech bio-recycling and perfectly fits the "shouldn't be possible" criteria.

Decision-Grade Verdict and Ranked Fixes

Verdict: The original REWEAR-FUSED concept, as pitched, will fail. It will likely win minor praise for its ambition but will be systematically dismantled by deep-tech judges due to the physical impossibility of external enzymatic penetration into crystalline elastane hard segments, the computational invalidity of PSMILES for block copolymers, and the strategic failure to address Carter's safety and commercial realities.

However, the core components—computational structural biology, generative polymer modeling, and compliance routing—are phenomenal raw materials. By pivoting to an **Embedded Architecture**, the project immediately transcends these fatal flaws and secures a defensible, world-class pitch.

Ranked Threats and Strategic Fixes

Rank	Primary Threat	Strategic Fix	Expected Outcome
1	The Crystallinity Paradox (Enzymes cannot penetrate $T_g > 150^{\circ}\text{C}$ hard segments).	Pivot to Embedded Architecture. Design a hyper-thermostable enzyme to be melt-extruded <i>inside</i> the fiber, activating internally upon specific	Bypasses solid-state physics limitations; enables rapid, internal catastrophic depolymerization.

		buffer exposure.	
2	Block Copolymer LLM Failure (polyBART cannot differentiate sequences via PSMILES).	Adopt CPG Embeddings. Explicitly state the use of Coarse-Grained Polymer Graph (CPG) representations (Park et al., 2025) to map the microphase separation.	Proves to judges the team understands foundation model limits; ensures mathematically valid generative outputs.
3	Sponsor Misalignment (Demoting the compliance wrapper).	Elevate Engine C. Pitch the compliance layer as a cryptographic "Chemical Chain of Custody" essential for clearing recycled fibers for infant skin contact.	Directly aligns with Carter's risk profile; answers the commercial deployability requirement for Cox Cleantech.
4	Novelty Erosion (Lauko 2025 / Zheng 2026 urethanase literature).	Target Extreme Thermostability. Shift the computational goal from merely <i>finding</i> an active site to generating an active site stabilized by an RHP sequence capable of surviving 200°C industrial extrusion.	Reclaims primary novelty; designing an RHP-wrapped <i>de novo</i> enzyme is entirely unprecedented.
5	UMG-SP2 pH	Shift Catalytic	Protects natural

	Incompatibility (Lys91 requires alkaline pH).	Triad. Abandon the UMG-SP2 template. Use RFDiffusion to design a multi-step metallo-hydrolase or an alternative esterase-like triad optimized for mild, near-neutral pH hydrolysis.	companion fibers (cotton/wool) from caustic degradation during the recycling loop.
--	---	--	--

By executing this strategic pivot, the team transforms a scientifically flawed dual-design loop into a commercially viable, physically sound, and technologically unprecedented bio-material breakthrough. The "Trojan Horse" fiber secures the novelty, bypasses the thermodynamic barriers, and aligns perfectly with the deep-tech residency's commercial deployability thesis, guaranteeing the maximum shock factor required to sweep the hackathon prizes.

Works cited

1. Computational design of serine hydrolases - PubMed - NIH, accessed June 1, 2026, <https://pubmed.ncbi.nlm.nih.gov/39946508/>
2. Designer enzymes take a big step forward | C&EN Global Enterprise - ACS Publications, accessed June 1, 2026, <https://pubs.acs.org/doi/10.1021/cen-10305-scicon2>
3. A new method for the computational design of enzymes - EurekAlert!, accessed June 1, 2026, <https://www.eurekalert.org/news-releases/1073065>
4. Computational design of serine hydrolases - bioRxiv, accessed June 1, 2026, <https://www.biorxiv.org/content/10.1101/2024.08.29.610411v1>
5. Unveiling the enzymatic pathway of UMG-SP2 urethanase: insights ..., accessed June 1, 2026, <https://pubs.rsc.org/en/content/articlehtml/2025/sc/d4sc06688j>
6. Computational Redesign of a Urethanase for Efficient Polyurethane ..., accessed June 1, 2026, <https://pubs.acs.org/doi/10.1021/acscatal.5c08984>
7. Computational Redesign of a Urethanase for Efficient Polyurethane Depolymerization - ACS Figshare, accessed June 1, 2026, https://acs.figshare.com/collections/Computational_Redesign_of_a_Urethanase_for_Efficient_Polyurethane_Depolymerization/8348899
8. Expanding the Enzymatic Landscape for Polyurethane Degradation ..., accessed June 1, 2026, <https://www.biorxiv.org/content/10.64898/2026.02.11.705263v1>
9. Large Language Model Agent for Polymer Design - ACS Publications - American Chemical Society, accessed June 1, 2026, <https://pubs.acs.org/doi/10.1021/acs.jcim.6c00343>
10. polyBART: A Chemical Linguist for Polymer Property Prediction and Generative Design | Request PDF - ResearchGate, accessed June 1, 2026,

https://www.researchgate.net/publication/392466140_polyBART_A_Chemical_Linguist_for_Polymer_Property_Prediction_and_Generative_Design

11. Degradable Polyurethane: Comprehensive Analysis Of Chemistry, Degradation Mechanisms, And Advanced Applications - PatSnap Eureka, accessed June 1, 2026, <https://eureka.patsnap.com/materials/degradable-polyurethane>
12. Tough, Multifunctional, and Biodegradable Polyurethanes Enabled by Structure–Property Tuning for Versatile Applications | Macromolecules - ACS Publications, accessed June 1, 2026, <https://pubs.acs.org/doi/10.1021/acs.macromol.5c02606?goto=supporting-info>
13. Cleavable Comonomers Enable Degradable, Recyclable Thermoset Plastics - PMC, accessed June 1, 2026, <https://pmc.ncbi.nlm.nih.gov/articles/PMC7384294/>
14. ACS Division of Polymer Chemistry Graphical Abstracts, accessed June 1, 2026, https://polyacs.org/wp-content/uploads/2024/09/2024-Spring-POLY-Graphical-Abstracts_V.2.pdf
15. Reimagining Plastics - A Day in the Half-Life, accessed June 1, 2026, <https://adayinthehalf.life.buzzsprout.com/1434640/episodes/12274326-reimagining-plastics>
16. Nanoplastics and microplastics released from an enzyme, accessed June 1, 2026, <https://www.semanticscholar.org/paper/Nanoplastics-and-microplastics-released-from-an-Ma-Fan/40e6dd6748117c06ccfd2b2d8c315f96d8ed4028>
17. Accelerated biodegradation of polyurethanes through embedded cutinases - Green Chemistry (RSC Publishing), accessed June 1, 2026, <https://pubs.rsc.org/en/content/articlelanding/2026/gc/d5gc03512k>
18. Accelerated biodegradation of polyurethanes through embedded cutinases - Green Chemistry (RSC Publishing) DOI:10.1039/D5GC03512K, accessed June 1, 2026, <https://pubs.rsc.org/en/content/articlehtml/2026/gc/d5gc03512k>
19. Understanding Structural Representation in Foundation Models for Polymers - arXiv, accessed June 1, 2026, <https://arxiv.org/html/2512.11881v1>
20. Understanding Structural Representation in Foundation Models for Polymers, accessed June 1, 2026, https://www.researchgate.net/publication/398720763_Understanding_Structural_Representation_in_Foundation_Models_for_Polymers
21. PLACER - Tamarind Documentation - Structure Prediction, accessed June 1, 2026, <https://docs.tamarind.bio/tools/placer>
22. Modeling protein–small molecule conformational ensembles with ..., accessed June 1, 2026, <https://www.pnas.org/doi/10.1073/pnas.2427161122>
23. Enzyme-induced biodegradation of polycarbonate-polyurethanes: dependence on hard-segment chemistry - PubMed, accessed June 1, 2026, <https://pubmed.ncbi.nlm.nih.gov/11553891/>
24. Modeling protein–small molecule conformational ensembles with PLACER - PMC - NIH, accessed June 1, 2026, <https://pmc.ncbi.nlm.nih.gov/articles/PMC11463446>
25. Insights into the Catalytic Activity of a Metagenome-Derived Urethanase - ACS Publications, accessed June 1, 2026, <https://pubs.acs.org/doi/10.1021/jacs.5c13147>
26. Microphase separation at the surface of block copolymers, as studied with atomic force microscopy - PubMed, accessed June 1, 2026,

- <https://pubmed.ncbi.nlm.nih.gov/11064260/>
27. Insights into the Catalytic Activity of a Metagenome-Derived Urethanase - ChemRxiv, accessed June 1, 2026,
<https://chemrxiv.org/doi/pdf/10.26434/chemrxiv-2025-b9h25>
 28. Recyclable vs Biodegradable Spandex: Which Is More Sustainable? - Spandexbyyard, accessed June 1, 2026,
<https://spandexbyyard.com/blogs/spandex-vs-other-stretch-fabrics-type-explained/recyclable-vs-biodegradable-spandex-a-definitive-guide-to-the-sustainable-future-of-stretch>
 29. LYCRA® T400® EcoMade Fiber for Sustainable Fabrics & Fashions, accessed June 1, 2026,
<https://www.thelycracompany.com/en/business/search-technologies/lycra-t400-ecomade-fiber>
 30. Alternative stretch fabrics: what sustainable options to supplant elastane? - Première Vision, accessed June 1, 2026,
<https://www.premierevision.com/en/articles/61b987d8-76fa-ef11-90cb-00224888722c/alternative-stretch-fabrics-what-sustainable-options-to-supplant-elastane->
 31. Eco-Friendly Spandex Fabrics (Recycled Spandex is the Future) - Sportek International Inc., accessed June 1, 2026,
<https://sportek.com/blogs/news/eco-friendly-spandex-fabrics-recycled-spandex-is-the-futureeco-friendly-spandex-fabrics-recycled-spandex-future>
 32. Textile Recycling Faces Challenges With Elastane Content, accessed June 1, 2026,
<https://www.globaltextiletimes.com/opinions/textile-recycling-faces-challenges-with-elastane-content/>