


- 24** A vehicle carries a microwave transmitter that emits microwaves of a constant frequency. A stationary observer has a microwave receiver.

The vehicle moves directly towards the observer at constant speed. The observer detects microwaves of frequency F_o .

The vehicle then accelerates, still moving towards the observer, travels at higher steady speed for a time and then decelerates until it stops.

What is the variation in the frequency of the microwaves that are detected by the observer?

- A** The observed frequency will fall, then remain steady then return to the frequency F_o .
 - B** The observed frequency will fall, then remain steady then rise to a higher frequency than F_o .
 - C** The observed frequency will rise, then remain steady then fall to a lower frequency than F_o .
 - D** The observed frequency will rise, then remain steady then return to the frequency F_o .
- 25** The diagram shows a cathode-ray oscilloscope display of an electromagnetic wave.



The time base setting is $0.20 \mu\text{s cm}^{-1}$.

Which statement is correct?

- A** The frequency of the wave is 2.5 MHz and it lies in the microwave region of the electromagnetic spectrum.
 - B** The frequency of the wave is 2.5 MHz and it lies in the radio-wave region of the electromagnetic spectrum.
 - C** The frequency of the wave is 5.0 MHz and it lies in the microwave region of the electromagnetic spectrum.
 - D** The frequency of the wave is 5.0 MHz and it lies in the radio-wave region of the electromagnetic spectrum.
- 26** In a double-slit interference experiment, light of frequency $6.0 \times 10^{14} \text{ Hz}$ is incident on a pair of slits. Bright fringes that are 3.0 mm apart are observed on a screen some distance away.

What is the separation of the bright fringes when the frequency of the light is changed to $5.0 \times 10^{14} \text{ Hz}$?

- A** 1.8 mm **B** 2.5 mm **C** 3.0 mm **D** 3.6 mm