

CS 320 Homework 4 in Scheme

Name _____

Complete these exercises and turn in a hard copy of your solutions in class.

Writing and Evaluating Scheme expressions

1. Give a Scheme expression for a list containing the values such that the number 7 is the first element, the symbol `a` the second, the number `-12` the third, and the symbol `???` the fourth.

2. Scheme has a function `symbol?` that takes one argument and returns `#t` or `#f` depending on whether the argument is a symbol or not. Give a Scheme expression that determines whether the first element of a three-element list is a symbol. (The result of the evaluation should be `#t`.)

3. Suppose that into the Scheme evaluator we enter the definition: `(define dozen 12)`
Give the value of the Scheme expression: `(number? dozen)`

4. Give two ways to write a Scheme expression of which the value is a one-element list with the empty list as its element.

5. Give a Scheme definition that will determine the sum of 30, 31, 30, 15 and bind the identifier `days-in-semester` to this sum. Be as concise as possible.

6. Evaluate this Scheme statement. (Do this by hand first; then check your answer by running it.)

```
((lambda (x) (+ x x)) 4)
```

7. Evaluate these Scheme statements. (Do this by hand first; then check your answer by running it.)

```
(define reverse-subtract  
  (lambda (x y)  
    (- y x)))  
(reverse-subtract 7 10)
```

8. These expressions form repetitions. Trace by hand the following loop and show the set of two lists it produces (in other words, the result will be lists within a list).

```
(let loop
  ((numbers '(3 -2 1 6 -5))
   (nonneg '())
   (neg '()))
  (cond ((null? numbers)
        (list nonneg neg))
        ((>= (car numbers) 0)
         (loop (cdr numbers)
               (cons (car numbers) nonneg)
               neg))
        (else
         (loop (cdr numbers)
               nonneg
               (cons (car numbers) neg))))))
```

Output:

9. Here is a function called "deleteall" that strips out all occurrences of a value in a given list. The call to the function: (deleteall 0 '(4 0 3 0 2 0 1)) results in the list (4 3 2 1).

```
(define (deleteall atm list)
  (cond
    ((NULL? list) '())
    ((EQ? atm (CAR list)) (deleteall atm (CDR list)))
    (ELSE (CONS (CAR list) (deleteall atm (CDR list)))))
  ))
```

Write a recursive Scheme procedure called "tally" that counts the number of occurrences of a value in a given list. Do not use a counter variable, but let the function result in the desired count. For example, the value of (tally 0 '(4 0 3 0 2 0 1)) will be 3. The procedure will be very similar to deleteall.

Lexical Binding (internal definitions)

The binding construct `let` defines Scheme block structure. In a `let` expression, the initial values are computed before any of the variables become bound. Evaluate these expressions by hand showing the effects of lexical binding in Scheme.

A.

```
(let ((x 2) (y 3))
  (* x y))
```

Output:

B.

```
(let ((x 2) (y 3))
  (let ((foo (lambda (z) (+ x y z)))
        (x 7))
    ; call foo
    (foo 4)))
```

Output: