Bread (Sprint 3) â Installation Manual (PDF source)

This markdown file is the source for ‘INSTALLATION_MANUAL.pdf‘. It is also included in the submission zip for convenience.

System requirements

- **OS**: any OS that supports Docker (Linux/macOS/Windows)
- **Docker**: 24+ recommended
- **Docker Compose**: Docker Compose plugin (v2)
- **Browser**: Chrome/Firefox (latest)
- **Disk**: enough space for Docker images + volumes (Postgres/MinIO)
- **Ports**
  - ‘8080‘ (default): gateway (frontend + API proxy)
  - ‘5173‘ (optional): ‘frontend-dev‘ Vite dev server
  - ‘15432‘ (optional): Postgres port mapping for local debugging
  - ‘15672‘ (optional): RabbitMQ management UI
  - ‘9001‘ (optional): MinIO console

Repository contents (what is included)

The submission zip contains:

- ‘docker-compose.yml‘
- ‘backend/‘ (Django)
- ‘frontend/‘ (Vite/React)
- ‘nginx/‘ (reverse proxy gateway)
- ‘tests/‘ (unit + integration helpers)
- ‘README.md‘, ‘TESTING.md‘, ‘.env.example‘, and this manual

The zip does **not** include:

- ‘.git/‘
- ‘.env‘ (real secrets)
- ‘node_modules/‘, ‘.venv/‘, ‘__pycache__/‘, build caches, Docker volumes

Environment setup

1) Create your local environment file:

‘‘‘bash
cp .env.example .env
‘‘‘

2) Adjust variables in ‘.env‘ if needed.

Required for local Docker run (dev defaults provided in ‘.env.example‘):
- ‘DJANGO_SECRET_KEY‘
- Postgres: ‘PG_DB‘, ‘PG_USER‘, ‘PG_PASSWORD‘
- RabbitMQ: ‘MQ_USER‘, ‘MQ_PASS‘
- MinIO: ‘S3_ACCESS_KEY‘, ‘S3_SECRET_KEY‘, ‘S3_BUCKET‘
- ‘PUBLIC_MEDIA_URL‘
- ‘GATEWAY_PORT‘

Optional (can be blank):
- Gmail OAuth variables (‘GMAIL_*‘)
- DeepSeek/LLM variables (‘DEEPSEEK_*‘)

Build & run with Docker Compose

From the project root (same folder as ‘docker-compose.yml‘):

Build images:

‘‘‘bash
docker compose build
‘‘‘

Start the stack:

‘‘‘bash
docker compose up -d
‘‘‘

Check status:

‘‘‘bash
docker compose ps
docker compose logs -f
‘‘‘

Stop:

‘‘‘bash
docker compose down
‘‘‘

To remove data volumes (fresh database / fresh MinIO):

‘‘‘bash
docker compose down -v
‘‘‘

Database setup (migrations / seed)

- The backend container runs migrations at startup.
- If you need to run migrations manually:

‘‘‘bash
docker compose exec backend python manage.py migrate
‘‘‘

How to access the system

- **Main entry (frontend + API gateway)**: ‘http://localhost:8080‘ (or ‘http://localhost:${GATEWAY_PORT}‘)

- **Backend API (via gateway)**: ‘http://localhost:8080/api/...‘

Notes:
- The gateway serves the frontend and proxies ‘/api/‘ and ‘/media/‘ to backend/storage.

Default/demo credentials

For marking and local testing:
- Verification code is fixed to **‘1234‘** in dev/test mode (no real email required).
- Some flows require ‘.edu.au‘ emails (see ‘tests/integration/README.md‘ for examples).

Testing instructions

See ‘TESTING.md‘ for:
- What tests exist (frontend unit, backend unit, integration helpers)
- How to run each test suite
- What must be tested manually (auth, profile, courses, posts, dashboards, uploads, notifications)

Quick commands:

Frontend unit:

‘‘‘bash
cd tests/frontend-unit
npm install
npm test
‘‘‘

Backend unit:

‘‘‘bash
python -m venv .venv
source .venv/bin/activate
pip install -r backend/requirements.txt
pip install -r tests/backend-unit/requirements.txt
cd tests/backend-unit
pytest
‘‘‘

Troubleshooting

- **Port already in use**: change ‘GATEWAY_PORT‘ in ‘.env‘ (and restart: ‘docker compose down && docker compose up -d‘)
- **Containers unhealthy**: run ‘docker compose logs -f‘ and verify Postgres healthcheck passes
- **Database connection errors**: ensure ‘postgres‘ is healthy; check ‘PG_*‘ values in ‘.env‘
- **Uploads not accessible**: ensure ‘PUBLIC_MEDIA_URL‘ matches gateway URL and that ‘minio‘ + ‘minio-init‘ are running
- **AI features slow or failing**: leave ‘DEEPSEEK_API_KEY‘ empty to disable AI, or increase gateway timeout if enabling
- **Gmail not configured**: leave ‘GMAIL_*‘ blank; demo mode should still allow core flows to work