



The Mobile Tower for Professionals

AluLight®

S-Variant, C-Variant + SD-Variant

The AluLight-Tower range is designed and built for the construction equipment rental market. With superb quality and strength, robotic welded slip-resistant rungs, offering unbeatable utilization, and a high return on investment.

Product features:

- ▶ Working height up to 14 m
- ▶ Super light, extremely resilient
- ▶ No tools required for assembly
- ▶ Including 2-fold braked castors with spindle for height adjustment (diameter 200 mm)
- ▶ High-strength self-locking aluminium claws, for quick and easy assembly
- ▶ No wall anchor necessary, even at 14 m
- ▶ All rungs are non-slip profiled
- ▶ 2 widths: 70 cm and 135 cm
- ▶ 2 lengths: 2.5 m and 3 m
- ▶ All parts can be retrofitted individually

Technical specifications:

- ▶ Rolling scaffold according to EN-1004-3-8/12 (DIN4422)
- ▶ System length 2.5 m up to 300 kg per platform
- ▶ System length 3.0 m up to 360 kg per platform
- ▶ Scaffolding group 3 (200kg/qm)
- ▶ Dimensions type 70: 2.5 m or 3.0 m x 0.7 m
- ▶ Dimensions type 135: 2.5 m or 3.0 m x 1.35 m
- ▶ Max. outdoor working height 10 m
- ▶ Working height in closed rooms 14 m
- ▶ Pipe diameter 50.6 mm x 2.1 mm
- ▶ Covering: Screen printing plate (7-fold veneer) with aluminium frame, non-slip
- ▶ EN 1004 certification by TÜV-SÜD

Type of use:

- ▶ Rental, Premium contract,
Major contractor groups, Construction