Pneumatic impact wrench 1/2" Model RC22277

Item no.: 8951000349



The RC2277 1/2" impact wrench is the ideal choice for users who work with tire changes or industrial maintenance and are looking for the best performance, high robustness and the optimal comfort.



Pneumatic impact wrench 3/8"

Model RC2177 Item no.: 8951000043

Ergonomic and lightweight tool with very good weight distribution. Non-slip and shock-absorbing handle, high performance for quick disassembly with low compressed air requirement.

Compact design for confined spaces. Durable DUOPACT hammer mechanism



#### Pneumatic impact wrench 1/2" Model RC2203

Item no.: 8951000387

The RC2203 is known for its ultra-compact design and its high performance. It is the best choice for users working in hard-toreach places and looking for an excellent power-to-weight ratio.



# Pneumatic impact wrench 1/2"

Model RC2205 Item no.: 8951000085

The popular classic. One-hand operation with left/right switch and 4-stage power regulation when tightening Full power when loosening - max. 800 Nm. Attachment option for sound-absorbing hose



# Pneumatic impact wrench 1/2"

Model RC2267

Item no.: 8951000044

Ergonomic and lightweight tool with very good weight distribution. Non-slip and shock-absorbing handle, high performance for quick disassembly with low compressed air requirement.

Compact design for confined

spaces.



# Pneumatic impact wrench 1/2"

Model RC2266

Item no.: 8951000436

The RC2266 1/2" impact wrench is impressive with its versatility, its excellent price-performance ratio and the well-known RODCRAFT quality.



Recommended accessories **SOCKET SET** See page 10





## Pneumatic impact wrench 3/4" Model RC2377

Item no.: 8951000045

Ergonomic tool with very good weight distribution (best weight/power ratio in its class). Non-slip and shock-absorbing handle and durable DUOPACT hammer mechanism.



# Pneumatic impact wrench 3/4" Model RC2315

Item no.: 8951077130

All-rounder for every application. DUOPACT hammer mechanism, 3-stage power reduction when tightening. Handle with insulating rubber coating.



MODEL	RC2277	RC2203	RC2267	RC2205	RC2266	RC2235	RC2177	RC2377	RC2315
Item number	8951000349	8951000387	8951000044	8951000085	8951000436	8951000286	8951000043	8951000045	8951077130
Output drive size	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	3/8"	3/4"	3/4"
Max. loosening torque	1,950 Nm	1,254 Nm	1,150 Nm	800 Nm	1,600 Nm	450 Nm	950 Nm	2,200 Nm	1,700 Nm
Max. torque in reverse	1,300 Nm	650 Nm	660 Nm	580 Nm	1,000 Nm	300 Nm	580 Nm	1,950 Nm	1,500 Nm
Working torque range (forward)	60-900 Nm	90-450 Nm	22-486 Nm	34-420 Nm	140-750 Nm	60-220 Nm	37-258 Nm	234-1,391 Nm	177-1,100 Nm
Free speed	8,200 rpm	10,500 rpm	10,200 rpm	7,800 rpm	9,000 rpm	7,400 rpm	8,200 rpm	5,760 rpm	5,600 rpm
Impact mechanism	DUOPACT	Twin Ham- mer	DUOPACT	Pin clutch	DUOPACT	Jumbo hammer	DUOPACT	DUOPACT	DUOPACT
Air intake thread size	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	3/8"	3/8"
Noise level	94 dB(A)	90 dB(A)	93 dB(A)	87.4 dB(A)	96.4 dB(A)	97 dB(A)	90 dB(A)	96.8 dB(A)	91.1 dB(A)
Length	194 mm	115 mm	164 mm	200 mm	185 mm	341 mm	164 mm	221 mm	242 mm
Weight	2 kg	1.1 kg	1.25 kg	2.4 kg	2.18 kg	1.85 kg	1.25 kg	3.5 kg	4.7 kg

## Pneumatic impact wrench 1" Model RC2405

Item no.: 8951000075



The RC2377/RC2405 range of impact wrenches is the perfect companion for vehicle and tire services with their excellent power-to-weight ratio and ergonomics.

#### Pneumatic impact wrench 1" Model RC2437Xi

Item no.: 8951000068



The RC2437Xi range contains the perfect 1" impact wrenches for workshops looking for low weight and high torque

#### Pneumatic impact wrench 1" Model RC2461

Item no.: 8951000354

Short anvil



Take advantage of the benefits of the 1" RC2461 and RC2471 impact wrenches.

They enable the operator to easily loosen wheel nuts on commercial vehicles.

These 1"impact wrenches offer high reliability thanks to their durable impact mechanism and metal housing.

## Pneumatic impact wrench 1" Model RC2471

Item no.: 8951000355

Long anvil



## Pneumatic impact wrench 1" Model RC2457Xi

Item no.: 8951000135

Short anvil



The RC2457Xi and RC2477Xi models are perfect for tightening and loosening wheel nuts on commercial vehicles.

The low weight and the compact design also offer you a high level of comfort in your daily work and ultimately increase your productivity.

#### Pneumatic impact wrench 1" Model RC2477Xi

Item no.: 8951000046

Long anvil



MODEL	RC2405	RC2437Xi	RC2461	RC2471	RC2457Xi	RC2477Xi
Item number	8951000075	8951000068	8951000354	8951000355	8951000135	8951000046
Output drive size	1"	1"	1"	1"	1"	1"
Max. loosening torque	2,300 Nm	3,650 Nm	3,345 Nm	3,345 Nm	3,950 Nm	3,950 Nm
Max. torque in reverse	1,950 Nm	2,700 Nm	2,600 Nm	2,600 Nm	2,900 Nm	2,900 Nm
Working torque range (forward)	174-1,061 Nm	500-2,000 Nm	760-1,800 Nm	760-1,800 Nm	500-2,000 Nm	500-2,000 Nm
Free speed	5,760 rpm	6,000 rpm	3,900 rpm	4,600 rpm	5,900 rpm	5,900 rpm
Impact mechanism	DOUBLE DOG	DUOPACT	Closed Hammer mecha- nism	Closed Hammer mecha- nism	DUOPACT	DUOPACT
Air intake thread size	3/8"	1/2"	3/4"	3/4"	1/2"	1/2"
Noise level	96.8 dB(A)	100.8 dB(A)	103.3 dB(A)	103.3 dB(A)	106 dB(A)	106 dB(A)
Length	221 mm	280 mm	428 mm	530 mm	337 mm	490 mm
Weight	3.6 kg	7.2 kg	11.8 kg	12.8 kg	7.2 kg	8.1 kg

