

Plug nipples + quick couplings



Item number	Designation
8951011809	Plug nipple with thread BSP 1/4" external thread
8951011810	Plug nipple with thread BSP 3/8" external thread
8951011811	Plug nipple with thread BSP 1/2" external thread



8951011812	Plug nipple with thread BSP 1/4" internal thread
8951011813	Plug nipple with thread BSP 3/8" internal thread
8951011814	Plug nipple with thread BSP 1/2" internal thread



8951011795	Nipple ISO7, 2 mm, for hoses 6-7 mm
8951011796	Nipple ISO7, 2 mm, for hoses 9 mm
8951011797	Nipple ISO7, 2 mm, for hoses 13 mm



8951011784	Quick coupling BSP 1/4" external thread
8951011785	Quick coupling BSP 3/8" external thread
8951011786	Quick coupling BSP 1/2" external thread



8951011787	Quick coupling BSP 1/4" internal thread
8951011788	Quick coupling BSP 3/8" internal thread
8951011789	Quick coupling BSP 1/2" internal thread



8951011790	Quick coupling for hoses 6-7 mm
8951011791	Quick coupling for hoses 9-10 mm
8951011792	Quick coupling for hoses 13 mm



8951011819	2-way distributor with quick coupling BSP 3/8" internal thread
8951011820	3-way distributor with quick coupling BSP 3/8" internal thread

PE pneumatic air hose with coupling

Model PE pneumatic air hose



Item number	Designation
8951011842	PUR Spiral hose, 8mm inner diameter and 4m long EUR7,2 coupling and nipple connector
8951011843	PUR Spiral hose, 8mm inner diameter and 6m long EUR7,2 coupling and nipple connector
8951011844	Length 8 m, Internal diameter 8 mm, External diameter 10 mm, max. working pressure 15 bar



8951011845	Spiral hose 6,5mm inner diameter with 1/4" AG thread Lenght 6m made from polyurethane PUR
8951011846	Spiral hose 8mm inner diameter with 3/8" AG thread Lenght 6m made from polyurethane PUR
8951011847	Spiral hose 8mm inner diameter with 3/8" AG thread Lenght 4m made from polyurethane PUR
8951011848	Spiral hose 8mm inner diameter with 3/8" AG thread Lenght 8m made from polyurethane PUR

RODCRAFT FRL maintenance units: Cleaner air, full power

With the RODCRAFT maintenance unit, you extend the service life of your compressed air tools and reduce the energy requirement. Your tools are automatically set to the optimum oil quantity supplied and the filter provides protection against dirt and water

Maintenance unit –
connections ½"

Item no.: 8951000164

Maintenance unit –
connection ¼" BSP

Item no.: 8951000162

- Stable aluminum housing with composite containers.
- 5-Micron filter
- Semi-automatic manual drain
- Max. inlet pressure 15 bar
- Max. air passage 2,080 l/min



Hose reel

With length adjustment, ratchet lock, swiveling wall bracket and all-round movable air connection

High-quality hose for all applications, lighter and more flexible than rubber. Latch spring locks the hose after unrolling and pulls it effortlessly with return power on again.

Rubber protection protects against stress on the crimp connections.

Drum spring: up to 20,000 - 25,000 cycles for excellent durability. Movable retraining ball allows adjustment of the minimum hose length.



Model	SAR21	SAR22	SAR31	SAR32
Item number	8951000148	8951000149	8951000150	8951000151
Length	10 m	16 m	10 m	160 m
Internal diameter	8 mm	10 mm	8 mm	10 mm
Thread size	1/4" BSP	3/8" BSP	1/4" BSP	3/8" BSP
Hose material	Polyurethane			

Device oiler Model G1K

Item no.: 8951011851



Small oiler with a volume of 4 ml that is attached directly to the tool. 1/4" thread

Air oil RCA1000

Item no.: 8955000117

For the lubrication of pneumatic tools. Contains additives that constantly maintain the protective film against rust and corrosion

Air oil, 1,000 ml



- Very good flow properties at low temperatures
- Very good protection against corrosion
- High pressure and impact resistant
- Non-toxic