

The Test of Non-Specificity of Analogies (TNSA): A Method for Evaluating the Evidential Value of Analogical Inference in Cognitive and Behavioral Neuroscience

Steve Girard

Abstract

Analogical reasoning is pervasive in cognitive and behavioral neuroscience, from cross-species comparisons to metaphors linking neural circuits and cognitive functions. We present the **Test of Non-Specificity of Analogies (TNSA)**, a five-step protocol adapted to neuroscience that assesses whether observed resemblances between heterogeneous entities carry discriminative, mechanistic, or causal weight. The TNSA operationalizes selection, category extraction, transfer, and inversion procedures to determine whether analogies reflect domain-specific mechanisms or arise from broadly applicable descriptive categories. We illustrate the method with domain-relevant examples and discuss implications for inference from behavioral homologies, model organism generalization, and theory building. **Key conclusion:** resemblance alone is insufficient as evidence for shared mechanisms; independent theoretical or empirical discriminants are required.

Introduction

Analogies and resemblance-based arguments are central to hypothesis generation in neuroscience: researchers compare species, brain regions, computational models, or behavioral paradigms to infer shared mechanisms of learning, memory, perception, and decision-making. While analogies can be heuristically productive, they risk overreach when descriptive similarities are taken as evidence of common causal or mechanistic bases. The TNSA formalizes a reproducible test to probe the **specificity** of analogies: if categories used to describe one pair of entities apply, without loss of coherence, to other independent pairs, then those categories are likely non-discriminative and cannot by themselves support claims of shared neural mechanisms.

Methods — TNSA adapted for Cognitive and Behavioral Neuroscience

The TNSA comprises five sequential steps, each adapted here to the epistemic needs of neuroscience research.



Figure X. Schéma du Test de non-spécificité des analogies (TNSA) montrant les cinq étapes et les métriques recommandées pour l'évaluation quantitative.

Horizontal flowchart illustrating the Test of Non-Specificity of Analogies (TNSA) in five sequential steps: Step 1 — Contrastive selection (choose an *a priori* independent pair; document phylogeny, ontology, measurement); Step 2 — Operational category extraction (create a replicable codebook of measurable categories such as centrality, influence, observability, temporality); Step 3 — Control pair selection (select a distinct but relevant control pair and ensure measurement comparability); Step 4 — Transfer test (apply the codebook without modification; assess operational coherence and empirical plausibility); Step 5 — Inversion and symmetry (apply control-derived categories back to the original pair; symmetry indicates non-specificity). A separate box on the right lists recommended quantitative evaluations: AUC, mutual information, cross-validated accuracy, permutation p-values, and effect sizes.

Step 1 Contrastive selection of the initial pair

Objective. Choose a pair of entities that are *a priori* independent to maximize the strength of the test: the greater the conceptual distance, the less any observed convergence can be attributed to a genuine kinship.

Application in neuroscience. For a manuscript in *Cognitive and Behavioral Neuroscience*, this typically means selecting, for example, (i) a stereotyped behavior observed in a model organism (e.g., repetitive exploration in mice) and (ii) a human cognitive phenomenon (e.g., an attentional bias in a clinical disorder) that have no obvious homology. Precisely document why the pair is considered independent (phylogeny, experimental ontology, temporal scale, measurement modalities). **Practical criteria:** make explicit the sources, operational definitions, and known limitations for each entity; specify measurement modalities (behavioral assays, electrophysiology, imaging) so that the comparison does not rest on methodological artefacts.

The first step consists in selecting a pair of entities that, *a priori*, have no historical, causal, biological, or conceptual link.

Step 2 Systematic and operational extraction of categories

Objective. Extract explicit, measurable descriptive categories that account for potential resemblances without resorting to vague formulations.

Application in neuroscience. Translate general categories into operational variables relevant to the field: **centrality** → degree of integration of a node in a functional network (measured by degree, betweenness); **influence** → causal effect measurable on task performance (perturbation, stimulation); **observability** → signal-to-noise ratio and inter-trial reliability; **temporality** → characteristic temporal scales (latency, periodicity). For each category provide: (a) a formal definition, (b) a recommended measurement method, (c) thresholds or comparison metrics, and (d) concrete examples drawn from the literature. This step should produce a replicable **codebook** that will serve as the basis for subsequent transfers.

It is important to document each commonality by explaining how it is defined and applied to both entities, so that the procedure is transparent and replicable.

Step 3 Selection of the control pair

Objective. Choose a second pair of entities that are independent and distinct from the first to test the specificity of the extracted categories.

Application in neuroscience. The control pair should come from a different conceptual domain while remaining relevant to neuroscientific questions (e.g., compare an EEG oscillatory signature with an activity motif in a computational model, or contrast an interspecific social behavior with dynamics from agent-based simulations).

Methodological considerations: ensure comparability of data modalities where possible (map categories onto analogous measures), document the absence of an *a priori* link, and justify the choice as a methodological control (not an ad hoc counterexample). The goal is to obtain a false-positive test: if the same categories describe the control pair, they are likely non-discriminative.

Step 4 Transfer test

Objective. Apply, without substantive modification, the categories defined in Step 2 to the control pair and evaluate coherence and descriptive plausibility.

Application in neuroscience. For each category perform two complementary evaluations:

- **Operational coherence:** does the category retain a measurable meaning in the new domain (e.g., is the network centrality metric computable and interpretable for the control pair's data)?
- **Empirical plausibility:** is the resulting description compatible with empirical knowledge and methodological constraints in the control domain?

Recommended analyses: discriminability tests (e.g., cross-validated classification), analyses of variance on category metrics between pairs, and cross-validation on independent datasets. If the transfer succeeds (coherence + plausibility), this indicates that the categories are general and non-specific, and that they do not suffice to establish mechanistic homology.

Step 5 Inversion and symmetry of transferability

Objective. Apply the categories extracted from the control pair to the original pair to test reciprocity; symmetry strengthens the argument for non-specificity.

Application in neuroscience. Perform the inversion by taking the codebook derived from the control pair and applying it to the initial pair, then compare results to the original descriptions.

Evaluation criteria: For neuroscience applications, supplement qualitative plausibility with empirical checks where possible: cross-validation against independent datasets, statistical tests of category discriminability, or model comparison metrics that quantify explanatory power beyond descriptive fit. Similarity of metric profiles (correlations, distance measures), preservation of descriptive plausibility, and absence of ad hoc adjustments required to obtain a good fit. If the inversion succeeds, conclude that the resemblances are primarily the product of reusable descriptive categories rather than a shared causal or structural link. If the inversion systematically fails, this signals potential specificity that warrants deeper mechanistic investigation (e.g., causal perturbations, connectivity analyses, controlled cross-species studies).




Figure 2. Heatmaps of category profiles across pairs; left: category metrics per entity; right: transfer/inversion similarity. Metrics: AUC, mutual information, cross-validated accuracy, permutation p-values, effect sizes.

Figure 2. Heatmaps of category profiles across pairs; left: category metrics per entity (rows = Centrality, Influence, Observability, Temporality, Signature Patterns; columns = Entity A1, Entity A2, Entity B1, Entity B2); right: transfer/inversion similarity (rows = categories; columns = Transfer, Inversion). Metrics reported: AUC, mutual information, cross-validated accuracy, permutation p-values, effect sizes. Left panel titled “Category Metrics per Entity” shows rows for Centrality, Influence, Observability, Temporality, and Signature Patterns and columns for Entity A1, Entity A2 (Pair 1) and Entity B1, Entity B2 (Pair 2). Each cell is annotated with the mean metric value and colored on a blue–white–red scale. Right panel titled “Transfer / Inversion Similarity” shows the same category rows with two columns (Transfer, Inversion) and annotated similarity values; a vertical colorbar indicates the numeric scale. Layout is horizontal, publication style, sans-serif font, white background.

Methodological remarks and practical recommendations

- **Quantification and transparency:** always provide definitions, analysis scripts, and thresholds so other teams can reproduce the TNSA on different pairs.
- **Empirical complementarity:** treat the TNSA as a diagnostic filter — it identifies non-discriminative analogies but does not replace causal evidence (perturbation experiments, out-of-sample prediction, multimodal convergence).
- **Formal extensions:** consider information-theoretic discriminability measures (mutual information, classification AUC) to convert the protocol into a quantitative test of specificity.

Empirical Illustration (Conceptual examples relevant to the journal)

To make the method concrete for readers in cognitive and behavioral neuroscience, we outline two conceptual case studies (kept deliberately schematic to avoid overclaiming empirical facts).

Example A — *Model organism behavior vs human cognitive syndrome*

- **Pair 1 (contrastive):** A stereotyped rodent exploratory behavior and a human attentional deficit syndrome. Extracted categories might include *contextual centrality* (role within behavioral repertoire), *influence on task performance*, *variability and observability*, and *signature patterns across trials*.
- **Pair 2 (control):** A neural network model's activation pattern and a population-level electrophysiological signature (e.g., LFP oscillation). Apply the same categories and assess whether they meaningfully describe both pairs.
- **Interpretation:** If categories such as “signature patterns” and “variability” apply equally well across both pairs, their descriptive generality cautions against inferring mechanistic homology between the rodent behavior and the human syndrome on the basis of resemblance alone.

Example B — *Cross-species social behavior vs computational agent dynamics*

- **Pair 1 (contrastive):** Social dominance behaviors in two distantly related species.
- **Pair 2 (control):** Emergent coordination in multi-agent simulations.
- **Transfer/inversion:** If categories like *influence on group dynamics* and *observability of state transitions* transfer bidirectionally, then resemblance is likely driven by high-level descriptive constructs rather than shared neural substrates.

These illustrations show how TNSA highlights the difference between **descriptive fit** and **mechanistic evidence**, a distinction crucial for claims about neural bases of cognition and behavior.




Figure 3. Scatterplots of similarity scores for Transfer and Inversion with 95% confidence intervals.

Figure 3. Transfer and inversion scatterplots showing category-wise similarity between pairs. Left panel: Transfer — similarity scores per category when applying the original codebook to the control pair; points = mean, vertical bars = 95% CI, fitted regression line with shaded 95% CI. Right panel: Inversion — same layout for control-derived codebook applied back to the original pair. Pearson r and permutation p -values are reported. Two-panel scatterplot. Left panel titled “Transfer” shows five colored points (Centrality, Influence, Observability, Temporality, Signature Patterns) on a vertical similarity axis (–1 to 1), each with a vertical 95% CI bar and an overlaid regression line with shaded 95% CI; inset lists Pearson r and permutation p -value. Right panel titled “Inversion” mirrors the left with analogous points, CIs, and regression. Points are color-coded by category and jittered for readability.

Discussion

The TNSA provides a practical, transparent framework for evaluating analogical claims in neuroscience. Its strengths include:

- **Explicit operationalization** of categories, reducing rhetorical or ad hoc analogizing.
- **A control-transfer logic** that distinguishes domain-specific from domain-general descriptions.
- **Compatibility with empirical validation**, since categories can be linked to measurable signals and statistical discriminants.

Implications for common neuroscience practices. The protocol warns against several

common inferential pitfalls: (1) equating behavioral similarity with shared circuitry, (2) overgeneralizing model results to biological systems without discriminative tests, and (3) relying on metaphorical mappings (e.g., “the brain is a computer”) as explanatory endpoints. TNSA encourages researchers to supplement analogical reasoning with independent mechanistic evidence: lesion studies, causal perturbations, cross-validated predictive models, or convergent multi-modal measurements.

Limitations and extensions. TNSA is not a substitute for theory; rather, it is a diagnostic tool. Some analogies are legitimately mechanistic when supported by independent constraints; TNSA helps identify when such constraints are absent. Future work could formalize TNSA quantitatively (e.g., information-theoretic measures of category specificity) and integrate it into comparative pipelines for cross-species inference.

Conclusion

For cognitive and behavioral neuroscience, the TNSA is a methodological safeguard: it makes explicit when analogies are merely descriptive and when they merit mechanistic inference. Researchers should treat resemblance as a starting point for hypothesis generation, not as standalone evidence for shared neural mechanisms. As Girard (2026) emphasizes, *ressemblance, prise isolément, n'est pas une preuve*; rigorous transfer and inversion tests, combined with independent empirical discriminants, are required to elevate analogical claims to explanatory status.

Acknowledgments