

Configuraciones

named.conf	named.conf.options	named.conf.local	db.xuan.com	db.172
------------	--------------------	------------------	-------------	--------

```
// This is the primary configuration file for the BIND DNS server named.
//
// Please read /usr/share/doc/bind9/README.Debian for information on the
// structure of BIND configuration files in Debian, *BEFORE* you customize
// this configuration file.
//
// If you are just adding zones, please do that in /etc/bind/named.conf.local

include "/etc/bind/named.conf.options";
include "/etc/bind/named.conf.local";
include "/etc/bind/named.conf.root-hints";
```

named.conf	named.conf.options	named.conf.local	db.xuan.com	db.172
------------	--------------------	------------------	-------------	--------

```
options {
    directory "/var/cache/bind";

forwarders {
    8.8.8.8;
};
};
```

db.172	named.conf.local	db.xuan.com
--------	------------------	-------------

```
//
// Do any local configuration here
//
zone "xuan.com" {
    type master;
    file "/etc/bind/db.xuan.com";
};

zone "20.172.in-addr.arpa" {
    type master;
    file "/etc/bind/db.172";
};
```

db.172	named.conf.local	db.xuan.com
--------	------------------	-------------

```
$TTL 43200
@ IN SOA ns.xuan.com. root.xuan.com. (
    2511180855 ; Serial
    3600 ; Refresh
    1800 ; Retry
    2419200 ; Expire
    43200) ; Negative Cache TTL

@ IN NS ns.xuan.com.
@ IN A 127.0.0.1
ns IN A 172.20.3.104

route IN A 172.20.0.1
real IN A 172.20.3.4
server IN A 172.20.3.104
www IN CNAME real
```

db.172	named.conf.local	db.xuan.com
--------	------------------	-------------

```
$TTL 43200
@ IN SOA ns.xuan.com. root.xuan.com. (
    2511180855 ; Serial
    3600 ; Refresh
    1800 ; Retry
    2419200 ; Expire
    43200) ; Negative Cache TTL
;
@ IN NS ns.xuan.com.
104 IN PTR ns.xuan.com.

$ORIGIN 20.172.in-addr.arpa.

1.0 IN PTR route.xuan.com.
4.3 IN PTR real.xuan.com.
104.3 IN PTR server.xuan.com.
```

named-check

```
root@ServidorXuan:~# named-checkzone 20.172.in-addr.arpa. /etc/bind/db.172
zone 20.172.in-addr.arpa/IN: loaded serial 2511180855
OK
root@ServidorXuan:~# named-checkzone xuan.com /etc/bind/db.xuan.com
zone xuan.com/IN: loaded serial 2511180855
OK
root@ServidorXuan:~# systemctl reload named
root@ServidorXuan:~# named-checkconf /etc/bind/named.conf.local
root@ServidorXuan:~# named-checkconf /etc/bind/named.conf.options
root@ServidorXuan:~# █
```

ping y nslookup

```
root@debian13-Xuan:~# ping www.xuan.com
PING real.xuan.com (172.20.3.4) 56(84) bytes of data.
64 bytes from real.xuan.com (172.20.3.4): icmp_seq=1 ttl=127 time=1.54 ms
64 bytes from real.xuan.com (172.20.3.4): icmp_seq=2 ttl=127 time=1.47 ms
64 bytes from real.xuan.com (172.20.3.4): icmp_seq=3 ttl=127 time=2.83 ms
64 bytes from real.xuan.com (172.20.3.4): icmp_seq=4 ttl=127 time=1.65 ms
root@debian13-Xuan:~# nslookup
> ns.xuan.com
Server:          172.20.3.104
Address:         172.20.3.104#53

Name:   ns.xuan.com
Address: 172.20.3.104
> set type=CNAME
> www
Server:          172.20.3.104
Address:         172.20.3.104#53

www.xuan.com    canonical name = real.xuan.com.
> set type=PTR
> 172.20.0.1
Server:          172.20.3.104
Address:         172.20.3.104#53

1.0.20.172.in-addr.arpa name = route.xuan.com.
> █
```

obtener informacion del servidor DNS del instituto

```
> set type=S0A
> www.iesrodeira.com
Server:          172.20.3.104
Address:         172.20.3.104#53

Non-authoritative answer:
www.iesrodeira.com    canonical name = ies.iesrodeira.com.

Authoritative answers can be found from:
iesrodeira.com
    origin = iesrodeira.com
    mail addr = xavi.iesrodeira.com
    serial = 2025301119
    refresh = 28800
    retry = 7200
    expire = 604800
    minimum = 10800
>
```