

# 5. Repetition

6. Iteration

7. Other Conditional and Iterative Statements

## The while Statement (1)

```
#include <iostream>
int main() {
    int count = 1; // Initialize counter
    while (count <= 5) {
        std::cout << count << '\n'; // Display counter, then
        count++; // Increment counter
    }
}
```

while( **condition** )

**statement**

## The while Statement (2)

```
#include <iostream>
int main() {
    char input;
    int count = 0;
    bool done = false;
    while (!done) {
        std::cout << count << '\n';
        std::cout << "Please enter \"Y\" to continue or \"N\" to quit:";
        std::cin >> input;
        if(input != 'Y' && input != 'y' && input != 'N' && input != 'n')
            std::cout << "\"" << input << "\""
                << " is not a valid choice" << '\n';
        else if (input == 'Y' || input == 'y')
            count++;
        else if (input == 'N' || input == 'n')
            done = true;
    }
}
```

## The while Statement (3)

```
#include <iostream>
int main() {
    int input = 0,          // Ensure the loop is entered
        sum = 0;           // Initialize sum

    // Request input from the user
    std::cout << "Enter numbers to sum, negative number ends list:";
    while (input >= 0) {    // A negative number exits the loop
        std::cin >> input;  // Get the value
        if (input >= 0)
            sum += input;   // Only add it if it is nonnegative
    }

    std::cout << "Sum = " << sum << '\n'; // Display the sum
}
```

## The while Statement (4)

```
#include <iostream>
int main() {
    int input, sum = 0;
    std::cout << "Enter numbers to sum, type 'q' to end the list:";
    while (std::cin >> input) // ^Z(Windows), ^D(Unix)
        sum += input;

    std::cout << "Sum = " << sum << '\n';
}
```

## The while Statement (5)

```
#include <iostream>
#include <iomanip>
// Print the powers of 10 from 1 to 1,000,000,000
int main() {
    int power = 1;
    while (power <= 1000000000) {
        // Right justify each number in a field 10 wide
        std::cout << std::setw(10) << power << '\n';
        power *= 10;
    }
}
```


## The while Statement (6)

```
#include <iostream>
#include <iomanip>
#include <locale>
// Print the powers of 10 from 1 to 1,000,000,000
int main() {
    int power = 1;
    std::cout.imbue(std::locale(""));
    while (power <= 1000000000) {
        // Right justify each number in a field 10 wide
        std::cout << std::setw(13) << power << '\n';
        power *= 10;
    }
}

// std::cout.imbue(std::locale("")); // global locale
// std::cout.imbue(std::locale("german")); // imbue locale
```

## The while Statement (7)

```
// Decision tree for troubleshooting a computer system
```



# Nested Loops

```
#include <iostream>
int main() {
    int size; // The number of rows and columns in the table
    std::cout << "Please enter the table size: ";
    std::cin >> size;
    // Print a size x size multiplication table
    int row = 1;
    while (row <= size) {          // Table has size rows.
        int column = 1;           // Reset column for each row.
        while (column <= size){ // Table has size columns.
            int product = row*column; // Compute product
            std::cout << product << " "; // Display product
            column++; // Next element
        }
        std::cout << '\n'; // Move cursor to next row
        row++; // Next row
    }
}
```

# Abnormal Loop Termination (1)

```
#include <iostream>
int main() {
    int input, sum = 0;
    std::cout << "Enter numbers to sum, negative number ends list:";
    while (true) {
        std::cin >> input;
        if (input < 0)
            break; // Exit loop immediately
        sum += input;
    }
    std::cout << "Sum = " << sum << '\n';
}
```


## Abnormal Loop Termination (2)

```
#include <iostream>
int main() {
    int count = 1; // Initialize counter
top:
    if (count > 5)
        goto end;
    std::cout << count << '\n';           // Display counter, then
    count++;                             // Increment counter
    goto top;
end:
    ; // Target is an empty statement
}
```

## Abnormal Loop Termination (3)

```
#include <iostream>
int main() {
    int input, sum = 0;          bool done = false;
    while (!done) {
        std::cout << "Enter positive integer (999 quits): ";
        std::cin >> input;
        if (input < 0) {
            std::cout << "Negative value " << input << " ignored\n";
            continue; // Skip rest of body for this iteration
        }
        if (input != 999) {
            std::cout << "Tallying " << input << '\n';
            sum += input;
        }
        else
            done = (input == 999); // 999 entry exits loop
    }
    std::cout << "sum = " << sum << '\n';
}
```

## Abnormal Loop Termination (4)



## Infinite Loops

```
while(true) {  
    // Do something forever...  
}  
  
// Accidental infinite loop  
#include <iostream>  
int main() {  
    int n = 1;  
    const int MAX = 20;  
    while (n <= MAX) {  
        int factor = 1;  
        std::cout << n << ": ";  
        while (factor <= n)  
            if (n % factor == 0) {  
                std::cout << factor << " ";  
                factor++;  
            }  
        std::cout << '\n';  
        n++;  
    }  
}
```

```
1: 1  
2: 1 2  
3: 1
```

# Iteration Examples (1)

```
#include <iostream>
int main() {
    int height;
    std::cout << "Enter height of tree: ";
    std::cin >> height;
    int row = 0;
    while (row < height) {
        int count = 0;
        while (count < height - row) {
            std::cout << " ";
            count++;
        }
        count = 0;
        while (count < 2*row + 1) {
            std::cout << "*";
            count++;
        }
        std::cout << '\n';
        row++;
    }
}
```

Enter height of tree: 5

```
  *
 ***
*****
*****
*****
```

# Iteration Examples (2)

```
#include <iostream>
int main() {
    int max_value;
    std::cout << "Display primes up to what value? ";
    std::cin >> max_value;
    int value = 2;
    while (value <= max_value) {
        bool is_prime = true;
        int trial_factor = 2;
        while (trial_factor < value) {
            if (value % trial_factor == 0) {
                is_prime = false;
                break;
            }
            trial_factor++;
        }
        if (is_prime) std::cout << value << " ";
        value++;
    }
}
```



# The switch Statement (1)

```
switch(integralExpression) {  
    case integralConstant_1:  
        statementSequence_1;  
        break;  
    case integralConstant_2:  
        statementSequence_2;  
        break;  
    case integralConstant_n-2:  
    case integralConstant_n-1:  
        statementSequence_n-2_n-1;  
        break;  
    case integralConstant_n:  
        statementSequence_n;  
        break;  
    [default:  
        defaultStatementSequence;  
    ]  
}
```

# The switch Statement (2)

```
std::cin >> key;  
  
switch (key) {  
    case 'p':  
    case 'P':  
        std::cout << "You choose \"P\"\\n\"";  
        break;  
    case 'q':  
    case 'Q':  
        done = true;  
        break;  
}
```

# The Conditional Operator


```
(condition)?expression_1:expression_2
```

```
x = (z != 0) ? y/z : 0;
```


```
(x < 0) ? ++n : n
```

# The do/while Statement (1)

```
do  
    statement;  
while(condition);
```



while flowchart



do/while flowchart

## The do/while Statement (2)

```
#include <iostream>
int main() {
    int in_value = -1;
    std::cout << "Please enter an integer in the range 0-10: ";
    while (in_value < 0 || in_value > 10)
        std::cin >> in_value;
    std::cout << "Legal value entered was " << in_value << '\n';
}

-----

#include <iostream>
int main() {
    int in_value;
    std::cout << "Please enter an integer in the range 0-10: ";
    do
        std::cin >> in_value;
    while (in_value < 0 || in_value > 10);
    std::cout << "Legal value entered was " << in_value << '\n';
}
```

## The for Statement (1)

```
for(initialization;condtion;modification)
    statement;

initialization
while(condtion) {
    statement;
    modification;
}

#include <iostream>
int main() {
    for (int count = 1; count <= 5; count++)
        std::cout << count << '\n';
}
```

## The for Statement (2)

```
#include <iostream>
int main() {
    int max_value;
    std::cout << "Display primes up to what value? ";
    std::cin >> max_value;
    for (int value = 2; value <= max_value; value++) {
        bool is_prime = true;
        for (int trial_factor = 2; is_prime && trial_factor < value;
            trial_factor++)
            is_prime = (value % trial_factor != 0);

        if (is_prime)
            std::cout << value << " ";
    }
}
```

## The for Statement (3)

```
for (int i = 0, j = 100; i < j; i++) {
    ...
}

for (; i < 10; i++) {
    ...
}

for (int i = 0; ; i++) {
    ...
}

for (int i = 0; i < 10; i++);

for ( ;; ) {
    ...
}
```