

Device	Model	Inputs	Outputs	Roles (e.g., FOH Mix, Stream Audio, Confidence Monitor)	Connection types (HDMI, SDI, XLR, USB, Dante, NDI, etc.)	Logical Flow (Source → Processor → Output)
Board	Behringer X32			Process Source Audio to generate FOH Mix and Stream Audio	IN ??? OUT: ???	IN: Multiple Audio Sources OUT: 1) FOH Feed 2) Video Feed Are we using Ethernet?
Isolator -- NOT USED	Radial J-ISO Stereo Isolator	NA	NA	???	IN ??? OUT: ???	IN: OUT:
Encoder	URayCoder USE265-1L	Video / Audio Mix: SDI From Switcher Control/Config: Ethernet	Stream: Ethernet to Internet	Process Video and Audio into standard format for streaming	IN ??? OUT: ???	IN: OUT:
Video Switcher	Black Magic Model???	Video: HDMI from Cameras Audio: Balanced Line from Board		* Receive Video From Cameras * OPTIONAL: Receive Audio from Selected Source * Select Video Source to Send * Send Selected Video (and Audio if Desired) to Encoder	IN ??? OUT: ???	IN: OUT:
Ethernet Switch				* Local Ethernet Communication * Tie to CPC Network and Internet	IN: OUT:	IN: OUT: