





The Ninety Minute Chair is a lounge chair comprised of 9 pieces. Loads are distributed across its interlocking seat, arms, and legs. It can be made of almost any material and finished as desired.

As shown, one chair can be milled from two sheets of 4'x8' material. The chair requires a set of 3D printed keys (shown at right) that simplify assembly and lock pieces into place. These are included in the files and can also be found at www.thingiverse.com/atfab.







DIGITAL CUT FILE


Cut file provides 1 chair that can be cut from 2 sheets* of 18.5 (3/4") material.


KEY


White Lines = outside cuts Yellow Lines = inside cuts Red Lines = .375" pocket cut

 Green Circles = drilled holes (size to match your fastener)


*In order to optmize sheet material, nest other AtFAB pieces onto the sheets, or widen the Lounge Chair. By adding a third sheet, profiles can be reconfigured to yield two chairs from 3 sheets of material. Jig can also be nested into sheets.








jig parts in atfab_jig.dxf







LOUNGE CHAIR ASSEMBLY INSTRUCTIONS

ASSEMBLY:

Assembly requires placing pieces together in the right order. The jig (atfab_jig.dxf) and/or a friend are very useful at this stage. With the jig assembled on a worksurface and parts A-G laid out within reach, working upside down:

- Place Seat (E) face down onto jig
- Slot tab of Front (C) into Seat (E) slot
- Slot Seatback (D) onto tab of Seat (E)
- Place Arm (F) around Seatback (D)
- Work parts C-F into oneanother so that matching slots and tabs interlock, have a friend loosely hold these parts together.
- Carefully rotate (like a DeLorean door) Left Side (A) inside of Arm (F) and into Front piece (C)
- At this point it seems impossible, but keep shimmying Side (A) slowly into place so side tabs of Seatback and Seat align and slot into Side (A).
- Do the same with Right Side (A)
- Slot Back (B) into Arm (F)
- Place Feet (F) onto Sides and Back


FASTENING

Drill through the pre-drilled holes and into the edge of opposing part, then add peg or fastener of your choice:

- Keeping chair upside down, work around chair to fasten back, front and sides
- Fasten feet and turn chair upright
- · Fasten remaining holes
- Insert 3D printed LC Keys into pockets of sides, fasten and lock 3D printed Plugs into place, flush with Keys.
- Have a seat and enjoy!

STL files to 3D print the LC Key set, Large and Small LC Keys and plugs, are included and also can be found at thingiverse.com/ atfab. These keys lock the seat and seat-back into place.

Fit the Large LC Key and Small LC Key into the pockets of Sides (A), fasten Key through Sides (A) and into Seat (E) and Seatback (D). Fit a plug over the fastener. If Keys and Plugs fail to fit perfectly flush into the plywood, an adjusted STL file can be 3D printed to fit your chair perfectly.



Fabrication Suggestions

These suggestions, which come from our research experience, are our best effort to share insights about the fabrication process. They are by no means comprehensive; we always welcome your feedback.

PLANNING YOUR MATERIALS

- Simpler AtFAB furniture objects require a single sheet, while the larger complex pieces require 6 or more.
 We advise purchasing a 20% material surplus for testing.
- Cut files provided are scaled for 18.5mm (3/4") Hardwood Veneer Plywood (we used Home Depot's PureBond successfully in many of our prototypes). Some objects will require ½" sheet material for infill parts, shelves and drawers.
- Consult sheet material supplier and manufacturer instructions for finishing prep. Different sandpaper grits for edges and for faces of lumber products is useful, and wrapping sandpaper around dowels is helpful to sand the inside of the curved sniglets.
- If sealing, coating, painting or finishing your furniture piece in some way, consult manufacturer instructions for finishing with oils, waxes, paint and sealers.
- AtFAB's design using slots, tabs and notches makes objects easy to assemble with a couple of people.
 Moving quilts to protect the pieces and your floor are handy.
- Blue painters tape is especially helpful in holding pieces together as you assemble your object.
- For increased durability, we recommend securing joints with dowels.
 The cut files provide these dowel holes for the CNC to pre-drill into the face of the furniture pieces.

- If securing joints with dowels, a hand drill and 1/4"x11/2" pre-cut hardwood dowels of oak, maple or walnut have worked well with our plywood prototypes. Ask your material supplier for recommendations.
- The pre-drilled holes can accommodate mechanical fasteners, and they can be elminated altogether if you prefer to glue pieces together.
- CNC machines require their own supplies, consult your fabricator to find out recommended bit sizes for CNC routers, masking to protect your materials, and anything else the machines need.

FABRICATION HINTS

- DXF cut files are provided. After importing into the CNC Machine's proprietary CAM software, check that polylines remain continuous and closed, and inflected sniglet curves are consistent with the drawing included in this document.
- Every AtFAB object has inside cuts, outside cuts and drilled holes. These are separated by layers in the DXF file and noted on the accompanying sheet in this document. Cutting on the appropriate side of the line is critical to ensure tabs and slots fit together.
- Inside cuts (especially slots) may leave a piece of waste material that can be vibrated out of place and interfere with cutting. Secure this piece or pause the machine to remove it on the final pass.
- A lower cutting speed and greater number of passes produce a more refined edge that requires less sanding/filing.

USING THE TEST PIECE

Before proceeding with your entire job, test your sheet material and machine settings to ensure AtFAB pieces fit together as intended:

- Using your 20% material surplus, cut the test-piece provided in AtFAB_ test.dxf
- Multiple settings can be evaluated by cutting multiple test pieces and "bracketing" toolpath offsets, cutting speeds, bit sizes, etc with each piece.
- Finish the test piece(s) as you would your furniture object. Evaluate how the slots and the tabs of the finished test pieces fit together.

A successful fit using 18.5 (3/4") plywood allows 1-3 business cards to easily pass between the joints. If not:

- Measure the thickness of your sheet material in several places to see if it matches the slot dimensions in the cut files.
- If your material thickness is greater than 18.5 (¾"), CAD files can be scaled by up to 1-2% to adjust for your actual material thickness.
- Alternatively, you can incrementally increase bit diameter settings in your CAM software without changing your actual bit. This will enable the machine to remove slightly more material as it cuts on the same toolpath.
- Do not offset the CAD polylines to make fit adjustments. This will make AtFAB slots smaller and tabs bigger, ensuring ill-fitting pieces.

Terms & Conditions

TERMS & CONDITIONS

All AtFAB designs, information and cut files are prepared, prototyped and tested to the best of our abilities, with the sincerest intention for a successful outcome.

While it is our goal for the technical information contained in the downloaded AtFAB files to yield a finished furniture object that brings you maximum utility and enjoyment, the use of the downloaded information must be combined with your own due diligence.

By downloading any AtFAB file, you agree to the following:

- AtFAB is not liable for any failure of actions taken by you, or taken by others on your behalf, to produce a furniture object.
- You expressly agree to hold AtFAB, its designers, and its employees, harmless for any property damage, personal injury and/or death, or any other loss or damage that may result from your use of the digital information and designs provided.
- You further agree that the use of this design and all content contained herein are at your own risk and there is no warranty expressly made herein.
- You agree to indemnify AtFAB, and its designers and employees, from all and any damages, obligations, losses, liabilities, costs or debt, and expenses (including but not limited to attorney's fees) arising from use of AtFAB designs and derivative designs that are allowed under Creative Commons License.

CREATIVE COMMONS LICENSE

AtFAB designs are licensed under a Creative Commons Attribution-Non-Commercial Share Alike 3.0 Unported License. Under this license you are free to Share (copy, distribute and transmit the designs) and Remix (adapt the designs) under the following conditions:

- You must attribute the work in the manner specified by the author or licensor (but not in any way that suggests that they endorse you or your use of the work). In the case of AtFAB, score, etch or appliqué the AtFAB logo on your finished piece (some placement are shown on the next page and logo is in the cut file).
- If you alter, transform, or build upon this work, you may distribute the resulting work only under the same or similar license to this one. With the understanding that any of the above conditions can be waived if you get permission from Filson and Rohrbacher.
- For any reuse or distribution, you must make clear to others the license terms of this work. The best way to do this is to reference CC BY-NC-SA 3.0 Complete terms of this license can be found on creativecommons. org

NON-COMMERCIAL USE ONLY

All AtFAB Work (designs, technical drawings, digital cut files, instructions and other supporting material) are Copyright of Filson and Rohrbacher 2013.

The Creative Commons License is not applicable for commercial uses of AtFAB (either in commercial contexts or by manufacturing the designs with the intention of selling them).

If you would like to use these designs or variations of them in a commercial context, Filson and Rohrbacher would be delighted to provide commercial licensing arrangements for the designs. Please contact us for these licenses, as well as customization, fabrication or other services that can deliver AtFAB to the full benefit of your commercial enterprise.

CONTACT

info@filson-rohrbacher.com www.filson-rohrbacher.com