# **Monitor an EC2 Instance**

### Lab overview

Logging and monitoring are techniques implemented to achieve a common goal. They work together to help ensure that a system's performance baselines and security guidelines are always met.

**Logging** refers to recording and storing data events as log files. Logs contain low-level details that can give you visibility into how your application or system performs under certain circumstances. From a security standpoint, logging helps security administrators identify red flags that are easily overlooked in their system.

**Monitoring** is the process of analyzing and collecting data to help ensure optimal performance. Monitoring helps detect unauthorized access and helps align your services' usage with organizational security.

In this lab, you create an Amazon CloudWatch alarm that initiates when the Amazon Elastic Compute Cloud (Amazon EC2) instance exceeds a specific central processing unit (CPU) utilization threshold. You create a subscription using Amazon Simple Notification Service (Amazon SNS) that sends an email to you if this alarm is goes off. You log in to the EC2 instance and run a stress test command that causes the CPU utilization of the EC2 instance to reach 100 percent.

This test simulates a malicious actor gaining control of the EC2 instance and spiking the CPU. CPU spiking has various possible causes, one of which is malware.

## **Objectives**

After completing this lab, you should be able to:

- Create an Amazon SNS notification
- Configure a CloudWatch alarm
- · Stress test an EC2 instance
- · Confirm that an Amazon SNS email was sent
- · Create a CloudWatch dashboard

#### **Duration**

This lab requires approximately **60 minutes** to complete.

### Lab environment

The lab environment includes one preconfigured EC2 instance named **Stress Test** with an attached AWS Identity and Access Management (IAM) role that you can use to connect via AWS Systems Manager session manager.

All backend components, such as Amazon EC2, IAM roles, and some AWS services, have been built into the lab already.

## **Accessing the AWS Management Console**

At the upper-right corner of these instructions, choose ▶ Start Lab

Troubleshooting tip: If you get an Access Denied error, close the error box, and choose ▶ Start Lab again.

- 2. The following information indicates the lab status:
  - A red circle next to AWS at the upper-left corner of this page indicates that the lab has not been started.
  - o A yellow circle next to AWS o at the upper-left corner of this page indicates that the lab is starting.

A green circle next to <u>AWS</u> at the upper-left corner of this page indicates that the lab is ready.

Wait for the lab to be ready before proceeding.

3. At the top of these instructions, choose the green circle next to AWS •

This option opens the AWS Management Console in a new browser tab. The system automatically sign you in.

**Tip**: If a new browser tab does not open, a banner or icon at the top of your browser might indicate that your browser is preventing the site from opening pop-up windows. Choose the banner or icon, and choose **Allow pop-ups**.

- 4. If you see a dialog prompting you to switch to the new console home, choose Switch to the new Console Home.
- 5. Arrange the AWS Management Console tab so that it displays along side these instructions. Ideally, you should be able to see both browser tabs at the same time so that you can follow the lab steps.

▲ Do not change the lab Region unless specifically instructed to do so.

## Task 1: Configure Amazon SNS

In this task, you create an SNS topic and then subscribe to it with an email address.

Amazon SNS is a fully managed messaging service for both application-to-application (A2A) and application-to-person (A2P) communication.

- 6. In the AWS Management Console, enter SNS in the search Q bar, and then choose Simple Notification Service.
- 7. On the left, choose the **\equiv** button, choose **Topics**, and then choose **Create topic**.
- 8. On the Create topic page in the Details section, configure the following options:
  - Type: Choose Standard.
  - Name: Enter MyCwAlarm
- 9. Choose Create topic.
- 10. On the MyCwAlarm details page, choose the Subscriptions tab, and then choose Create subscription.
- 11. On the Create subscription page in the Details section, configure the following options:
  - Topic ARN: Leave the default option selected.
  - Protocol: From the dropdown list, choose Email.
  - Endpoint: Enter a valid email address that you can access.
- 12. Choose Create subscription.

In the **Details** section, the **Status** should be **Pending confirmation**. You should have received an **AWS Notification - Subscription Confirmation** email message at the email address that you provided in the previous step.

- 13. Open the email that you received with the Amazon SNS subscription notification, and choose Confirm subscription.
- 14. Go back to the AWS Management Console. In the left navigation pane, choose Subscriptions.

The Status should now be **Confirmed**.

## Summary of task 1

In this task, you created an SNS topic and then created a subscription for the topic by using an email address. This topic is now able to send alerts to the email address that you associated with the Amazon SNS subscription.

## Task 2: Create a CloudWatch alarm

In this task, you view some metrics and logs stored within CloudWatch. You then create a CloudWatch alarm to initiate and send an email to your SNS topic if the **Stress Test** EC2 instance increases to more than 60 percent CPU utilization.

CloudWatch is a monitoring and observability service built for DevOps engineers, developers, site reliability engineers (SREs), IT managers, and product owners. CloudWatch provides you with data and actionable insights to monitor your applications, respond to system-wide performance changes, and optimize resource utilization. CloudWatch collects monitoring and operational data in the form of logs, metrics, and events. You get a unified view of operational health and gain visibility of your AWS resources, applications, and services running on AWS and on premises.

- 15. In the AWS Management Console, enter Cloudwatch in the search Q bar, and then choose it.
- 16. In the left navigation pane, choose the Metrics dropdown list, and then choose All metrics.

CloudWatch usually takes 5-10 minutes after the creation of an EC2 instance to start fetching metric details.

17. On the Metrics page, choose EC2, and choose Per-Instance Metrics.

From this page, you can view all the metrics being logged and the specific EC2 instance for the metrics.

18. Select the check box with CPUUtilization as the Metric name for the Stress Test EC2 instance.

The following image shows the metrics and instance that you should select.

Stress Test	I-07-	StatusCheckFailed_System ▼
Stress Test	I-07-	StatusCheckFailed_Instance ▼
Stress Test	i-07	NetworkPacketsIn <b>▼</b>
Stress Test	i-07-	NetworkPacketsOut <b>▼</b>
✓ Stress Test	i-07	CPUUtilization <b>▼</b>
☐ Stress Test	I-07·	NetworkIn <b>▽</b>

This option displays the graph for the CPU utilization metric, which should be approximately 0 because nothing has been done yet.

19. In the left navigation pane, choose the ▶Alarms dropdown list, and then choose All alarms.

You now create a metric alarm. A metric alarm watches a single CloudWatch metric or the result of a math expression based on CloudWatch metrics. The alarm performs one or more actions based on the value of the metric or expression relative to a threshold over a number of time periods. The action then sends a notification to the SNS topic that you created earlier.

- 20. Choose Create alarm.
- 21. Choose Select metric, choose EC2, and then choose Per-Instance Metrics.
- 22. Select the check box with CPUUtilization as the Metric name for the Stress Test instance name.
- 23. Choose Select metric.
- 24. On the **Specify metric and conditions** page, configure the following options:

#### Metric

- Metric name: Enter CPUUtilization
- o InstanceId: Leave the default option selected.
- Statistic: Enter Average
- o Period: From the dropdown list, choose 1 minute.

#### **Conditions**

- o Threshold type: Choose Static.
- Whenever CPUUtilization is...: Choose Greater > threshold.
- than... Define the threshold value: Enter 60

The following image illustrates an example of an alarm configuration.

Percent	×	Land or high common transport		
60		Namespace		
		AWS/EC2		
40		Metric name		
		CPUUtilization		
20	1	InstanceId		
		i-09		
17:00 1  CPUUtilization	8:00 19:00	Instance name Stress Test		
		Statistic		
		Q Average		)
		Period		
Conditions		Period 1 minute		1,3
	old	Carameters		
		1 minute  O Anomaly detection		
Threshold type  Static Use a value as a threshown in the condition.  Define the alarm condition.	S	Anomaly detection Use a band as a thresh	old	
Threshold type  Static Use a value as a threshold  Whenever CPUUtilization in Define the alarm condition.  Greater > threshold	s      Greater/Equal	1 minute  Anomaly detection Use a band as a thresh	old ○ Lower	
Threshold type  Static Use a value as a threshold Whenever CPUUtilization in Define the alarm condition.  Greater	s      Greater/Equal	1 minute  Anomaly detection Use a band as a thresh	old ○ Lower	

25. Choose **Next**.

26. On the  ${\bf Configure\ actions}$  page, configure the following options:

#### **Notification**

- Alarm state trigger: Choose In alarm.
- Select an SNS topic: Choose Select an existing SNS topic.
- Send a notification to ...: Choose the text box, and then choose MyCwAlarm.
- 27. Choose **Next**, and then configure the following options:

### Name and description

- Alarm name: Enter LabCPUUtilizationAlarm
- Alarm description optional: Enter Cloudwatch alarm for Stress Test EC2 instance CPUUtilization
- 28. Choose Next
- 29. Review the **Preview and create** page, and then choose **Create alarm**.

## Summary of task 2

In this task, you viewed some Amazon EC2 metrics within CloudWatch. You then created a CloudWatch alarm that initiates an **In alarm** state when the CPU utilization threshold exceeds 60 percent.

#### Task 3: Test the Cloudwatch alarm

In this task, you log in to the **Stress Test** EC2 instance and run a command that stresses the CPU load to 100 percent. This increase in CPU utilization activates the CloudWatch alarm, which causes Amazon SNS to send an email notification to the email address associated with the SNS topic.

- 30. Navigate to the Vocareum console page, and choose the **i** AWS Details button.
- 31. Next to EC2InstanceURL, there is a link. Copy and paste this link into a new browser tab.

This link connects you to the **Stress Test** EC2 instance.

32. To manually increase the CPU load of the EC2 instance, run the following command:

```
sudo stress --cpu 10 -v --timeout 400s
```

The output from the command should look similar to the following image.

Session ID: user14 Instance ID:

```
sh-4.2$ sudo stress --cpu 10 -v --timeout 400s
stress: info: [32549] dispatching hogs: 10 cpu, 0 io, 0 vm, 0 hdd
stress: dbug: [32549] using backoff sleep of 30000us
stress: dbug: [32549] setting timeout to 400s
stress: dbug: [32549] --> hogcpu worker 10 [32550] forked
stress: dbug: [32549] using backoff sleep of 27000us
stress: dbug: [32549] setting timeout to 400s
stress: dbug: [32549] --> hogcpu worker 9 [32551] forked
stress: dbug: [32549] using backoff sleep of 24000us
stress: dbug: [32549] setting timeout to 400s
stress: dbug: [32549] --> hogcpu worker 8 [32552] forked
stress: dbug: [32549] using backoff sleep of 21000us
stress: dbug: [32549] setting timeout to 400s
stress: dbug: [32549] --> hogcpu worker 7 [32553] forked
stress: dbug: [32549] using backoff sleep of 18000us
stress: dbug: [32549] setting timeout to 400s
stress: dbug: [32549] --> hogcpu worker 6 [32554] forked
```

```
stress: dbug: [32549] setting timeout to 400s
stress: dbug: [32549] --> hogcpu worker 5 [32555] forked
stress: dbug: [32549] using backoff sleep of 12000us
stress: dbug: [32549] setting timeout to 400s
stress: dbug: [32549] --> hogcpu worker 4 [32556] forked
stress: dbug: [32549] using backoff sleep of 9000us
stress: dbug: [32549] setting timeout to 400s
stress: dbug: [32549] --> hogcpu worker 3 [32557] forked
stress: dbug: [32549] using backoff sleep of 6000us
stress: dbug: [32549] setting timeout to 400s
stress: dbug: [32549] --> hogcpu worker 2 [32558] forked
stress: dbug: [32549] using backoff sleep of 3000us
stress: dbug: [32549] setting timeout to 400s
```

This command runs for 400 seconds, loads the CPU to 100 percent, and then decreases the CPU to 0 percent after the allotted time.

- 33. Navigate to the Vocareum console page, and choose the **i** AWS Details button.
- 34. Copy and paste the URL text next to **EC2InstanceURL** into another new browser tab to open a second terminal for the **Stress Test** instance.
- 35. In the new terminal, run the following command:

```
top
```

This command shows the live CPU usage.

- 36. Navigate back to the AWS console where you have the CloudWatch Alarms page open.
- 37. Choose LabCPUUtilizationAlarm.
- 38. Monitor the graph while selecting the refresh button every 1 minute until the alarm status is In alarm.
  - It takes a few minutes for the alarm status to change to In alarm and for an email to send.

On the graph, you can see where CPUUtilization has increased above the 60 percent threshold.

39. Navigate to your email inbox for the email address that you used to configure the Amazon SNS subscription. You should see a new email notification from **AWS Notifications**.

## Summary of task 3

In this task, you ran a command to load the EC2 instance to 100 percent for 400 seconds. This increase in CPU utilization activated the alarm to go into the **In alarm** state, and you confirmed the spike in the CPU utilization by viewing the CloudWatch graph. You also received a email notification alerting you of the **In alarm** state.

## Task 4: Create a CloudWatch dashboard

In this task, you create a CloudWatch dashboard using the same CPUUtilization metrics that you have used throughout this lab.

CloudWatch dashboards are customizable home pages in the CloudWatch console that you can use to monitor your resources in a single view. With CloudWatch dashboards, you can even monitor resources that are spread across different Regions. You can use CloudWatch dashboards to create customized views of the metrics and alarms for your AWS resources.

- 40. Go to the CloudWatch section in the AWS console. In the left navigation pane, choose **Dashboards**.
- 41. Choose Create dashboard.

- 42. For Dashboard name, enter LabEC2Dashboard and then choose Create dashboard.
- 43. Choose Line.
- 44. Choose Metrics.
- 45. Choose EC2, and then choose Per-Instance Metrics.
- 46. Select the check box with Stress Test for the Instance name and CPUUtilization for the Metric name.
- 47. Choose Create widget.
- 48. Choose Save dashboard.

Now you have created a quick access shortcut to view the CPUUtilization metric for the Stress Test instance.

### Lab summary

In this lab, you created a CloudWatch alarm that activated when the **Stress Test** instance exceeded a specific CPU utilization threshold. You created a subscription using Amazon SNS that sent an email to you if this alarm goes off. You logged in to the EC2 instance and ran a stress test command that spiked the EC2 instance to 100 percent CPU utilization.

This test simulated what could happen if a malicious actor were to gain control of an EC2 instance and spike CPU utilization. CPU spiking has various possible causes, one of which is malware.

## Conclusion

Congratulations! You now have successfully:

- Created an Amazon SNS notification
- · Configured a Cloudwatch alarm
- Stress tested an EC2 instance
- · Confirmed that an Amazon SNS email was sent
- · Created a CloudWatch dashboard

## Lab complete

- 49. Choose **End Lab** at the top of this page, and then choose **Yes** to confirm that you want to end the lab.
- 50. An Ended AWS Lab Successfully message is briefly displayed indicating that the lab has ended.