11. Routing Fundamentals & Static Routing

Routing Fundamentals

What is Routing?

Routing is the process that routers use to determine the best path for IP packets to travel through a network to reach their destination.

Key Points:

- **Routers** make routing decisions by consulting a **routing table**, which contains routes to known destinations.
- When a router receives an IP packet, it refers to its routing table to determine the **next-hop** or the next destination for the packet.

Types of Routing

There are two primary methods that routers use to learn and manage routes:

1. Dynamic Routing

- **Dynamic Routing Protocols** (e.g., OSPF, EIGRP, BGP) are used.
- Routers share routing information **automatically**, updating their routing tables as the network changes.
- **Advantages**:
    - Automatically adapts to network changes.
    - Scales well for larger, more complex networks.
- **Disadvantages**:
    - Requires more CPU, memory, and bandwidth.
    - Can take time to converge after network changes.

2. Static Routing

- Routes are manually configured by a network administrator.
- Used in small or stable networks where paths rarely change.
- **Advantages**:
    - Simple to configure.
    - Consumes no extra resources (e.g., bandwidth, CPU).
- **Disadvantages**:
    - Does not adapt to network changes automatically.
    - Labor-intensive for larger networks.

Routing Decision Process

A route tells the router one of three things:

1. **Next-Hop Routing:**
    - For destination X, forward the packet to next-hop Y.
2. **Directly Connected:**
    - If the destination is on a network directly connected to the router, send the packet to the destination directly.
3. **Local Delivery:**
    - If the destination is the router's own IP address, the router processes the packet itself (does not forward it).

Routers will choose the most specific matching route.

WAN and Routing

A **Wide Area Network (WAN)** spans a large geographical area, often connecting multiple smaller networks (LANs). Routers are crucial in WANs to manage traffic between geographically separated locations.

Visual Aids

1. **Routing Table Example:** R1# show ip route
   The routing table contains the following for each route:

   · **L - local**
   → A route to the actual IP address configured on the interface. (with a /32 netmask)
   · **C - connected**
   → A route to the network the interface is connected to. (with the actual netmask configured on the interface)

    - **Destination:** The network or device to reach.
    - **Next-Hop:** The next device (or interface) to forward the packet to.
    - **Metric:** A value that indicates the cost of the route (lower is better).
    - **Interface:** The router's interface used to send the packet.
2. **Routing in a WAN:**
    - Routers within the WAN maintain routes to other routers and networks.
    - Dynamic routing protocols are often used in large WANs to handle complex topologies.

- **WAN Diagram:** Visualizes routers and their connections across a large geographical area.

- **Routing Table Visualization:** Explains how routers reference routes for decision-making.
- **Next-Hop Example:** Shows how packets are forwarded step-by-step in a network.

Key Takeaways



- Routing ensures efficient delivery of IP packets across networks.
- **Static routing** is simple but inflexible; **dynamic routing** adapts but requires more resources.
- Routers play a pivotal role in WANs, ensuring connectivity over vast geographical areas.

Static Routing

Review

Switches vs. Routers

- **Switches**: Operate within a **Local Area Network (LAN)** to forward traffic between devices on the same network.
- **Routers**: Operate **between LANs**, forwarding traffic to destinations across different networks.

WAN (Wide Area Network)

- A WAN is a network that spans large geographic areas, connecting multiple LANs.
- Routers enable communication between networks across a WAN.

Static Routing Overview

Static routing involves manually configuring routes on routers. This type of routing is used in small, stable networks or in specific parts of larger networks.

Key Characteristics:

1. **Manually Configured**: A network administrator specifies the route to a destination.
2. **Simple and Resource-Efficient**: No additional CPU or bandwidth is required.
3. **Inflexible**: Routes do not adapt to network changes automatically.

Why Use Static Routing?

- It provides greater control over routing decisions.
- It is efficient for predictable, small, or simple network topologies.

Static Route Configuration

Basic Syntax:

ip route <destination-network> <subnet-mask> <next-hop-IP>

Parameters Explained:

1. `destination-network`: The network you want to route packets to.
2. `subnet-mask`: The subnet mask for the destination network.
3. `next-hop-IP`: The IP address of the next router in the path to the destination.

Static Route with Exit Interface

Another way to configure static routing is by specifying the **exit-interface** instead of the next-hop IP address.

Syntax:

ip route <destination-network> <subnet-mask> <exit-interface>

Example:

ip route 192.168.2.0 255.255.255.0 Serial0/0/0

- In this example, packets destined for `192.168.2.0/24` are sent out the router's `Serial0/0/0` interface.

Default Routes

A **default route** is used when no other route matches the destination of a packet. It serves as a "catch-all" route.

Syntax:

ip route 0.0.0.0 0.0.0.0 <next-hop-IP>

Key Points:

- **`0.0.0.0/0`** represents any network address.
- The router forwards packets that do not match any specific routes to the default route's next hop.

---

1. **Static Route Configuration**:
    - Displays examples of static route syntax and implementation.
2. **Static Route with Exit-Interface**:
    - Demonstrates the alternative method of specifying an interface instead of the next-hop IP.
3. **Default Route**:
    - Highlights the importance of the default route for packets without a specific destination.

Key Takeaways

- **Static routes** are manually configured and suitable for small or stable networks.
- Using the **exit interface** in static routing reduces dependency on the next-hop IP address but can have limitations in complex topologies.
- A **default route** is essential for handling traffic with unknown destinations, especially when connecting to external networks like the internet.