Climograph

Steven Black

Project home: https://github.com/StevenBlack/climographs

Introduction

The motivation for this repository is, given a location, create its clomograph.


See: https://en.wikipedia.org/wiki/Climograph.

Examples (images)

Example: You can pass a single location Entity and get its climograph.


In[339]:=
In[340]:=

In[328]:= climograph Vancouver CITY




Out[340]=






Example: You can pass a list of location Entities and get a list of their climographs.

```
In[329]:= climograph [ New York City CITY , Paris CITY ]
         , TemperaturePlotRange \rightarrow {0, 30}
         , PrecipitationPlotRange \rightarrow \{0, 50\}
         , Background → LightYellow
```





The Code

```
In[341]:=
      ClearAll[climograph];
       (* These are the options, and the defaults, provided
        by the function *)
      Options[climographx] = {
          "StartDate" \rightarrow {1980, 1, 1}
          , "EndDate" → {2022, 12, 31}
          , "InnerFrame" → None
          , "InnerFrameStyle" \rightarrow LightGray
          , "TemperaturePlotRange" → Automatic
          , "TemperatureJoined" → True
          , "PrecipitationPlotRange" \rightarrow Automatic
          , "PrecipitationJoined" → True
            "Background" → White
            "Frame" → True
          , "FrameStyle" → Gray
         };
       (★ The interface for passing a single Entity and options. ★)
       climograph[location_Entity, opts:OptionsPattern[climographx]] := (
          Return[climographx[location, opts]];
         );
```

```
(* The interface for passing a list of Entities with options. *)
climograph[locations_List, opts: OptionsPattern[climographx]] := (
   Return[climographx[#, opts] & /@ locations];
  );
(* This function does the work *)
climographx[location_, OptionsPattern[]] := (
   startDate = OptionValue["StartDate"];
   endDate = OptionValue["EndDate"];
   (* Temperature plot - the upper plot *)
   tempByMonth =
    WeatherData[location, "MeanTemperature", {startDate, endDate, "Month"}];
   tempGroupByMonth =
    GroupBy[tempByMonth["DatePath"], DateValue[First[#], "MonthNameShort"] &];
   tempMinMaxMean = {Min[Map[Last, #]], Max[Map[Last, #]], Mean[Map[Last, #]]} & /@
     tempGroupByMonth;
   tempRange = OptionValue["TemperaturePlotRange"];
   If[ tempRange == Automatic,
     maxTemp = Max[tempByMonth[2][1][1]];
     minTemp = Min[tempByMonth[2][1][1]];
     tempRange = {minTemp, maxTemp} // QuantityMagnitude;
    ), Nothing];
   ptemp = BoxWhiskerChart[
     tempMinMaxMean
     , Joined → TemperatureJoined
     , Frame → {{True, True}, {None, True}}
     , FrameTicks → {{All, All}, {None, All}}
     , PlotTheme → "Detailed"
     , PlotRange → OptionValue["TemperaturePlotRange"]
     , Ticks → All
    ];
   (* Precipitation plot - the lower plot *)
   precipByMonth = DeleteMissing[WeatherData[location,
      "TotalPrecipitation", {startDate, endDate, "Month"}]];
   precipGroupByMonth = GroupBy[
     precipByMonth["DatePath"], DateValue[First[#], "MonthNameShort"] &];
   precipMeanByMonth = Mean[Map[Last, #]] & /@ precipGroupByMonth;
   precipMinMaxMean =
    {Min[Map[Last, #]], Max[Map[Last, #]], Mean[Map[Last, #]]} & /@
     precipGroupByMonth;
   maxPrecip = Max[precipByMonth[2][1][1]];
```


```
minPrecip = 0; (* By definition *)
 If[precipRange == Automatic,
   maxPrecip = Max[precipByMonth[2][1][1]];
   precipRange = {minPrecip, maxPrecip} // QuantityMagnitude;
  ), Nothing];
 pprecip = BoxWhiskerChart[
   precipMinMaxMean
   , ChartLabels → Automatic
   , Joined \rightarrow PrecipitationJoined
   , Frame → {{True, True}, {True, None}}
   , FrameTicks → {{All, All}, Automatic}
   , PlotTheme → "Detailed"
   , PlotRange → OptionValue["PrecipitationPlotRange"]
   , Ticks → All
  ];
 (* Joining the precipitation
  and temperature plots together, and returning *)
 Return[
  GraphicsColumn[
   {TextCell[location["Name"], "Subsection"],
     ToString[startDate[1]] <> " - " <> ToString[endDate[1]], "Text"],
    GraphicsColumn[
      {ptemp, pprecip}
      , Frame → OptionValue["InnerFrame"]
      , FrameStyle → OptionValue["InnerFrameStyle"]
      , Background → OptionValue["Background"]
    1
   },
   Frame → OptionValue["Frame"]
   , FrameStyle → OptionValue["FrameStyle"]
   , Background → OptionValue["Background"]
  ]
 ]
);
```

Live Examples

Example 1: This call with no options produces a default climograph.

```
In[346]:=
       climograph Vancouver CITY
```


Out[346]=





Example 2: This call uses options to set the background color, and normalizes the vertical ranges for both the temperature and precipitation plots.

```
In[347]:=
       climograph [ { New York City CITY ,
                                          Paris CITY
        , TemperaturePlotRange → {0, 30}
        , PrecipitationPlotRange → {0, 50}
        , Background → LightYellow
```

Out[347]=








Example 3: This call uses options to omit the lines joining temperature and precipitation mean values.

In[348]:= climograph Chicago CITY,

TemperatureJoined → False, PrecipitationJoined → False

Out[348]=




Example 4: This call uses options to not show an outer frame.

In[349]:= climograph stanbul cmy, Frame → False Out[349]=

Istanbul

1980 - 2022



Example 5: This call uses options to show the inner frame with a particular style.

```
In[350]:=
```

```
climograph[
```

Tokyo CITY

- InnerFrame → True
- InnerFrameStyle → Directive[Red, Dotted, Thick]

Out[350]=

