

RADBOUD UNIVERSITY

Final Project

Authors:

Steven BRONSVELD
Jelmer FIRET
Thijs van LOENHOUT
Thomas BERGHUIS
Robert KOPRINKOV
Bram PULLES

Teacher:

P. van BOMMEL
Student assistant:
Jan van Bommel

Contents

1	Introduction	2
2	Description	3
2.1	Focus on properties	3
2.2	Product justification	3
2.3	Specifications	3
3	Design	4
3.1	Global design	4
3.2	Detailed design	5
3.2.1	Server-client relation	5
3.2.2	Parties	6
3.2.3	Level design	7
3.2.4	Game rendering	8
3.2.5	Game logic	9
3.3	Design justification	12
4	Project management	13
5	Evaluation	20

1 Introduction

This is the project report for *Arcemii*. Shortly put: Arcemii is a multiplayer rogue-like app for android.

Arcemii came to be, mainly because of one reason: there really wasn't anything like it yet. The idea was actually planted over a year ago. During the summer break before this year, Steven and Thijs wanted to play something with their friends, something with a lot of replayability. We looked for multiplayer rogue-likes, but could not find any. Summer ended, university started, but this idea remained. Now with this course, *Research and Development*, it was finally time to realize it!

Above, the term 'Rogue-like' is mentioned often, and it will be mentioned even more frequently later on. But what is a 'Rogue-like'? According to wikipedia: *Roguelike is a subgenre of role-playing video game characterized by a dungeon crawl through procedurally generated levels, turn-based gameplay, tile-based graphics, and permadeath of the player character, mostly with a fantasy narrative.*

So, Arcemii is a game where you go through randomly generated levels, killing fiends along the way. However, there are few rogue-likes that have a proper multiplayer-mode. This serves as the spot Arcemii has to fill. Alongside that, we want the game to be able to be played in short bursts, like in the break of a lecture. We hope to create something people can jump into easily and can bring them quick enjoyment.

The demographic we aim at, therefore, are people who would like to play a game on their phone with friends. Maybe they normally game on a dedicated system or their pc, but we want to bring that experience, alongside the chaotic fun of multiplayer games, to their phones.

2 Description

2.1 Focus on properties

2.2 Product justification

2.3 Specifications

3 Design

In this section we give a global and detailed description of the design of Arcemii. Furthermore we give a justification for our design choices.

3.1 Global design

3.2 Detailed design

In this section we give a detailed description of the design in terms of classes, methods and attributes.

3.2.1 Server-client relation

Arcemii makes use of clients and a server to enable the possibility for playing the game in multiplayer mode. In this section we will describe the most important details of this server-client relation.

Arcemii can be played in two different modes: offline and online mode (for singleplayer and multiplayer respectively). In both cases, we make use of a server. When playing in offline mode, the server is running in the background of the mobile phone. When playing in online mode the server is running on a dedicated server, which can be connected to through the internet. Apart from this, the only real difference between singleplayer and multiplayer mode is to which ip-address the mobile phone will try to connect. In singleplayer mode, this is the so called **loop back address**, also known as **localhost** or **127.0.0.1**, whereas in multiplayer mode, it tries to connect to the ip of the dedicated server.

Server Let's start with a detailed description of the server. The server-side has four classes: **ArcemiiServer**, **Server**, **ServerGameHandler** and **Console**.

Since the server needs to be able to run on its own, we have a **main** method in the **ArcemiiServer** class. This method creates a new object of all the other classes to start the server. **ArcemiiServer** also contains a **stop** method which stops the **Server** and **ServerGameHandler** classes from running. When the server is run on a dedicated machine, we can just run the program separately from the rest of the application. When the server is run on the background of the mobile phone we just call the **main** method which simulates the exact same behavior, but then locally.

The first class we instantiate when we run the server is the **Console** class. This class creates a terminal interface for interaction with the server. This is very useful when the server is run on a dedicated machine to enable some control over the program. The console has three commands: **help**, **stop** and **log**. The **help** command gives a list of all the available commands. The **stop** command terminates the program. And the **log** command toggles the logging on and off. Logging is very useful for debugging the server. All the classes in the server call the method **log** in the console to send debug information.

The second class we instantiate is the **ServerGameHandler** class. This class, as the name already says, handles all the game logic on the server-side. When this class starts, it creates a new thread which sends an update message to every party on the server every tick (which is set at 20 per second, in the version that was handed in). Apart from this, there are two very important methods in this class. Namely: **addPlayer** and **handlePlayerInput**. When the first method is called, a new thread is created which listens for messages coming from that specific client. Every time a message arrives, the second method is called to handle the message from the client. This method calls the appropriate method for all the possible messages. The messages are all a subclass of the abstract class **Message**. Some examples of messages are:

- **CreatePartMessage**, to indicate to the server that the client wants to create a party.
- **JoinPartyMessage**, to indicate to the server that the client wants to join a specific party.
- **ActionMessage**, to indicate which actions the player wants to execute while playing the game.

The last class we instantiate is the **Server** class. This class continuously listens for new clients, creates a connection with these clients and adds the client to the **ServerGameHandler**. In order to prevent overloading of the server we also check if there is already a client on the server with the same ip-address. If this is the case the old client will be removed since this one is now replaced by the new client. This reduces the load on the server, because the server does not have to listen for messages coming from the old client this way. Note that we have an exception for the **loop back address** to make it possible to connect with multiple emulators to the server for testing purposes.

Client Here we will give a detailed description of the client. The client-side has two classes: **Connection** and **ClientGameHandler**.

The first class, which will be instantiated already from the **MainActivity**, is the singleton **ClientGameHandler** class. The first thing this class does, is create a new connection in either offline or online mode (more about that in the next sub-paragraph). When this connection is created, the client starts listening for messages from the server. This works exactly the same as on the server. We listen for messages and handle the messages with the **handleInput** method.

Next up the **ClientGameHandler** starts a listener for a change in server mode (online / offline), since it is possible to change this setting in the **SettingsActivity**. Whenever a change of server mode is detected, the **ClientGameHandler** stops the old connection and starts a new one.

The last thing the **ClientGameHandler** does when instantiated is start the **gameLoop** method. This method draws the game on the screen and gets the actions of the player and sends these to the server every tick.

The second and last class which will be instantiated is the **Connection** class. This class either starts a connection with the online server or starts a server on the background and connects to this server. The ip-address of the server is set according to the server mode. This class contains the very important method **sendMessage** which is called whenever the client wants to send a message to the server. This class also contains a **stop** method which is very important to prevent memory leaks (due to not stopped threads) and to be able to start a new connection with a server.

3.2.2 Parties

The server keeps track of all the clients using parties. The usage of parties enables the clients to play with their friends. Whenever a client is connected to the server the client can **create** or **join** a new party. This party gets assigned a random so called **party id** which can be used by the players to identify their party and join their friends' party.

As stated in section 3.2.5, every party gets updated per game tick. We also want this update message to be used to determine whether the client is still connected to the server. Upon connection with the server, the client gets assigned a party just for that client. The game update messages from the server, sent to this party every game tick, can then be used to determine the connection status. Note that the connection status does not make use of this feature yet, but this is for future implementations.

A client can only be in one party at the time. When the client joins a new party, it gets removed from the previous party. The party also uses the ready status of all the clients to determine if the master of a party can start a new game. This is only possible when all the clients in the party are ready (except for the master, the master-client is set ready automatically when it sends the `StartGameMessage` to the server).

3.2.3 Level design

Levels are generated each time a new game is started. Levels have to fulfill a number of requirements:

1. The Level should consist of a number of different rooms, connected with roads.
2. The roads connecting different rooms should not intersect (so the graph should be planar).

In order to generate a level, we start off with a small grid that represents the final level on a more global scale. Each cell on this grid is called a `Block` because it represents a cluster of tiles on the full map, and it takes on of the values from the enum `Block` (`Empty`, `Room`, `Road` or `RoomEdge`). On this globalized map of the grid, we randomly pick a number of cells and designate them rooms. Then, we increase the size of the rooms by adding cells bordering room cells to the room, so we get bigger rooms. All of these room tiles are their own ‘island’ still. So, we have a lot of individual rooms that are not connected.

In order to connect the rooms, we see each room as a node in the graph representing the grid and we add an edge between every two rooms of length equal to the manhattan distance between them. This is a better approximation than the eculidean distance, considering roads will only be added above, to the left, to the right and to the top of a room. To get a subset of edges such that none of them overlap, we use the minimum spanning tree, which we find by applying Kruskal’s algorithm. The method `kruskals()` returns an `ArrayList` of `Edges` showing all the edges in the minimum spanning tree. We will use these edges to connect all the rooms. We go through all the edges and do a breadth-first-search from the beginning to the end of every edge and connect the two points with the shortest path. All nodes the shortest path passes through are marked on the global grid as 1×1 tiles (as `Road` from the enum `Block`). However, as rooms contain multiple cells, roads are thinner than rooms. Now we have a level that is connected and is planar. To avoid the begin and the end points of the level spawning too close to eachother, we also monitored the two nodes which are the furthest apart, and put the begin point in one room and the end point in the other. So, the player will awlays have to walk the maximum distance.

Now, we are ready to enlarge the miniature grid with which we have worked until now. For that we create a new grid that contains for every cell `blockheight`

rows and `blockwidth` columns, and we simply enlarge the miniature grid, copying every cell from the miniature grid into the bigger grid but `blockwidth` \times `blockheight` times bigger. In this process, everything that is `Empty` (so not a road or a room) is converted to an empty tile. Empty tiles are converted to walls.

Now we have an empty level and have to fill it with monsters. We go through all the cells, randomly assigning turning a room into a room with skeletons, with slimes and with slimes and skeletons. If we find that a cell is the end point, we spawn the boss in that cell.

3.2.4 Game rendering

Arcemii makes use of animations and static sprites in-game. These have to be displayed on the screen properly. In this section, everything concerning this, is explained.

GameView The rendering of the level with all it's entities is done in the `GameView` class. `GameView` extends the standard Android `View`, therefore it has to be assigned to a layout. This is done within the `GameActivity` class (`client/activities/GameActivity.java: onCreate`). After it is assigned to a layout, the `init()` method is called to initialize all objects used in rendering of the `GameView`, using the dimensions of the layout. Then two methods are used to render levels: `updateLevel` and `onDraw`. `updateLevel(Level)` prepares a level to be drawn by converting it's tiles and entities to `RenderItems`, and figuring out in which order to draw them. `onDraw(Canvas)` then takes these `RenderItems` and draws them to the canvas in such a way that the player is centered. Locks are used between these functions because `onDraw` is executed on a different thread than `updateLevel` and they both use the `renderItems` list.

RenderItem All aspects of rendering a single texture are handled in the `RenderItem` class. A `RenderItem` contains the following attributes:

- `texture` defines which bitmap to draw.
- `x,y` defines the position where the texture should be drawn.
- `refX,refY` defines the position within the bitmap used for alignment.
- `layer` defines the layer on which this object is drawn.
- `animationOffset` the number of frames this object's animation is ahead of the default animation
- `rotation` defines the number of degrees to turn this image counter-clockwise.
- `flip` defines whether this image should be flipped horizontally.

The function `compareTo(RenderItem)` determines which of two `RenderItems` should be drawn first. The function `renderTo(Canvas)` renders this `RenderItem` to the canvas, applying all transformations specified.

Texture This class handles the loading of textures, to prevent a **Bitmap** to be loaded every time it needs to be drawn. It has a **HashMap** that stores all textures using a **String** as a key. The key corresponds to the path of the texture within the assets/sprites folder. **getTexture** is a factory method that loads a **Bitmap** to the **HashMap** if necessary and returns the corresponding **Texture** object. **getBitmap** returns the **Bitmap** associated with a **Texture** object.

Animation **Animation** is a decoration of the **Texture** class, in order to be able to handle animations. It's **getBitmap** method takes the current time into account to return a certain frame of the animation.

Generation of RenderItems **RenderItems** are created in the classes of the objects they visualize (`shared/entities/...`; `shared/tiles/...`). This was done to prevent shadow classes for each entity that only generates **RenderItems**. Unfortunately the objects are shared between the server and client, which means that a server can't be run without compiling all the client code with it. We didn't find it worthwhile to adjust this before the deadline, as we would run the server from within Android Studio for testing.

3.2.5 Game logic

Before we can explain how the game logic works, a few definitions have to be given:

Tile **Tiles** are the building blocks of Arcemii's levels. A **Tile** can either be solid or non solid, meaning entities can either move through it or not. The most important **Tile**-types are:

Wall A solid tile.

Empty A non-solid tile.

Void A tile outside of the bounds of the level.

Start A tile on which players are spawned at the start of a game.

Finish A tile denoting the final room of a level.

Entity An **Entity** is a non-tile game-object with a specific position within a level. An **Entity**'s position is not limited to whole numbers (where the a **Tile**'s position is). Every **Entity** is identified by a unique UUID. The entities currently implemented are:

Player Controlled by the actual players of the game.

Skeleton Enemy of player, shoot arrows and flees from the player.

Slime Enemy of player, attacks player by jumping toward them.

Boss Enemy of player, teleports and summons slime entities.

Arrow Flies in certain direction, can either hit player or non-player entities. Deals damage to entities it hits.

Level A level contains a grid of tiles (instances of the `Tile` class). These tiles represent the world. Furthermore the level contains a list of entities (instances of the `Entity` class). A more detailed description can be found in 3.2.3.

Ability Arcemii is based on the notion of abilities. Players can choose the abilities they want to use in the game at the beginning of a run. Every entity has abilities. An **Ability** can be executed with `execute`. When a **Ability** is executed, its action is performed on the level or the entity that performed the **Ability**. An **Ability** can be executed directly, or in some cases it can be invoked first. If an ability is invoked, certain parameters needed to execute the abilities are set. For example: if an entity wants to execute the **Move** ability, it needs to specify in which direction it wants to move, so the entity has to invoke the ability with a `direction` parameter. How invocation a execution works in practice is explained in more detail later. What follows is a list of some of the abilities present in Arcemii:

Bow When `executed`: create a new arrow entity.

To `invoke`: The direction in which to shoot, as well as information about whether it can hit the player or not.

Heal When `executed`: heal the entity that executed the ability

To `invoke`: The amount to heal is needed

Melee When `executed`: deals damage to entities in range of the entity that executed the ability.

To `invoke`: whether to damage players and the amount of damage is needed.

Teleport When `executed`: teleports the entity that uses it.

To `invoke`: The direction in which to teleport is needed.

Additionally, **Move** and **Spawn**, etc, are also abilities, albeit not explicitly for the user. Everything a player can do, is seen as an ability, and every **Ability** could theoretically be executed by every **Entity**.

Game logic explanation Because Arcemii is a multiplayer game, it is split into two main sections: the server and the client. In relation to the actual game, the client acts only as the view, and a little bit as the controller part. The actual game logic happens on the server side. The current state of the game is saved as a property of **Party**, because each party has their own game-state. This game-state is saved in the shared object **Level**. The level class contains the current world-state of the game. The server-gameloop updates all parties every `TICKSPEED` amount of time. When a party is in-game, and `update` is called the following happens:

1. **Invoke** The `invokeAll` method of all entities, except for players, is called. This method invokes all abilities that the entities want to execute (based on their A.I.). All executed abilities are saved in an `actions` list. The actions players want to take are added to their respective `actions` when they submit new actions to the server.
2. **Execute** All entities now have a list of the actions they want to execute. The execute method of these actions (abilities) are called and the changes are recorded.

3. **Send updates** All changed entities are collected and sent to all party members.

3.3 Design justification

4 Project management

Introduction

This section contains a log for the process of building our teams second app for the *Research and Development* Course at Radboud University. Our process will be presented in a weekly description of the active tasks that week, project meetings, assignment of tasks, problems we encountered, etc.

Week 19

After the spring break, in which we did not yet start our new project as most would've been unable to work on it, we decided that a meeting on Monday morning would be wise. This meeting took place in Mercator I, lasted from 10:30 till 12:15, and was attended by Jelmer, Robert, Steven, Thijs and halfway through also by Thomas. The main topic of this meeting was choosing which app idea we would run with. We had three prominent ones:

- A multiplayer dungeon crawler. This idea had us very excited at first, but we realized that this would mean a very similar project structure to the Sokoban app of the previous assignment, so we dismissed the idea.
- An medical application in cooperation with medicine students, as suggested by Patrick van Bommel. This idea seemed cool, but did not motivate us as much, as we would have to deal with outside requirements instead of our own ideas about what would make a good addition to the app.
- A Mario-party-like game with multiplayer minigames. By now we had settled on the idea of building a game, as we had a lot of fun doing the previous assignment. By making a game centred around minigames, we think we'll be able to make this process fun for ourselves. We'll have to put some effort in making a connection between two phones.

The third is the idea we had settled on about halfway through the meeting. We made some sketches of the project layout and brainstormed on some minigames (like spyfall and charades)

We planned our next meeting for Thursday, third block. By then, Steven will have set-up a new Github repository.

Thursday we had our next meeting, which was attended by everyone. In the previous days, we had all thought about the idea of something using a server, and had become sceptical about how good of an idea it was. We discussed the following risks:

- Our app will probably be tested by one person, but they will have to be able to use the app's full functionality to properly grade it. Robert has sent an e-mail to our TA with questions about this, so we'll await their response and then look at this risk again.
- It is risky that our whole app relies on one connection. If something goes wrong in the connection part, the whole app will suffer from it.

- Four weeks for an app is already a short timeframe. Will we be able to afford the time to spend on multiplayer functionality? This is something we'll have to decide upon once we have more concrete ideas about games we'd like to make.

Because of the above mentioned risks, we further discussed the possibilities of single-player games, as the idea of the app being a game remained unchanged. Thomas and Thijs were charged with the task to think about games in the rogue-like genre, in order to see if such a game would be a valuable app idea. Steven will make the structure of a client-server program. This way, we can have some extra days to decide on our idea, as we'd like the whole group to be fully behind it, hard as it is, while also getting started on some code.

Week 20

We had our first meeting of the week on Monday morning, again. Over the weekend, more doubts about the party-game idea had arisen. Everyone was present, though Robert was there only the second half. First order of business was making the final decision for our idea. We all felt this was actually long due, and were all a bit frustrated because of this. So: today we were to make a definite decision and we would stick with it.

Our main two problems with the party game were design-problems: we would have to make some smaller, individually not very impressive things, that would have a very simple structure. This did not feel like enough of a challenge, even the multiplayer aspect taken into account. The second problem was that it would be hard to make it one well-rounded app. Additionally, because it had pieces that were so disjunct from others, we would evade the whole project idea of this course. To conclude: we switched back to the idea of one game. till multiplayer. The remaining of the meeting, we discussed possibilities. Firstly, we looked at possibilities to expand on one of the discussed minigames:

- Curve Fever
- Bomberman
- Spyfall

However, for the aforementioned reason of not being complex enough, we looked further. A game like hill-climb racing was discussed, but we did not have concrete enough ideas for implementing multiplayer into that game. In the end, we landed on the idea of a multiplayer rogue-like yet again. Here is a small run-down of how we envision it:

You create a party with your friends. Every player is presented a random selection of 'abilities', of which they can choose some. They enter a level of some kind and fight enemies. On the end of a level, there is a 'boss fight', after which the players are rewarded and can go down to the next level. Some opportunities for player-versus-player were mentioned, like the strongest player being a final boss after all levels had been completed, but we decided to postpone these ideas.

When Robert joined us for the meeting, he and Steven discussed the way we would tackle the multiplayer/server aspect code-wise. They proposed different approaches:

- Steven suggested to start with a full-scale client-server connection, so that we would not have to spend much time later on in the project to change existing code to make it suitable for multiplayer and such.
- Robert suggested to first make the game in single-player form and add multiplayer later, as this could prove tricky and time-consuming.

It was agreed upon that Steven would work on his vision for the next meeting, where we would decide if we would stick with it or not.

Thursday was our next meeting. Everyone but Steven was present, because he 'is too cool to use the bus'. We started a Discord-call with him however, and he showed us his work from the past days. In the end, he used Roberts approach. Thijs made a little character animation to look at possible styles and possibility for animations. We'll definitely use pixel-art, as it is less time-consuming while still being charming.

Main item on the agenda were dividing task:

- Jelmer: Graphics rendering
- Bram: Being able to create and join parties
- Robert: Dungeon generation
- Thijs: Sprites
- Thomas: Looking at abilities

Week 21

As usual, we had our first meeting on Monday morning. Everyone was present, though Robert only attended the second half. We started with discussing what everyone had achieved over the weekend. Actually, the divided tasks were pretty big, so everyone was still busy with them. Because of Jelmer's rendering, we could see the first animations on screen.

We then discussed the game envisioned in more detail:

- We want players to be able to play the game in short bursts (like in the breaks in the middle of lectures), so we're aiming at 15-20 minutes per total game. That means that we'll probably have 3 levels per game. In the future, we can expand this with an option to choose between a short, medium and long game.
- We'll start with making just 3 abilities, of which the player can choose 2 or 3 at the beginning of the game. The idea is that this will be easy to expand on later.
- For enemies, we'll start with 3 basic ones:
 - An enemy that does damage on touch: a slime. A slime will be able to make a jump attack.
 - An enemy that attacks with range: a skeleton that will shoot at players.

– A boss that is bigger and does more damage.

- We discussed abilities being on cooldown versus using mana to use them. The majority is pro cooldown, but we'll come back to this later when the implementation becomes relevant.

We set our next meeting for Thursday and gave everyone new tasks (well, most of them are continuations of the last ones). New ones are:

- Steven: make it able to test multiplayer.
- Thomas: work on ability selection
- Bram: finalize the lobby activity.

Thursday was our second meeting. Everyone but Thomas was present. This is very inconvenient, as he did not finish his task.

Jelmer had continued with his rendering and the only thing left is rendering outside of a level.

Thijs was assigned the task to work on some sprites, and he made these animations:

- Idle and walking animations for 4 player characters
- Idle and jumping animations for a slime
- Idle, walking and shooting animations for a skeleton
- A floating animations for a boss
- A tree

Robert is almost done with the dungeon generator, and he'll finish this for next Monday. We made some more dungeon specifications for him to generate: enemy locations and start en goal positions.

Thijs and Bram discussed the layout and style for the different activities. Mainly, the lobby activity, where the party waits for the game to start and players choose their abilities, has to change so that abilities will actually be able to be chosen. This is a task given to Bram for next Monday.

Steven aims to make all game-logic that is not directly dependent on tasks given to others.

Thomas is given the task to start on the in-game UI.

Saturday, Steven implemented a simple skeleton AI, but this will need later polish, as the skeletons just run away to the upper-right corner (even walking through strees that are supposed to be solid)

Week 22

At Steven's request, because he had an appointment, the meeting started later than usual. This meant a shorter meeting, as Thomas had to leave us in the break. Sadly, not everyone was on time, so we effectively had only 45 minutes for our meeting. This is very sub-optimal as we start to realize that there is still a *lot* of work to be done before we have an presentable application.

Robert has completed the dungeon generator, but will make some final adjustments before he will merge it with the master branch on GitHub.

Steven did some work on passing objects between the server and the client. Still a lot has to be done in this part before we can properly test everything. A big part of our struggles are that most tasks seem intertwined with others: Thomas would like to work on in-game abilities, but he can't until a proper connection is made. Bram would like to work on the lobby activity, but this has little meaning when there are no abilities.

An important breakthrough this weekend was that Bram was able to join Jelmer via the app! This means the connection that *is* being made, will probably work correctly later on. Still though, we realize that working with multiplayer was probably a very ambitious idea and the risks we were afraid of in earlier weeks are staring us in the face.

Bram spent most of his weekend working on a bug that causes the player not to enter a good multiplayer mode after they have first switched to singleplayer mode – as a side note: there is a singleplayer toggle added, which just ‘tricks’ the app into thinking it's local device is the server, for the purpose of testing and later on for true offline game possibilities.

Thomas has not been busy yet with the UI and controls. We urge him to look at this quickly, we want (theoretical) player movement by Thursday!

Thursday was Ascension Day, and the university was closed. We did not arrange a meeting, as most had family-obligations to attend, but we discussed some important things via Whatsapp, so that everyone would still be able to work this weekend.

There were some problems with the dungeon generation (namely that rooms are not connected) that Robert fixed immediately at Wednesday.

Thursday, Thomas added a joystick for movement, but this is not yet fully integrated in the app.

Week 23

This is the final week of this project and because we still have a lot to do, we'll discuss our activities on a day-by-day basis for this week. But first, these are the major things we'll have to work on to make our app ready for submission:

- Most importantly: the game is not yet playable. To change this, we'll have to make sure player movement works, abilities can be cast and entities have health and can be killed. As we had these ideas already when we started coding, the structure for these properties is already present. We'll just have to implement them. Steven will work on the first two points, and Jelmer on the last. Problematic is, that Thomas needs to clean up his code behind the in-game UI first.
- Multiplayer will have to work on mobile phones. In theory, this has to work, but the previous assignment has taught us that a theoretically working program isn't everything, especially not on the subject of reliability. To properly test this, the points mentioned above should be implemented first, so that we can be sure the server-client connection handles these request properly.

- There needs to be a lobby activity where players can choose their abilities.

Additionally, there are a lot of things that need polish, or would be very nice to be implemented as well: the overall UI is pretty terrible and ugly, music would be nice, there are a lot of animations not yet used, while the situations where they should be used are present, you can still walk through walls even though stat should not be possible.

Monday 10:30 was our standard meeting and it was...stressfull. Everyone was present. The deadline is creeping closer and closer. We discussed the main tasks mentioned above. Steven will work on movement and ability casting. Bram will make multiplayer ready for mobile phones and look into some nasty bugs. Jelmer will take on enemy UI and in-game logic like nog being able to walking through trees. Thijs will add app-icons and a melee attack animation. Thomas will have to make this ability cards in the in-game UI change dynamically and Robert will have to make the lobby activity, including choosing abilities. Everyone should finish their tasks before an additional meeting planned on Wednesday, 15:15.

Today, we received our Sokoban grade, and this served as a major boost to our morale: we got a 9.5!

Tuesday, an unscheduled meeting happened organically. Thomas was not present, Robert was later. Thijs will make the music player this afternoon. Bram will make is so that the hosting player can only start the game when all other players are 'ready', a state they can toggle to using a button. Player will also be able to press 'ready' when they have chosen three abilities. All these tasks were completed this afternoon. Bram also made the first multiplayer contact where both players can walk (still using emulators though) Jelmer made health changeable and improved the AI.

Wednesday, Thomas was not at the meeting. Steven added most of his documentation (others added theirs directly after writing the code). He also fixed the UI buttons, so the app won't crash anymore when pressing them and also made the player able to shoot arrows. Thijs improved the lobby UI and added general styles in the XML. Bram fixed more of the bugs occurring when trying multiplayer, and made singlelayer not crash the app again.

At Thursday's meeting, everyone was present. Thomas made these buttons change dynamically (later than the deadline). Today, we had the first mobile multiplayer test, admittedly a bit late, but earlier was not viable due to reasons explained above. And the result was...the app crashed almost immediately. We suspected that Jelmer's server, which we used, was not powerful enough. Steven's priority will now be optimization of this process. Jelmer made a lot of fixed with the arrows. Everyone but Thomas had a call on Discord for the entire evening making small fixes, testing, polishing. Thijs made a gif for the main activity. Multiplayer runs a lot smoother now. Not very smartly, everyone was quickly pushing to GitHub, causing a lot of merging problems. Bram added the boss' teleport ability to the player's ability options, but this is still buggy.

Today is presentation and hand-in day! Although it was not planned, everyone was making a lot of small changes this morning: teleport is less buggy, server testing, etc. Testing is actually a lot of fun now.

Bram and Jelmer gave our presentation to Jan van Bommel, our TA. This went very well. Everything ran smooth and there were no server problems. His joking reaction was ‘that we are crazy to have done this’, hinting at the amount of work it must have been. He said everything looked good and he did not note any points of improvement. This is good news and made us relax! The afternoon was spent by making more small changes, like scaling the ability cards in-game nearest-neighbor instead of bilinear, before Robert handed in the app.

5 Evaluation