

CS561: Database Management Systems Notes

Steven DeFalco

Fall 2023

Contents

1	Introduction	2
2	Entity-Relationship Model	3
2.1	Attributes	3
2.2	Keys	4
2.3	E-R Diagrams	4
3	Relational Model	4
3.1	Query Languages	5
3.2	Relational Algebra	5

1 Introduction

Database management systems (DBMS) consist of **data**, **software** (programs such as data interfaces), and **environments** (operating systems). DBMS contains information about a particular enterprise. They are collections of interrelated data, a set of programs to access the data, and an environment that is both *convenient* and *efficient* to use. The *user* should only have to define what it is that they want from the database, whereas the *database* is responsible for defining how this query can be fulfilled; relational databases are good at this.

The three primary data models are **entity-relationship model** (diagrams), **relational model** (relational algebra), **relational database** (SQL).

Drawbacks to using **file systems** to store data include the following:

- data *redundancy* and *inconsistency* (multiple formats, duplication of information, etc.)
- difficulties in *accessing* data
- data isolation (multiple files and formats)
- concurrency issues (among multiple users)
- *integrity* problems
- atomicity of updates
- security problems (hard to provide varied levels of user access)

There are varying **levels of abstraction** in a database. The **physical level** defines how a record is stored. The **logical level** describes data stored in the database and the relationships among data. The **view level** is a way to hide details of data types and information for security purposes.

The **schema** is the logical structure of the database; this is analagous to type information of a variable in a program. **Physical schema** refer to database design at the physical level. **Logical schema** refer to database design at the logical level. An **instance** is the actual content of the database at a particular time; this is analagous to the value of a variable. **Physical data independence** is the ability to modify the physical schema without changing the logical schema.

Remark The schema of a table is the attributes of the table. For example, the schema of a table whose column titles are "A,B,C,D" is simply A,B,C,D.

Data manipulation languages (DML) are languages for accesing and manipulating the data organized in a DBMS. **Procedural languages** are ones in which the user specifies what data is required and how to get that data.

Declarative (nonprocedural) languages are ones in which the user specifies what data is required without specifying how to get such data. **SQL** is the most widely used query language.

A *data definition language (DDL)* is the specific notation for defining the database schema. The *DDL compiler* generates a set of tables stored in a data dictionary. Data dictionary contains metadata.

A *relational database* is based on the relational data model. Data and relationships among the data are represented by a collection of tables. These include both a **DML** and **DDL**. The most common relational database systems employ the **SQL** query language.

2 Entity-Relationship Model

A *database* can be modeled as a collection of entities or a relationship among entities. An *entity* is an object that exists and is distinguishable from other objects (e.g. specific person, company, even, plant). These *entities* have *attributes* (e.g. people have names and addresses). An *entity set* is a set of entities of the same type that share the same properties (e.g. set of all persons, companies). In the ER-model we refer to specific objects as *entities* which have *attributes* and are all a part of the entire *entity set*.

A *relationship* is an association among several entities. A *relationship set* is a mathematical relation among $n \geq 2$ entities, each taken from entity sets.

$$\{(e_1, e_2, \dots, e_n) | e_1 \in E_1, e_2 \in E_2, \dots, e_n \in E_n\}$$

where (e_1, e_2, \dots, e_n) is a relationship.

2.1 Attributes

An *attribute* can also be property of a relationship set. For instance, the *depositer* relationship set between entity sets *customer* and *account* may have the attribute *access-date*. Relationship sets that involve two entity sets are *binary* (degree two). Relationship sets may involve more than two entity sets. Relationships between more than two entity sets are rare (i.e. most are binary).

An *entity* is represented by a set of attributes, that is descriptive properties possessed by all members of an entity set. *Domain* is the set of permitted values for each attribute. The **types of attributes** include the following:

- *simple* (atomic) and *composite* attributes
- *single-valued* and *multi-valued* attributes

- *derived* attributes (can be computed from other attributes)

When attributes are *simple* and *single-valued*, then we say that the data is in **First Normal Form**.

2.2 Keys

A **super key** of an entity set is a set of one or more attributes whose values uniquely determine each entity. Once you have defined a *super key*, you can add attributes and it is still considered a *super key*. A **candidate key** of an entity set is a minimal super key (e.g. *customer_id* is a candidate key of *customer*). Candidate keys *only* contain the necessary attributes to make something unique. Although several candidate keys may exist, one of the candidate keys is selected to be the **primary key**.

The combination of primary keys of the participating entity sets forms a super key of relationship set. This means a pair of entity sets can have at most one relationship for each access.

A relation schema may have an attribute that corresponds to the primary key of another relation. The attribute is called a **foreign key**. Foreign key is the primary key of the parent table. Only values occurring in the primary key attribute of the **referenced relation** may occur in the foreign key attribute of the **referencing relation**.

2.3 E-R Diagrams

Rectangles represent entity sets. Diamonds represent relationship sets. Lines link attributes to entity sets and entity sets to relationship sets. Ellipses represent attributes: double ellipses represent multivalued attributes while dashed ellipses denote derived attributes. Underline indicates primary key attributes.

3 Relational Model

Formally, given sets D_1, D_2, \dots, D_n a **relation** r is a subset of

$$D_1 \times D_2 \times \dots \times D_n$$

Thus, a relation is a set of n -uples (a_1, a_2, \dots, a_n) where each $a_i \in D_i$.

Each attribute of a relation has a name. The set of allowed values for each attribute is called the **domain** of the attribute. Attribute values are (normally) required to be **atomic**; that is, indivisible. Domain is said to be atomic if all its members are atomic. The special value *null* is a member of every domain. The null value causes complications in the definition of many operations.

A_1, A_2, \dots, A_n are attributes. $R = (A_1, A_2, \dots, A_n)$ is a **relation schema**. $r(R)$ denotes a relation r on the relation schema R .

The current values (**relation instance**) of a relation is specified by a table. An element t of r is a *tuple*, represented by a row in a table. Relations are unordered and thus the order of tuples is irrelevant (tuples may be stored in an arbitrary order).

A **database** consists of multiple relations. Information about an enterprise is broken up into parts, with each relation storing one part of the information. The two types of database management systems are OLTP (**Online Transactional Processing**) and OLAP (**Online Analytical Processing**). OLTP databases are update/change oriented (*most* common databases are this category): write oriented. OLAP databases are for viewing and analyzing the data: read oriented. In OLTP, a good table is a table about *one thing only*: **third normal form**. For example, a good OLTP table will have a table containing information about customers only and customers only. OLTP tables are normalized, but OLAP tables must be denormalized and this can be achieved by using *join operations*.

3.1 Query Languages

A **query language** is a language in which users request information from the database. **Pure languages** are relational algebra, tuple relational calculus, or domain relational calculus. *Pure languages* form the underlying basis of query languages that people use.

3.2 Relational Algebra

Relational algebra is a procedural language with six basic operators:

- select: σ **WHERE** in SQL
- project: Π **SELECT** in SQL
- union: \cup **UNION** in SQL
- set difference: $-$ **EXCEPT** in SQL
- cartesian product: \times **, (comma)** in SQL
- rename: ρ **AS** in SQL

The operators take one or two relations as inputs and produce a new relation as a result.

Example 3.1 Translate the following relational algebra to SQL...

- $\sigma_{A=B \wedge D>5}(r)$
 SELECT * FROM r WHERE A=B and D>5

- $\Pi_{A,C}(r)$
SELECT A,C FROM R
- $r \cup s$
SELECT * FROM r
UNION
SELECT * FROM S