

# Computational Models of Motion

Contact Mechanics

*Slides adapted from David Hahn*

# Motivation



# Motivation



# Motivation



- Contact constraints
- Coulomb friction
- Hard vs. soft constraints
- Soft body simulation

# Contact Constraints

- 1D point mass ( $x, m$ )

$$m\ddot{x} = f$$

- Gravity


$$f_{\text{ext}} = -9.81m$$

- Obstacle (floor)

$$x \geq 0$$

- Contact force

$$f_{\text{floor}} = \lambda$$



# Contact Constraints

- 1D point mass ( $x, m$ )

$$m\ddot{x} = -9.81m + \lambda$$


$$x \geq 0$$

- Contact force must never pull

$$\lambda \geq 0$$

- No contact force without contact

$$x \lambda = 0$$





# Complementarity Formulation

- Complementarity problem: find  $\mathbf{z} \in \mathbf{R}^n$  such that

$$\mathbf{0} \leq \mathbf{z} \perp \mathbf{f}(\mathbf{z}) \geq \mathbf{0} \quad (1)$$

where  $\mathbf{f}(\mathbf{z}): \mathbf{R}^n \rightarrow \mathbf{R}^n$  is a continuous function

- The complementarity condition (1) is short for

$$\mathbf{z} \geq \mathbf{0}, \quad \mathbf{f}(\mathbf{z}) \geq \mathbf{0} \quad \text{and} \quad z_i f_i(\mathbf{z}) = 0 \quad \forall i$$

- Complementarity conditions avoid discontinuous functions
  - Modeling  $\lambda = \lambda(x)$  would require  $\lambda \rightarrow \infty$
  - Using  $\lambda$  and  $x$  as independent variables with complementarity conditions avoids these problems



# Linear Complementarity Problems

- Linear Complementarity problem (LCP): find  $\mathbf{z} \in \mathbf{R}^n$  such that

$$\mathbf{0} \leq \mathbf{z} \perp \mathbf{f}(\mathbf{z}) \geq \mathbf{0}$$

where  $\mathbf{f}(\mathbf{z}) = \mathbf{M}\mathbf{z} + \mathbf{q} : \mathbf{R}^n \rightarrow \mathbf{R}^n$  is an affine function

## Remarks

- LCP are truly nonlinear problems
- Useful for numerical modeling of contact mechanics problems


# Contact constraints

- 1D point mass ( $x, m$ )

$$m\ddot{x} = -9.81m + \lambda$$


$$0 \leq \lambda \perp x \geq 0$$

- What happens on impact?
  - Stay on the floor or
  - Bounce back?
  - If so, how fast?




# Contact constraints

- Real world: no perfectly rigid objects
- What happens on impact?
- Rigid model: no deformation allowed




# Elastic Contact

- Real world: no perfectly rigid objects




# Elastic Contact

- Real world: no perfectly rigid objects




# Elastic Contact

- Hertz theory of elastic contact
  - Moving down, surface in contact
  - Upward force causes compressive wave



- Hertz theory of elastic contact
  - Shock wave reflects on the free surface
  - Maximal compression







# Contact Constraints

- Hertz theory of elastic contact
  - Moving back up, contact breaks
  - Duration of contact:

$$t_c \sim \sqrt[5]{\frac{m^2}{E^2 R v}}$$



- Real world: no perfectly rigid objects




# Bridging Rigidity and Elasticity

- Real world: no perfectly rigid objects

$$m\ddot{x} = -9.81m + \lambda$$

$$0 \leq \lambda \perp x \geq 0$$


- Rigid model: no deformation allowed



- Perfectly elastic contact  
→ velocity reflection

$$x = 0 \wedge \dot{x}^- < 0:$$

$$\dot{x}^+ = -\dot{x}^-$$



# Contact with Impact Law

- 1D point mass ( $x, m$ )

$$x > 0:$$

$$m\ddot{x} = -9.81m$$


Free flight

$$x = 0 \wedge \dot{x}^- < 0:$$

$$m\ddot{x} = -9.81m + \lambda$$

$$0 \leq \lambda \perp (\dot{x}^+ + \dot{x}^-) \geq 0$$

In contact



# Time Discretization

- BDF1 (aka. implicit Euler)

$$m\ddot{x} = f$$

$$m\dot{v} = f$$

$$\dot{x} = v$$

$$m(v_{i+1} - v_i) = \Delta_t f(x_{i+1})$$

$$x_{i+1} - x_i = \Delta_t v_{i+1}$$

$$\underbrace{mv_{i+1} - mv_i - \Delta_t f(x_i + \Delta_t v_{i+1})}_{r(v_{i+1})} = 0$$

$$\text{init: } \hat{v} = 0$$

$$S = dr / d\hat{v}$$

$$\Delta_v = -S^{-1}r(\hat{v})$$


$$\hat{v} \leftarrow \hat{v} + \Delta_v$$

$$\text{loop while } \|r(\hat{v})\| > \varepsilon$$

- How to include constraints?

- BDF1 (aka. implicit Euler)
- How to include constraints?

$$\underbrace{mv_{i+1} - mv_i - \Delta_t f(x_i + \Delta_t v_{i+1})}_{r(v_{i+1})} = 0$$



$$\begin{aligned} r(v_{i+1}) &= \lambda \\ 0 &\leq \lambda \perp (x_i + \Delta_t v_{i+1}) \geq 0 \end{aligned}$$



- BDF1 with contact constraints

$$r(v_{i+1}) = \lambda$$

$$0 \leq \lambda \perp (x_i + \Delta_t v_{i+1}) \geq 0$$

$$r(\hat{v} + \Delta_v) \approx r(\hat{v}) + \frac{dr}{d\hat{v}} \Delta_v$$

- Leads to LCP for the unknown  $\Delta_v$

$$\frac{dr}{d\hat{v}} \Delta_v = \lambda - r(\hat{v})$$

$$0 \leq \lambda \perp (x_i + \Delta_t(\hat{v} + \Delta_v)) \geq 0$$

- Leads to LCP for the unknown  $\Delta_v$

$$\frac{dr}{d\hat{v}} \Delta_v = \lambda - r(\hat{v})$$

$$0 \leq \lambda \perp (x_i + \Delta_t(\hat{v} + \Delta_v)) \geq 0$$

- Formulate as Quadratic Program (QP)

$$\min \frac{1}{2} \Delta_v^t \frac{dr}{d\hat{v}} \Delta_v + \Delta_v^t r(\hat{v})$$

$$\text{s.t. } \Delta_v \geq -(\hat{v} + \frac{1}{\Delta_t} x_i)$$

- Note:  $\lambda$  and complementarity conditions are implicit

## Reminder: Inequality Constrained Problems

- Lagrangian 
$$\mathcal{L}(x, \lambda) = f(x) + \sum_{i \in \mathcal{E} \cup \mathcal{I}} \lambda_i c_i(x)$$
- First-order optimality (KKT) conditions

$$\nabla_x \mathcal{L}(x^*, \lambda^*) = 0,$$

$$c_i(x^*) = 0, \quad \text{for all } i \in \mathcal{E},$$

$$c_i(x^*) \geq 0, \quad \text{for all } i \in \mathcal{I},$$

$$\lambda_i^* \leq 0, \quad \text{for all } i \in \mathcal{I},$$

$$\lambda_i^* c_i(x^*) = 0, \quad \text{for all } i \in \mathcal{E} \cup \mathcal{I}.$$

**Feasibility:** Inequality constraints have to be satisfied

**One-sidedness:** Inequality constraints can only push, not pull

**Complementary slackness:** Either constraint is active, or its LM is zero

- BDF1 w/ contact constraints

$$r(v_{i+1}) = \lambda$$

$$0 \leq \lambda \perp (x_i + \Delta_t v_{i+1}) \geq 0$$


$$r(\hat{v} + \Delta_v) \approx r(\hat{v}) + \frac{dr}{d\hat{v}} \Delta_v$$

$$\min \left( \frac{1}{2} \Delta_v^\top \frac{dr}{d\hat{v}} \Delta_v + \Delta_v^\top r(\hat{v}) \right)$$

$$\text{s.t. } \Delta_t \Delta_v \geq -(x_i + \Delta_t \hat{v})$$


# Time Discretization

- BDF1 with contact constraint



- BDF1 with impact law
  - Solve unconstrained equations of motion
  - Apply impact law when contact detected

$$x_{i+1} \leq 0 \wedge v_i < 0:$$
$$0 \leq \lambda \perp (v_{i+1} + v_i) \geq 0$$



# Hard vs. Soft Constraints

Hard constraints

$$x \geq 0$$

$$f_{\text{floor}} = \lambda$$



Soft constraints

$$x < 0: \quad f_{\text{floor}} = kx$$


$$x \geq 0: \quad f_{\text{floor}} = 0$$

- Formally unconstrained
- Conservative force (spring analogy)
- Nonlinear force




# Soft Constraints


- BDF1, BDF2 with soft constraints



# Comparison




# Comparison



- So far: 1D motion normal to floor
- Rigid contact: complementarity condition  
Restitution modelled via impact law
- Soft contact: allow (small) constraint violation  
Conservative forces – no need for impact law

# Coulomb Friction


- Now: tangential motion in contact
- Coulomb model:  $f_t \leq \mu f_n$
- Sticking:  $f_t < \mu f_n \quad \wedge \quad v_t = 0$
- Sliding:  $f_t = \mu f_n$



- 2D point mass

$$m\ddot{\mathbf{x}} = \mathbf{f}, \quad \mathbf{x} = \begin{pmatrix} x \\ y \end{pmatrix}, \quad \mathbf{f}_{\text{ext}} = \begin{pmatrix} 0 \\ -9.81m \end{pmatrix}$$

- Floor  $\mathbf{n}^\top \mathbf{x} \geq 0$ ,  $\mathbf{n} = \begin{pmatrix} n_x \\ n_y \end{pmatrix} = \begin{pmatrix} \sin \alpha \\ \cos \alpha \end{pmatrix}$



- Contact force  $\mathbf{f}_{\text{floor}} = \mathbf{f}_n + \mathbf{f}_t$ ,  $\mathbf{f}_n = \mathbf{n}\lambda$ ,  $\|\mathbf{f}_t\| \leq \mu \|\mathbf{f}_n\|$
- How to determine  $\mathbf{f}_t$ ?

# Maximum Dissipation Principle

Out of all admissible tangential forces  $\tilde{\mathbf{f}}_t \in \mathcal{F}$  with

$$\mathcal{F} = \{\tilde{\mathbf{f}}_t \mid \|\tilde{\mathbf{f}}_t\| \leq \mu \|\mathbf{f}_n\|\},$$

the friction force  $\mathbf{f}_t$  is the one that maximizes the rate of energy dissipation, i.e.,

$$\mathbf{f}_t = \operatorname{argmin}_{\tilde{\mathbf{f}}_t \in \mathcal{F}} -\tilde{\mathbf{f}}_t^t \mathbf{v}_t$$


where  $\mathbf{v}_t$  is the relative tangential velocity at the contact point.



- 2D point mass

$$m\ddot{\mathbf{x}} = \mathbf{f}, \quad \mathbf{x} = \begin{pmatrix} x \\ y \end{pmatrix}, \quad \mathbf{f}_{\text{ext}} = \begin{pmatrix} 0 \\ -9.81m \end{pmatrix}$$

- Floor  $\mathbf{n}^\top \mathbf{x} \geq 0$ ,  $\mathbf{n} = \begin{pmatrix} n_x \\ n_y \end{pmatrix} = \begin{pmatrix} \sin \alpha \\ \cos \alpha \end{pmatrix}$




- Contact force  $\mathbf{f}_{\text{floor}} = \mathbf{f}_n + \mathbf{f}_t$ ,  $\mathbf{f}_n = \mathbf{n}\lambda$ ,  $\|\mathbf{f}_t\| \leq \mu \|\mathbf{f}_n\|$

- Max. dissipation sliding  $\max(-\mathbf{f}_t^\top \mathbf{T}\dot{\mathbf{x}})$  s.t.  $\|\mathbf{f}_t\| = \mu \|\mathbf{f}_n\|$   
 $\mathbf{T} = (\mathbf{I} - \mathbf{n}\mathbf{n}^\top)$

- Contact force  $\mathbf{f}_{\text{floor}} = \mathbf{f}_n + \mathbf{f}_t$ ,  $\mathbf{f}_n = \mathbf{n}\lambda$ ,  $\|\mathbf{f}_t\| \leq \mu \|\mathbf{f}_n\|$
- 2D: friction force in interval  $-\mu\lambda \leq f_t \leq \mu\lambda$   
Linear constraint
- 3D: friction force in disk  $\|\mathbf{f}_t\| \leq \mu\lambda$   
Nonlinear constraint
- Admissible friction force depends on normal force  
→ friction cone

# Friction cone

- Contact force  $\mathbf{f}_{\text{floor}} = \mathbf{f}_n + \mathbf{f}_t$ ,  $\mathbf{f}_n = \mathbf{n}\lambda$ ,  $\|\mathbf{f}_t\| \leq \mu \|\mathbf{f}_n\|$
- Friction cone
  - Radius of friction force disk depends linearly on  $\lambda$
  - Stacking up disks for all values of  $\lambda$  leads to friction cone




- **Problem:** nonlinear friction constraint  $\|\mathbf{f}_t\| \leq \mu\lambda$  is difficult to model
- **Idea:** linearize friction constraint  $\rightarrow$  polygonal friction cone approximation

# Pyramidal friction cone


Nonlinear Cone

$$\|\mathbf{f}_t\| \leq \mu \|\mathbf{f}_n\|$$



Pyramid

$$\mathbf{f}_t = \beta_1 \mathbf{d}_1 + \beta_2 \mathbf{d}_2 \quad \text{with} \quad -\tilde{\mu}\lambda \leq \beta_i \leq \tilde{\mu}\lambda$$





Outer approximation:

$$\tilde{\mu} = \mu$$

# General polygonal approximation

- $m$ -sided linear approximation of friction cone

$$\mathbf{D} = (\mathbf{d}_1, \dots, \mathbf{d}_m) \quad \mathbf{f}_t = \mathbf{D}\boldsymbol{\beta}, \quad \mathbf{1}^\top \boldsymbol{\beta} \leq \mu\lambda, \quad \boldsymbol{\beta} \geq 0$$



# Coulomb friction

see also Anitescu & Potra,  
Nonlinear Dynamics 14 (1997)

- Simulation time step
  - Collision detection: find contact point and normal
  - Apply impact law
  - Include approximate friction constraints
  - System of equations:

$$\mathbf{r}(\mathbf{v}_{i+1}) = \mathbf{n}\lambda + \mathbf{D}\boldsymbol{\beta} \quad \text{Newtonian motion}$$

$$0 \leq \lambda \perp \mathbf{n}^\top (\mathbf{v}_{i+1} + \mathbf{v}_i) \geq 0 \quad \text{Normal contact}$$

$$\mathbf{1}^\top \boldsymbol{\beta} \leq \mu\lambda \perp \boldsymbol{\gamma} \geq 0, \quad -\mathbf{D}^\top \mathbf{v}_{i+1} \leq \boldsymbol{\gamma} \mathbf{1} \perp \boldsymbol{\beta} \geq 0 \quad \text{Linearized friction}$$

# Complementarity Conditions

$$0 \leq \lambda \perp \mathbf{n}^T (\mathbf{v}_{i+1} + \mathbf{v}_i) \geq 0$$

$$\mathbf{1}^T \boldsymbol{\beta} \leq \mu \lambda \perp \gamma \geq 0, \quad -\mathbf{D}^T \mathbf{v}_{i+1} \leq \gamma \mathbf{1} \perp \boldsymbol{\beta} \geq 0$$

Case 1: if  $\mathbf{n}^T (\mathbf{v}_{i+1} + \mathbf{v}_i) < 0$ , no contact

$$\rightarrow \lambda = 0$$

$$\rightarrow \boldsymbol{\beta} = \mathbf{0}$$

$\rightarrow \gamma \geq 0$  such  $\mathbf{D}^T \mathbf{v}_{i+1} + \gamma \mathbf{1} \geq 0$  is satisfied.



# Complementarity Conditions

$$\mathbf{1}^\top \boldsymbol{\beta} \leq \mu\lambda \perp \gamma \geq 0, \quad -\mathbf{D}^\top \mathbf{v}_{i+1} \leq \gamma \mathbf{1} \perp \boldsymbol{\beta} \geq 0$$

Case 2: if  $\mathbf{1}^\top \boldsymbol{\beta} < \mu\lambda$

$$\rightarrow \gamma = 0$$

$$\rightarrow \mathbf{v}_{i+1} = 0$$

$\rightarrow$  static contact, no sliding.

# Complementarity Conditions

$$\mathbf{1}^\top \boldsymbol{\beta} \leq \mu \lambda \perp \gamma \geq 0, \quad -\mathbf{D}^\top \mathbf{v}_{i+1} \leq \gamma \mathbf{1} \perp \boldsymbol{\beta} \geq 0$$

Case 3: if  $\mathbf{1}^\top \boldsymbol{\beta} = \mu \lambda$

$\rightarrow \gamma > 0 \rightarrow \mathbf{v}_{i+1} \rightarrow \text{sliding}$

- There is only one  $\gamma$  for all directions
- For  $\beta_j > 0$ , we must have  $-\mathbf{d}_j^\top \mathbf{v} = \gamma$
- For two active  $\beta_j, \beta_k > 0$ , we must have  $\mathbf{d}_j^\top \mathbf{v} = \mathbf{d}_k^\top \mathbf{v}$ 
  - $\rightarrow$  for direction pairs where  $\mathbf{d}_j = -\mathbf{d}_k$ , we must have  $\beta_j \beta_k = 0$
  - $\rightarrow$  typically, only one  $\beta_j$  will be nonzero
  - $\rightarrow$  no guarantee that friction force is aligned with  $\mathbf{v}_{i+1}$

# Complementarity Conditions

$$\mathbf{1}^\top \boldsymbol{\beta} \leq \mu \lambda \perp \gamma \geq 0, \quad -\mathbf{D}^\top \mathbf{v}_{i+1} \leq \gamma \mathbf{1} \perp \boldsymbol{\beta} \geq 0$$

Remark 3: from  $-\mathbf{D}^\top \mathbf{v}_{i+1} \leq \gamma \mathbf{1} \perp \boldsymbol{\beta} = \mathbf{0}$

- We have  $\beta_j (\mathbf{d}_j^t \mathbf{v}_{i+1} + \gamma) = 0 \rightarrow \beta_j \mathbf{d}_j^t \mathbf{v}_{i+1} \leq 0 \ \forall j$   
 $\rightarrow$  friction force  $\mathbf{D}\boldsymbol{\beta}$  acts against relative velocity (i.e., does negative work)
- It can be shown that  $\boldsymbol{\beta}$  maximizes dissipation

- Simulation time step

- Eliminate  $\Delta_v$

- LCP form  $\mathbf{A}\mathbf{z} + \mathbf{q} = \mathbf{w}$

$$0 \leq \mathbf{w} \perp \mathbf{z} \geq \mathbf{q}$$

$$\mathbf{r}(\mathbf{v}_{i+1}) = \mathbf{n}\lambda + \mathbf{D}\boldsymbol{\beta}$$

$$\mathbf{r}(\hat{\mathbf{v}} + \Delta_v) \approx \mathbf{r}(\hat{\mathbf{v}}) + \mathbf{S}\Delta_v$$

$$\mathbf{S} := d\mathbf{r} / d\hat{\mathbf{v}}$$

$$\Delta_v = \mathbf{S}^{-1}(\mathbf{n}\lambda + \mathbf{D}\boldsymbol{\beta} - \mathbf{r}(\hat{\mathbf{v}}))$$

$$\mathbf{z} = \begin{pmatrix} \lambda \\ \boldsymbol{\beta} \\ \gamma \end{pmatrix}, \quad \mathbf{A} = \begin{pmatrix} \mathbf{n}^\top \mathbf{S}^{-1} \mathbf{n} & \mathbf{n}^\top \mathbf{S}^{-1} \mathbf{D} & 0 \\ \mathbf{D}^\top \mathbf{S}^{-1} \mathbf{n} & \mathbf{D}^\top \mathbf{S}^{-1} \mathbf{D} & \mathbf{1} \\ \mu & -\mathbf{1}^\top & 0 \end{pmatrix}$$

see also Anitescu & Potra,  
Nonlinear Dynamics 14 (1997)

$$\begin{aligned} \mathbf{A}\mathbf{z} + \mathbf{q} &= \mathbf{w} \\ 0 \leq \mathbf{w} \perp \mathbf{z} \geq \mathbf{q} \end{aligned} \quad \mathbf{z} = \begin{pmatrix} \lambda \\ \boldsymbol{\beta} \\ \gamma \end{pmatrix}, \quad \mathbf{A} = \begin{pmatrix} \mathbf{n}^\top \mathbf{S}^{-1} \mathbf{n} & \mathbf{n}^\top \mathbf{S}^{-1} \mathbf{D} & 0 \\ \mathbf{D}^\top \mathbf{S}^{-1} \mathbf{n} & \mathbf{D}^\top \mathbf{S}^{-1} \mathbf{D} & \mathbf{1} \\ \mu & -\mathbf{1}^\top & 0 \end{pmatrix}$$

Existence of solution [Anitescu & Potra, 1997]

- The LCP is guaranteed to have a solution
- The solution can be computed using Lemke's algorithm

- Soft constraints

$$\mathbf{n}^\top \mathbf{x} \geq 0$$

$$\mathbf{f}_n = \mathbf{n} \lambda$$



$$\mathbf{n}^\top \mathbf{x} < 0: \quad \mathbf{f}_n = -k_n \mathbf{n} \mathbf{n}^\top \mathbf{x}$$

$$\mathbf{n}^\top \mathbf{x} \geq 0: \quad \mathbf{f}_n = 0$$

- Sticking

$$\mathbf{T} \dot{\mathbf{x}} = 0$$

$$\mathbf{T} := (\mathbf{I} - \mathbf{n} \mathbf{n}^\top)$$



$$\mathbf{f}_t = -k_t \mathbf{T} \dot{\mathbf{x}}$$

$$\text{if } \|\mathbf{f}_t\| < \mu \|\mathbf{f}_n\|$$

- Sliding


$$\max(-\mathbf{f}_t^\top \dot{\mathbf{x}})$$

$$\text{s.t. } \|\mathbf{f}_t\| = \mu \|\mathbf{f}_n\|$$





$$\mathbf{f}_t = -\mu \mathbf{n}^\top \mathbf{f}_n (\mathbf{T} \dot{\mathbf{x}} / \|\mathbf{T} \dot{\mathbf{x}}\|)$$

# Coulomb Friction



## Extensions

- Separate  $\mu_s$  for sticking and  $\mu_k$  for sliding





## Extensions

- Separate  $\mu_s$  for sticking and  $\mu_d$  for sliding
- Anisotropic models  
See also Erleben et al., “The Matchstick Model for Anisotropic Friction Cones” [doi.org/10.1111/cgf.13885](https://doi.org/10.1111/cgf.13885)
- Adhesive contact

- Normal forces
  - Contact condition and normal force
  - Impact law for elastic contacts
- Tangential forces
  - Coulomb law for friction force magnitude
  - Max. dissipation principle for direction
- Complementarity as central modelling paradigm
- Linearization results in LCP

# Generalization to Rigid Bodies

- From point mass to rigid body simulation
  - Generalized coordinates: position and orientation
  - Constraints on contact points remain
  - Map contact points to generalized coordinates
  - Linearize (EoM, friction cone, rotations, ..) to obtain LCP

## X-walker

Example application for soft robot control.

# Soft Feet



- Discretize soft body with finite elements
- Equations of motion


$$\mathbf{M}\ddot{\mathbf{x}} = \mathbf{f}(\mathbf{x}, \mathbf{v}) + \mathbf{N}\boldsymbol{\lambda}$$

$$\mathbf{x} = \begin{pmatrix} x_1 \\ y_1 \\ x_2 \\ \vdots \end{pmatrix}$$

- Contact constraints

$$0 \leq \boldsymbol{\lambda} \perp \mathbf{N}^T \mathbf{x} \geq 0$$

- Note that  $\mathbf{N} \in \mathbf{R}^{dn \times l}, \boldsymbol{\lambda} \in \mathbf{R}^l$   
 $n \dots$  nr. of nodes       $d \dots$  dimension (2 or 3)  
 $l \dots$  nr. of (possible) contacts



## Soft body

- Motion  $\mathbf{M}\ddot{\mathbf{x}} = \mathbf{f}(\mathbf{x}, \mathbf{v}) + \mathbf{N}\boldsymbol{\lambda} + \mathbf{f}_t$


- Contact  $0 \leq \boldsymbol{\lambda} \perp \mathbf{N}^T \mathbf{x} \geq 0$

- Static friction (sticking)

$$\mathbf{T}\dot{\mathbf{x}} = 0 \quad \wedge \quad \|\mathbf{f}_t\| \leq \mu \|\mathbf{N}\boldsymbol{\lambda}\|$$


- Dynamic friction (sliding)

$$\max(-\mathbf{f}_t^T \mathbf{T}\dot{\mathbf{x}}) \quad \text{s.t.} \quad \|\mathbf{f}_t\| = \mu \|\mathbf{N}\boldsymbol{\lambda}\|$$



# Options for Solution

- Hard Constraints
  - Accurate solution
  - Easy for normal contact
  - Difficult for friction
- Soft constraints
  - Simple to implement and solve
  - (Small) penetrations
  - Drift for sticking contact






- Equations of motion

$$\mathbf{M}\ddot{\mathbf{x}} = \mathbf{f}(\mathbf{x}, \mathbf{v}) + \mathbf{f}_n + \mathbf{f}_t$$


- Contact forces per node

$$\begin{aligned}\mathbf{f}_n &= -k_n \mathbf{n} \mathbf{n}^\top \mathbf{x} && \text{if } \mathbf{n}^\top \mathbf{x} \leq 0 \\ \mathbf{f}_t &= -k_t \mathbf{T} \mathbf{v} && \text{if } \|k_t \mathbf{T} \mathbf{v}\| < \mu \|\mathbf{f}_n\| \\ \mathbf{f}_t &= -\mu \|\mathbf{f}_n\| \mathbf{T} \mathbf{v} / \|\mathbf{T} \mathbf{v}\| && \text{otherwise}\end{aligned}$$

## Frictionless case




## Friction via soft constraints




# FEM Examples

Soft Constraints  $t = 0.0010$



Hard Constraints  $t = 0.0010$



## ADD: Analytically Differentiable Dynamics for Multi-Body Systems with Frictional Contact

MORITZ GEILINGER\* and DAVID HAHN\*, ETH Zürich

JONAS ZEHNDER, Université de Montréal

MORITZ BÄCHER, Disney Research

BERNHARD THOMASZEWSKI, ETH Zürich and Université de Montréal

STELIAN COROS, ETH Zürich




Fig. 1. Applications of our differentiable simulation framework (left-to-right): estimation of stiffness, damping and friction properties from real-world experiments, manipulation of multi-body systems, self-supervised learning of control policies for a throwing task, and physics-based motion planning for robotic creatures with compliant motors and soft feet.

M. Geilinger et al. “ADD: Analytically Differentiable Dynamics for Multi-Body Systems with Frictional Contact”. ACM Transactions on Graphics (Proc. SIGGRAPH ‘20)

# ADD: Analytically Differentiable Dynamics for Multi-Body Systems with Frictional Contact

M. Geilinger<sup>\*1</sup>, D. Hahn<sup>\*1</sup>, J. Zehnder<sup>#</sup>, M. Bächer<sup>+</sup>, B. Thomaszewski<sup>\*\*</sup>, and S. Coros<sup>\*</sup>

<sup>\*</sup>Computational Robotics Lab, ETH Zürich

<sup>+</sup>Disney Research Zürich

<sup>#</sup>Université de Montreal

<sup>1</sup> Joint first authors



ETH zürich

CRL



# Summary

- Contact constraints

$$0 \leq \lambda \perp \mathbf{N}^\top \mathbf{x} \geq 0$$

- Coulomb friction

$$\|\mathbf{f}_t\| \leq \mu \|\mathbf{f}_n\|$$

- Hard constraints  $\rightarrow$  LCP or QP (linearized)

- Soft constraints  $\rightarrow$  choose penalty factor

# Further Reading

Hertz H., "Über die Berührung fester elastischer Körper", J. reine und angewandte Math. 92 (1881)

M. Anitescu & F. A. Potra, "Formulating dynamic multi-rigid-body contact problems with friction as solvable linear complementarity problems", Nonlinear Dynamics 14 (1997)

D. E. Stewart, "Rigid-Body Dynamics with Friction and Impact", SIAM Review 42, 1 (2000)

D. M. Kaufman et al., "Staggered Projections for Frictional Contact in Multibody Systems", ACM Trans. Graph. 27, 5 (2008)

V. L. Popov, "Contact Mechanics and Friction", Springer (2010)



# Further Reading

D. Stewart, J.C. Trinkle, “An Implicit Time-Stepping Scheme for Rigid Body Dynamics with Coulomb Friction”, Int. J. Num. Methods in Engineering, 1996.

D.E. Stewart and J.C. Trinkle. “An implicit time-stepping scheme for rigid body dynamics with inelastic collisions and coulomb friction.” International Journal of Numerical Methods in Engineering, 39:2673–2691, 1996.

M. Geilinger et al. “ADD: Analytically Differentiable Dynamics for Multi-Body Systems with Frictional Contact”. ACM Transactions on Graphics (Proc. SIGGRAPH ‘20)