REQUETES SPRINT 1

Actualités :
1.
select new_titre,new_contenu,new_date,usr_pseudo from T_NEWS_new
join T_UTILISATEUR_usr using(usr_id);

2.
select new_titre,new_contenu,new_date from T_NEWS_new where new_id = 1;

3.
select new_titre,new_contenu,new_date from T_NEWS_new
order by new_id DESC
LIMIT 5;

4.
SELECT new_titre, new_contenu,new_date from T_NEWS_new where new_titre LIKE
'%Modification%'
select * from T_PROFIL_pfl
5.
select new_titre,new_contenu,new_date,usr_pseudo from T_NEWS_new
join T_UTILISATEUR_usr using(usr_id)
where new_date = '2022-10-10';

Matchs :
1.
select * from T_MATCH_mat where mat_code is not null;

2.
INSERT INTO `T_JOUEUR_jou` (`jou_pseudo`, `jou_score`, `jou_id`, `mat_id`) VALUES
('ricodico', '0', NULL, '4');

3.
select * from T_MATCH_mat
join T_JOUEUR_jou using(mat_id)
where jou_pseudo = 'Steven' and mat_id=1;

4.
select mat_id, que_intitule,rep_intitule from T_MATCH_mat
join T_QUESTION_que using(qui_id)
join T_REPONSE_rep using(que_id)
where mat_id = 1

Actualités :
1.
select new_titre,new_contenu,new_date from T_NEWS_new
join T_UTILISATEUR_usr using(usr_id)
where usr_pseudo = 'Lucie23';

Profils (formateurs / administrateurs) :

1.
```
select * from T_PROFIL_pfl ;
```

2.
```
select * from T_PROFIL_pfl
join T_UTILISATEUR_usr using(usr_id)
where usr_role = 'F';
```

3.
```
select * from T_UTILISATEUR_usr where usr_pseudo = 'responsable' and usr_mdp
='c52071294f899907b3e2ccea671dcef0a2c0f88cb7eca55825df66dab9a26a80';
```

4.
```
select * from T_PROFIL_pfl where usr_id = 2;
```

5.
```
select pfl_prenom, pfl_nom,usr_pseudo, usr_etat from T_UTILISATEUR_usr
join T_PROFIL_pfl using(usr_id)
```

Quiz :
1.
```
select * from T_QUIZ_qui
join T_QUESTION_que using(qui_id)
join T_REPONSE_rep using(que_id)
where qui_id=1;
```

2.
```
select count(que_id) from T_QUESTION_que
where qui_id = 1;
```

Matchs :
1.
```
SELECT mat_id, que_intitule, rep_intitule from T_MATCH_mat
join T_QUESTION_que using(qui_id)
join T_REPONSE_rep using(que_id)
where mat_id = 1
```

2.
```
select count(jou_id) from T_JOUEUR_jou where mat_id =1;
```

3.
```
select AVG(jou_score) from T_JOUEUR_jou where mat_id = 1 ;
```

4.
```
select jou_pseudo,jou_score from T_JOUEUR_jou where mat_id = 1
```

5.
```
select * from T_MATCH_mat where usr_id = 3;
```

6.
select mat_id from T_MATCH_mat where qui_id = 2;

REQUETES SPRINT 2

Matchs :
5.
select * from T_QUESTION_que
join T_MATCH_mat using(qui_id)
where mat_id = 1 and mat_visualisation = 'A';

6.
select * from T_REPONSE_rep where rep_id = 1 and rep_bonne_reponse = 1;

7.
update T_JOUEUR_jou set jou_score = 10 where jou_id = 1;

8.
select jou_score from T_JOUEUR_jou where jou_id = 1;

Quiz :

3.
select qui_nom from T_QUIZ_qui

4.
SELECT qui_nom, usr_pseudo from T_QUIZ_qui
join T_UTILISATEUR_usr using(usr_id)

5.
select mat_id, qui_nom,usr.usr_pseudo as auteur_match, usr2.usr_pseudo as auteur_quiz
from T_QUIZ_qui as qui
inner join T_MATCH_mat as mat on mat.qui_id = qui.qui_id
inner join T_UTILISATEUR_usr as usr on usr.usr_id = mat.usr_id
inner join T_UTILISATEUR_usr as usr2 on usr2.usr_id = qui.usr_id
ORDER by mat_id;

6.
SELECT qui_nom from T_QUIZ_qui where usr_id = 3;

7.
SELECT qui_nom, qui_id,mat_id from T_QUIZ_qui
join T_UTILISATEUR_usr using(usr_id)
left outer join T_MATCH_mat using(qui_id)
where usr_pseudo = 'Lucie23';

Matchs :

7.
INSERT INTO `T_MATCH_mat` (`mat_date_debut`, `mat_date_fin`, `mat_actif`, `mat_visualisation`, `mat_id`, `usr_id`, `qui_id`) VALUES (NULL, NULL, 'A', 'A', NULL, '3', '2');

8.
```
UPDATE `T_MATCH_mat` SET `qui_id` = '3' WHERE
`T_MATCH_mat`.`mat_id` = 9;
```

9.
delete from T_MATCH_mat where mat_id = 10;

10.
```
UPDATE `T_MATCH_mat` SET `mat_actif` = 'N' WHERE
`T_MATCH_mat`.`mat_id` = 6;
```

11.
update T_MATCH_mat set mat_date_debut = NULL, mat_code = NULL, mat_date_fin = NULL, nat_actif = 'N',mat_visualisation = 'N' where mat_id = 6;