

CS162

Operating Systems and Systems Programming

Lecture 11

Scheduling (finished),
Deadlock, Address Translation

March 1st, 2017

Prof. Ion Stoica

<http://cs162.eecs.Berkeley.edu>

Recap: What if we Knew the Future?


- Could we always mirror best FCFS?
- Shortest Job First (SJF):
 - Run whatever job has least amount of computation to do
 - Sometimes called “Shortest Time to Completion First” (STCF)
- Shortest Remaining Time First (SRTF):
 - Preemptive version of SJF: if job arrives and has a shorter time to completion than the remaining time on the current job, immediately preempt CPU
 - Sometimes called “Shortest Remaining Time to Completion First” (SRTCF)
- These can be applied to whole program or current CPU burst
 - Idea is to get short jobs out of the system
 - Big effect on short jobs, only small effect on long ones
 - Result is better average response time



Recap: Discussion


- SJF/SRTF are the best you can do at minimizing average response time
 - Provably optimal (SJF among non-preemptive, SRTF among preemptive)
 - Since SRTF is always at least as good as SJF, focus on SRTF
- Comparison of SRTF with FCFS and RR
 - What if all jobs the same length?
 - » SRTF becomes the same as FCFS (i.e. FCFS is best can do if all jobs the same length)
 - What if jobs have varying length?
 - » SRTF (and RR): short jobs not stuck behind long ones

Example to illustrate benefits of SRTF



- Three jobs:
 - A, B: both CPU bound, run for week
 - C: I/O bound, loop 1ms CPU, 9ms disk I/O
 - If only one at a time, C uses 90% of the disk, A or B could use 100% of the CPU
- With FIFO:
 - Once A or B get in, keep CPU for two weeks
- What about RR or SRTF?
 - Easier to see with a timeline

SRTF Example continued:



SRTF Further discussion

- Starvation
 - SRTF can lead to starvation if many small jobs!
 - Large jobs never get to run
- Somehow need to predict future
 - How can we do this?
 - Some systems ask the user
 - » When you submit a job, have to say how long it will take
 - » To stop cheating, system kills job if takes too long
 - But: hard to predict job's runtime even for non-malicious users




SRTF Further discussion (Cont.)


- Bottom line, can't really know how long job will take
 - However, can use SRTF as a yardstick for measuring other policies
 - Optimal, so can't do any better
- SRTF Pros & Cons
 - Optimal (average response time) (+)
 - Hard to predict future (-)
 - Unfair (-)

Predicting the Length of the Next CPU Burst

- **Adaptive**: Changing policy based on past behavior
 - CPU scheduling, in virtual memory, in file systems, etc
 - Works because programs have predictable behavior
 - » If program was I/O bound in past, likely in future
 - » If computer behavior were random, wouldn't help
- Example: SRTF with estimated burst length
 - Use an estimator function on previous bursts:
Let $t_{n-1}, t_{n-2}, t_{n-3}$, etc. be previous CPU burst lengths. Estimate next burst $\tau_n = f(t_{n-1}, t_{n-2}, t_{n-3}, \dots)$
 - Function f could be one of many different time series estimation schemes (Kalman filters, etc)
 - For instance,
exponential averaging
 $\tau_n = \alpha t_{n-1} + (1-\alpha)\tau_{n-1}$
with $(0 < \alpha \leq 1)$




Multi-Level Feedback Scheduling




- Another method for exploiting past behavior (first use in CTSS)
 - Multiple queues, each with different priority
 - » Higher priority queues often considered “foreground” tasks
 - Each queue has its own scheduling algorithm
 - » e.g. foreground – RR, background – FCFS
 - » Sometimes multiple RR priorities with quantum increasing exponentially (highest: 1ms, next: 2ms, next: 4ms, etc)
- Adjust each job’s priority as follows (details vary)
 - Job starts in highest priority queue
 - If timeout expires, drop one level
 - If timeout doesn’t expire, push up one level (or to top)

Scheduling Details



- Result approximates SRTF:
 - CPU bound jobs drop like a rock
 - Short-running I/O bound jobs stay near top
- Scheduling must be done between the queues
 - Fixed priority scheduling:
 - » serve all from highest priority, then next priority, etc.
 - Time slice:
 - » each queue gets a certain amount of CPU time
 - » e.g., 70% to highest, 20% next, 10% lowest

Scheduling Details




- **Countermeasure:** user action that can foil intent of OS designers
 - For multilevel feedback, put in a bunch of meaningless I/O to keep job's priority high
 - Of course, if everyone did this, wouldn't work!
- Example of Othello program:
 - Playing against competitor, so key was to do computing at higher priority than the competitors.
 - » Put in **printf's**, ran much faster!

Real-Time Scheduling (RTS)


- Efficiency is important but **predictability** is essential:
 - We need to predict with confidence worst case response times for systems
 - In RTS, performance guarantees are:
 - » Task- and/or class centric and often ensured a priori
 - In conventional systems, performance is:
 - » System/throughput oriented with post-processing (... wait and see ...)
 - Real-time is about enforcing predictability, and does not equal fast computing!!!
- Hard Real-Time
 - *Attempt to meet all deadlines*
 - EDF (Earliest Deadline First), LLF (Least Laxity First), RMS (Rate-Monotonic Scheduling), DM (Deadline Monotonic Scheduling)
- Soft Real-Time
 - *Attempt to meet deadlines with high probability*
 - Minimize miss ratio / maximize completion ratio (firm real-time)
 - Important for multimedia applications
 - CBS (Constant Bandwidth Server)

Example: Workload Characteristics

- Tasks are preemptable, independent with arbitrary arrival (=release) times
- Tasks have deadlines (D) and known computation times (C)
- Example Setup:




Example: Round-Robin Scheduling Doesn't Work




Earliest Deadline First (EDF)

- Tasks periodic with period P and computation C in each period: (P, C)
- Preemptive priority-based dynamic scheduling
- Each task is assigned a (current) priority based on how close the absolute deadline is
- The scheduler always schedules the active task with the closest absolute deadline




A Final Word On Scheduling


- When do the details of the scheduling policy and fairness really matter?
 - When there aren't enough resources to go around
- When should you simply buy a faster computer?
 - (Or network link, or expanded highway, or ...)
 - One approach: Buy it when it will pay for itself in improved response time
 - » Assuming you're paying for worse response time in reduced productivity, customer angst, etc...
 - » Might think that you should buy a faster X when X is utilized 100%, but usually, response time goes to infinity as utilization \Rightarrow 100%
- An interesting implication of this curve:
 - Most scheduling algorithms work fine in the “linear” portion of the load curve, fail otherwise
 - Argues for buying a faster X when hit “knee” of curve




Deadlock



Starvation vs Deadlock



- Starvation vs. Deadlock
 - Starvation: thread waits indefinitely
 - » Example, low-priority thread waiting for resources constantly in use by high-priority threads
 - Deadlock: circular waiting for resources
 - » Thread A owns Res 1 and is waiting for Res 2
 - » Thread B owns Res 2 and is waiting for Res 1



- Deadlock \Rightarrow Starvation but not vice versa
 - » Starvation can end (but doesn't have to)
 - » Deadlock can't end without external intervention

Conditions for Deadlock

- Deadlock not always deterministic – Example 2 mutexes:

Thread A

`x.P();`

`y.P();`

`y.V();`

`x.V();`

Thread B

`y.P();`


`x.P();`

`x.V();`

`y.V();`

- Deadlock won't always happen with this code
 - » Have to have exactly the right timing (“wrong” timing?)
 - » So you release a piece of software, and you tested it, and there it is, controlling a nuclear power plant...
- Deadlocks occur with multiple resources
 - Means you can't decompose the problem
 - Can't solve deadlock for each resource independently
- Example: System with 2 disk drives and two threads
 - Each thread needs 2 disk drives to function
 - Each thread gets one disk and waits for another one


Bridge Crossing Example




- Each segment of road can be viewed as a resource
 - Car must own the segment under them
 - Must acquire segment that they are moving into
- For bridge: must acquire both halves
 - Traffic only in one direction at a time
 - Problem occurs when two cars in opposite directions on bridge: each acquires one segment and needs next
- If a deadlock occurs, it can be resolved if one car backs up (preempt resources and rollback)
 - Several cars may have to be backed up
- Starvation is possible
 - East-going traffic really fast \Rightarrow no one goes west

Train Example (Wormhole-Routed Network)

- Circular dependency (Deadlock!)
 - Each train wants to turn right
 - Blocked by other trains
 - Similar problem to multiprocessor networks
- Fix? Imagine grid extends in all four directions
 - Force ordering of channels (tracks)
 - » Protocol: Always go east-west first, then north-south
 - Called “dimension ordering” (X then Y)



Dining Philosophers Problem



- Five chopsticks/Five philosophers
 - Free-for all: Philosopher will grab any one they can
 - Need two chopsticks to eat
- What if all grab at same time?
 - Deadlock!
- How to fix deadlock?
 - Make one of them give up a chopstick (Hah!)
 - Eventually everyone will get chance to eat
- How to prevent deadlock?
 - Never let philosopher take last chopstick if no hungry philosopher has two chopsticks afterwards


Four requirements for Deadlock

- Mutual exclusion
 - Only one thread at a time can use a resource.
- Hold and wait
 - Thread holding at least one resource is waiting to acquire additional resources held by other threads
- No preemption
 - Resources are released only voluntarily by the thread holding the resource, after thread is finished with it
- Circular wait
 - There exists a set $\{T_1, \dots, T_n\}$ of waiting threads
 - » T_1 is waiting for a resource that is held by T_2
 - » T_2 is waiting for a resource that is held by T_3
 - » ...
 - » T_n is waiting for a resource that is held by T_1

Resource-Allocation Graph

- System Model

- A set of Threads T_1, T_2, \dots, T_n
- Resource types R_1, R_2, \dots, R_m
CPU cycles, memory space, I/O devices
- Each resource type R_i has W_i instances
- Each thread utilizes a resource as follows:
 - » Request () / Use () / Release ()




- Resource-Allocation Graph:


- V is partitioned into two types:
 - » $T = \{T_1, T_2, \dots, T_n\}$, the set threads in the system.
 - » $R = \{R_1, R_2, \dots, R_m\}$, the set of resource types in system
- request edge – directed edge $T_i \rightarrow R_j$
- assignment edge – directed edge $R_j \rightarrow T_i$

Resource Allocation Graph Examples


- Recall:
 - request edge – directed edge $T_i \rightarrow R_j$
 - assignment edge – directed edge $R_j \rightarrow T_i$



Simple Resource Allocation Graph



Allocation Graph With Deadlock




Allocation Graph With Cycle, but No Deadlock

Administrivia

- Midterm #1 grades/solutions are available
 - Regrades request deadline: 3/13 at 11:59PM
- Upcoming deadlines:
 - Project 1 final code due on Fri 3/3
 - HW2 due on Mon 3/6
 - Final report for Project 1 due on Mon 3/6

BREAK


Methods for Handling Deadlocks



- Allow system to enter deadlock and then recover
 - Requires deadlock detection algorithm
 - Some technique for forcibly preempting resources and/or terminating tasks
- Ensure that system will *never* enter a deadlock
 - Need to monitor all lock acquisitions
 - Selectively deny those that *might* lead to deadlock
- Ignore the problem and pretend that deadlocks never occur in the system
 - Used by most operating systems, including UNIX

Deadlock Detection Algorithm

- Only one of each type of resource \Rightarrow look for loops
 - More General Deadlock Detection Algorithm
 - Let $[X]$ represent an m-ary vector of non-negative integers (quantities of resources of each type):
 - $[FreeResources]$: Current free resources each type
 - $[Request_x]$: Current requests from thread X
 - $[Alloc_x]$: Current resources held by thread X
 - See if tasks can eventually terminate on their own
- ```
[Avail] = [FreeResources]
Add all nodes to UNFINISHED
do {
 done = true
 Foreach node in UNFINISHED {
 if ($[Request_{node}] \leq [Avail]$) {
 remove node from UNFINISHED
 $[Avail] = [Avail] + [Alloc_{node}]$
 done = false
 }
 }
} until(done)
```
- Nodes left in **UNFINISHED**  $\Rightarrow$  deadlocked



# What to do when detect deadlock?

---

- Terminate thread, force it to give up resources
  - In Bridge example, Godzilla picks up a car, hurls it into the river. Deadlock solved!
  - Shoot a dining lawyer
  - But, not always possible – killing a thread holding a mutex leaves world inconsistent
- Preempt resources without killing off thread
  - Take away resources from thread temporarily
  - Doesn't always fit with semantics of computation
- Roll back actions of deadlocked threads
  - Hit the rewind button on TiVo, pretend last few minutes never happened
  - For bridge example, make one car roll backwards (may require others behind him)
  - Common technique in databases (transactions)
  - Of course, if you restart in exactly the same way, may reenter deadlock once again
- Many operating systems use other options

# Four requirements for Deadlock

---

- Mutual exclusion
  - Only one thread at a time can use a resource.
- Hold and wait
  - Thread holding at least one resource is waiting to acquire additional resources held by other threads
- No preemption
  - Resources are released only voluntarily by the thread holding the resource, after thread is finished with it
- Circular wait
  - There exists a set  $\{T_1, \dots, T_n\}$  of waiting threads
    - »  $T_1$  is waiting for a resource that is held by  $T_2$
    - »  $T_2$  is waiting for a resource that is held by  $T_3$
    - » ...
    - »  $T_n$  is waiting for a resource that is held by  $T_1$

# Techniques for Preventing Deadlock

---

- Infinite resources
  - Include enough resources so that no one ever runs out of resources. Doesn't have to be infinite, just large
  - Give illusion of infinite resources (e.g. virtual memory)
  - Examples:
    - » Bay bridge with 12,000 lanes. Never wait!
    - » Infinite disk space (not realistic yet?)
- No Sharing of resources (totally independent threads)
  - Not very realistic
- Don't allow waiting
  - How the phone company avoids deadlock
    - » Call to your Mom in Toledo, works its way through the phone lines, but if blocked get busy signal.
  - Technique used in Ethernet/some multiprocessor nets
    - » Everyone speaks at once. On collision, back off and retry
  - Inefficient, since have to keep retrying
    - » Consider: driving to San Francisco; when hit traffic jam, suddenly you're transported back home and told to retry!




# Techniques for Preventing Deadlock (cont'd)

- Make all threads request everything they'll need at the beginning.
  - Problem: Predicting future is hard, tend to over-estimate resources
  - Example:
    - » If need 2 chopsticks, request both at same time
    - » Don't leave home until we know no one is using any intersection between here and where you want to go; only one car on the Bay Bridge at a time
- Force all threads to request resources in a particular order preventing any cyclic use of resources
  - Thus, preventing deadlock
  - Example (x.P, y.P, z.P,...)
    - » Make tasks request disk, then memory, then...
    - » Keep from deadlock on freeways around SF by requiring everyone to go clockwise

# Review: Train Example (Wormhole-Routed Network)

- Circular dependency (Deadlock!)
  - Each train wants to turn right
  - Blocked by other trains
  - Similar problem to multiprocessor networks
- Fix? Imagine grid extends in all four directions
  - Force ordering of channels (tracks)
    - » Protocol: Always go east-west first, then north-south
  - Called “dimension ordering” (X then Y)



# Banker's Algorithm for Preventing Deadlock

- Toward right idea:
  - State maximum resource needs in advance
  - Allow particular thread to proceed if:  
(available resources - #requested)  $\geq$  max remaining that might be needed by any thread
- Banker's algorithm (less conservative):
  - Allocate resources dynamically
    - » Evaluate each request and grant if some ordering of threads is still deadlock free afterward
    - » Technique: pretend each request is granted, then run deadlock detection algorithm, substituting  
 $([Max_{node}] - [Alloc_{node}] \leq [Avail])$  for  $([Request_{node}] \leq [Avail])$   
Grant request if result is deadlock free (conservative!)



# Banker's Algorithm for Preventing Deadlock

- ```
[Avail] = [FreeResources]
  Add all nodes to UNFINISHED
  do {
    done = true
    Foreach node in UNFINISHED {
      if ([Requestnode] <= [Avail]) {
        remove node from UNFINISHED
        [Avail] = [Avail] + [Allocnode]
        done = false
      }
    }
  } until(done)
```
-



» Technique: pretend each request is granted, then run deadlock detection algorithm, substituting
 $([Max_{node}] - [Alloc_{node}] \leq [Avail])$ for $([Request_{node}] \leq [Avail])$
Grant request if result is deadlock free (conservative!)

Banker's Algorithm for Preventing Deadlock

- ```
[Avail] = [FreeResources]
Add all nodes to UNFINISHED
do {
 done = true
 Foreach node in UNFINISHED {
 if ($[Max_{node}] - [Alloc_{node}] \leq [Avail]$) {
 remove node from UNFINISHED
 $[Avail] = [Avail] + [Alloc_{node}]$
 done = false
 }
 }
} until(done)
```
- 




- » Technique: pretend each request is granted, then run deadlock detection algorithm, substituting  $([Max_{node}] - [Alloc_{node}] \leq [Avail])$  for  $([Request_{node}] \leq [Avail])$   
Grant request if result is deadlock free (conservative!)

# Banker's Algorithm for Preventing Deadlock

- Toward right idea:
  - State maximum resource needs in advance
  - Allow particular thread to proceed if:  
(available resources - #requested)  $\geq$  max remaining that might be needed by any thread
- Banker's algorithm (less conservative):
  - Allocate resources dynamically
    - » Evaluate each request and grant if some ordering of threads is still deadlock free afterward
    - » Technique: pretend each request is granted, then run deadlock detection algorithm, substituting  
 $([Max_{node}] - [Alloc_{node}] \leq [Avail])$  for  $([Request_{node}] \leq [Avail])$   
Grant request if result is deadlock free (conservative!)
    - » Keeps system in a “SAFE” state, i.e. there exists a sequence  $\{T_1, T_2, \dots, T_n\}$  with  $T_1$  requesting all remaining resources, finishing, then  $T_2$  requesting all remaining resources, etc..
  - Algorithm allows the sum of maximum resource needs of all current threads to be greater than total resources



# Banker's Algorithm Example



- Banker's algorithm with dining philosophers
  - “Safe” (won't cause deadlock) if when try to grab chopstick either:
    - » Not last chopstick
    - » Is last chopstick but someone will have two afterwards
  - What if k-handed philosopher? Don't allow if:
    - » It's the last one, no one would have k
    - » It's 2<sup>nd</sup> to last, and no one would have k-1
    - » It's 3<sup>rd</sup> to last, and no one would have k-2
    - » ...



# Deadlock Prevention – The Reality

---

- Deadlock Prevention is HARD
  - How many resources will each thread need?
  - How many total resources are there?
- Also Slow/Impractical
  - Matrix of resources/requirements could be big and dynamic
  - Re-evaluate on every request (even for small/non-contended)
  - Banker's algorithm assumes everyone asks for max
- REALITY
  - Most OSs don't bother
  - Programmers job to write deadlock-free programs (e.g. by ordering all resource requests).



# Summary

---

- Starvation (thread waits indefinitely) versus Deadlock (circular waiting for resources)
- Four conditions for deadlocks
  - Mutual exclusion
    - » Only one thread at a time can use a resource
  - Hold and wait
    - » Thread holding at least one resource is waiting to acquire additional resources held by other threads
  - No preemption
    - » Resources are released only voluntarily by the threads
  - Circular wait
    - »  $\exists$  set  $\{T_1, \dots, T_n\}$  of threads with a cyclic waiting pattern
- Techniques for addressing Deadlock
  - Allow system to enter deadlock and then recover
  - Ensure that system will *never* enter a deadlock
  - Ignore the problem and pretend that deadlocks never occur in system