

#Programming #JavaScript #js #date #invalid #text [2 more...](#)[\[Edit\]](#) EN

## JavaScript - detecting invalid date

1 contributors 2 contributions 0 discussions

In this article, we're going to have a look at how to check if data is invalid in JavaScript.

Date correctness can be checked basing on internal state of `Date` object.

Incorrect date object returns:

- `false` for call `isFinite(myDate)`,
- `true` for call `isNaN(myDate)`,
- `Invalid Date` string for `toString()` method call.

Created by:  Lily ☆ 208★ 8  
points

Quick solution:

```
1 var correctDate = new Date(2020, 10, 15);
2 var incorrectDate = new Date(NaN);
3
4 console.log( isFinite( correctDate ) ); // true
5 console.log( !isNaN( correctDate ) ); // true
6 console.log( isFinite( incorrectDate ) ); // false
7 console.log( !isNaN( incorrectDate ) ); // false
```

Run

Auto running

Reset

Look below to see different practical examples:

### 1. `Date` object test example [Edit](#)

This approach bases on fact: `isFinite` method returns `false` for incorrect dates.

```
1 function isCorrectDate(date) {
2     return date instanceof Date && isFinite(date);
3
4     // return date instanceof Date && !isNaN(date);
5 }
6
7 // Usage example:
8
9 var correctDate = new Date(2020, 10, 15);
10 var incorrectDate = new Date(NaN);
11
12 console.log( isCorrectDate( correctDate ) ); // true
13 console.log( isCorrectDate( incorrectDate ) ); // false
```

Run

Auto running

Reset

### 2. `getTime()` or other getter test example [Edit](#)

This approach bases on fact: incorrect date returns `NaN` values from getters. So we can make simple test for example with `getTime()` method.

```
1 function isCorrectDate(date) {
2     return date instanceof Date && isFinite(date.getTime());
3
4     // return date instanceof Date && !isNaN(date.g
5 }
6
7 // Usage example:
8
```

Welcome. By using dirask, you confirm that you have read and understood [Terms, Privacy & Cookie policy](#).

Ok, I understand

```

9  var correctDate = new Date(2020, 10, 15);
10 var incorrectDate = new Date(NaN);
11
12 console.log( isCorrectDate( correctDate ) ); // true
13 console.log( isCorrectDate( incorrectDate ) ); // false

```

Run

Auto running

Reset

### 3. toString() method test example [Edit](#)

This approach is based on fact: incorrect date object returns "Invalid Date" string for toString() method call. It is good to call toString method with prototype API that prevents for methods overriding.

```

1  function isCorrectDate(date) {
2      if (date instanceof Date) {
3          var text = Date.prototype.toString.call(date);
4          return text !== 'Invalid Date';
5      }
6      return false;
7  }
8
9  // Usage example:
10
11 var correctDate = new Date(2020, 10, 15);
12 var incorrectDate = new Date(NaN);
13
14 console.log( isCorrectDate( correctDate ) ); // true
15 console.log( isCorrectDate( incorrectDate ) ); // false

```

Run

Auto running

Reset

### 4. Detecting correct date string or date object example [Edit](#)

Example presented in this section allows to check correctness of date provided as string or object. String date should be formatted according to one of the standards:

- IETF-compliant RFC 2822 timestamps,
- ISO 8601.

Run following code to see effect:

```

1  function isCorrectDate(date) {
2      return isFinite(date instanceof Date ? date : new Date(date));
3
4      // return isFinite(date instanceof Date ? date : Date.parse(date));
5      // return !isNaN(date instanceof Date ? date : new Date(date));
6      // return !isNaN(date instanceof Date ? date : Date.parse(date));
7  }
8
9  // Usage example:
10
11 var date1 = '2020-10-15';
12 var date2 = '2020-10-x5'; // <----- incorrect date
13 var date3 = 'This is not date'; // <-- incorrect date
14 var date4 = new Date(2020, 10, 15);
15 var date5 = new Date(NaN); // <----- incorrect date
16
17 console.log( isCorrectDate( date1 ) ); // true
18 console.log( isCorrectDate( date2 ) ); // false
19 console.log( isCorrectDate( date3 ) ); // false
20 console.log( isCorrectDate( date4 ) ); // true
21 console.log( isCorrectDate( date5 ) ); // false

```

Run

Auto running

Reset

Jobs you may like



Senior Scala Developer  
Undisclosed salary

Welcome. By using dirask, you confirm that you have read and understood [Terms, Privacy & Cookie policy](#).

Ok, I understand



#### Software Engineer - Java

Undisclosed salary  
Klarna 📍 Milan, IT



#### Senior Game Server Engineer (Java)

Undisclosed salary  
8Bit 📍 Warsaw, PL



#### Insurance Broking - HTML/CSS Developer - SE/SSE

Undisclosed salary  
Paytm 📍 Mumbai, IN

[More job offers](#)

## Native Advertising



Get your tech brand or product in front of software developers.

For more information [Contact us](#)

### Posts you may like

- Python - split string by new line character
- React - how to pass props to react components
- Python - math.sin() method example
- Python - boolean values
- JavaScript - how to make drag and drop div with handle?
- Dirask - automatic content translation

[Show more](#)

Dirask - we help you to  
solve coding problems.

[Ask question.](#)



Join

Welcome. By using dirask, you confirm that you have read  
and understood [Terms, Privacy & Cookie policy](#)

Ok, I understand

## Features

[Home](#)

[Wiki](#)

[Q & A](#)

[Findings & News](#)

[Jobs](#)

## About

[About & Contact](#)

[Terms](#)

[Cookie Policy](#)

[Privacy](#)

[GDPR Privacy Policy](#)

[Policies](#)

## Other

[Formatters](#)

[Funny generators](#)

[Post lists](#)

[Links](#)

[Site map](#)

© 2021 dirask - created with passion

Welcome. By using dirask, you confirm that you have read and understood [Terms, Privacy & Cookie policy](#).

Ok, I understand