

Recharts set Y-axis range

On **YAxis** component set the domain value from 0 to 100(or whatever u want)

```
<YAxis type="number" domain={[0, 20000]} />
```

Check this fiddle Link

Domain DEFAULT: [0, 'auto']

Specify the domain of axis when the axis is a number axis. The length of domain should be 2, and we will validate the values in domain. And each element in the array can be a number, 'auto', 'dataMin', 'dataMax', a string like 'dataMin - 20', 'dataMax + 100', or a function that accepts a single argument and returns a number. If any element of domain is set to be 'auto', comprehensible scale ticks will be calculated, and the final domain of axis is generated by the ticks.

FORMAT:

```
<YAxis type="number" domain={['dataMin', 'dataMax']} />
<YAxis type="number" domain={[0, 'dataMax']} />
<YAxis type="number" domain={['auto', 'auto']} />
<YAxis type="number" domain={[0, 'dataMax + 1000']} />
<YAxis type="number" domain={['dataMin - 100', 'dataMax + 100']} />
<YAxis type="number" domain={[dataMin => (0 - Math.abs(dataMin)), dataMax => (dataMax * 2)]} />
```

If the values of the chart exceed the customized domain range, then the domain boundaries set get ignored. I've had this problem because I use custom shapes, where negative values get stacked like positive values on top (but in a different color). Specifying the `domain={[0, 'dataMax + 1000']}` did not work, as the y axis still showed negative numbers – until i set `allowDataOverflow={true}`

```
<YAxis domain={[0, 'dataMax + 1000']} allowDataOverflow={true} />
```

Tags: [Reactjs](#) / [Recharts](#)

Related

[How to add protected routes in react redux](#)

[What has happened to Ant Design? Deleted from GitHub](#)

[React Native - npx react-native run-ios doesn't work after initializing the project](#)

[How to dynamically use react routing](#)

[Why shouldn't I use catch\(\) to handle errors in React useEffect API calls?](#)

[Why can't `useCallback` always return the same ref](#)

[Does redux evaluate all listeners to the store on any update to the store?](#)

[how can use hsl instead of rgb for scss global declaration javascript api](#)

[How does React re-use child components / keep the state of child components when re-rendering the parent component?](#)

[Is it possible to only show half of a SVG icon?](#)

Recent Posts

[Pandas how to find column contains a certain value](#)

[Recommended way to install multiple Python versions on Ubuntu 20.04](#)

[Build super fast web scraper with Python x100 than BeautifulSoup](#)